

85HF(R) Series

STANDARD RECOVERY DIODES 85 AMP

FEATURES

- Available as "HR" (high reliability) screened per MIL-PRF-19500, JANTX level. Add "HR" suffix to base part number.
- Available as non-RoHS (Sn/Pb plating), standard, and as RoHS by adding "-PBF" suffix.

MAXIMUM RATINGS

Parameter	Symbol	Test Conditions	85HF(R)		Units
			10 to 120	140 to 160	
Maximum average forward current	$I_{F(AV)}$		85 @ $T_C = 140^\circ\text{C}$	85 @ $T_C = 110^\circ\text{C}$	Amps
Maximum RMS forward current	$I_{F(RMS)}$		133		Amps
Maximum peak, on cycle, non-repetitive forward surge current	I_{FSM}	@ 50Hz @ 60Hz	1700 1800		Amps
Maximum I^2t for fusing	I^2t	@ 50Hz @ 60Hz	14500 13500		A ² s
Maximum repetitive peak reverse voltage	V_{RRM}		100-1200	1400-1600	Volts
Junction temperature range	T_J		-65 to 180	-65 to 150	°C

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise specified)

Part number	Maximum repetitive peak reverse voltage	Maximum non-repetitive peak reverse voltage	Maximum repetitive reverse current at $T_J = T_J$ maximum
	V_{RRM}	V_{RSM}	I_{RRM}
	Volts	Volts	mA
85HF10(R)	100	200	9
85HF20(R)	200	300	
85HF40(R)	400	500	
85HF60(R)	600	700	
85HF80(R)	800	900	
85HF100(R)	1000	1100	
85HF120(R)	1200	1300	
85HF140(R)	1400	1500	4.5
85HF160(R)	1600	1700	

85HF(R) Series

STANDARD RECOVERY DIODES 85 AMP

FORWARD CONDUCTION

Parameter	Symbol	Test Conditions		85HF(R)		Units
				10 to 120	140 to 160	
Maximum average forward current at case temperature	$I_{F(AV)}$	180° conduction, half sine wave $T_C = 140^\circ\text{C}$		85 @ $T_C = 140^\circ\text{C}$	85 @ $T_C = 110^\circ\text{C}$	Amps
Maximum RMS forward current	$I_{F(RMS)}$			133		Amps
Maximum peak, one cycle, non-repetitive forward surge current	I_{FSM}	t = 10ms	No voltage reappplied	Sinusoidal half wave, initial $T_J = T_J$ maximum	1700	Amps
		t = 8.3ms			1800	
		t = 10ms	100% V_{RRM} reappplied		1450	
		t = 8.3ms			1500	
Maximum I^2t for fusing	I^2t	t = 10ms	No voltage reappplied	Sinusoidal half wave, initial $T_J = T_J$ maximum	14500	A^2s
		t = 8.3ms			13500	
		t = 10ms	100% V_{RRM} reappplied		10500	
		t = 8.3ms			9400	
Maximum I^2Vt for fusing	I^2Vt	t = 0.1ms to 10ms, no voltage reappplied		16000		A^2Vs
Value of threshold voltage (up to 1200V)	$V_{F(TO)}$	$T_J = T_J$ maximum		0.68		Volts
Value of threshold voltage (1400V, 1600V)				0.69		Volts
Value of forward slope resistance (up to 1200V)	r_{FL}	$T_J = T_J$ maximum		1.62		m Ω
Value of forward slope resistance (1400V, 1600V)				1.75		m Ω
Maximum forward voltage drop	V_{FM}	$I_{pk} = 267A$, $T_J = 25^\circ\text{C}$, $t_p = 400\mu\text{s}$ rectangular wave		1.2	1.4	Volts
THERMAL CHARACTERISTICS						
Maximum junction and storage temperature range	T_J, T_{stg}			-65 to 180	-65 to 150	$^\circ\text{C}$
Maximum thermal resistance, junction to case	R_{thJC}	DC operation		0.35		K/W
Thermal resistance, case to heatsink	R_{thCS}	Mounting surface, smooth, flat and greased		0.25		K/W
Maximum allowable mounting torque (+0%, -10%)		Not lubricated threads		3.4 (20)		N-m (lbf-in)
		Lubricated threads		2.3 (20)		

85HF(R) Series

STANDARD RECOVERY DIODES
85 AMP


ΔR_{thJC} Conduction

Conduction angle	Sinusoidal conduction	Rectangular conduction	Test conditions	Units
180°	0.10	0.08	$T_J = T_{J \text{ maximum}}$	K/W
120°	0.11	0.11		
90°	0.13	0.13		
60°	0.17	0.17		
30°	0.26	0.26		

*The table above shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC

MECHANICAL CHARACTERISTICS

Case	DO-5 (R)
Marking	Alpha numeric 85HFR is an acceptable alternate prefix
Polarity	Cathode is stud
Reverse polarity	Anode is stud



	DO-5(R)			
	Inches		Millimeters	
	Min	Max	Min	Max
A	1/4-28 UNF2A threads			
B	0.669	0.688	16.990	17.480
C	-	0.794	-	20.160
D	-	1.000	-	25.400
E	0.422	0.453	10.720	11.510
F	0.115	0.200	2.920	5.080
G	-	0.450	-	11.430
H	0.220	0.249	5.580	6.320
J	0.250	0.375	6.350	9.530
K	0.156	-	3.960	-
M	-	0.667	-	16.940
N	0.030	0.080	0.760	2.030
P	0.140	0.175	3.560	4.450

85HF(R) Series

STANDARD RECOVERY DIODES 85 AMP




Fig. 1 - Current Ratings Characteristics




Fig. 3 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 4 - Current Ratings Characteristics

85HF(R) Series

STANDARD RECOVERY DIODES 85 AMP




Fig. 5 - Forward Power Loss Characteristics




Fig. 6 - Forward Power Loss Characteristics




Fig. 7 - Forward Power Loss Characteristics




Fig. 8 - Forward Power Loss Characteristics




Fig. 9 - Maximum Non-Repetitive Surge Current




Fig. 11 - Forward Voltage Drop Characteristics (up to 1200 V)




Fig. 10 - Maximum Non-Repetitive Surge Current




Fig. 12 - Forward Voltage Drop Characteristics (for 1400 V, 1600 V)




Fig. 13 - Thermal Impedance Z_{thJC} Characteristics