

P8894-I

This high-performance display, the first Philips solution to offer CIF+ resolution as supported by the Symbian Series 60 Platform, delivers superior LTPS TFT LCD performance. It has built-in low-power features and combines excellent color quality with a backlight to produce images that are readable in all conditions, even in direct sunlight.

Its 352 x RGB x 416 resolution displays all S60 Symbian software and applications at a sharpness that is higher than QCIF+ and QVGA displays, so email is easy to read, downloaded images are crisp and bright, and snapshots look great.

Philips has succeeded in reducing the module size by 25%, so the display takes up less room, enabling smaller phone form factors or freeing up space (for a larger battery, perhaps) in existing designs.



2.12" CIF+, 352 x RGB x 416

LTPS Transflective Display Module



SPECIFICATIONS

Mechanical

Width	41.20 mm
Height	53.80 mm
Module Thickness	3.05 mm
Weight	12.04 grams
Active Area	34.85 x 41.18 mm
Pixel Pitch	0.099 mm
Resolution	352 x RGB x 416
Pixel Configuration	RGB Vertical Stripe

Electrical

Technology	LTPS Active Matrix LCD
Supply Voltage	Logic 1.65V - 1.95V
	Analog 2.3V - 2.9V
Power Supply	14.4V
Consumption LED	216mW(serial)
BL Power Consumption	15 mA @ 14.4V (typ)
IC	R69600

Temperature Conditions

Operating	-30°C to +70°C
Storage	-40°C to +85°C

Interface

3-wire serial, 18 bit RGB

Optical

Image Mode	Normally White
Illumination Mode	Transflective
Backlight	4 LED's (white)
Color	262k
Response Time	30 ms (Ton + Toff)

Backlight ON

Contrast Ratio	125:1
NTSC (u'v')	40%
Viewing Angle Top-Down, CR>=2	>60°
Viewing Angle Left-Right, CR>=2	>60°
Luminance (module)	200 Cd/m ²
Uniformity	1.2

Backlight OFF

Reflectance Diffuse	6%
Contrast Ratio Diffuse	10:1
NTSC (u'v')	5%
Viewing Angle Top-Down, CR>=2	>60°
Viewing Angle Left-Right, CR>=2	>60°

APPLICATION INFORMATION

- Mobile Phones, TV-on-Mobile, Mobile Video Players

PRODUCT ADVANTAGES

- Superior transflective performance: sparkling colors, total readability even under direct sunlight
- LifePix™, a smart, embedded video-algorithm which renders the display to perceived color performance higher than 40%
- Twice the available pixels of any QVGA displays for ultra-sharp pictures, videos, games
- 25% reduction in module size
- Viewing angle performance equal in all directions

PHILIPS

P8894-I

2.12" CIF+, 352 x RGB x 416, LTPS Transflective Display Module


Pinning

PIN	SYMBOL	I/O	FUNCTION
1	XRES	I	Reset, active low
2	HS	I	Horizontal sync.
3	VS	I	Vertical sync.
4	D17(R5)	I	Data bus
5	D15(R3)	I	Data bus
6	GND	P	Ground (0 V)
7	D13(R1)	I	Data bus
8	D11(G5)	I	Data bus
9	D9(G3)	I	Data bus
10	D7(G1)	I	Data bus
11	GND	P	Ground (0 V)
12	D5(B5)	I	Data bus
13	D3(B3)	I	Data bus
14	D1(B1)	I	Data bus
15	SCL	I	Serial clock
16	GND	P	Ground (0 V)
17	VDDI	P	Supply voltage
18	VDD	P	Supply voltage
19	GND	P	Ground (0 V)
20	LEDIN	LED	LED current source
21	LEDOUT	LED	LED current sink
22	GND	P	Ground (0 V)
23	XCS	I	Chip select
24	DOUT	O	Serial data
25	DIN	I	Serial data
26	D0(B0)	I	Data bus
27	D2(B2)	I	Data bus
28	GND	P	Ground (0 V)
29	D4(B4)	I	Data bus
30	D6(G0)	I	Data bus
31	D8(G2)	I	Data bus
32	GND	P	Ground (0 V)
33	D10(G4)	I	Data bus
34	D12(R0)	I	Data bus
35	D14(R2)	I	Data bus
36	D16(R4)	I	Data bus
37	GND	P	Ground (0 V)
38	PCLK	I	Pixel clock
39	GND	P	Ground (0 V)
40	DE	I	Data enable



www.mds.philips.com

Block Diagram



CONTACT INFORMATION

Philips Mobile Display Systems

2/F, Philips Electronics Building

5 Science Park East Avenue

Hong Kong Science Park

Shatin, The New Territories

HONG KONG

Tel : (852) 2666 2888

Fax : (852) 2664 4183

©Koninklijke Philips Electronics N.V. 2005

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent - or other industrial or intellectual property rights.

date of release: May 2005

Published in Hong Kong

Philips confidential.

