

Constant Voltage Mode

CVH Range	0.000 ~ 120.0	V
CVM Range	0.000 ~ 60.00	V
CVL Range	0.000 ~ 12.00	V
Transient Time Range		
Fast Band(Default,Osc1)	0.500 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Temperature Coefficient	100 ppm / °C of Rated Voltage	

Program	CV Resolution*2	1/16000 of Rated Voltage
	CVH Accuracy*2	0.05% ± 0.120 V
	CVM Accuracy*2	0.05% ± 0.120 V
	CVL Accuracy*2	0.05% ± 0.120 V

Display	CVH Resolution	1/16000 of Rated Voltage
	CVH Accuracy	0.05% ± 0.120 V
	CVM Accuracy	0.05% ± 0.120 V
	CCL Accuracy	0.05% ± 0.120 V

Constant Current Mode

CCH Range	0.000 ~ 1,500	A
CCM Range	0.000 ~ 750.0	A
CCL Range	0.000 ~ 150.0	A
Transient Time Range		
Fast Band(Default,Osc1)	0.050 ~ 51.19	ms
Slow Band(Osc2,Osc3)	0.500 ~ 511.9	ms
Minimum Voltage(I _{Max})	0.600	V
Temperature Coefficient	100 ppm / °C of Rated Current	

Program	CC Resolution*2	1/16000 of Rated Current
	CCH Accuracy*2	0.05% ± 1.500 A
	CCM Accuracy*2	0.05% ± 1.500 A
	CCL Accuracy*2	0.05% ± 1.500 A

Display	CC Resolution	1/16000 of Rated Current
	CCH Accuracy	0.05% ± 1.500 A
	CCM Accuracy	0.05% ± 1.500 A
	CCL Accuracy	0.05% ± 1.500 A

Programmable Protection

Power(OPP)		
Range	31.50 ~ 25,200	W
Resolution	3.150	W
Accuracy	0.50% ± 63.00	W
Voltage(OVP)		
Range	0.079 ~ 126.0	V
Resolution	0.008	V
Accuracy	0.20% ± 0.158	V
Current(OCF)		
Range	0.984 ~ 1,575	A
Resolution	0.098	A
Accuracy	0.20% ± 1.969	A
Under Voltage Lockout(UVL)		
Mode	Input On / Continuous	
Range	0.090 ~ 120.0	V
Resolution	0.030	V
Accuracy	2.50% ± 0.150	V
Anti-Oscillation	Default / Osc1 / Osc2 / Osc3 / Disable	

Protection

Over Power Protection(OP)	25,200 ± 480.0	W
Over Voltage Protection(OV)	126.0 ± 2.400	V
Over Current Protection(OC)	1,650 ± 15.71	A
Over Temperature Protection(OTP)	50.00 ± 5.000	°C
Reverse Maximum Current(RCP)	1,650	A
Short Maximum Current	1,530	A
Remote Inhibit(RI)	Short	
Fault Indicator	SPDT Relay (30Vdc/0.5A or 125Vac/0.25A)	

Dielectric Strength

Primary Circuit To Chassis	1500 Vac for 1 min
Primary Circuit To Load Terminal	1500 Vac for 1 min
Load Terminal To Chassis	1500 Vdc for 1 min

Constant Power Mode

CPH Range	0.000 ~ 24,000	W
CPM Range	0.000 ~ 12,000	W
@ lin	≤ 750.0	A
CPL Range	0.000 ~ 2,400	W
@ lin	≤ 150.0	A
Transient Time Range	Same As CC Mode	
Temperature Coefficient	300 ppm / °C of Rated Power	

Program	CP Resolution*2	1/16000 of Rated Power
	CPH Accuracy*2	1.00% ± 120.0 W
	@lin	> 75.00 A
	& Vin	> 12.00 V
	CPM Accuracy*2	1.00% ± 120.0 W
	@lin	> 15.00 A
	& Vin	> 12.00 V
	CPL Accuracy*2	1.00% ± 120.0 W
	@lin	> 1.500 A
	& Vin	> 24.00 V

Constant Resistance Mode

CRH Range	0.8000 ~ 40.00	Ω
@ lin	≤ 150.0	A
CRM Range	0.0800 ~ 20.00	Ω
CRL Range	0.0004 ~ 0.0800	Ω
Transient Time Range	Same As CC Mode	
CRM / CRH	Same As CV Mode	
CRL	Same As CV Mode	
Temperature Coefficient		
CRM / H	300 ppm / °C of Minimum Resistance	
CRL	300 ppm / °C of Maximum Resistance	

Program	CR Resolution*2	1/16000 Of Rated Value
	CRH Accuracy*2	1.00% ± 6.250 mS
	@lin	> 1.500 A
	& Vin	> 24.00 V
	CRM Accuracy*2	1.00% ± 25.00 mS
	@lin	> 15.00 A
	& Vin	> 12.00 V
	CRL Accuracy*2	1.00% ± 0.080 mΩ
	@lin	> 150.0 A
	& Vin	> 0.120 V

External Programming Mode

Analog Program	0~10 Volts Input yields
	0~selected full scaled loading in all modes
Accuracy	Same As Internal ± 0.1% Rating
Input Impedance	400 kΩ ± 1 %
BandWidth(-3dB)	Limited By Internal Transient Time
Monitor output Signal	0~10 Volts output for 0~full scaled Value
VMON Accuracy	0.10% ± 0.120 V
IMON Accuracy	0.10% ± 1.500 A
Transient Mode	
Frequency Range	0.100 ~ 10,000 Hz
Accuracy	0.1%
Duty Range	1.000 ~ 100.0 %
Accuracy	0.1%
Transient Time Accuracy	10.0% ± 50% of Minimum Time
Remote Interface	GPIOB / RS-232 / ETHERNET / USB

General

Fluid	
Valve	Normal Close(Power On Thermal Control)
Flow Rate(Pmax)	≥ 6.0 GPM @ 15°C Fluid In
Derating for higher temperatures	(-)3% Rated Power / °C
Pressure	<80 PSI
Pipe Size	Dual 1/2"(3/4"-Manifold) NPT Female
Decondensation	Valve Thermal Control
AC Input	95~240 Vac 48~62 Hz
Power Consumption	160 VA
Operating Temperature	5 °C ~ 40 °C
Dimension	27.5"(L)x17"(W)x7.0"(H)

Weight	140 lbs	63.5 kg
Approx.Shipping Weight	160 lbs	72.6 kg

PLW24K-120-1500 (120V,1500A,24KW) OPERATIONAL CURVE

