




BARRETT COMMUNICATIONS
ADVANCED **HF SSB** EQUIPMENT



2075 High Power HF Transmitter

The Barrett 300-1000 Watt HF SSB Transmitter is a compact rack mounted unit developed for base applications in large HF networks. The transmitter comes as a complete package with exciter, power supply, RF power amplifier, interconnect cables and all rack mount hardware. The exciter is a Barrett 2050 transceiver with a 500 channel capacity and all mode capability.

The RF power amplifier is a rugged solid state unit with a comprehensive LCD display that displays the amplifier operating parameters. No tuning adjustments are required and the amplifier's ALC system protects the unit from severe mismatches. The separate switch mode power supply operates over a range of voltages from 110* to 250VAC and is fully protected against overloads.

Features

- All solid state
- Broadband 2-30MHz
- Instantaneous frequency changes
- No tuning adjustments
- 110* to 250VAC power supply, no switching required
- Meets CCIR specifications

Consists of

- Barrett 2050 HF Transceiver
- Barrett 2022 Power Supply Unit
- Barrett 2075 Linear Amplifier
- Barrett 2075 Power Supply Unit
- Cable (control) transceiver to linear
- Cable (coaxial) transceiver to linear
- Fan option to suit Barrett 2050 HF Transceiver (BCA20002)
- Rack mounting kit to suit Barrett 2050 and 2022 (BCA20007)
- 39U 19" rack cabinet for floor mounting or 18U 19" rack unit for desk mounting
- 19" Blanking panels and hardware

Technical Specifications

Frequency Range:	2-30MHz Broadband
Power Output:	Adjustable 300-1000 Watt PEP SSB, 1000 Watt Avg. FSK, CW
Duty Cycle:	50%
Intermodulation Distortion:	-30dB typical
Harmonics and Spurious:	-50dB
Output Impedance:	50 Ohms < 2:1 VSWR
Primary Voltage:	110*/250VAC
Dimensions 39U rack unit:	1886(h) x 600(w) x 700(d)
Dimensions 18U rack unit:	953(h) x 600(w) x 700(d)
Weight 39U rack unit:	143Kg
Weight 18U rack unit:	102Kg

*Note :- at 110VAC input the 2075 transmitter will produce 500W PEP maximum power output.

Head Office:

Barrett Communications Pty Ltd
P O Box 1214, Bibra Lake WA 6965 AUSTRALIA
Toll Free Tel: 1800 999 580 Tel: +61 (0) 8 9434 1700 Fax: +61 (0) 8 9418 6757
email: information@barrettcommunications.com.au

European Office:

Barrett Europe Limited, Unit 9, Fulcrum 2, Victory Park, Solent Way, Whiteley,
PO15 7FN UNITED KINGDOM
Tel: (44) 1420 542254 Fax: (44) 1420 543373
email: information@barretteurope.co.uk

Americas Office:

Barrett USA LLC 15941 W. 65th Street
Suite 373, Shawnee, Kansas 66217 USA
Tel: +1 913 322 6231 Fax +1 913 273 0779
email: information@barrettusa.com



www.barrettcommunications.com.au

BCB20750/4

ISO 9001
BUREAU VERITAS
Certification
No 149438



BARRETT COMMUNICATIONS 2000 SERIES