

FURMAN
PURIFY YOUR POWER

the
IT-REFERENCE 15



The IT-Reference 15 Features

- Discrete symmetrical balanced power cancels hum-inducing noise
- Power Factor correction provides surplus current for power-starved amplifiers
- Linear Filtering Technology for unequaled audio / video clarity
- Series Multi-Stage Protection Plus provides virtually maintenance-free AC surge suppression
- Detachable surge suppression module for telco and cable / satellite connectors

Introduction

For over 31 years, Furman has pioneered the development of AC power products for the most demanding audio, video, and broadcast professionals. Though the need for pristine AC power is nothing new, the IT-Reference 15's technology and its unique implementation are revolutionary and without peer.

The extreme AC demands encountered in the professional audio/video arena have required technological developments far in excess of typical home theater/audiophile power products. In studios, live sound, and broadcast facilities, breakdown is unacceptable. Equipment failure or poor performance is costly. The same is true of today's home theater. Our solution based technology, extensive engineering expertise, and robust build quality have answered the challenge of today's corrupted power lines, and led to the creation of the IT-Reference 15.

Today's AC lines are plagued with ever increasing noise. When AC noise couples into your system's critical components, it masks low level signals and cripples performance. This low level content is critical because it relays the crucial harmonics and ambience in audio, and depth and clarity in video. With the IT-Reference 15's exclusive Discrete Symmetrical Power, video screens, projectors, CD-DVD players, pre-amplifiers, and scalars are fed either linearly-filtered ultra-low-noise power, as well as symmetrically balanced power. This dramatically reduces AC noise, ensuring peak operation of your critical components. For the first time, you will see and hear your theater or

audio system as it should be – uncompromised.

Further, our Discrete Symmetrical Power features total isolation between the filtered-high current outlets, and the isolated symmetrical balanced power AC outlet banks. This positively breaks noise-inducing ground loops, hum bars, and power supply backwash between critical interconnected equipment, all without compromising electrical safety. This enables a plasma, LCD screen, or video projector to function without AC ground contamination from an audio processor or power amplifiers.

The IT-Reference 15 also employs our unique Power Factor Correction Circuit. For the first time, low-level analog, digital, and video components are not modulated or distorted via the power amplifier's extreme AC current demands. Further, the power amplifier sees a highly filtered, extremely low-impedance supply of AC power. The IT-Reference 15, in fact, has in excess of 4 Amps of continuous current reserve (over 55 amps peak charge) for the most extreme peak power demands. This technology enables power amplifiers and powered subwoofers to work at peak efficiency and reach levels of performance previously unattainable.

No longer will your amplifier's performance be at the mercy of your home's incoming AC power or inferior AC protection/filtering devices. The net effect is as if your power amplifier has nearly doubled in power and improved immeasurably in quality. When employing the IT-Reference 15 you will immediately notice far clearer, stunningly

focused sound and visual images from your system. Video presentation will be crisp and colors true with greater gray and black scale definition, as well as noticeably improved depth and clarity. Sonic transients will be startlingly fast with bass fundamentals that shake foundations with their weight and visceral impact. Mid and high frequencies will bloom with sweet, non-glaring ease while imaging improves dramatically, all the while remaining true to your system's inherent virtues.

Installation:

Unpacking

Before unpacking your unit, inspect the carton for any obvious severe damage to the box and internal protective materials. If internal damage is likely, contact the carrier who delivered the unit before proceeding with unpacking. If, after unpacking, shipping damage is evident, contact the carrier. Save all shipping and packing materials. You may need them if you should ever have to return the unit to the factory for servicing.

The box should contain the IT-Reference 15 unit, detachable AC cord, rack mount kit, owner's manual, and warranty registration card. If anything is missing, please contact Furman Customer Service. Fill out and return your warranty registration card. Registration is recommended because it can be used to establish whether the unit is within the warranty period should your original ownership documents be lost, and it assists us in informing you about upgrades or other vital information.

Safety Information - Warnings

Please read and observe all of the safety and operating instructions before the IT-Reference 15 is operated. Retain these instructions for future reference.

- Do not disassemble or modify in any way. No user-serviceable parts inside
- Keep away from moisture and avoid excessive humidity
- Do not allow liquids or foreign objects to enter the unit
- Household lighting equipment may not be connected to the IT-Reference 15 because their sockets are not designed for use with balanced symmetrical power and may present a shock hazard. We recommend that only audio, video and computer processing equipment be connected to the IT-Reference 15.

The IT-Reference 15 should be serviced by qualified service personnel when:

- The power supply cord or plug has been frayed or cut.
- Objects have fallen or liquid has spilled into the unit.
- The IT-Reference 15 has been exposed to rain or other moisture.
- The IT-Reference 15 does not appear to operate normally, or exhibits a marked change in performance.
- The IT-Reference 15 has been dropped, or the enclosure damaged.

The IT-Reference 15 requires that a safety ground be present for proper operation. Any attempt to operate the IT-Reference 15

without a safety ground is considered improper operation and will invalidate the warranty.

Power Source

The power source to which the IT-Reference 15 is connected should be adequate for use at 15 Amps. The IT-Reference 15 will operate with a 10 Amp service outlet; however, nuisance tripping at the circuit breaker panel may result if the system's continuous current draw exceeds 9 Amps.

Placement

The IT-Reference 15 is manufactured with four rubber feet for placement on any table, cabinet, shelf, or floor capable of supporting its 53lbs weight. These rubber feet may be easily removed with a standard Philips screw driver when rack mounting adjacent to other components. Because of the IT-Reference 15's internal shielding, placement or proximity to other components is not critical, and the IT-Reference 15 does not produce any appreciable heat under standard use. The IT-Reference 15 may also be rack mounted in a standard 19" rack by attaching the IT-Reference 15 rack ears. These rack ears (contained within the plastic rack kit package) mount flush with the back portion of the IT-Reference 15's front panel. They are attached to the chassis by removing the (2) countersunk screws on each forward-side of the chassis top cover. Each rack ear is installed with (3) pan-head Philips screws contained within the IT-Reference 15 rack mounting kit. The third screw used for each rack ear is for the center hole, located towards the rear and aids in stabilizing the unit when rack mounted.

Connection:

AC Cable Routing

Once the IT-Reference 15 is placed, its AC cord's female end must be plugged into the male IEC connector located on the lower left hand side of the rear panel (when facing the rear panel). Next the male Edison plug must be connected to an appropriate socket (see current rating recommendation above).

Connecting Components to the Symmetrical Power Banks

The IT-Reference 15's two "Symmetrically Balanced Power Outlets" should be employed for critical video components such as DVD players, projectors, Plasma, or LCD video screens. When employing the IT-Reference 15 for a 2-channel audio system, a pre-amplifier and/or CD player would be ideally suited for these outlets.

Connecting Components to the Linear Filtering Power Banks

The IT-Reference 15's four rear panel and one front panel "Linear Filtering Power Outlets" should be employed for any component not connected to the two "Symmetrically Balanced Power Outlets," with the exception of receivers, power amplifiers and powered sub-woofers. These outlets, though neither isolated or balanced, still possess incredible filtering to maximize system performance through vast AC noise reduction.

Connecting Components to the High Current Power Amplifier Banks

All power amplifiers, receivers and powered

sub-woofers should be connected to these four outlets.

Many Audiophile and premium Home Theater systems will have combined continuous current demands below 15 Amps. It is rare, in fact, for large power amplifiers to draw more than 4 Amps continuously. For superior performance, it is vital that an AC filter possess extraordinarily low impedance, and have the capability to pass peak current demands far in excess of the RMS (continuous) current rating.

The IT-Reference 15 was designed to more than meet this demand. Additionally, our Power Correction Circuitry effectively creates a current reserve in excess of 55 amps peak up-charge that is cleaner and faster than a dedicated line from your local power station. This feature eliminates any concern towards the current compression that can result from typical power conditioners, and the peak power reservoir benefits any power amplifiers performance dramatically.

Note about Power Factor Correction and Current Consumption

When power correction technology is employed with even the most sophisticated circuit breakers, it effectively adds to the perceived current load. Though the IT-Reference 15 was designed for steady 15 Amp operation, and peak current demands many times that, the maximum total continuous current draw may be limited to a range between 1300 - 1700 Watts per IT-Reference 15 employed.

The RMS current available before the circuit

breaker trips varies due to what is referred to as a vector load. Simply put, the type of power supplies or electronic circuits connected to the IT-Reference 15 will have an effect on its circuit breakers perceived current load, and therefore, when it will trip. Though the benefits of power factor correction far outweigh the small reduction in continuous current draw, this must be accounted for when constructing a large system with high current demands.

The total continuous current draw of most electronic components is typically listed in Watts by their AC input cord or AC connector. Watt ratings are simply added to determine the total system RMS current draw. It should also be noted that the IT-Reference 15's power correction circuitry has no actual effect on the power drawn from your utilities' power meter. The IT-Reference 15 draws a mere 8.5 Watts independent of other components, so it may be left on at all times.

Soft Start - Continuous Use and Break-In Time

When power is first applied to the IT-Reference 15, (the front panel breaker- power toggle must be switched to the "on" position) the Soft Start feature is activated. There is an audible "clack" when the IT-Reference is first turned on or off. This sound is produced by the Soft Start circuit's 30 Amp relay engaging or disengaging. There is virtually nothing in the IT-Reference 15's construction, design, or componentry to wear over the life time of the product, and there is no power draw from your electric service meter aside from the LED power indicator, relay, and GFCI protection circuit. For this reason the IT-Reference 15 may

be left with its power engaged permanently at a cost of pennies per month. This is an added benefit, as many audio/videophiles find performance improves significantly when leaving low-powered components permanently charged (turned on). In fact, this is true of the IT- Reference 15. Though it will function flawlessly right from its shipping carton, the performance of its circuit parts will improve after approximately two weeks of continuous use or “break-in.”

Ground Fault Interrupter (GFCI)

The IT- Reference 15's “Discrete Symmetrical Filtered AC outlets” incorporate a balanced AC power output, whereby both the neutral and positive leads of the AC cable run at 60 Volts AC in opposing polarity, referenced to ground (0 Volts AC). This is but one of the IT- Reference 15's advantages over other AC-filter/protection designs.

Though virtually all domestically produced electronic equipment is designed to detect electrical shorts and other potentially dangerous equipment problems in the Line lead referenced to its Neutral, this is inadequate when power is “balanced.” With the IT-Reference 15's balanced outlets, both neutral and positive legs contain 60 VAC relative to their Ground tab. This is not a problem or safety hazard, unless there is a defect in either the IT- Reference 15's transformer, or the power supply of a connected component. In this instance, we need to assure that safety is always maintained. The solution is our GFCI (ground fault circuit interrupter).

The Furman GFCI detects any imbalance in the current flowing in the two hot legs. The missing current is presumed to be flowing through the ground conductor (the round pin on an AC outlet). Ground current often indicates a dangerous partial or full short circuit. If an imbalance is detected, the GFCI will trip the outlets internal breaker, and the Duplex AC outlet will no longer supply AC power of any sort. To restore operation, correct the fault, press the reset tab located between the two balanced AC outlets. 5 mA of current is enough to cause the GFCI to trip; to troubleshoot this type of problem, start with nothing connected to the IT-Reference 15's balanced power outlets. Then, add each piece of equipment until the GFCI trips. Contact the manufacturer of the suspect unit for possible solutions.

AC Transient Voltage Surge Suppression and Extreme Voltage Shutdown

Extreme Voltage Shutdown Indicator:

This LED is normally off. It monitors AC wiring faults – for example, accidental connection to an open neutral from a 208 or 240VAC feed (this is a common occurrence if the 15 Amp outlet source is not a dedicated line, but instead has been wired with a daisy-chained neutral from a homes breaker box). The Series Multi-Stage Protection Plus (SMP+) circuit senses voltages that are so high that operation would be impossible and shuts the power down before damage can occur. Upon initially applying power to these units, the Extreme Voltage indicator LED will light if the input voltage is above the extreme voltage cutoff, and power will not be applied to the unit's

outlets. If the unit has been operating with an acceptable input voltage and subsequently that voltage exceeds 137V, it will shut off power to the outlet and the Extreme Voltage LED will light.

Protection OK Indicator:

Although the Furman SMP+ circuit assures virtually maintenance free protection from transient voltage spikes and surges, nature has a way of occasionally creating electrical forces that are beyond the capabilities of any Transient Voltage Surge Suppression device to absorb without some degree of damage. In the rare instance that this occurs, the blue LED located in the center of the front panel will dim, even though AC power is present at the unit's outputs. If this happens, some level of protection from voltage surges will remain, but the Furman's clamping voltage rating will be compromised. The unit must be returned to Furman Sound, or an authorized Furman Service center for repair.

NOTE: If the mains power is above the high cutoff voltage and has caused the unit to remove power from its outlets, it cannot restore power without the operator manually turning the unit off, then on again. Avoid turning the unit back on, without first checking the source of the problem, and perhaps changing the AC source.

Telco – Satellite – Cable Transient Voltage Surge Suppressors

The IT- Reference 15 features transient voltage surge suppression for both standard telephone lines, as well as cable or satellite lines utilizing standard coaxial connectors. As these surge

suppressors are in-line, they will require an additional cable to connect from their output to the control device requiring protection.

All in-line surge suppressors feature our exclusive ground contamination free technology. This aids in eliminating audio buzzing, and the video hum-bars that can result from typical in-line suppressors. Further, our cable and satellite suppressors are TIVO friendly as well as HD-Digital Television ready. Both DC carrier signals as well as high bandwidth signals can pass through our circuit. In fact the bandwidth is less than 0.1dB loss at 1GHz!


To connect your cabling to these in-line protectors, simply follow the in and out indications marked next to the Telco, Cable and Satellite connectors.

Note: It is not possible to make an in-line cable or satellite protector "virtually maintenance-free" as we have accomplished with the 120 VAC line. This would necessitate limited signal bandwidth that would not allow the signal to pass. Under extreme conditions, it is possible that the surge suppression in one of these devices could sacrifice itself after a catastrophic event. If the telephone, cable or satellite signal will no longer pass through our protector, please contact your local service representative, installer or Furman for servicing. Since these circuits are modular, replacement may be accomplished in seconds with a new TVSS module. To test this, simply disconnect the incoming and out going cable from the IT-Reference 15. Connect the incoming connector to the component that

IT-REFERENCE 15 OWNER'S MANUAL

formerly received the out going connector, thus by-passing the in-line protection. If the signal is present (but not when used with the IT-Reference 15) then the protection circuit is damaged (assuming it worked properly before a storm or catastrophic event).

Suggested AC Connection



Warranty

Furman Sound, Inc. warrants to the original purchaser of this product, the Furman IT-Reference 15, that the product will be free from defects in material and workmanship for a period of five years from the date of purchase. The purchaser of the product is allowed fifteen days from the date of purchase to complete warranty registration by mail or on-line at the Furman website. If the purchaser fails to complete the aforementioned registration, the warranty period will be reduced to one year from the date of purchase.

If the product does not conform to this Limited Warranty during the warranty period (as herein above specified), purchaser shall notify Furman in writing of the claimed defects. If the defects are of such type and nature as to be covered by this warranty, Furman shall authorize the purchaser to return the product to the Furman factory or to an authorized Furman repair location. Warranty claims

should be accompanied by a copy of the original purchase invoice showing the purchase date; this is not necessary if the Warranty Registration was completed either by mailing in the completed warranty card or by registering on-line at the Furman website. Shipping charges to the Furman factory or to an authorized repair location must be prepaid by the purchaser of the product. Furman shall, at its own expense, furnish a replacement product or, at Furman's option, repair the defective product. Return shipping charges back to purchaser will be paid by Furman.

CONNECTED EQUIPMENT WARRANTY: Furman Sound's Connected Equipment Warranty covers equipment that is damaged by transient voltage (an "Occurrence") while properly connected through the Furman IT-Reference 15 to a properly wired AC power line with a protective ground in an indoor location. Furman's Connected Equipment Warranty is limited to the amount of the deductible on the Purchaser's personal property insurance policy up to \$500.00. In order to make a claim for this

Connected Equipment Warranty, the Purchaser must forward a copy of his/her personal property insurance claim for the damaged equipment to Furman and complete the Furman Connected Equipment Warranty claim form (call Furman at (707) 763-1010 to obtain the form). Furman reserves the right to review the damaged Furman product, the damaged connected equipment, and the site where the damage occurred. All cost of shipping damaged equipment to Furman for inspection shall be borne solely by the Purchaser. Damaged equipment must remain available for inspection until the claim is finalized. The Connected Equipment Warranty is also in effect for a period of five years unless the Purchaser does not complete the warranty registration within fifteen days from date of purchase, at which time, the Connected Equipment Warranty period is also reduced to one year from the date of purchase.

All warranties contained herein are null and void if: the Furman Surge Protector in use during the occurrence is not provided to Furman for inspection upon Furman's request at the sole expense of the Purchaser, Furman determines that the Furman Surge Protector has been opened, improperly installed, altered in any way or tampered with, Furman determines that the damage did not result from the Occurrence or that no Occurrence in fact took place or Furman determines that the connected equipment was not used under normal operating conditions or in accordance with Manufacturer's instructions for the connected equipment. All Furman Surge Protectors must be plugged directly into a properly wired AC power line with a protective ground and must not be "daisy-chained" together in serial fashion with other power strips, UPS's, other surge protectors, three-to-two-prong adapters, or extension cords. Any such installation voids this warranty. The Furman warranty only protects against damage to properly connected equipment where Furman has determined, at its sole discretion, that the damage resulted from an Occurrence and does not protect against acts of God (other than lightning) such as flood, earthquake, war, terrorism, vandalism, theft, normal-use wear and tear, erosion, depletion, obsolescence, abuse, damage due to low-voltage disturbances (i.e. brownouts or sags), non-authorized program, or system equipment modification or alteration. Do not use this product in anyway with a generator, heater, sump pump, water-related device, life support device, medical device, automobile, motorcycle, or golf-cart battery charger. To be used indoors only and in dry areas. All warranties contained herein are null and void if used in anyway with

any of the aforementioned devices.

THE FOREGOING IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Furman does not warrant against damages or defects arising out of improper or abnormal use or handling of the product; against defects or damages arising from improper installation, against defects in products or components not manufactured by Furman, or against damages resulting from such non-Furman made products or components. This warranty shall be cancelable by Furman at its sole discretion if the product is modified in any way without written authorization from Furman. This warranty also does not apply to products upon which repairs have been affected or attempted by persons other than pursuant to written authorization by Furman.

THIS WARRANTY IS EXCLUSIVE. The sole and exclusive obligation of Furman shall be to repair or replace the defective product in the manner and for the period provided above. Furman shall not have any other obligation with respect to this product or any part thereof, whether based on contract, tort, strict liability, or otherwise. Under no circumstances, whether based on this Limited Warranty or otherwise, shall Furman be liable for incidental, special, or consequential damages. Furman's employees or representatives' ORAL OR OTHER WRITTEN STATEMENTS DO NOT CONSTITUTE WARRANTIES, shall not be relied upon by purchaser, and are not a part of the contract for sale or this limited warranty. This Limited Warranty states the entire obligation of Furman with respect to the product. If any part of this Limited Warranty is determined to be void or illegal, the remainder shall remain in full force and effect.

Warranty claims should be accompanied by a copy of the original purchase invoice showing the date of purchase (if a Warranty Registration Card was mailed in at the time of purchase or if the product was registered on-line, this is not necessary). Before returning any equipment for repair, please be sure it is adequately packed and cushioned against damage in shipment, and that it is insured.

IT-Reference 15 SPECIFICATIONS

AC Current Capacity:

Input - 20 Amp capacity required

Output - 11 - 15 Amp RMS * (maximum, all outlets combined - continuous)

* (Due to the Power Factor Correction circuit, available RMS power varies with the reactance of the load (vector). However, this only affects the circuit breaker for continuous RMS current draw. Since power amplifiers will require high transient current demands, the IT-Reference 20 will never succumb to current compression. Quite the opposite, in fact, it will buffer the power amplifier's power supply, while lowering the AC input impedance, allowing power amplifiers to work more efficiently.

Linear Noise Attenuation:

Transverse (Differential) Mode: >40 dB from 10Khz. - 100 kHz. >80 dB from 100 kHz. - 1GHz.

(Linear attenuation curve from 0.05 - 100 ohms line impedance)

Common Mode: >90 dB, 10Hz. - 50 kHz. >40 dB 50kHz. - 1MHz.

Outlets:

2 (symmetrical balanced outlets)

5 (linearly filtered outlets)

4 (power factor corrected outlets - 4 amps RMS reserve - resistive load - over 55 amps peak charge)

Transient Voltage Surge Suppression:

120VAC Line - Zero Ground Contamination. (188V peak clamping @ 6000V 3000A input)

Telco Cable / Satellite (less than .1dB line loss)

Dimensions:

4" H x 17" W x 16.25" D (standard 2RU without feet)

Weight:

53 lbs.

Power Consumption:

8.5 Watts for display and control circuits independent of actual load.

Safety Agency Listing:

C-ETL (pending)

FURMAN

Furman Sound, Inc.
1997 South McDowell Blvd.
Petaluma, California 94954-6919 USA
Phone: 707-763-1010 Fax: 707-763-1310
Web: www.furmansound.com
E-mail: info@furmansound.com