

STORAGE

Mobile

Desktop

Enterprise

THE POSSIBILITIES ARE INFINITE

FUJITSU



Optical

The DynaMO® Family of Magneto-Optical Removable Storage Drives

The DynaMO series of magneto-optical drives feature fast, innovative technologies with capacities of up to 1.3 gigabytes at an affordable price.

- Available in a multitude of interfaces—FireWire, Ultra SCSI, USB and ATAPI
- Data transfer rates up to 5.9 MB/sec
- Up to 20 MB/s interface
- Dust, liquids and magnets do not affect data stored on MO disks
- Unlimited rewrite capability on MO disks
- Drives are backward compatible with 1.3GB, 640MB, 540MB, 230MB or 128MB media

Fujitsu takes the convenience of magneto-optical (MO) technology to exciting new levels with the DynaMO family of removable storage drives. Featuring the FireWire DynaMO 1300FE/640FE, SCSI and USB external DynaMO 1300SF+USB/640SF+USB, SCSI internal DynaMO 1300SZI/640SZI and ATAPI DynaMO 640AI. These state-of-the-art drives feature various interfaces—FireWire, ATAPI, USB and SCSI—the highest performing and easiest-to-use external drive interfaces on the market today. The speed and simplicity of these drives partnered with the reliability and backwards compatibility of MO technology make the 1.3GB DynaMO 1300 and 640MB DynaMO families superior removable storage solutions.

High-Performance Storage

The DynaMO external and internal drives provide high-capacity, high-reliability storage. The 400 Mbits/sec. DynaMO FireWire interface is 2.5 times faster than Ultra SCSI. Offering up to 5.9MB/sec. data transfer rates and up to 1.3GB of

storage, these DynaMO drives are perfect for capturing video, audio, large graphic files and other demanding applications.

Protecting Investments in Data

Fujitsu 3.5-inch MO disks are extremely rugged and highly tolerant of the problems that plague magnetic media. Shock, vibration, moisture, dust and magnetic fields won't destroy data stored on a MO disk. Each disk comes with a lifetime warranty and because of their ruggedness, they make the perfect medium for office, home or industry.

Multiple Disk Options

The DynaMO external and internal drives are read/write compatible with all ISO compliant, 3.5-inch disk capacities: 640MB, 540MB, 230MB and 128MB, as well as Over-Write disks. Using Over-Write disks can increase write performance by up to 33%. The DynaMO 1300FE/SF+USB/SZI drives can also read and write to 1.3GB GIGAMO standard disks. No other storage solution offers as many options to tailor the media selection to the application while providing such a high level of investment protection and affordability.

About Fujitsu Computer Products of America, Inc.

Fujitsu Computer Products of America, Inc. is a wholly owned subsidiary of Fujitsu Limited, one of the world's largest computer companies with \$49.6 billion in worldwide revenue in fiscal year 2000. Benefiting from Fujitsu Limited's \$3 billion annual investment in research and development, FCPA provides innovative solutions for the U.S. marketplace. Current product offerings include high-performance disk drives, tape drives, magneto-optical drives, high-volume scanners, and printers.

DynaMO Family Product Specifications

Model		DynaMO 1300SF/1300 SZI/1300 USB/ 640SF/1300FE/640FE/640 AI/640 USB			DynaMO 1300FE/ SF/SZI/USB
Functional Specifications					
Storage capacity by disk		128MB	230MB	540MB	640MB
Standard		ISO/IEC 10090	ISO/IEC 13963	ISO/IEC 15041	GIGAMO
Sector capacity		512 bytes		2,048 bytes	
Format			90 mm		
Data transfer rate (max.)	Drive	640 SF-USB/ FE/AI/SZI	1.1 MB/s	1.3-2.1 MB/s	2.3-3.9 MB/s
		1300 SF+USB/ FE/SZI	1.3 MB/s	1.6-2.6 MB/s	2.9-4.9 MB/s
Interface					
Ultra SCSI	1300SZI/ 640SZI		5 MB/s (async.)	20 MB/s (sync.)	
IDE (ATAPI)	640 AI		16.6 MB/s (PIO Mode 4/DMA Mode 4)		N/A
Ultra SCSI	1300SF+USB/ USB 1.1	640SF+USB	Ultra SCSI, 5 MB/s (async.)	20 MB/s (sync.)	
			USB 1.1, 12 Mbits/s		
IEEE 1394	1300FE/ (FireWire)	640FE		400 Mbits/s	
Recording density (BPI)		24,400	29,300	52,900	89,100
Track density (TPI)		15,875	18,275	23,090	28,200
Random Seek time			28 ms		
Average latency time			8.3 ms (640) / 6.6 ms (1300)		9.3 ms
Rotational speed		3,600 RPM (640SF/SZI/FE/AI) / 4,500 RPM (1300)		3,214 RPM	
Recording code		2-7 RLL		1-7 RLL	
Load/unload time		7 sec. (640) / 8 sec. (1300)		12 sec.	
Buffer size			2 MB		
Physical Specifications					
Power requirements	AC adapter	1394 power	100-240 V AC	8-33 V DC (2 amp min.)	
(H x W x D)	1300SF+USB/640SF+USB	1300FE/640FE	1300SZI/640SZI/640AI	33.5 mm x 122 mm x 224 mm	33 mm x 121.5 mm x 225 mm
				25.4 mm x 101.6 mm x 150 mm	
Weight	1300SF+USB/640SF+USB	1300FE/640FE	1300SZI/640SZI/640AI	1000 g or less	900 g or less
				480 g (with bezel)	
Ambient temperature	Operating	Non-operating	Gradient	5°C - 35°C	0°C - 50°C
				15° C/h (operating)	
Relative humidity				10% - 85% (non-condensing)	
Vibration	Operating	Non-operating		0.4 G (5 to 500Hz)	1.0 G (5 to 500Hz)
Shock	Operating	Non-operating		2.0 G (10 ms)	50.0 G (10 ms)
Altitude	Operating	Non-operating		3,000 m	12,000 m
Limited Warranty	1 year (from date of purchase) / No Excuses End User Replacement Program available for certain purchasers. Visit www.fcpa.com for full details and restrictions.				

© 2000 Fujitsu Computer Products of America, Inc. All rights reserved. Fujitsu Computer Products of America, Inc. offers a limited warranty on selected consumer products distributed through authorized distribution channels. United States resident end-users who have originally purchased products covered under the limited warranty not for resale may be eligible to participate in the No Excuses End User Replacement Program. Certain restrictions apply to the limited warranty and the No Excuses End User Replacement Program; for full details go online at www.fcpa.com or call 800-626-4686. All statements herein are valid only in the U.S. for U.S. residents, are based on normal operating conditions, are provided for informational purposes only, and are not intended to create any express or implied warranty. Fujitsu Computer Products of America, Inc. reserves the right to modify at any time without prior notice these statements, our products, their performance specifications, availability, price, and warranty and post-warranty programs, including the addition or deletion of covered products. Fujitsu and the Fujitsu logo are registered trademarks of Fujitsu Limited. DynaMO is a registered trademark of Fujitsu Computer Products of America, Inc. FireWire is a trademark of Apple Computer, Inc. All other trademarks mentioned herein are the property of their respective owners.



FUJITSU COMPUTER PRODUCTS OF AMERICA, INC.
2904 Orchard Parkway
San Jose, CA 95134-2009
(800) 626-4686
(408) 432-6333
Web site: <http://www.fcpa.com>
Email: info@fcpa.fujitsu.com