

hp StorageWorks Cable Management Spool Option Kit

Version: 1.0

Read instructions completely before beginning the installation procedure



© Copyright 2003 Hewlett-Packard Development Company, L.P.

Hewlett-Packard Company makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

This document contains proprietary information, which is protected by copyright. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard. The information contained in this document is subject to change without notice.

Product names mentioned herein may be trademarks of their respective companies, as reflected by an associated footnote.

Hewlett-Packard Company shall not be liable for technical or editorial errors or omissions contained herein. The information is provided "as is" without warranty of any kind and is subject to change without notice. The warranties for Hewlett-Packard Company products are set forth in the express limited warranty statements for such products. Nothing herein should be construed as constituting an additional warranty. Printed in the U.S.A.

Cable Management Spool Option Kit Installation Instructions First Edition (October 2003) Part Number: EK-CMSOK-IG. A01

About this Document

This document provides instructions for installation of cable management spools on the internal mounting rail of the Enterprise Virtual Array 5000 cabinet.

Installing the Cable Management Spool Option Kit

A flathead screwdriver is the only tool required to complete this procedure.

Use the following procedure to install the cable management spool in the Enterprise Virtual Array 5000 cabinet.

- 1. Unlock the twist lock on the cable management spool with a flathead screwdriver.
- 2. Position the spool so that the twist lock is inserted into the internal mounting rail hole, as shown in Figure 1.




Figure 1: Positioning the spool

3. Secure the cable management spool to the internal mounting rail by locking the twist lock into place with the flathead screwdriver, as shown in Figure 2.




Figure 2: Securing the spool to the rail

4. Wrap the cables around the spool, as shown in Figure 3.




Figure 3: Wrapping the cables

5. Secure the cables to the spool by snapping the rubberbands into place, as shown in Figure 4.




Figure 4: Securing the cables on the spool

Installation is complete.