Reservations on Explicit Paths with RSVP

Roch Guérin Sanjay Kamat Eric Rosen IBM Corp. IBM Corp. Cisco Systems

(draft-guerin-expl-path-rsvp-00.txt)

Outline


- Why is explicit route support in RSVP useful?
 - Benefits in MPLS environment
 - Benefits to QoS routing
- What does it means for RSVP?
- Summary and extensions

Scope and Motivations

- Why explicit routes?
 - Provisioning for and differentiating traffic from different users with MPLS
 - Tighter and simpler control of path and resource usage with QoS routing
- But also want ability to reserve resources on explicit routes
 - Would rather not invent another protocol
 - RSVP is obvious candidate but some extensions are needed
- → Allow reservations on explicit routes using RSVP with the *least* impact

Explicit Routes and Resource Reservation with MPLS

• Sample ISP network



- ISP provisioning requirements:
 - 1. Packets from S1 on A-B-E-F-D, and packets from S2 on B-C-D
 - 2. Reserve resources for each "flow"
- MPLS enables 1
- Use of RSVP for 2 requires that RSVP PATH messages follow explicit (MPLS) path

Explicit Routes and Resource Reservation with QoSRouting

- QoS routing tries to pick paths that "best" match flow (and network) requirements
- Explicit routes make sure the path actually followed is the one that was selected (single vs multiple decision points)
 - Eliminates loop problem
 - Simpler accounting of existing reservations
 - Tighter control of actual usage of network resources
- Explicit routes facilitate enforcement of high level admission control policies

RSVP Extension - Explicit Route Object

- RSVP carries opaque object specifying explicit route generated by path selection
 - Exact object(s) format to be finalized, but should support IPv4 and IPv6 addresses, path recording ability, simple parsing, possible "expansion", etc.
- RSVP passes object to routing (together with other relevant information)
- Routing returns (modified) outgoing route object along with next hop information

Summary

- Reservations on explicit routes supported with RSVP through addition of opaque routing object
 - Passed to routing by RSVP
 - Returned to RSVP by routing with next hop information
- Maintains decoupling between RSVP and routing but enables support of wide range of routing mechanisms
 - Of benefits to MPLS and QOS routing
- Follow-up
 - Finalize definition of explicit route object(s)
 - Loose source routes and error scenarios
 - Possible combination with path setup for MPLS