

KM-1635

MONOCHROME A3 DIGITAL COPIER WITH PRINTING OPTION

► print ► copy ► scan ► fax

PRODUCTIVE WORKGROUP COPIER WITH MORE INSIDE THAN MEETS THE EYE.

Where efficiency and productivity are essential to your workgroup environment, this fast multifunctional device will deliver every time. Numerous digital copy functions and paper handling options make the KM-1635 the perfect office partner. As an added bonus the GDI printing option turns your digital copier into an affordable printer.

- 16 pages per minute in A4, 8 pages per minute in A3
- Optional GDI printer functionality
- Time to first copy: 5.9 seconds from power on
- 32MB RAM for full digital functionality including scan-once-print-many
- Optional reversing document processor for up to 50 sheets
- Optional duplex unit
- Long-life components, easy maintenance

Product depicted includes optional extras



Fill trays less frequently and use multiple paper types by adding paper capacity of up to 1,250 sheets.

The optional GDI functionality allows printing from any Windows PC.



KM-1635

MONOCHROME A3 DIGITAL COPIER WITH PRINTING OPTION

The KM-1635 incorporates extremely durable components that guarantee smooth and reliable operation. The device is designed to last for extremely long hardware maintenance cycles. Thus, the KM-1635 keeps your overall operating costs low and productivity high – at the same time ensuring minimum impact on the environment.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speeds: Max.16/8 pages per minute A4/A3
Resolution: 600 x 600 dpi, 256 greyscales
Time to first copy: 5.9 seconds or less
Warm-up time: 20 seconds or less from power on
Power source: AC 220 ~ 240V, 50/60Hz
Power consumption: Copying: 461W, Stand-by: 104W, Power-Saving (ECOpower): 43W
Noise (ISO 7779): Copying: 64dB(A), Stand-by: 40dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): 574 x 552 x 502mm
Weight: Main unit: Approx. 39kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 300-sheet universal paper cassette, 64-105g/m², A3, A4, A5, Ledger, Letter, Legal, Folio
50-sheet multi-purpose tray, 45-160g/m², A3, A4, A5, Ledger, Letter, Legal, Folio, Custom (98 x 147mm to 297 x 432mm)
Max. input capacity with options: 1,250 sheets
Output capacity: 250 sheets face-down

COPY FUNCTIONS

Max. original size: A3
Continuous copying: 1-999
Memory capacity: Standard 32MB, 18MB of bitmapping memory and 14 MB of image storage memory, max. 160MB (1 empty DIMM slot for 16, 32, 64, 128MB)
Zoom range: 25-400% in 1% steps
Digital features: Scan-once-print-many, electronic sort/copy, rotate sort/copy^{*1}, automatic paper selection, duplex copying^{*2}, combined inch/metric copying, layout mode (2-in-1, 4-in-1), ECOcopy mode, program key mode, management mode
^{*1} additional paper feeder PF-410 is required
^{*2} additional duplex unit DU-410 is required
Exposure mode: Auto, manual: 5 or 9 steps
Image adjustments: Text + photo, text, photo

CONTROLLER PRINT FUNCTIONS (OPTIONAL PRINT-X)

Processor: ARM 946-S 150MHz, FlexRISC
Memory: Standard 32MB, max. 32MB
Emulations: Host based printing system for Windows

INTERFACE

Standard interface: USB 2.0 (Hi-Speed)

OPTIONS

Printing system (X)
Paper handling
DP-410 Reversing document processor: 50 sheets, duplex scan, 45-160g/m², A3-A5R, Folio, Ledger-Statement-R
PF-410 Paper feeder: 300 sheets, 64-105g/m², A3-A5R, Folio, Ledger-Statement-R (maximum three PF-410 can be added)
DU-410 Duplex unit: 60-80g/m², A3-A5R, Folio, Ledger-Statement-R

Memory
Max. 160MB, 1 slot (16, 32, 64, 128MB DIMM)
Others
Platen cover (D): Platen cover
Cabinet: Cabinet with storage capacity for toner and paper stocks (includes castors)
CB-410 (high cabinet)
CB-415 (low cabinet)

IB110: External network board

CONSUMABLES

TK-410 Toner-kit: Microfine toner for 15,000 pages with 6% A4 coverage
Capacity of starter toner for 3,000 pages with 6% A4 coverage



Select the options to suit your needs:

DP-410 Reversing document processor

DU-410 Duplex unit

PF-410 Paper feeder

PF-410 Paper feeder

PF-410 Paper feeder



Product depicted includes optional extras

Your Kyocera Business Partner:

Kyocera Mita (UK) Ltd, 8 Beacontree Plaza, Gillette Way, Reading RG2 0BS
Tel 0118 931 1500, Fax 0118 931 1108, email: info@kyoceramita.co.uk, www.kyoceramita.co.uk

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

