DATA SHEET

MODEL 4220-1



SR Series Hamon Adaptor

- Automate Calibration ESI SR Series Hamon's
- Reduce Calibration Times

MODEL INFORMATION

The Model 4220-1 was developed as an easy means of calibrating SR1010 type resistance boxes. When used in conjunction with the Model 4220A, 20 channel, low thermal matrix scanner, and Models 6010B, 6242A & 6000A measurement systems, calibration time of an SR Series Hamon Transfer Standard can be significantly reduced. What normally takes a full day of manual measurement, data collection and administration can now be accomplished in less than 30 minutes. The Model 4220-1 plugs directly into the unit under test and can be used to measure each individual element or the total sum of the elements when connected in series. The Model 4220-1 uses 13 four terminal channels.

Specifications:

Insulation Resistance	>10 ¹³
Standard Lead Lengths	1 meter
Maximum Current	150 mA
Product Details	
Dimensions (H x W x D)	35 x 100 x 310 mm
Weight	1 kg
Shipping Weight	1.5 kg

MI-Canada

Measurements International Ltd. PO Box 2359, 118 Pirelli Drive Prescott, Ontario, Canada K0E 1T0

Phone: (613) 925-5934

Toll-Free: 1-800-324-4988 Fax: (613) 925-1195 Email: sales@mintl.com

MI-USA

Measurements International Inc. 812 Proctor Ave. Ogdensburg, NY, USA 13669

Phone: (315) 393-1323

Toll Free: 1-800-324-4988 Fax: (315) 393-1452 Email: sales@mintl.com

MI-Europe

Druzstevni 845, 686 05 Uherske Hradiste

Czech Republic

Phone: (420) 572 572 801 Fax: (420) 572 572 358 Email: mieurope@mintl.com

www.mintl.com

