

Nuvis A20

Advanced Photo System Autofocus Compact.

- Autofocus and auto exposure
- Pocket-sized and lightweight
- Auto Flash and Anytime Flash
 - Red-Eye Reduction
 - Stylish sliding lens cover
 - Self-timer
 - Easy film handling
- Three selectable print types (C, H, P)



- Type of camera:** IX240 (Advanced Photo System™) type autofocus lens-shutter camera
- Usable film:** IX240 (Advanced Photo System™) film cartridge (16.7 × 30.2mm)
- Information exchange system:** Optical Information Exchange (Opt. IX) system
- Lens:** 25mm f/5.6 (31mm converted to 35mm [135] format); 3 elements in 3 groups
- Lens cover:** Opening/closing lens cover turns power ON/OFF
- Shutter speed:** 1/200 and 1/125 sec.; 1/50 sec. when flash is in use
- Focusing:** Infrared-active autofocus system; range: 0.9m or 3.0 ft. to infinity (∞)
- Viewfinder:** Reverse-Galilean Albada-type bright-frame viewfinder
- Viewfinder information:** C/H/P type image size frame marks, autofocus frame
- Film speed setting:** ISO 100 or 200 film automatically set; ISO 200 or higher film automatically set to ISO 200 regardless of actual ISO rating
- Film operation:** Drop-in loading system; Double Exposure Prevention (DEP) available; auto rewind at the end of film roll; mid-roll rewind possible; safety lock provided
- Frame counter:** Shown in the LCD panel; count-up type
- Self-timer:** Electronically controlled; activated by depressing self-timer button; 10 sec. duration; one-shot operation; cancelable
- Built-in flash:** Guide number: 13 (ISO 200, m); flash shooting range: 0.9-3.9m or 3.0-12.8 ft. (ISO 200); approx. 7 sec. recycling time
- Flash modes:** Auto Flash, Anytime Flash (activated by pressing Anytime Flash/Red-Eye Reduction button), and Red-Eye Reduction (activated by pressing Anytime Flash/Red-Eye Reduction button in low light [EV11.8 or lower with ISO200 film])
- Battery life:** Approx. 15 rolls of 25-exposure film with flash for half of all exposures
- Power source:** Two 1.5V LR6 (AA-type alkaline) batteries
- Dimensions (W × H × D):** Approx. 113 × 62 × 35.5mm or 4.4 × 2.4 × 1.4 in.
- Weight (without batteries):** Approx. 150g or 5.3 oz.

All specifications apply when fresh CR2-type batteries are used at normal temperature (20°C / 68°F).
Specifications and designs are subject to change without any notice or obligation on the part of
the manufacturer.
© 2000 Nikon Corporation



NIKON CORPORATION

FUJII BLDG., 2-3, MARUNOUCHI 3-CHOME, CHIYODA-KU, TOKYO 100-8331, JAPAN
www.nikon-image.com/eng/

January 2001