




Endura Desoldering Tips

Tip (3/16" Shank)	Description	Size	Part Number
<i>Recommended for Thru-Hole Desoldering</i>			
	Thermo-Drive	.030" (.76mm) I.D. X .080" (2.03mm) O.D.	1121-0625-P5
	Thermo-Drive	.040" (1.02mm) I.D. X .090" (2.29mm) O.D.	1121-0624-P5
	Thermo-Drive	.060" (1.52mm) I.D. X .120" (3.05mm) O.D.	1121-0626-P5
	Thermo-Drive	.090" (2.29mm) I.D. X .200" (5.1mm) O.D.	1121-0627-P5
	Extended Reach Thermo-Drive	.030" (.76mm) I.D. X .090" (2.29mm) O.D.	1121-0628-P5
	Extended Reach Thermo-Drive	.040" (1.02mm) I.D. X .10" (2.54mm) O.D.	1121-0629-P5
	Extended Reach Thermo-Drive	.060" (1.52mm) I.D. X .120" (3.05mm) O.D.	1121-0630-P5
<i>Recommended for Thru-Hole Desoldering in Tight Areas</i>			
	Precision	.020" (.5mm) I.D. X .070" (1.79mm) O.D.	1121-0680-P5
	Precision	.030" (.76mm) I.D. X .080" (2.03mm) O.D.	1121-0679-P5
	Precision	.040" (1.02mm) I.D. X .090" (2.29mm) O.D.	1121-0678-P5
	Precision	.060" (1.52mm) I.D. X .110" (2.79mm) O.D.	1121-0690-P5
	Precision	.090" (2.29mm) I.D. X .140" (3.55mm) O.D.	1121-0695-P5
<i>Recommended for Surface Mount Land and Via Desoldering</i>			
	Flo-D-Sodr	.060" (1.52mm) I.D. X .188" (4.78mm) O.D.	1121-0631-P5
	Flo-D-Sodr, Precision	.020" (.5mm) I.D. X .070" (1.78mm) O.D.	1121-0681-P5
	Flo-D-Sodr, Precision	.030" (.76mm) I.D. X .080" (2.03mm) O.D.	1121-0682-P5
	Flo-D-Sodr, Precision	.040" (1.02mm) I.D. X .090" (2.29mm) O.D.	1121-0683-P5