



**Data Sheet** 

## Cheetah® NS.2

Lowest power, highest reliability for 3.5-inch Tier 1 solutions

# 600, 450 and 300 GB • 10K RPM • 6-Gb/s SAS 2.0 (600 GB and 450 GB) and 4-Gb/s FC

### **Key Advantages**

- Lowest-power 3.5-inch Tier 1 drive (over 20 percent lower than any other 3.5-inch Tier 1 drive)
- Highest-capacity Tier 1 drive (600 GB)
- · Highest reliability rating in the industry
- Seagate PowerTrim<sup>™</sup> technology dynamically reduces power usage.
- Supports 6-Gb/s SAS 2.0 (600 GB and 450 GB) and 4-Gb/s FC
- Government-grade Self-Encrypting Drive option<sup>1</sup>

### **Best-Fit Applications**

- Email
- · Business processing
- · Transaction processing
- · Decision support
- Storage area networks
- Networked attached storage
- · Internet and e-commerce

1 The Self-Encrypting Drive option is available only to major OEMs.



### Cheetah® NS.2

### Lowest power, highest reliability for 3.5-inch Tier 1 solutions



### **Lowest Cost of Ownership**

- The Seagate Cheetah NS.2 drive is the lowest-power, highest-capacity and highest-reliability solution for 3.5-inch Tier 1 requirements.
- Lower watts/GB ratio helps achieve reduced power and cooling costs while optimizing capacity requirements.

### **MTBF** Improvement

- Seagate continues to focus on reliability and data protection. MTBF is increased to 1.6 million hours.
- Enhanced error correction code better maintains performance throughout the life of the drive and reduces the probability of lost data.
- Seagate-exclusive Background Media Scan proactively scans the media for potential defects during drive idle time. It enables incipient errors to be corrected before data is lost.
- Our Quick and Robust Download feature loads new firmware in less than 2 seconds, and built-in protection ensures no corruption in the event of a power failure during firmware switch.

### **Seagate Global Customer Support**

- Get presales and technical support at support.seagate.com.
- Visit our knowledge base for answers to common support questions.
- Find documentation for current and legacy drives.
- Utilize our online troubleshooting and diagnostic tools.
- Download DiscWizard<sup>™</sup> to help migrate data from an older drive.
- Seagate also offers multi-lingual phone, email and chat support.

<b>Specifications</b>	600 GB <sup>1</sup>	450 GB <sup>1</sup>	300 GB <sup>1</sup>
Model Number	ST3600002FC ST3600002SS	ST3450802FC ST3450802SS	ST3300602FC
Capacity			
Formatted 512 KB/Sector (GB)	600	450	300
Performance			
External Transfer Rate 4-Gb/s Fibre Channel (MB/s) 6-Gb/s SAS 2.0² (MB/s)	400 600	400 600	400
Spindle Speed (RPM)	10K	10K	10K
Average Latency (ms)	3.00	3.00	3.00
Seek Time Average Read/Write (ms) Track-to-Track Read/Write (ms) Transfer Rate Maximum Internal (Mb/s)	3.8/4.4 0.2/0.2	3.8/4.4 0.2/0.2	3.8/4.4 0.2/0.2
Typical Sustained (MB/s)	150	150	150
Cache, Multisegmented (MB)	16	16	16
Configuration/Reliability			
Disks	4	3	2
Heads	8	6	4
Nonrecoverable Read Errors per Bits Read	1 sector per 10E16	1 sector per 10E16	1 sector per 10E16
Reliability Rating at Full 24x7 Operation (Annualized Failure Rate/MTBF hours)	0.55%/1,600,000	0.55%/1,600,000	0.55%/1,600,000
Power			
Typical Operating (W) 4-Gb/s Fibre Channel 6-Gb/s SAS 2.0²	10.07 9.75	9.54 9.15	9.3
ldle (W) 4-Gb/s Fibre Channel 6-Gb/s SAS 2.0²	6.49 6.22	5.96 5.74	5.6
Environmental			
Temperature, Operating (°C) Temperature, Nonoperating (°C) Shock, Operating (Read Only): 2 ms (Gs) Shock, Nonoperating: 2 ms (Gs) Acoustics, Idle (bels—sound power) Withortion, Operating (Gs)	5 to 55 -40 to 70 60 300 3.3	5 to 55 -40 to 70 60 300 3.3	5 to 55 -40 to 70 60 300 3.3
Vibration, Operating (Gs) Vibration, Nonoperating (Gs)	1.0 3.0	1.0 3.0	1.0 3.0
Physical	0.0	5.0	3.0
Height (in/mm)	1.0/25.4	1.0/25.4	1.0/25.4
Width (in/mm)	4.0/101.6	4.0/101.6	4.0/101.6
Depth (in/mm)	5.76/146.52	5.76/146.52	5.76/146.52
Weight (Ib/kg)	1.51/0.686	1.51/0.686	1.48/0.671

<sup>1</sup> One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to hard drive capacity.

www.seagate.com 1-800-SEAGATE (1-800-732-4283)

AMERICAS ASIA/PACIFIC EUROPE, MIDDLE EAST AND AFRICA Seagate Technology LLC 920 Disc Drive, Scotts Valley, California 95066, United States, 831-438-6550
Seagate Technology International Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
Seagate Technology SAS 130-136, rue de Silly, 92773, Boulogne-Billancourt Cedex, France 33

<sup>2</sup> SAS interface is 6-Gb/s capable and 3-Gb/s verified. The drive will negotiate 6-Gb/s speeds on 6-Gb/s HBA or Expander. Verification of 6 Gb/s will occur at a later date.