

**TPRO-cPCI, PMC/TSAT-cPCI, PMC
SYNCHRONIZABLE TIMECODE
GENERATOR with
COMPACT PCI BUS INTERFACE**

*Linux Driver
Application Programmer's Guide*

*95 Methodist Hill Drive
Rochester, NY 14623*

Phone: US +1.585.321.5800

Fax: US +1.585.321.5219



www.spectracomcorp.com

Part Number 1152-5004-0050

Manual Revision A

28 April 2008

Copyright © 2008 Spectracom Corporation. The contents of this publication may not be reproduced in any form without the written permission of Spectracom Corporation. Printed in USA.

Specifications subject to change or improvement without notice.

Spectracom, NetClock, Ageless, TimeGuard, TimeBurst, TimeTap, LineTap, MultiTap, VersaTap, and Legally Traceable Time are Spectracom registered trademarks. All other products are identified by trademarks of their respective companies or organizations. All rights reserved.

SPECTRACOM LIMITED WARRANTY

LIMITED WARRANTY

Spectracom warrants each new product manufactured and sold by it to be free from defects in software, material, workmanship, and construction, except for batteries, fuses, or other material normally consumed in operation that may be contained therein AND AS NOTED BELOW, for five years after shipment to the original purchaser (which period is referred to as the "warranty period"). This warranty shall not apply if the product is used contrary to the instructions in its manual or is otherwise subjected to misuse, abnormal operations, accident, lightning or transient surge, repairs or modifications not performed by Spectracom.

The GPS receiver is warranted for one year from date of shipment and subject to the exceptions listed above. The power adaptor, if supplied, is warranted for one year from date of shipment and subject to the exceptions listed above.

THE ANALOG CLOCKS ARE WARRANTED FOR ONE YEAR FROM DATE OF SHIPMENT AND SUBJECT TO THE EXCEPTIONS LISTED ABOVE.

THE TIMECODE READER/GENERATORS ARE WARRANTED FOR ONE YEAR FROM DATE OF SHIPMENT AND SUBJECT TO THE EXCEPTIONS LISTED ABOVE.

The Rubidium oscillator, if supplied, is warranted for two years from date of shipment and subject to the exceptions listed above.

All other items and pieces of equipment not specified above, including the antenna unit, antenna surge suppressor and antenna pre-amplifier are warranted for 5 years, subject to the exceptions listed above.

WARRANTY CLAIMS

Spectracom's obligation under this warranty is limited to in-factory service and repair, at Spectracom's option, of the product or the component thereof, which is found to be defective. If in Spectracom's judgment the defective condition in a Spectracom product is for a cause listed above for which Spectracom is not responsible, Spectracom will make the repairs or replacement of components and charge its then current price, which buyer agrees to pay.

Spectracom shall not have any warranty obligations if the procedure for warranty claims is not followed. Users must notify Spectracom of the claim with full information as to the claimed defect. Spectracom products shall not be returned unless a return authorization number is issued by Spectracom.

Spectracom products must be returned with the description of the claimed defect and identification of the individual to be contacted if additional information is needed. Spectracom products must be returned properly packed with transportation charges prepaid.

Shipping expense: Expenses incurred for shipping Spectracom products to and from Spectracom (including international customs fees) shall be paid for by the customer, with the following exception. For customers located within the United States, any product repaired by Spectracom under a "warranty repair" will be shipped back to the customer at Spectracom's expense unless special/faster delivery is requested by customer.

Spectracom highly recommends that prior to returning equipment for service work, our technical support department be contacted to provide trouble shooting assistance while the equipment is still installed. If equipment is returned without first contacting the support department and "no problems are found" during the repair work, an evaluation fee may be charged.

EXCEPT FOR THE LIMITED WARRANTY STATED ABOVE, SPECTRACOM DISCLAIMS ALL WARRANTIES OF ANY KIND WITH REGARD TO SPECTRACOM PRODUCTS OR OTHER MATERIALS PROVIDED BY SPECTRACOM, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OR MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Spectracom shall have no liability or responsibility to the original customer or any other party with respect to any liability, loss, or damage caused directly or indirectly by any Spectracom product, material, or software sold or provided by Spectracom, replacement parts or units, or services provided, including but not limited to any interruption of service, excess charges resulting from malfunctions of hardware or software, loss of business or anticipatory profits resulting from the use or operation of the Spectracom product or software, whatsoever or howsoever caused. In no event shall Spectracom be liable for any direct, indirect, special or consequential damages whether the claims are grounded in contract, tort (including negligence), or strict liability.

EXTENDED WARRANTY COVERAGE

Extended warranties can be purchased for additional periods beyond the standard five-year warranty. Contact Spectracom no later than the last year of the standard five-year warranty for extended coverage.

Table of Contents

1	OVERVIEW	1-1
2	INSTALLING THE DRIVER.....	2-1
2.1	Application Example	2-1
3	INTERFACE TO THE LINUX API	3-2
3.1	Header File	3-2
3.2	TPRO API — Routine Descriptions	3-6

1 Overview

The Linux Driver for the Spectracom TPRO/TSATcPCI, PMC boards provides the interface for multiple users to access the board using the API documented in Chapter Three.

The TPRO/TSAT-cPCI, PMC performs timing and synchronization functions referenced to an input time code signal. The board synchronizes its on-board clock to the incoming time code. The on-board clock's time is also provided as an IRIG-B output. The board includes a time-tag TTL input, a programmable “heartbeat” pulse or squarewave output (with interrupt capability), and a programmable “match” start/stop time output (with interrupt capability)

The TPRO/TSAT-cPCI, PMC continues to increment time (“freewheel”) in the absence of an input time code. Thus, the board can be used as an IRIG-B time code generator by setting the initial time via the PCI bus.

The input time code format (IRIG-B, IRIG-A, or NASA36) is detected automatically. Synchronization to the input time code is also automatic and can be enabled/disabled via the PCI bus. A propagation delay offset may be specified to compensate for cable delays.

The time code input is an amplitude-modulated sine wave. An automatic gain control (AGC) circuit permits a wide range of input amplitudes. The time code input is differential; the board does not reference this signal to ground. A single-ended input (referenced to ground) is also acceptable.

2 Installing the Driver

1. Log in to the system as the “root” user.
2. Type “/sbin/insmod tpropci.o” at the shell prompt.
3. Find the driver major number of the tpropci device by typing “more /proc/devices”.
4. Make a node to the device “mknod /dev/tpropci c <major number> 0”.

NOTE: Type “/sbin/rmmod tpropci” at the shell prompt to uninstall the driver.

2.1 Application Example

```
#include <stdlib.h>
#include <stdio.h>

#include <tpro.h>

int main (void)
{
    TPRO_BoardObj *pBoard;
    TPRO_TimeObj tproTime;

    unsigned char rv;

    /**
     ***  open board
     **/

    if (rv = TPRO_open (&pBoard, "/dev/tpropci"), rv != TPRO_SUCCESS) {
        printf ("Could Not Open Board!! [%d]\n", rv);
        return (1);
    }

    /**
     ***  get time
     **/

    if (rv = TPRO_getTime (pBoard, &tproTime), rv != TPRO_SUCCESS) {
        printf ("Could not retrieve time!! [%d]\n", rv);
        return (1);
    }
    printf ("  Days: %d\n", tproTime.days);
    printf ("  Hours: %d\n", tproTime.hours);
    printf ("  Minutes: %d\n", tproTime.minutes);
    printf ("  Seconds: %f\n", tproTime.secsDouble);

    /**
     ***  close board
     **/

    if (rv = TPRO_close (pBoard), rv != TPRO_SUCCESS) {
        printf ("Could Not Close Board!! [%d]\n", rv);
        return (1);
    }

    return (0);
}
```

3 Interface to the Linux API

3.1 Header File

The following is the “TPRO.H” API Interface Header File.

```

/*****
    DSPCon TPRO/tsAT - Interface Header

    DSPCon, Inc.
    380 Foothill Road
    Bridgewater, NJ 08807

    e-mail: info@dspcon.com

    (C) Copyright 2001 DSPCon, Inc. All rights reserved.
    Use of copyright notice is precautionary and does not imply publication
    *****/

/*****
    TPRO.H
    *****/

#ifndef _defined_TPRO_
#define _defined_TPRO_

/*****
    SUPPORT CONSTANTS
    *****/

/**
    *** Heartbeat constants
    **/

#define SIG_PULSE      (0xE5)      /*-- heartbeat is a pulse -----*/
#define SIG_SQUARE     (0xE7)      /*-- heartbeat is a squarewave ---*/

#define SIG_NO_JAM      (0)         /*-- start next cycle -----*/
#define SIG_JAM         (1)         /*-- start immediately -----*/

/**
    *** Match constants
    **/

#define MATCH_TIME_START      (0)          /*-- start time -----*/
#define MATCH_TIME_STOP      (1)          /*-- stop time -----*/

/**
    *** Oscillator frequencies - for Compact PCI Card Only
    **/

#define OSC_OUT_OFF           (0)
#define OSC_OUT_1KHZ          (1)
#define OSC_OUT_1MHZ          (2)
#define OSC_OUT_5MHZ          (3)
#define OSC_OUT_10MHZ         (4)

```

```

/*****
                                OBJECTS
*****/

/*=====
                                TPRO BOARD OBJECT
=====*/

typedef struct TPRO_BoardObj
{ /*-----*/
    int file_descriptor;
    unsigned short devid;

    unsigned short options;

    unsigned char firmware[5];
    unsigned char FPGA[5];
    unsigned char driver[7];
} /*-----*/
TPRO_BoardObj;

/*=====
                                TPRO ALTITUDE OBJECT
=====*/

typedef struct TPRO_AltObj
{ /*-----*/
    float          meters;          /*-- meters -----*/
} /*-----*/
TPRO_AltObj;

/*=====
                                TPRO DATE OBJECT
=====*/

typedef struct TPRO_DateObj
{ /*-----*/
    unsigned short year;            /*-- year -----*/
    unsigned char  month;           /*-- month -----*/
    unsigned char  day;             /*-- day -----*/
} /*-----*/
TPRO_DateObj;

/*=====
                                TPRO LONGITUDE/LATTITUDE OBJECT
=====*/

typedef struct TPRO_LongLat
{ /*-----*/
    unsigned short degrees;         /*-- degrees -----*/
    float          minutes;         /*-- minutes -----*/
} /*-----*/
TPRO_LongObj, TPRO_LatObj;

/*=====
                                TPRO MATCH OBJECT
=====*/

typedef struct TPRO_MatchObj
{ /*-----*/
    unsigned char  matchType;       /*-- start/stop time ----*/

    double         seconds;         /*-- seconds -----*/
    unsigned char  minutes;         /*-- minutes -----*/
    unsigned char  hours;           /*-- hours -----*/
}

```

```

    unsigned short  days;                                /*-- days -----*/
} /*-----*/
TPRO_MatchObj;

/*=====
TPRO SATINFO OBJECT
=====*/

typedef struct TPRO_SatObj
{ /*-----*/
    unsigned char  satsTracked;                        /*-- num sats tracked ----*/
    unsigned char  satsView;                          /*-- num sats in view ----*/
} /*-----*/
TPRO_SatObj;

/*=====
TPRO HEARTBEAT OBJECT
=====*/

typedef struct TPRO_HeartObj
{ /*-----*/
    unsigned char  signalType;                        /*-- square or pulse ----*/
    unsigned char  outputType;                       /*-- jamming option -----*/

    double  frequency;                                /*-- heartbeat freq -----*/
} /*-----*/
TPRO_HeartObj;

/*=====
TPRO TIME OBJECT
=====*/

typedef struct TPRO_TimeObj
{ /*-----*/
    double      secsDouble;                            /*-- seconds floating pt -*/
    unsigned char  seconds;                            /*-- seconds whole num ---*/
    unsigned char  minutes;                            /*-- minutes -----*/
    unsigned char  hours;                              /*-- hours -----*/
    unsigned short days;                              /*-- days -----*/

    unsigned short year;                              /*-- year for CPCI board -*/
} /*-----*/
TPRO_TimeObj;

/*=====
TPRO WAIT OBJECT
=====*/

typedef struct TPRO_WaitObj
{ /*-----*/
    int ticks;                                         /*-- # ticks to wait ----*/

    double  seconds;                                  /*-- seconds -----*/
    unsigned char  minutes;                          /*-- minutes -----*/
    unsigned char  hours;                            /*-- hours -----*/
    unsigned short days;                              /*-- days -----*/
} /*-----*/
TPRO_WaitObj;

/*=====
TPRO MEM OBJECT FOR PEEK/POKE
=====*/

typedef struct TPRO_MemObj
{ /*-----*/
    unsigned short offset;

```

```

    unsigned short value;

    unsigned long l_value;
} /*-----*/
TPRO_MemObj;

/*****
                        ERROR CODES
*****/

#define TPRO_SUCCESS          (0)    /*-- success -----*/
#define TPRO_HANDLE_ERR      (1)    /*-- error bad handle ----*/
#define TPRO_OBJECT_ERR      (2)    /*-- error creating obj --*/
#define TPRO_CLOSE_HANDLE_ERR (3)    /*-- err closing device --*/
#define TPRO_DEVICE_NOT_OPEN_ERR (4) /*-- device not opened ---*/
#define TPRO_INVALID_BOARD_TYPE_ERR (5) /*-- invalid device -----*/
#define TPRO_FREQ_ERR        (6)    /*-- invalid frequency ---*/
#define TPRO_YEAR_PARM_ERR    (7)    /*-- invalid year -----*/
#define TPRO_DAY_PARM_ERR     (8)    /*-- invalid day -----*/
#define TPRO_HOUR_PARM_ERR    (9)    /*-- invalid hour -----*/
#define TPRO_MIN_PARM_ERR     (10)   /*-- invalid minutes ----*/
#define TPRO_SEC_PARM_ERR     (11)   /*-- invalid seconds ----*/
#define TPRO_DELAY_PARM_ERR   (12)   /*-- invalid delay -----*/
#define TPRO_TIMEOUT_ERR      (13)   /*-- device timed out ---*/
#define TPRO_COMM_ERR         (14)   /*-- communication error -*/

/*****
                        PUBLIC ROUTINE PROTOTYPES
*****/

unsigned char TPRO_open          (TPRO_BoardObj *hnd, char *deviceName);
unsigned char TPRO_close        (TPRO_BoardObj *hnd);

unsigned char TPRO_getAltitude   (TPRO_BoardObj *hnd, TPRO_AltObj *Altp);
unsigned char TPRO_getDate      (TPRO_BoardObj *hnd, TPRO_DateObj *Datep);
unsigned char TPRO_getLatitude  (TPRO_BoardObj *hnd, TPRO_LatObj *Latp);
unsigned char TPRO_getLongitude (TPRO_BoardObj *hnd, TPRO_LongObj *Longp);
unsigned char TPRO_getSatInfo   (TPRO_BoardObj *hnd, TPRO_SatObj *Satp);
unsigned char TPRO_getTime      (TPRO_BoardObj *hnd, TPRO_TimeObj *Timep);
unsigned char TPRO_resetFirmware (TPRO_BoardObj *hnd);
unsigned char TPRO_setHeartbeat  (TPRO_BoardObj *hnd, TPRO_HeartObj *Heartp);
unsigned char TPRO_setMatchTime (TPRO_BoardObj *hnd, TPRO_MatchObj *Matchp);
unsigned char TPRO_setOscillator (TPRO_BoardObj *hnd, unsigned char *freq);
unsigned char TPRO_setPropDelayCorr (TPRO_BoardObj *hnd, int *us);
unsigned char TPRO_setTime      (TPRO_BoardObj *hnd, TPRO_TimeObj *Timep);
unsigned char TPRO_setYear      (TPRO_BoardObj *hnd, unsigned short *yr);
unsigned char TPRO_simEvent     (TPRO_BoardObj *hnd);
unsigned char TPRO_synchControl (TPRO_BoardObj *hnd, unsigned char *enbp);
unsigned char TPRO_synchStatus  (TPRO_BoardObj *hnd, unsigned char *status);
unsigned char TPRO_waitEvent    (TPRO_BoardObj *hnd, TPRO_WaitObj *waitp);
unsigned char TPRO_waitHeartbeat (TPRO_BoardObj *hnd, int *ticks);
unsigned char TPRO_waitMatch    (TPRO_BoardObj *hnd, int *ticks);

#endif // _defined_TPRO_

```

3.2 TPRO API — Routine Descriptions

3.2.1.1.1 TPRO_open

```
unsigned char TPRO_open (TPRO_BoardObj **hnd, char *deviceName);
```

This routine allocates a TPRO_BoardObj object, sets a handle to the tpro/tsat, and sets the driver firmware, FPGA revision (if applicable), and the driver revision strings.

Arguments: Pointer to TPRO_BoardObj handle
Device name - "TPROpci"

Returns: TPRO_OBJECT_ERR - error allocating board object
TPRO_HANDLE_ERR - error retrieving handle to device
TPRO_COMM_ERR - error communicating with driver
TPRO_SUCCESS - success

3.2.1.1.2 TPRO_close

```
unsigned char TPRO_close (TPRO_BoardObj *hnd);
```

This routine frees the allocated board object and closes the handle to the tpro/tsat device.

Arguments: Pointer to TPRO_BoardObj

Returns: TPRO_CLOSE_HANDLE_ERR - error closing handle to device
TPRO_DEVICE_NOT_OPEN - device is not open
TPRO_SUCCESS - success

3.2.1.1.3 TPRO_getAltitude

```
unsigned char TPRO_getAltitude (TPRO_BoardObj *hnd, TPRO_AltObj *Altp);
```

This routine retrieves the altitude information from the tSAT board. Altitude distance is in meters.

Arguments: Pointer to TPRO_BoardObj
Pointer to TPRO_AltObj

Returns: TPRO_INVALID_BOARD_TYPE_ERR - invalid board type for function
TPRO_COMM_ERR - error communicating with driver
TPRO_SUCCESS - success

3.2.1.1.4 TPRO_getDate

```
unsigned char TPRO_getDate (TPRO_BoardObj *hnd, TPRO_DateObj *Datep);
```

This routine retrieves the current date from the TPRO/tSAT board. The date is in Gregorian Format.

Arguments: Pointer to TPRO_BoardObj
 Pointer to TPRO_DateObj

Returns: TPRO_INVALID_BOARD_TYPE_ERR - invalid board type for
function
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.5 TPRO_getLatitude

```
unsigned char TPRO_getLatitude(TPRO_BoardObj *hnd, TPRO_LatObj  
*Latp);
```

This routine retrieves the latitude information from the tSAT device.

Arguments: Pointer to TPRO_BoardObj
 Pointer to TPRO_LatObj

Returns: TPRO_INVALID_BOARD_TYPE_ERR - invalid board type for
function
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.6 TPRO_getLongitude

```
unsigned char TPRO_getLongitude(TPRO_BoardObj *hnd, TPRO_LongObj *Longp);
```

This routine retrieves the longitude information from the /tSAT device.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the TPRO_LongObj

Returns: TPRO_INVALID_BOARD_TYPE_ERR - invalid board type for
function
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.7 TPRO_getSatInfo

```
unsigned char TPRO_getSatInfo(TPRO_BoardObj *hnd, TPRO_SatObj *Satp);
```

This routine retrieves the number of satellites tracked from the tSAT device.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the TPRO_SatObj

Returns: TPRO_INVALID_BOARD_TYPE_ERR - invalid board type for
 function
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.8 TPRO_getTime

```
unsigned char TPRO_getTime(TPRO_BoardObj *hnd, TPRO_TimeObj *Timep);
```

This routine retrieves the current time from the TPRO/tSAT device. The seconds value is received as type double.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the TPRO_TimeObj

Returns: TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.9 TPRO_resetFirmware

```
unsigned char TPRO_resetFirmware(TPRO_BoardObj *hnd);
```

This routine resets the firmware programmed on the TPRO/tSAT device. This function is for troubleshooting purposes only and should not be used in the main application.

Arguments: Pointer to the TPRO_BoardObj

Returns: TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.10 TPRO_setHeartbeat

```
unsigned char TPRO_setHeartbeat(TPRO_BoardObj *hnd, TPRO_HeartObj *Heartp);
```

This routine controls the heartbeat output. The heartbeat output may be a square wave or pulse at various frequencies.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the TPRO_HeartObj

Returns: TPRO_FREQ_ERR - invalid frequency value
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.11 TPRO_setMatchTime

```
unsigned char TPRO_setMatchTime(TPRO_BoardObj *hnd, TPRO_MatchObj *Matchp);
```

This routine drives the match output line high (start time) or low (stop time) when the desired time is met.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the TPRO_MatchObj

Returns: TPRO_DAY_PARM_ERR - invalid days parameter (must be 0-366)
 TPRO_HOUR_PARM_ERR - invalid hours parameter (must be 0 - 23)
 TPRO_MIN_PARM_ERR - invalid minutes parameter (must be 0 - 59)
 TPRO_SEC_PARM_ERR - invalid seconds parameter (must be 0 - 69)
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.12 TPRO_setPropDelayCorr

```
unsigned char TPRO_setPropDelayCorr (TPRO_BoardObj *hnd, int *us);
```

This routine sets the propagation delay correction factor.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to correction factor in microseconds

Returns: TPRO_DELAY_PARM_ERR - invalid propagation delay factor
 TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.13 TPRO_setTime

```
unsigned char TPRO_setTime(TPRO_BoardObj *hnd, TPRO_TimeObj *Timep);
```

This routine sets the time on the on-board clock of the TPRO/tSAT device. If the board is synchronized to a GPS antenna, this value will not be accepted.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the TPRO_TimeObj

Returns:

TPRO_DAY_PARM_ERR	- invalid days parameter (must be 0-366)
TPRO_HOUR_PARM_ERR	- invalid hours parameter (must be 0 - 23)
TPRO_MIN_PARM_ERR	- invalid minutes parameter (must be 0 - 59)
TPRO_SEC_PARM_ERR	- invalid seconds parameter (must be 0 - 69)
TPRO_COMM_ERR	- error communicating with driver
TPRO_SUCCESS	- success

3.2.1.1.14 TPRO_setYear

```
unsigned char TPRO_setYear(TPRO_BoardObj *hnd, unsigned short *yr);
```

This routine programs the TPRO/tSAT device with the desired year. If the board is synchronized to a GPS antenna, this value will not be accepted.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the desired year

Returns:

TPRO_INVALID_BOARD_TYPE_ERR	- invalid board type for function
TPRO_COMM_ERR	- error communicating with driver
TPRO_SUCCESS	- success

3.2.1.1.15 TPRO_simEvent

```
unsigned char TPRO_simEvent(TPRO_BoardObj *hnd);
```

This routine simulates an external time tag event.

Arguments: Pointer to the TPRO_BoardObj

Returns:

TPRO_COMM_ERR	- error communicating with driver
TPRO_SUCCESS	- success

3.2.1.1.16 TPRO_synchControl

```
unsigned char TPRO_synchControl(TPRO_BoardObj *hnd, unsigned char
*enbp);
```

This routine commands the TPRO/tSAT device to synchronize to input or freewheel. This distinction is made using the enable argument. If the enable argument is (0) the clock will freewheel, otherwise it will synchronize to input. When disabling synchronization (freewheeling), the device will continue to synchronize until the time is set.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the synch enable

Returns: TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.17 TPRO_synchStatus

```
unsigned char TPRO_synchStatus(TPRO_BoardObj *hnd, unsigned char
*status);
```

This routine reports the synchronization status of the TPRO/tSAT device. When status is equal to zero, the device is freewheeling. Otherwise, the device is synchronized to its input.

Arguments: Pointer to the TPRO_BoardObj
 Pointer to the synch status variable

Returns: TPRO_COMM_ERR - error communicating with driver
 TPRO_SUCCESS - success

3.2.1.1.18 TPRO_waitEvent

Not implemented in Version 1.000.

3.2.1.1.19 TPRO_waitHeartbeat

Not implemented in Version 1.000.

3.2.1.1.20 TPRO_waitMatch

Not implemented in Version 1.000.

REVISION HISTORY

[illegible]

Spectracom Corporation

95 Methodist Hill Drive

Rochester, NY 14623

www.spectracomcorp.com

Phone: US +1.585.321.5800

Fax: US +1.585.321.5219