

THERMAL TRANSFER RIBBONS



**Standard wound,
ink side in**
For EPC ML-5XX and
ML-4XX series printers



**Reverse wound,
ink side out**
For Zebra and Brady
printers

Ribbons Type	Part Number	Width	Length	Part Number	Width	Length
Type RS Standard Wax-based black. Suitable for use on paper where high-abrasion resistance is not required,	1330-0500-37	76 mm	410m	1330-0600-09	95mm	300m
	1330-0500-07	76 mm	210m	1330-0600-10	110mm	300m
	1330-0500-40	110mm	410m			
	1330-0500-10	110mm	210m			
	1330-0500-12	127mm	210m			
Type RHQ High Quality Wax-resin-based,black. Suitable for use on polyesters (WP&MP) where very fine detail must be printed crisply, but highest abrasion and solents resistance are not required,	1330-0506-07	76 mm	410m	1330-0606-09	89mm	300m
	1330-0506-10	110mm	410m			
	1330-0506-12	127mm	410m			
Type RHD High Durability Resin-based black. Suitable for use on polyesters (WP & MP) and other film materials. Exceptional abrasion and solvent resistance. With-stand temperatures up to 300°F (150°C) when printed on polyester and metalised polyester.	1330-0507-03	33 mm	360m	1330-0607-08	80mm	300m
	1330-0507-06	64 mm	360m	1330-0607-10	95mm	300m
	1330-0507-07	76 mm	210m			
	1330-0507-10	110mm	210m			
	1330-0507-20	110mm	410m			
	1330-0507-12	127mm	210m			
Type RHT-30 High Temperature Resin-based,black.Suitable for use on EPC "T1K" kapton material	1330-0516-05	53mm	210m	1330-0616-05	54mm	210m
	1330-0516-10	110mm	210m	1330-0616-09	90mm	210m
				1330-0616-10	110mm	210m
Type RHT-35 High Temperature Resin-based, black. Excellent on polyesters (WP & MP) and Kapton (T1K). Very high temperature,mechanical and solvent resistance,	1330-0518-05	50 mm	410m	1330-0618-06	60mm	450m
	1330-0518-10	110mm	410m	1330-0618-08	83mm	450m
				1330-0618-10	110mm	450m
Type RHT-40 High Temperature Resin-based, black.Very good on Polyesters (WP & MP) and Kapton (T1K).	1330-0517-05	50 mm	210mm	1330-0617-10	110mm	300mm
	1330-0517-10	110mm	210mm			
Type RHCA High Performance colour Resin-based, available in colours listed right. Specifically designed for polyester or metal-ised polyester. NOT suitable for paper or white/yellow vinyl (SB/SBY).	Ribbon Width: 110mm					
	1330-0520-10	Red	360m	1330-0620-10	Red	450m
	1330-0521-10	Blue	360m	1330-0621-10	Blue	450m
	1330-0522-10	Green	360m			
	1330-0524-10	Light Blue	360m			
	1330-0525-10	White	360m			

Type RHCB Colour Wax-resin-based, available in colours listed right. Specifically designed for paper and white/yellow vinyl (SB/SBY).	Ribbon Width 1330-0530-10 1330-0531-10 1330-0532-10 1330-0533-10	110mm Red Blue Green Yellow	360mm 360mm 360mm 360mm
---	---	--	----------------------------------

Ribbons for 212 Printers

Ribbon Type and Application	Part Number	Width	Length
Type RHD High Durability Resin-based,black. Suitable for use on polyester (WP&MP) and other film materials. Exceptional abrasion and solvent resistance. Withstands temperatures up to 300 ^o F (150 ^o C) when printed on polyester.	1330-0821-00	108mm	80m

Type RBR Black resin ribbon is best for metalized Polyester (MP), White Polyester(WP), Destructible Polyethylene (TN), and White Vinyl Materials (SB).	1330-0814-00	108mm	73m
--	--------------	-------	-----

Type RGP Black resin/wax ribbon is best for coated paper (EP),	1330-0807-00	108m	73m
--	--------------	------	-----

GUIDE TO SPECIFYING EPC THERMAL TRANSFER RIBBONS

Code	EPC Material	Highest Durability	High Print Quality	Most Economical	Test in Your Application	Color	NOT RECOMMENDED
BP	Blue Polyester	RHD	RHT-35 [†] , RHQ			RHCA	
CP	Clear Polyester	RHD	RHT-35 [†] , RHD			RHCA	
EP	Coated Paper			RS		RHCB	RHCA
HM	High-Tack Metalized Polyester	RHD	RHT-35 [†] , RHD			RHCA	
HW	High-Tack White Polyester	RHD	RHT-35 [†] , RHD			RHCB	
MP	Metalized Polyester	RHD	RHT-35 [†] , RHD			RHCA	
MV	Void Metalized Polyester	RHD	RHT-35 [†] , RHD			RHCA	
NC	Nylon Cloth	RHD	RHT-35			RHCB	RHCA
QR	Quality Removable Paper			RS		RHCB	RHCA
SB	White Transparent Vinyl	RHD	RHT40, RHQ			RHCB	RHCA
SBY	Yellow Transparent Vinyl	RHD	RHT40, RHQ			RHCB	RHCA
T1K	Kapton®	RHT-35			RHT-30, RHT-40		
T2Y	Modified Polyimide	RHT-30	RHQ				RHT-40
TN	Destructible Poethylene	RHD	RHT-35 [†] , RHQ, RHT-40			RHCA	
WP	White Polyester	RHD	RHT-35 [†] , RHT-40, RHQ			RHCA	
WP1	1 Mil White Polyester	RHD	RHT-35 [†] , RHT-40, RHQ			RHCA	
WS	White Polystyrene	RHD	RHT-35 [†] , RHT-40			RHCA	
WV	White Vinyl	RHT-35	RHT-35 [†] , RHQ			RHCA	
YP	Yellow Polyester	RHD	RHT-35 [†] , RHQ			RHCA	

[†] Best print quality

DOT MATRIX RIBBONS



Key to Ribbon Type:

RF = Insta-Dry Indelible Ink

Solvents-resistant, immediately usable

RI = Indelible Ink

Solvents-resistant when allowed to cure for 24 hours, or by applying heat.

RS = Standard Ink

Paper only; not recommended for solvents.

Part Number	Type	Printer	Part Number	Type	Printer
1330-0014-00 RI		ML-II(D),ML-4/14/15	1330-0035-00 RI		Epson 80 Series
1330-0014-01 RS		ML-II(D),ML-4/14/15	1330-0036-00 RI		Epson 100 Series
1330-0014-06 RF		ML-II(D),ML-4/14/15			
1330-0020-00 RI		ML-20	1330-0037-00 RI		Epson LQ200-870 Series
1330-0020-01 RS		ML-20	1330-0037-06 RF		Epson LQ200-870 Series
1330-0020-06 RF		ML-20	1330-0038-00 RI		Epson LQ1000-1170 Series
1330-0021-00 RI		ML-3000	1330-0043-00 RI		Okidata 80/82/83
1330-0021-01 RS		ML-3000	1330-0044-00 RI		Okidata 292
1330-0021-06 RF		ML-3000			
			1330-0072-06 RF		Dta I/O