

⁴ Hosford, M. J. and Rosebrock, T. L. "The ballistic pendulum applied to pulsed plasma acceleration," Allison Div., General Motors Corp., EDR 2253 (March 1962).

Reply by Authors to D. L. Clingman and T. L. Rosebrock

T. J. GOODING,* B. HAYWORTH,† AND R. H. LOVBERG‡
General Dynamics/Aeronautics, San Diego, Calif.

IN a previous paper,¹ the authors wanted to illustrate that the simple ballistic pendulum is subject to error, and effects such as were observed should be considered before accepting impulse data obtained with pendulums. It was not intended to condemn ballistic pendulums per se; in fact, it was hoped to apply this technique in the authors' present work.

The solution to the ablation problem proposed by D. L. Clingman and T. L. Rosebrock seems to be a good one. Another approach simply is to reduce the energy density of the plasma at the surface of the pendulum by moving the pendulum away from the plasma accelerator so that the beam can spread radially and axially; however, the pendulum must become larger to collect all of the beam.

Received January 31, 1963.

* Staff Scientist, Space Science Laboratory. Member AIAA.

† Senior Physicist, Space Science Laboratory. Member AIAA.

‡ Consultant, Space Science Laboratory. Member AIAA.

¹ Gooding, T. J., Hayworth, B. R., and Lovberg, R. H., "Use of ballistic pendulums with pulsed plasma accelerators," ARS J. 32, 1599-1600 (1962).

Comment on "Invariant Two-Body Velocity Components"

S. P. ALTMAN* AND J. S. PISTINER†
United Aircraft Corporate Systems Center,
Farmington, Conn.

IN a previous paper,¹ Cronin and Schwartz discussed the invariant two-body velocity components of orbital body motion. Speculation was presented on possible useful applications of this property of invariance to the solution of two-body trajectory problems.

Since about three years ago, various studies of such applications have been conducted and are continuing. As noted in a XIIIth International Astronautical Congress paper,² additional literature on such applications is available.³⁻¹⁴ Also, Newton's paper¹⁵ is based upon this invariance property.

In general, the invariance of the specified orbital velocity components describes a circle that defines the orbital velocity vector in inertial space. This figure is known as the velocity hodograph, originally discovered by Hamilton and Möbius.

References

¹ Cronin, J. L. and Schwartz, R. E., "Invariant two-body velocity components," J. Aerospace Sci. 29, 1384-1385 (1962).

Received December 17, 1962.

* Supervisor, Space Sciences. Member AIAA.

† Senior Engineer, Guidance and Control. Member AIAA.

² Altman, S. P. and Gilbert, A. C., "Variable transformations for the analysis of space flight trajectories," XIIIth International Astronautical Congress; also United Aircraft SCTM 134 (July 1962).

³ Altman, S. P., "Orbital transfer for satellites," *Proceedings of the Fourth Ballistic Missile and Space Technology Symposium*, 1959 (Pergamon Press Inc., New York, 1961), pp. 132-144.

⁴ Boksenbom, A. S., "Graphical trajectory analysis," NASA Rept. D-64 (December 1959).

⁵ Sun, F. T., "A special hodograph for orbital motion," *Proceedings of the 2nd International Symposium of Rockets and Astronautics*, Tokyo, 1960 (Yokendo, Tokyo, 1961), Paper 26, pp. 163-189.

⁶ Altman, S. P. and Pistiner, J. S., "Hodograph analysis for the orbital transfer problem for coplanar, non-aligned elliptical orbits," ARS J. 31, 1217-1225 (1961); also ARS Preprint 1147-60 (December 1960).

⁷ Paul E. W., "The hodograph and ballistic missile trajectory problems," *Aerospace Eng.* 20, 24-25, 70-72 (February 1961).

⁸ Altman, S. P. and Pistiner, J. S., "Polar hodograph for ballistic missile trajectories," ARS J. 31, 1592-1594 (1961).

⁹ Altman, S. P. and Pistiner, J. S., "A new orbital rendezvous guidance concept and its mechanization," *XII International Astronautical Congress*, Washington, D. C., 1961 (Academic Press Inc., New York, 1963).

¹⁰ Regan, F. J., "Comment on an orbital hodograph analysis by Altman and Pistiner," ARS J. 32, 113-114 (1962).

¹¹ Wen, L. W., "A unified treatment of variation of parameters and differential expressions methods in trajectory prediction and error analysis," J. Aerospace Sci. 29, 61-66, 120 (1962).

¹² Altman, S. P. and Pistiner, J. S., "Minimum velocity increment solution for two-impulse coplanar orbital transfer," AIAA J. 1, 435-442 (1963); also United Aircraft Corp. SCTM 124 (January 1962).

¹³ Altman, S. P. and Pistiner, J. S., "Comment on the correlation of Stark's two-terminal trajectory optimization with an orbital hodograph analysis," ARS J. 32, 983 (1962).

¹⁴ Altman, S. P. and Pistiner, J. S., "Hodograph transformations and mapping of the orbital conics," ARS J. 32, 1109-1111 (1962).

¹⁵ Newton, R. R., "Variables that are determinate for any orbit," ARS J. 31, 364-366 (1961).

Explicit Solution of the "Three-Moments Equation"

T. WOLFF*

GFD Fluid Dynamics, New York, N. Y.

THE solution of the "three-moments equation" given by the author¹ requires the search for eigenvalues and eigenvectors of a certain operator. To remove these difficulties and to find the explicit solution, one can substitute, instead of a finite-difference operator and boundary conditions, a new operator that transforms the boundary-value problem into an algebraic equation, without previously solving the problem. Commutation properties of this operator with Green's function make it possible to find the solution in classical form.

The "three-moments problem" has the notation

$$L_{mn}M_n = -G_m$$

$$M_0 = M_N = 0 \quad n = 0, 1, \dots, N \quad (1)$$

where the finite-difference operator L and boundary conditions can be written as follows:

$$\left. \begin{aligned} L_{mn} &= \delta_{m+1,n} + 4\delta_{m,n} + \delta_{m-1,n} \\ M_0 &= M_N = 0 \end{aligned} \right\} \quad n = 0, 1, \dots, N \quad (2)$$

Received December 28, 1962.

* President.

¹ Wolff, T., "Direct solution of the 'three-moments equation'," AIAA J. 1, 718 (1963).