

Technical Comments

Comment on "Derivation of Axisymmetric Flexural Vibration Equations of a Cylindrically Aeolotropic Circular Plate"

CHI LUNG HUANG*

Kansas State University, Manhattan, Kansas

THOUGH the basic governing differential equations for a cylindrically aeolotropic plate subjected to bending and vibration have been developed by several researchers,¹⁻⁵ the axisymmetric flexural vibration equations and associated boundary conditions of a cylindrically aeolotropic circular plate of varying thickness have been ingeniously derived by Joung⁶ using the method of variational calculus. As stated by Joung the advantage of this method is that both the differential equations and the appropriate boundary conditions can be obtained simultaneously.

In Joung's Note some errors should be noted and corrections made. As a result of the extremizations of the functional,

$$I = \int_{t_1}^{t_2} \iint_S f(t, r, w, w_r, w_{rr}, w_t, w_{tr}) r dr d\theta dt \quad (1)$$

the differential equation of motion and the appropriate boundary conditions should read

$$\begin{aligned} D(c^2 w_{rrrr} + 2c^2 r^{-1} w_{rrr} - r^{-2} w_{rr} + r^{-3} w_r) + \\ D_r[2c^2 w_{rrr} + (2c^2 + \nu)r^{-1} w_{rr} - r^{-2} w_r] + \\ D_{rr}(c^2 w_{rr} + \nu r^{-1} w_r) + \mu w_{tt} = p(r, t) \quad (2) \\ [rD(c^2 w_{rr} + \nu r^{-1} w_r)\eta]_b^a = 0 \end{aligned}$$

and

$$\{[rD(c^2 w_{rrr} + c^2 r^{-1} w_{rr} - r^{-2} w_r) + rD_r(c^2 w_{rr} + \nu r^{-1} w_r)]\eta\}_b^a = 0 \quad (3)$$

For isotropic material, $c^2 = 1$, Eqs. (2) and (3) yield the results given by Eqs. (10) through Eqs. (13) in the Note. However, for the case of an annular plate of aeolotropic material with constant thickness, the differential equation should read

$$c^2 w_{rrrr} + 2c^2 r^{-1} w_{rrr} - r^{-2} w_{rr} + r^{-3} w_r + D^{-1} \mu w_{tt} = D^{-1} p(r, t) \quad (4a)$$

and the boundary conditions for simple support and free hole are

$$\begin{aligned} w = 0, \quad c^2 w_{rr} + \nu r^{-1} w_r = 0 \quad \text{at } r = a \quad (4b) \\ c^2 w_{rr} + \nu r^{-1} w_r = 0 \end{aligned}$$

and

$$c^2 w_{rrr} + c^2 r^{-1} w_{rr} - r^{-2} w_r = 0 \quad \text{at } r = b \quad (4c)$$

For static problems, Eq. (4a) reduces to the differential equation for the axisymmetric bending of the cylindrically aeolotropic plate, which is given by Carrier as Eq. (7) in Ref. 1.

Received September 26, 1969.

* Associate Professor of Applied Mechanics. Member AIAA.

Incidentally, a typographical error appears both in Ref. 1 and Ref. 6. The definition of ν should be

$$\nu = -a_{12}/a_{22}.$$

References

- Carrier, G. F., "The Bending of the Cylindrically Aeolotropic Plate," *Journal of Applied Mechanics*, Vol. 11, 1944, pp. A129-A134.
- Conway, H. D., "Note on the Bending of Circular Plates of Variable Thickness," *Journal of Applied Mechanics*, Vol. 71, 1949, pp. 209-210.
- Hoppmann, W. H., II, "Flexural Vibrations of Orthogonally Stiffened Circular and Elliptical Plates," *Proceedings of the 3rd U. S. National Congress of Applied Mechanics*, 1958, pp. 181-187.
- Minkarah, I. A. and Hoppmann, W. H., II, "Flexural Vibration of Cylindrically Aeolotropic Circular Plates," *The Journal of the Acoustical Society of America*, Vol. 36, 1964, pp. 470-475.
- Salzman, A. P. and Patel, S. A., "Natural Frequencies of Orthotropic Circular Plates of Variable Thickness," Task NR 064-427, April 1968, Department of Aerospace Engineering and Applied Mechanics, Polytechnic Institute of Brooklyn, Brooklyn, N. Y.
- Joung, K. S., "Derivation of Axisymmetric Flexural Vibration Equations of a Cylindrically Aeolotropic Circular Plate," *AIAA Journal*, Vol. 7, No. 7, July 1969, pp. 1386-1398.

Reply by Author to C. L. Huang

KI S. JOUNG*

Allis-Chalmers Manufacturing Co., Milwaukee, Wis.

I WOULD like to thank Professor Huang for his comments and pointing out errors.

Received December 2, 1969.

* Research Analyst. Member AIAA.

Comment on "Separation Solutions for Laminar Boundary Layer"

DAVID F. ROGERS*

United States Naval Academy, Annapolis, Md.

IN Ref. 1 Fox and Saland report on the separation solutions for the compressible similar laminar boundary-layer equations with mass transfer. The reported results were limited to unit Prandtl number.

In Ref. 1 the governing boundary-value problem for the compressible similar laminar boundary layer with mass transfer [Eqs. (1, 2, 5, and 6) of Ref. 1] was integrated using a

Received June 8, 1970. The partial support of the Office of Naval Research under Project Order PO 9-0103 is acknowledged.

* Associate Professor, Aerospace Engineering Department. Member AIAA.