

equations N is too large. Practical experience indicates that the reported nineteen time inputs used by the authors is beyond the safe margin.

Lastly, the model chosen by the authors is suspect, since a finite hollow tube is replaced by a circular hole in an infinite plate. Solutions to the inverse problem indicate that the temperature extrapolation is sensitive. Under the circumstances indicated, a hollow finite walled tube with the outer face regarded as insulated or at a constant temperature would have been more suitable. It would have been very useful had the authors presented a comparison of these models with theirs. Finally, the authors' citation of Ref. 8 is incorrect as it appears. It should be Imber, M. and Khan, J.

References

- ¹Chen, C.J. and Thomsen, D.M., "On Transient Cylindrical Surface Heat Flux Predicted from Interior Temperature Response," *AIAA Journal*, Vol. 13, May 1975, pp. 697-699.
- ²Sparrow, E.M., Hadji-Sheikh, A., and Lundgren, T.S., "The Inverse Problem in Transient Heat Conduction," *Transactions of the ASME, Ser. E: Journal of Applied Mechanics*, Vol. 31, 1964, pp. 369-375.
- ³Imber, M. and Khan, J., "Prediction of Transient Temperature Distributions with Embedded Thermocouples," *AIAA Journal*, Vol. 10, June 1972, pp. 784-789.
- ⁴Imber, M., "A Temperature Extrapolation Method for Hollow Cylinders," *AIAA Journal*, Vol. 11, Jan. 1973, pp. 117-118.

Reply by Author to M. Imber

C.J. Chen*

University of Iowa, Iowa City, Iowa

WE would like to thank Professor Imber for taking the interest to comment on our paper. We were well aware of Professor Imber and Dr. Khan's work when we did our project.

We would like first to clarify what we meant by "only one interior probe." By this we mean that in the actual experimental measurement of heat flux to the inner surface of a hollow cylinder, only one probe is needed interior to the cylinder wall. We know that for the problem, the partial differential equation, Eq. (1) of our paper (Ref. 1), requires one initial and two boundary conditions, Eqs. (2-4) of Ref. 1. For our problem, we considered that the initial temperature distribution is uniform and that the two boundary temperatures are given by an interior probe and a probe at the outer surface. For a short time duration in which the temperature at the outer surface does not change we may replace the outer boundary by a larger radius. A practical situation of this type is the gun barrel heating problem where the duration of a shot is only 2 to 5 milliseconds while the temperature at the barrel outer surface does not change for 5 to 10 seconds after the firing.

The reason that we favor only one interior probe is that in practice any probes embedded interior to the cylinder will distort the temperature field and hence create errors in measurement.^{2,4} On the other hand, at least one probe must be embedded interior to the cylinder wall to improve the response time and the magnitude of response which is important in the inversion problem. Therefore we conducted all our experiments with only one interior probe and the other probe was located at the outer surface. When the outer probe did not respond we found that we could not apply your Eqs. (8) and (7) (of your Ref. 4) for backward extrapolation. This is why

we performed our analysis. Therefore for relatively short times our solution should apply satisfactorily and your analysis may apply only when both probes start to respond.

You are right in pointing out that the matrix associated with the use of our polynomial, Eq. (10), can be nearly singular when the number of equations, N , is too large. We had in our computer code a maximum of $N=20$ with good results. We found that a ten term polynomial is sufficient to give satisfactory results and use of N more than 20 will probably make the inversion of the matrix difficult because of increasing singular behavior as you mentioned.

In all our calculations we always checked the predicted temperature at the outer surface to validate our assumption of constant temperature. Finally we apologize for the typing error in Dr. Khan's name.

References

- ¹Chen, C.J. and Thomsen, D.M., "On Transient Cylindrical Surface Heat Flux Predicted from Interior Temperature Response," *AIAA Journal*, Vol. 13, May 1975, pp. 697-699.
- ²Chen, C.J. and Li, Peter, "Theoretical Error Analysis of Temperature Measurement by an Embedded Thermocouple," *Letters in Heat and Mass Transfer*, Vol. 1, No. 2, 1974, p. 171.
- ³Chen, C.J. and Danh, T.M., "Experimental Study of Transient Distortion in a Slab Due to Thermocouple Cavity," *AIAA Journal*, Vol. 14, 1976, to be published.
- ⁴Beck, J.V. and Hurwicz, H., "Effect of Thermocouple Cavity on Heat Sink Temperature," *Journal of Heat Transfer*, Vol. 82, Feb. 1960, pp. 27-36.

Comment on "Boundary-Layer Transition on Supersonic Cones in an Aeroballistic Range"

A.B. Bailey*

ARO, Inc., Arnold Air Force Station, Tenn.

POTTER¹ recently reported on a study of boundary-layer transition on supersonic cones in an aeroballistic range. A conclusion drawn from this investigation is that the local Reynolds number of transition increases with increasing unit Reynolds number. It is the purpose of this Note to show that measurements of the Reynolds number at which full turbulence occurs in the wake of high-speed cones shows a similar variation. The results of two aeroballistic range investigations of transition in the wake^{2,3} are compared with Potter's results in Fig. 1. The subscript δ denotes computed body surface or "edge-of-boundary-layer" flow conditions, and the length characterizing transition is axial distance measured from cone apex. The good agreement between these wake and body transition measurements when compared in this manner suggests that they may be related phenomena. Similar effects are present in other aeroballistic range measurements of transition Reynolds numbers.⁴⁻⁷

In some of the attempts to correlate wake transition measurements^{2,4,7} a Reynolds number based on body diameter has been used as a correlating parameter. A con-

Received July 31, 1975. The research reported herein was conducted by the Arnold Engineering Development Center and sponsored by Air Force Cambridge Research Laboratories. Research results were obtained by personnel of ARO, Inc., contract operator of the Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), Arnold Air Force Station, Tennessee.

Index category: Boundary-Layer Stability and Transition.

*Research Engineer, Aerodynamics Project Branch, von Karman Gas Dynamics Facility, Associate Fellow AIAA.

Received December 30, 1975.

Index categories: LV/M Aerodynamic Heating; Rocket Engine Testing; Heat Conduction.

*Associate Professor, Energy Division, College of Engineering.