

Errata

Motion and Deformation of Very Large Space Structures

Ramesh B. Malla

University of Connecticut, Storrs, Connecticut
and

William A. Nash and Thomas J. Lardner
University of Massachusetts, Amherst, Massachusetts

[AIAAJ 27, No. 3, pp. 374-376 (1989)]

Control of Flexible Structures by Applied Thermal Gradients

Donald L. Edberg

*Jet Propulsion Laboratory,
California Institute of Technology,
Pasadena, California*

[AIAAJ 25, No. 6, pp. 877-883 (1987)]

THE following errors were made inadvertently during production of this paper. On page 375, Eqs. (3a) and (3c) contained errors. The correct equations are as follows:

$$m\ddot{r}_c - mr_c\dot{\theta}^2 + \mu \left[\frac{m_1(r_c + x_1 \cos\phi)}{r_1^3} + \frac{m_2(r_c - x_2 \cos\phi)}{r_2^3} \right] = Q_r \quad (3a)$$

$$\begin{aligned} m\ddot{x} - m\dot{x}(\dot{\theta} + \dot{\phi})^2 + \dot{m}\mu \left[\frac{(x_1 + r_c \cos\phi)}{r_1^3} + \frac{m_2(x_2 - r_c \cos\phi)}{r_2^3} \right] \\ + \frac{Gm_1m_2}{x^2} + \frac{\partial U_e}{\partial x} = Q_x \end{aligned} \quad (3c)$$

On page 376, the penultimate sentence in the section titled "Physical Model and Initial Conditions" should read as follows:

Two elliptical orbits are considered—one with the initial orbital angular velocity $\dot{\theta}_0$ equal to 0.0738 rad/min, giving a small orbit eccentricity ($e = 0.0785$), and the other with $\dot{\theta}_0$ equal to 0.08883 rad/min, giving a fairly large orbit eccentricity ($e = 0.56$).

THE following errors were made inadvertently during production of this paper. On page 878, Eqs. (2) and (5) contained errors. The correct equations are as follows:

$$T \equiv \frac{\partial T_{\text{step}}(t)}{\partial t} = \frac{Q}{\rho ch S} \left[1 + \frac{2}{\pi^2} \sum_{n=1}^{\infty} \frac{(-1)^n}{n^2} \beta_n e^{-\beta_n t} \cos \frac{n\pi z}{h} \right] \quad (2)$$

$$\frac{T(t)}{V_c(t)} = \frac{C_{QV}}{\rho ch n_s S} \left[1 + \frac{2}{\pi^2} \sum_{n=1}^{\infty} \frac{(-1)^n}{n^2} \beta_n e^{-\beta_n t} \cos \frac{n\pi z}{h} \right] \quad (5)$$