tion by the Method of Least Squares (070)

CEP (July, 1961), p. 78

Discounted Cash Flow (066)

A General Method for Calculating the Specific Impulse of Propellant Systems (0.76)

CEP (August, 1961), p. 72

Batch Distillation of Binary Mixtures at Varying Reflux (076) Batch Distillation of Binary Mixtures at Constant Reflux (077)

CEP (September, 1961), p. 74

Arc Length (078) Numerical Mathematical Analysis (080)

ERRATA

The factor, $\sqrt{2}$, should be included on the right side of the equation defining the equivalent diameter D_* in the Notation for "An Experimentally Verified Theoretical Study of the Falling Viscometer," by John Lohrenz, G. W. Swift, and Fred Kurata, which appeared in the December, 1960, issue of the A.I.Ch.E. Journal.

In Equation (8) in "Chemical Reaction Processes in Two-Phase Systems: Theory and Experimental Results for Slow Chemical Reactions in Batch, Column, and Continuous Stirred Tank

Reactor Operations," by Pierre Trambouze, M. T. Trambouze, and Edgar Piret, which appeared in the March, 1961, issue of the A.I.Ch.E. Journal, a_1 and a_2 should be in italics. In Equation (17) of the same paper the second term should be da_2/dx .

The parameter η in "A Note on Transport to Spheres in Stokes Flow," by S. K. Friedlander, which appeared in the June, 1961, issue of the A.I.Ch.E.

Journal, should be defined as follows: $\eta = \alpha^{-1/3} y_1 \sin x_1/$

$$(\int_0^{x_1} \sin^2 x_1^1 d x_1^1)^{1/8}$$

Corrected Figure 5 for "Heat and Momentum Transport Characteristics of Non-Newtonian Aqueous Thorium Oxide Suspensions," by D. G. Thomas, which appeared in the December, 1960, issue of the A.I.Ch.E. Journal, appears below.

