

Different Generic Types of Aeration Equipment," *33rd Ann. Purdue Indust. Waste Conf.*, W. Lafayette, IN, p. 31 (1978).  
 Schaftlein, R. W., and T. W. F. Russell, "Two-Phase Reactor Design Tank-Type Reactors," *Ind. Eng. Chem.*, **60**, 12 (1968).  
 Sideman, S., O. Hortaceu, and J. W. Fulton, "Mass Transfer in Gas-Liquid Contacting Systems," *Ind. Eng. Chem.*, **58**, 32 (1966).  
 Towell, G. D., C. P. Strand, and G. H. Ackerman, "Mixing and Mass Transfer in Large-Diameter Bubble Columns," *AIChE J. Chem. E. Symp. Ser.*, **10**, 97 (1965).  
 Ueyama, K., S. Morooka, K. Koide, H. Kaji, and T. Miyauchi, "Behavior of Gas Bubbles in Bubble Columns," *Ind. Eng. Chem. Process Des. Dev.*, **19**, 592 (1980).  
 Ulbrecht, J. J., and Z. S. Baykara, "Significance of the Central Plume Velocity for the Correlation of Liquid Phase Mixing in Bubble Columns," *Chem. Eng. Commun.*, **10**, 165 (1981).

Urza, I. J., and M. L. Jackson, "Pressure Aeration in a 55 yd. Bubble Column," *Ind. Eng. Chem. Process Des. Dev.*, **14** (1975).  
 Weiland, P., "Influence of Draft Tube Diameter on Operation Behavior of Airlift Loop Reactors," *Ger. Chem. Eng.*, **7**, 374 (1984).

Manuscript received Jan. 2, 1986, and revision received Oct. 2, 1986.

See NAPS document no. 04476 for 4 pages of supplementary material. Order from NAPS c/o Microfiche Publications, P.O. Box 3513, Grand Central Station, New York, NY 10163. Remit in advance in U.S. funds only \$7.75 for photocopies for \$4.00 for microfiche. Outside the U.S. and Canada, add postage of \$4.50 for the first 20 pages and \$1.00 for each of 10 pages of material thereafter, \$1.50 for microfiche postage.

## Errata

In Table 1 of the R&D Note titled "P-V-T Relations of Propane in the Range 373.15–423.15 K and 0.2–4.0 MPa" (July, 1982, p. 695), the following column headings should be added across the table after 19 entries ending with 0.253 . . . :

Temp.: 403.15 K		Temp.: 413.15 K		Temp.: 423.15 K	
Pressure MPa	Compressibility Factor	Pressure MPa	Compressibility Factor	Pressure MPa	Compressibility Factor

In the same table, the compressibility factor at 1.074 MPa and 423.15 K is 0.9528, not 0.9697.

The price of the book titled "Mixing in the Process Industries" was given incorrectly as \$87.95 in the review (Aug. 1986, p. 1403). It is \$45.00.

In the paper titled "Diffusion and Mass Transfer in Supercritical Fluids," by P. G. Debenedetti and R. C. Reid [**32**(12), p. 2034, 1986], the following corrections are made:

p. 2035: First term of Eq. 11 should read " $\frac{2}{Re} (\nabla^+)^2 \psi^+$ ".

p. 2042: Line 12 should read "at any given temperature . . ."

p. 2044: In the Notation,  $Gz'$  should read " $x\mathcal{D}/\langle v \rangle b^2$ ".