

SUBJECT INDEX

Note: Page numbers followed by “*f*” indicate figures, and “*t*” indicate tables.

- Aciplex®, 158
- Aging phenomena, in PEMFCs
 - bimetallic alloy catalysts
 - degradation, 311–314
 - durability test protocols, 314
 - overview, 310
 - property design, 310–311
 - coupled membrane and catalytic layer
 - degradation
 - active species and radicals, formation of, 303, 304*f*
 - fuel (gas) crossover, 303
 - membrane creep formation, 304
 - platinum dissolution, 300–302
 - Pt dissolution on membrane
 - degradation, 302–303
 - experimental protocols
 - constant current density, 281–284
 - contaminants, 294–299
 - cyclic voltammetry, 280–281
 - freezing effect, 292–294
 - humidification, reacting gases, 289–292
 - long-term fuel cell operations, 280
 - periodic variations, current density, 284–288
 - sawtooth voltage profiles, 280–281, 281*f*
 - transient phenomenon, 280
- FC contamination
 - nonuniform cell behavior, CO
 - poisoning, 316–318
 - published data analysis, 314–316
- RH cycling
 - electrochemical behavior, 305–308
 - TEM, 308–309
- shutdown/start-up procedure
 - electrical phenomena, 321–322
 - electrode potential, 321
 - hydrogen introduction into anode, 320, 320*f*
 - qualitative assessment, cell
 - degradation, 322–324
 - qualitative consequences, 321
- Air compressor, 215–216
- Air supply subsystem, 202–208
- Air supply system, PEMFC system control
 - control strategies for, 237–238, 238*f*
 - cost function and time constant, 247*f*
 - with current regulations, 240–241
 - index function, 245–247
 - O₂ SR control, 242–243
 - air-flow rate, at stack inlet, 245*f*
 - compressor motor voltage, profile of, 245*f*
 - compressor speed, profile of, 246*f*
 - control block diagram, 242*f*
 - required current, load cycle of, 243*f*
 - set point, 244*f*
 - O₂SR fluctuations with current
 - regulation, 243–248
 - oxygen stoichiometry ratio, definition, 238
 - profiles of O₂SR, 248*f*
 - regulated current cycle, 248*f*
 - without current regulation, 239–240
- Anode gas recycle (AGR), SOFC
 - advantages, 412
 - definition, 411–412
- Anodic oxidation, of methanol, 149–151
- Arrhenius relationship, PEMFC kinetics, 74–76
- Autothermal reforming (ATR), 22, 406

- Balance of plant (BOP)
 - definition, 413
 - for fuel cells, 34–35
- Biomass, 17–18
- Bimetallic alloy catalysts, PEMFCs
 - degradation evaluation, 313–314
 - durability test protocols, 314
 - overview, 310
 - property design, 310–311
 - Pt/Co degradation, 311–312, 312*f*
- Bipolar plates, 278–279
- Boltzmann distribution, 82–83
 - modified, 98
- Booth's equation, 99
- BOP. *See* Balance of plant (BOP)
- Bruggeman factors, thermal conductivity, 88–89
- Butler–Volmer equation, 74–76
- Butler–Volmer form
 - elementary reaction in, 353
 - multiple reaction steps, 353–354
- Button cells, 368, 369*f*
- Canonical variate analysis (CVA), 165–166
- Carbon-to-oxygen ratio, 20–21
- Carman–Kozeny equation, 103–104
- Catalyst layer, in PEMFC
 - degradation
 - chemical analysis, 276
 - electrode active surface, 276
 - fuel (gas) crossover, 303
 - membrane creep formation, 304
 - platinum catalysts, 273–274, 274*f*
 - platinum dissolution, 300–303
 - polarization of performance curve, 275
 - techniques, for evaluation, 275–277, 275*t*
 - XRD and TEM, 277
 - modeling
 - conservation equation for oxygen, in
 - cathode, 116
 - current density, 119
 - dimensionless Thiele modulus, 116–119
 - effectiveness factor, 116–119, 118*f*
 - equivalent-circuit representation, of
 - porous electrode, 115–116, 115*f*
 - HOR kinetic expression, 116–119
 - interfacial area, 116
 - oxygen concentration, numerical
 - simulation results for, 113–115, 114*f*
 - reaction area, 119
 - reaction rate of ORR, 116–119
 - spherical agglomerate, 116–119
 - transport resistance of oxygen, 116–119
 - X-ray microtomography, macropore
 - distribution, 113–115, 114*f*
- Catalytic monoliths, 55, 56*f*
- Catalytic partial oxidation (CPOX), 406
 - of diesel, 28, 29
 - of ethanol/*iso*-octane blends, 27, 28*f*, 40–42, 49, 49*f*, 50*f*, 52–54, 54*f*
 - of gasoline, 27
 - hydrocarbon fuels conversion, 22
 - of hydrocarbons, 26–27
 - H₂ yields, 26–27, 26*f*
 - of methane, 46, 47–48, 55, 56*f*
 - of natural gas, 49
 - of propane, 40, 50
- Catalytic steam reforming (CSR)
 - benefits, 404
 - equilibrium predictions, 405, 405*f*
 - fuel-cell configurations, 403–404, 403*f*
 - solid carbon formation, 404–405
- Cathode gas recycle (CGR), in SOFC
 - advantages, 412–413
 - definition, 412
- Cathodic reduction of oxygen, in DMFC, 151–152
- Cell ohmic resistance, 305–306
- Cell-stack efficiency, 407
- Cell structure, in SOFC
 - composite anode, 340–341
 - composite cathode, 339–340
 - dense electrolyte membrane, 340
 - electrode microstructure, 341–342
 - MEA and channel structure, 338–339, 338*f*
- Cell voltage monitoring (CVM)
 - arrangement of, 249*f*
 - hardware structure, 250–252
 - exemplary system, 251, 252*f*
 - operational scheme of, 251, 251*f*
 - U*–*I* curve, of fuel cell, 250–251, 250*f*
 - research methods and challenges, 256–257
 - software design, 252
 - timer interruption program, flowchart
 - of, 253*f*
- Ceramic Fuel Cells Limited's BluGen®
 - technology, 33
- Charge-transfer reaction, in solid-oxide fuel cells, 340

- Charge transport, in PEMFC
 - Boltzmann distribution, 82–83
 - charge balance, 82–83
 - concentrated-solution approach, 84–85
 - and current densities, 82–83
 - dilute-solution approach, 83–84
 - double-layer capacitance, 82–83
 - Poisson's equation, 82–83
- Coal, 12
- Computational fluid dynamics (CFD), 198–199, 257
- Computational implementation, for solid-oxide fuel cells, 376–377
- Contaminants, in PEMFC
 - contamination capacity, 299
 - degradation effects, 297*t*
 - gas, 296
 - ions, 295–296
 - pollutant, 298*f*
- Cooling system, in lumped parameter model, 208, 208*f*
- Counter-flow planar fuel cell, 392, 393*f*
- CPOX. *See* Catalytic partial oxidation (CPOX)
- Crude oil, 12–14
- CSR. *See* Catalytic steam reforming (CSR)
- Current density
 - aging
 - DMFC cells, 282–283
 - low current density, 283–284
 - nominal, regular current density, 281–283
 - periodic variations, 284–288
 - catalyst layer modeling, 119
 - DMFC
 - porous electrode, 176
 - transient of, 190–191
- CVM. *See* Cell voltage monitoring (CVM)
- Darcy's law, 85–86, 103–104
- Dense electrolyte membrane, SOFC, 340
- Desulfurization, 18, 19*f*, 402–403
- Diesel, 14, 28–29, 29*f*
- Direct methanol fuel cells (DMFC)
 - aging, 282–283
 - at anode, carbon dioxide formation, 146–147
 - at cathode, water formation, 147
 - cell reaction, 147
 - drawback of, 147
 - dynamic behavior, of catalyst
 - current density, transient of, 190–191
 - intermediate species, transient of coverage, 187–190
 - OH on Ru sites, 188–189, 189*f*
 - reaction of CO_{ads}, 189–190
 - temperature, methanol concentration, and overpotential, 187, 188*f*
 - electromotive force, 147
 - liquid-feed system, 149
 - mathematical modeling
 - cell models, 161–163
 - cell polarization data, 154–155, 154*f*
 - components in, 155–156
 - dynamics and, 165–171
 - electrode modeling, 160–161
 - flow field, 154
 - membrane transport, 158
 - methanol crossover effect, on fuel-cell performance, 159–160
 - methanol oxidation, 157–158
 - nonisothermal modeling, 164
 - two-and three-dimensional modeling, 163–164
 - types of, 156
 - polarization curves and electrodes, 147–148, 148*f*
 - porous electrode, model of
 - assumptions in, 172
 - concentration, overpotential, and current density, distributions of, 180–182
 - 1D model of, 171–172
 - dual-site mechanism, for methanol oxidation, 172–174
 - effectiveness, 182–184
 - intermediate species, coverage ratios of, 177–179
 - macrokinetics model, 174–177
 - model validation, 184–187
 - polarization curves, 182
- as power sources, 191
- principles of operation
 - anodic oxidation of, 149–151
 - cathodic reduction, of oxygen, 151–152
 - materials and performance, 152–153
- with proton conducting membrane,
 - schematic diagram of, 147, 148*f*
- thermodynamic potential, 147
- vapor-feed system, 149

- Disturbance inputs, in SOFC process control, 430–431
- Disturbance rejection, in SOFC process control, 433–435
- DMFC. *See* Direct methanol fuel cells (DMFC)
- Dual-site mechanism, for methanol oxidation, 172–174
- Dusty-gas model (DGM), 355

- Electrochemical impedance spectroscopy (EIS)
 - methane, 370–371, 371*f*
 - qualitative aspects, 369–370, 369*f*
- Electrochemistry, SOFC
 - activation overpotentials, 346–347
 - Butler–Volmer form (*see* Butler–Volmer form)
 - concentration overpotentials, 347–348
 - ohmic overpotentials, 345–346
 - polarization and overpotentials, 345
 - reversible potential, 343–345
 - RH cycling, 305–308
- Electrode modeling, in DMFC, 160–161
- Energy conservation and transport, PEMFC
 - charge-transfer reactions, 88
 - enthalpy change, 86–88
 - Joule/ohmic heating, 88
 - Peltier coefficient, for charge-transfer reaction, 86–88
 - single thermal energy equation, 88
 - thermal conductivity, 88–89
 - thermal energy, 86–88
- Ethanol, 24–25, 25*f*
- Exergetic electric efficiency, 407
- Exergy analysis
 - evaluation of, 416–418
 - exergetic balances and efficiencies, 418–419
 - SOFC-CHP system, 419–422

- Faraday's law, 74–76, 174, 202
- Faradic current density, 353
- Fault diagnosis technology, for PEMFC system control, 249–257
- Fick's first law, 174
- Flemion®, 158
- Fluent®/Simulink® collaborative simulations, PEMFC system modeling applications, 223
- establishment of platform
 - air compressor, 215–216
 - data transmission, 214–215, 214*f*
 - fuel cell stack, 216–219
 - humidifier, 216
 - hydrogen supply, 215
 - model simplifications and assumptions, 215
- numerical implementation and elucidation
 - cathode pressure drop and air-flow change, with time, 219, 220*f*
 - cathode water saturation change with time, 221, 222*f*
 - current and voltage change with time, 219, 219*f*
 - species molar concentration change, with time, 220, 221*f*
- Freeze–thaw cycles, 293
- Freezing effect, PEMFC, 292–294
- Fuel-cell catalytic steam reforming configurations, 403*f*
- Fuel cell stack model
 - Fluent®/Simulink® collaborative simulations
 - conservation equations, in vector form, 216–217
 - flow inlet boundaries, 218*t*
 - outlet boundaries, 218*t*
 - saturation model, 217
 - walls, 218*t*
 - lumped parameter model development, 201–202
- Fuel flow, 6, 8*f*
- Fuel processing
 - applications, 6, 7*t* (*see also* Reaction networks, of fuel reforming)
 - cleaning
 - desulfurization, 18, 19*f*
 - pre-reforming, 20
 - conversion of hydrocarbon fuels to hydrogen
 - autothermal reforming, 22
 - carbon-to-oxygen ratio, 20–21
 - diesel, 28–29, 29*f*
 - ethanol, 24–25, 25*f*
 - gasoline, 25–27, 28*f*
 - methanol, 24
 - natural gas, 22–24
 - requirements, 18, 19*f*
- field of application
 - back-up systems, 32

- balance of plant (BOP), 34–35
- Ceramic Fuel Cells Limited's BluGen®
 - technology, 33
- for fuel cell types, 33–34
- large-scale power plants, 32
- mobile applications, 33
- replacement of conventional batteries, 33
- fuel flow, 6, 8*f*
- fuel quality, 8–10, 9*t*
- modeling
 - dynamics of monolithic catalytic reformers, 43–45, 44*f*
 - mass and heat transport, 42–43
 - physical and chemical processes, 35–36, 36*f*
 - rate of heterogeneous catalytic reactions, 37–40, 41*t*
 - rate of homogeneous reactions in the gas phase, 40–42
 - reformer design and operating conditions, 45
- primary fuels
 - biomass, 17–18
 - coal, 12
 - crude oil, 12–14
 - diesel, 14
 - gasoline, 13–14, 13*t*
 - hydrogen, 10–11
 - kerosene, 14
 - liquefied petroleum gas (LPG), 12–13
 - natural gas, 15–17
 - physical properties, 10, 11*t*
- product clean-up and optimization
- preferential oxidation of carbon monoxide (PrOX), 31
- removal of CO in syngas, 30
- WGS reaction, 30
- reaction networks (*see* Reaction networks, of fuel reforming)
- SOFC
 - autothermal reforming, 406
 - catalytic partial oxidation, 406
 - CSR (*see* Catalytic steam reforming (CSR))
 - definition, 401
 - desulfurization, 402–403
 - reforming processes, global reactions in, 401–402, 402*f*
- Fuel quality, 8–10, 9*t*
- Gas contaminants, 296
- Gas diffusion layer (GDL) degradation
 - causes, 277–278
 - corrosion, 278
- Gas flow channel and flowfields modeling, in PEMFC
 - dimensionalities model, fuel-cell schematic, 120, 120*f*
 - force-balance approach, 122–123
 - liquid water, 121–122
 - modeling domain, 2D sandwich model, 121, 121*f*
 - pressure force, 122–123
 - shear force, 122–123
- Gas/gas humidifier, 205–206
- Gasoline, 13–14, 13*t*, 25–27, 28*f*
- Gibbs free energy, 71–73
- Heat loss, SOFC, 415
- Heat management, PEMFC system control
 - literature review, 230–233
 - modeling and controller design
 - coolant flow distributor, 233–234
 - cooling network diagram for, 233*f*
 - heat balance for, 234
 - maximal heat taken, 235
 - required coolant mass flow rate, 235
 - temperature of combined coolant, 234
 - simulation and results, 236
 - feedforward+PID and feedforward+MPC, 237*f*
 - load cycle, of required current, 236*f*
- Hot-zone layout, SOFC, 395, 395*f*
- Humidification, reacting gases
 - periodic variations, gas humidity, 290–292, 291*t*
 - steady-state poor humidification conditions, 289–290
- Humidifier, 216
- Hydrocarbons
 - conversion to hydrogen, 20–29
 - pre-reforming/cracking of, 18–20
- Hydrogen, 10–11
 - fuel cell, thermodynamic potentials and definitions, 71–72, 72*f*
 - production, in fuel processing, 6, 10, 12, 15–16, 22, 23–24, 25, 35, 54–55
- Hydrogen-oxidation reaction (HOR), 76–77
 - kinetic expression, 116–119

- Hydrogen purge, PEMFC system control
 - cost function and parameter selection definition, 225
 - demonstration of, 225*f*
 - engineering optimization method, 226–228
 - H₂ utilization ratio and purge duration times, 228*f*
 - liquid water and purge duration times, 228*f*
 - optimum purge continuous time comparison, 232*f*
 - optimum values, 232*t*
 - parameter impaction, analysis of, 227*f*
 - results, 229
 - scope of parameters, 226
 - stack efficiency and purge duration times, 229*f*
 - stack voltage comparison, 230*f*
 - undulate voltage value comparison, 231*f*
 - literatures, 224–225
- Impedance modeling, in PEMFC, 124–125
- Internal reforming
 - pre-reformer
 - methane conversion, 409–410, 410*f*
 - purpose of, 409
 - temperature-gradient profiles, 410, 411*f*
- Ion contaminants, 295–296
- Ionomer content, in catalyst layer, 133, 133*f*
- Kelvin equation, 104
- Kerosene, 14
- Knudsen diffusion coefficients, 102–103, 103*f*, 355
- Leverett-J function, 105–106
- Life cycle costing (LCC), SOFC systems
 - capital recovery factor, 423
 - cost of electricity, 423
 - definition, 422
 - electricity capacity factor, 423
 - evaluation, 424
 - power system, 424
- Liquefied petroleum gas (LPG), 12–13
- Lumped parameter model development, in PEMFC system modeling, 199
 - air supply subsystem
 - air compressor, 203–205
 - angular velocity, of compressor, 204
 - back pressure valve, 207
 - expender, 207–208
 - gas/gas humidifier, 205–206
 - gas pipe, 207
 - intercooler, 205
 - inverse calculating method, 203
 - schematic diagram of, 202, 203*f*
 - fuel cell stack, 201–202
 - hydrogen supply
 - inlet pressure, 209
 - storage container model, 209, 210*f*
 - parasitic power, 209–210
 - simulation and results, 210
 - demand and total current, of stack, 211*f*
 - output voltage, of stack, 212*f*
 - predicted and measured stack polarization curve comparison, 211*f*
 - pressure, in air supply system, 212*f*
 - relative humidity, air supply system, 213*f*
 - temperature, in air supply system, 213*f*
 - structure of, 201, 201*f*
 - thermal management system, 208–209
- Lumped thermal model, 396–397
- Mass transfer phenomena, 285
- Mathematical modeling, of DMFC
 - cell models, 161–163
 - cell polarization data, 154–155, 154*f*
 - components in, 155–156
 - dynamics and
 - canonical variate analysis (CVA), 165–166
 - evolution of cell voltage, 167, 167*f*
 - nonisothermal optimization, 168
 - nonlinear circuit model, 169–171
 - open-circuit voltage response, cell temperature, 169, 170*f*
 - passive, 167
 - pulsed methanol-solution, effect of, 165, 166*f*
 - small single cells, under variable load conditions, 165, 165*f*

- transient-thermal behavior, 168–169
- unsteady-state model, 169
- electrode modeling, 160–161
- flow field, 154
- membrane transport, 158
- methanol crossover effect, on fuel-cell performance
 - methanol flow, at anode, 159–160
 - water transport (flux), 159
- methanol oxidation, 157–158
- nonisothermal modeling, 164
- oxygen reduction, 156–157
- two-and three-dimensional modeling, 163–164
- types of, 156
- MATLAB®, 210
- Membrane
 - creep formation, 304
 - degradation
 - high-frequency resistance, 273
 - Nafion®, 270–271
 - techniques, for evaluation, 271–272, 272f
 - water transfer coefficient, 272
 - thinning, 270–271
 - transport modeling, in DMFC, 158
- Membrane-electrode assembly (MEA), in SOFC
 - button cells, 368, 369f
 - energy balance, 367
 - modeling, 342–348
 - SEM, 342, 343f
- Membrane modeling, in PEMFC
 - dominant fluxes, schematic of, 90–91, 91f
 - governing equations
 - chemical potential, 94
 - current density, 92–93
 - gas crossover, 94
 - number of water molecules, 92–93
 - potential, 92–93
 - three-component system, 92
- macroscopic models, 91
- multi-ion transport, 99
 - Booth's equation, dielectric-constant distribution, 99
 - four-component system, 99–100
 - limiting current density, average potassium cation fraction, 100, 101f
 - modified Boltzmann distribution, 98
- Nafion, 89–90
- water content and transport properties
 - concentration of water, 97–98
 - differential equations, 95–97
 - mass-transfer coefficient, 95–97
 - partial molar volume, of dry membrane, 95–97
 - swelling, 95–97
 - thermodynamic driving force, 97–98
 - transport coefficient, 97–98
 - water-uptake curve, 94–95, 95f
 - water-uptake isotherm, 95–97
- Methane
 - chemical exergy, 417–418
 - CPOX of, 55, 56f
 - reaction networks, 46–48, 47f
 - reforming process, 401–402, 402f
- Methane-fueled SOFC CHP system, process flowsheet, 419, 420f, 421f
- Methanol
 - crossover effect, on DMFC performance, 159–160
 - oxidation, in DMFC
 - anodic oxidation of, 149–151
 - dual-site mechanism, 172–174
 - mathematical modeling, 157–158
 - steam reforming, 24
- Microchannel reactor, 391–392, 392f
- Modeling, reactor. *See* Reactor modeling, fuel processing
- Model-predictive control (MPC)
 - advantages, 436
 - data flow, 436, 437f
 - implementation, 436
 - model reduction, 440, 441f
 - results, 441–442, 442f
 - weighted Euclidean norm, 438
- Momentum conservation and transport, PEMFC
 - Darcy's law, 85–86
 - Navier–Stokes equation, 85–86
- Nafion®, 89–90, 95f, 147, 152, 158
- Natural gas, 15–17, 22–24
- Navier–Stokes equation, 85–86
- Nernst–Planck equation, 83–84
- Nernst potential, 342–343
- Nernst relation, in PEMFC
 - thermodynamics, 72–73
- Net system electrical efficiency, 407

Nonisothermal modeling, in DMFC, 164
Nyquist plot, 285–286

Ohmic overpotentials

PEMFC, single-parameter optimization,
127, 128*f*

SOFC electrochemistry, 345–346

Ohm's law, 68–69, 82–83, 102, 174, 176

Optimization

PEMFC

multiparameter, 135–139

single-parameter, 126–135

SOFC

fuel utilization, 425–427

life cycle costing, 422–425

optimal cell temperature and air
temperature rise, 427–429

optimal cell voltage, 425–427

Oswald ripening phenomenon, 273–274

Oxygen-reduction reaction (ORR), 77–78

reaction rate of ORR, 116–119

Oxygen stoichiometry ratio (O_2 SR) control,
242–243

fluctuations with current regulation,
243–248

Partial oxidation (POX), hydrocarbon
conversion processes, 21, 22, 23,
24, 25

Peltier coefficient, for charge-transfer
reaction, 86–88

PEMFCs. *See* Proton exchange membrane
fuel cells (PEMFCs)

Percolation theory, 358

Planar solid oxide fuel cell stack, 334–335,
335*f*

Platinum

dissolution on membrane degradation,
302–303

methanol oxidation, 149–151

Pt/Co degradation, 311–312, 312*f*

Poiseuille flow, 111–112

Poisson's equation, 82–83

Polymer-electrolyte fuel cells (PEFCs), 66

Polymer electrolyte membrane (PEM) fuel
cells. *See* Proton exchange membrane
fuel cells (PEMFCs)

Porous electrode, DMFC model
assumptions in, 172

calculated and experimental anode
polarization data, comparison
of, 186*f*

concentration, overpotential, and current
density, distributions of, 180–182

1D model of, 171–172

dual-site mechanism, for methanol
oxidation

Faraday's law, 174

Pt–Ru catalyst, steps for, 172

rate expression, 172–173

rates, of changes of surface
coverage, 173

effectiveness, 182–184, 185*f*

intermediate species, coverage ratios of,
177–179

macrokinetics model

boundary conditions, 174, 175

current density, 176

1D electrode, 175

dimensionless equations, 175

effectiveness factor, 176

Fick's first law, 174

flux of methanol, divergence of, 174

kinetics parameters, 178*t*

Ohm's law, 174

overpotential, nonlinear Poisson
equation, 175

physical parameters, 177*t*

model validation, 184–187

polarization curves, 182, 183*f*

Porous media, in PEMFC

Carman–Kozeny equation, 103–104

Darcy's law, in flux form, 103–104

domain pore size and contribution ratio,
102–103, 103*f*

gas phase, 102–103

Knudsen diffusion coefficient, 102–103,
103*f*

multiphase flow

back-of-the-envelope calculations,
Stefan–Maxwell equations,
109–110, 109*f*

capillary pressure, 104, 105*f*

contact-angle distribution, 106–108

effective permeabilities, 105–106

effective saturation, 106–108

integration approach, 106–108

Kelvin equation, vapor phase, 104

Leverett–J function, 105–106

liquid-phase velocity, 106–108

- liquid saturation, 104–105
- multiphase mixture approach, 106–108
- phase-change-induced flow, 108, 109–110, 109f
- reaction equation of, 104
- relative mobility, of liquid phase, 106–108
- relative permeability, of gas and liquid, 106–108
- SGL gas-diffusion layer, 105f
- Ohm's law, 102
- pore-network models
 - capillary pressure, 111–112
 - Poiseuille flow, 111–112
 - schematic of, 110–111, 111f
 - water distributions, 112–113, 113f
- scanning-electron micrograph, of catalyst and carbon paper gas-diffusion layer, 100–102, 101f
- tortuosity/diffusional path length, 102–103
- Potential-energy surfaces, in solid-oxide fuel cell, 351–352, 352f
- POX. *See* Partial oxidation (POX), hydrocarbon conversion processes
- Preferential oxidation of carbon monoxide (PrOX), 31
- Primary fuels
 - biomass, 17–18
 - cleaning, 18–20
 - coal, 12
 - crude oil, 12–14
 - diesel, 14
 - gasoline, 13–14, 13t
 - hydrogen, 10–11
 - kerosene, 14
 - liquefied petroleum gas (LPG), 12–13
 - natural gas, 15–17
 - physical properties, 10, 11t
- Proportion integration differentiation (PID) method, 231–233, 237f
- Proton exchange membrane fuel cells (PEMFCs)
 - aging phenomena (*see* Aging phenomena, in PEMFCs)
 - anode and cathode reactions, 67–68
 - cell design, optimization, 126
 - cell potential with current, 69–70
 - computational fluid dynamics (CFD), 198–199, 257
 - conservation and transport equations, 79–80
 - charge, 82–85
 - energy, 86–89
 - mass-averaged velocity, 80–81
 - material, 80–82
 - momentum, 85–86
 - degradation phenomena
 - bipolar plates and cell components, 278–279
 - catalyst layers, 273–277
 - gas diffusion layers, 277–278
 - membranes, 270–273
 - stack operation, 269–270
 - 1D model principle, 316, 316f
 - durability of, 266–267
 - electrical power, 68
 - energy conversion technology, 266–267
 - engineering-oriented modeling, 198–199, 257
 - kinetics
 - activation overpotential, 74–76
 - Arrhenius relationship, 74–76
 - coverage of Pt oxide, 78, 79f
 - current, 74–76
 - electrochemical reaction, 74
 - exchange current density, 77
 - HOR, 76–77
 - ORR, 77–78
 - rate of reversible electrochemical reaction, 74–76
 - reaction diagram, potential impact on elementary electrochemical reaction, 76, 76f
 - reference electrode, 74–76
 - surface/kinetic overpotential, 74–76
 - Tafel approximation, 77–78
 - layers/domains, schematic of, 67–68, 67f
 - membrane electrode assembly, 266
 - model classification, 70
 - modeling
 - boundary conditions, 123–124
 - catalyst layer, 113–119
 - gas flow channel and flowfields, 119–123
 - impedance modeling, 124–125
 - membrane, 89–100
 - porous media, 100–113
 - multicomponent system, 80–81, 84–85, 92, 99–100

- Proton exchange membrane fuel cells (PEMFCs) (*cont.*)
- multiparameter optimization
 - framework, implementation of, 137f
 - functional analysis, 136–137
 - history plot, 137–139, 138f
 - objective function, 136–137
 - optimization problem, 135–136
 - partial differential equations, 136–137
 - polarization curves, 137–139, 138f
 - polarization curve, dominant-loss regimes, 68–69, 69f
 - reliability, 266–267
 - resistive losses, 68–69
 - single-parameter optimization
 - activation and ohmic overpotentials, temperature effect on, 127, 128f
 - cell operating conditions influence, on performance, 127–128
 - fuel-cell potential and catalyst-layer thicknesses, with current density, 133–135, 134f
 - ionomer content, in catalyst layer, 133, 133f
 - oxygen partial pressure and capillary pressure, 130–131, 132f
 - physical and transport properties influence, on cell performance, 129–135
 - polarization and power-density curves, 127, 129f
 - simulations, with and without microporous layer, 130, 131f
 - stoichiometry, 127–128
 - system control, 199–200
 - air supply system, controller design for, 236–248
 - fault diagnosis technology, 249–257
 - heat management, 230–236
 - hydrogen purge, optimal control of, 224–229
 - system modeling
 - distributed parameter models, 199, 200
 - Fluent®/Simulink® collaborative simulations, 210–223
 - lumped parameter model, development of, 200–210
 - thermodynamics
 - efficiency of cell, 72–73
 - enthalpy potential, 71
 - equilibrium potential, 71–72
 - first law of, 71
 - Gibbs free energy, 71–73
 - heat loss, 72–73
 - hydrogen fuel cell, 71–72, 72f
 - ideal-gas law, 72–73
 - Nernst relation, 72–73
 - vapor pressure of water, 72–73
- Reaction networks, of fuel reforming
- coking prediction and control
 - catalyst deactivation, 50–51, 51f
 - coke precursors formation, 51–52, 53f
 - CPOX of methane, 55, 56f
 - flow rate impact on reforming efficiency, 52–55, 54f
 - fuel processor design, 55
 - of fuel reforming
 - iso-octane, 48–50, 49f
 - methane, 46–48, 47f
- Reactor modeling, fuel processing
- dynamics of monolithic catalytic reformers, 43–45, 44f
 - mass and heat transport, 42–43
 - physical and chemical processes, 35–36, 36f
 - rate of heterogeneous catalytic reactions, 37–40, 41f
 - rate of homogeneous reactions in the gas phase, 40–42
 - reformer design and operating conditions, 45
- Resistive model formulation
- lumped thermal model, 396–397
 - radiation resistor, 397
 - thermal resistance network, 397–399, 398f
- Reynolds number, 364–365
- Rolls-Royce architectures, 337
- Segmented-in-series (SIS) module, 336–337, 336f
- Shutdown/start-up procedure, PEMFC
- aging
 - electrical phenomena, 321–322
 - electrode potential, 321
 - hydrogen introduction into anode, 320, 320f
 - qualitative assessment, cell degradation, 322–324
 - qualitative consequences, 321

- Simulink® collaborative simulations.
 - See Fluent® /Simulink® collaborative simulations, PEMFC system modeling
- Solid-oxide fuel cells (SOFC)
 - advantages, 332–333
 - analysis
 - exergy (*see* Exergy analysis)
 - performance definitions, 407–408
 - anode gas recycle, 385, 385f
 - architectures
 - planar stack, 334–335, 335f
 - segmented-in-series module, 336–337, 336f
 - tubular stack, 335, 336f
 - balance of plant, 333
 - button cells and parameter fitting, 368, 369f
 - cell structure
 - composite anode, 340–341
 - composite cathode, 339–340
 - dense electrolyte membrane, 340
 - electrode microstructure, 341–342
 - MEA and channel structure, 338–339, 338f
 - channel-level models
 - channel-flow energy balance, 365–367
 - gas flow within channels, 364–365
 - MEA energy balance, 367
 - qualitative illustration, 367–368
 - computational implementation, 376–377
 - dynamics
 - disturbance rejection, 433–435
 - reference, 435–436
 - simple control system, 431–432, 432f
 - transfer function, 432–433
 - EIS
 - methane, 370–371, 371f
 - qualitative aspects, 369–370, 369f
 - electrochemistry
 - activation overpotentials, 346–347
 - Butler–Volmer form (*see* Butler–Volmer form)
 - concentration overpotentials, 347–348
 - ohmic overpotentials, 345–346
 - polarization and overpotentials, 345
 - reversible potential, 343–345
 - elementary approach, 348–349
 - fuel processing
 - autothermal reforming, 406
 - catalytic partial oxidation, 406
 - catalytic steam reforming, 403–405
 - definition, 401
 - desulfurization, 402–403
 - global reactions, on-anode reforming processes, 341, 341f
 - model formulation, 337–338
 - operating characteristics
 - anode gas recycle, 411–412
 - cathode gas recycle, 412–413
 - cell operating voltage, 413–415
 - heat loss, 415
 - internal reforming, 408–411
 - process control
 - dynamics effect, 431–436
 - inputs and outputs, 430–431, 431f
 - model-predictive control, 436–442
 - objectives, 429–430
 - physical constraints, 430
 - process-flow diagram, 333–334, 334f
 - spatially resolved MEA model
 - distributed energy transfer, 360–363
 - effective transport properties, 358–359
 - energy transport, 357–358
 - gas-phase transport, 355–356
 - interface charge-transfer model, 363
 - ion and electron transport, 356–357
 - thermal catalytic chemistry, 359–360
 - statepoint diagram, 400–401, 400f
 - steady-state stack
 - heat exchangers and catalytic reactors, 391–392
 - process overview, 388–389
 - SOFC stacks, 389–391
 - system-level models
 - electrochemical performance, 394–395
 - polarization characteristics, 393–394, 394f
 - system thermal modeling
 - resistive model formulation, 396–400
 - thermal management, 400–401
 - technoeconomic modeling and optimization
 - fuel utilization, 425–427
 - life cycle costing, 422–425
 - optimal cell temperature and air temperature rise, 427–429
 - optimal cell voltage, 425–427
 - timescale, 334
 - tubular cell performance
 - efficiency, 374–375
 - steady-state performance, 371–374
 - transient response, 375–376
 - utilization, 374–375

- Spatially resolved membrane-electrode assembly model
 - distributed energy transfer, 360–363
 - effective transport properties, 358–359
 - energy transport, 357–358
 - gas-phase transport, 355–356
 - interface charge-transfer model, 363
 - ion and electron transport, 356–357
 - thermal catalytic chemistry, 359–360
- Steady-state solid oxide fuel cell stack
 - computational fluid dynamics, 390
 - heat exchangers and catalytic reactors, 391–392
 - process overview, 388–389
 - tubular stack, 390–391, 390*f*
 - user defined function, 391
- Stefan–Maxwell equations, 80–81
- Tafel approximation, 77–78
- Tafel slopes approach, 347
- Teflon®, 102, 105*f*
- Ternary chart, solid carbon formation, 360, 361*f*
- THDA. *See* Total harmonic distortion analysis (THDA)
- Thermal catalytic chemistry, 359–360
- Thermally integrated solid oxide fuel cell system, 400–401, 400*f*
- Thermal management system, lumped parameter model
 - coolant flow rate, 208
 - coolant temperature, 208–209
 - cooling system, 208, 208*f*
 - heat convection, stack surface, 209
- Thermal resistance network, 397–399, 398*f*, 399*f*
- Thermodynamics, PEMFC, 71–73
- Thiele modulus, in catalyst layer modeling, 116–119
- Tortuosity, 356
- Total harmonic distortion analysis (THDA)
 - approach, 252–254
 - fuel cell critical status detection, stack voltage analysis, 254–256
 - AVL, 255, 256*f*
 - sinusoidal signal, distortion of, 255, 255*f*
 - research methods and challenges, 256–257
- Transfer function, SOFC dynamics, 432–433
- Tubular fuel-cell models, 391
- Tubular solid oxide fuel cell stack, 335, 336*f*
- Two-and three-dimensional modeling, in DMFC, 163–164
- Unzipping reaction, Pt dissolution, 302–303
- Weighted Euclidean norm, 438