

# Abstracts

## **A 2-GHz RF front-end transceiver chipset in CMOS technology for PCS and IMT-2000 applications (2002 Vol. I [MWSYM])**

---

*Yong-Sik Youn, Nam-Soo Kim, Jae-Hong Chang, Young-Jae Lee and Hyun-Kyu Yu. "A 2-GHz RF front-end transceiver chipset in CMOS technology for PCS and IMT-2000 applications (2002 Vol. I [MWSYM])." 2002 MTT-S International Microwave Symposium Digest 02.1 (2002 Vol. I [MWSYM]): 17-20 vol. 1.*

This paper describes RF front-end transceiver chipset for the dual-mode operation of PCS and IMT-2000. The transceiver chipset has been implemented in a 0.25  $\mu$ m single-poly five-metal CMOS technology. The receiver IC consists of a LNA and a down-mixer, and the transmitter IC integrates an up-mixer. Measurements show that the transceiver chipset covers the wide RF range from 1.8 GHz for PCS to 2.1 GHz for IMT-2000. The LNA has 2.5 dB NF, 13 dB gain and 6 dBm IIP3. The down mixer has 15.5 dB sim/16.0 dB DSB NF, 15-13 dB power conversion gain and 2 dBm IIP3. The up-mixer has 0 dB sim/2 dB power conversion gain and 6 dB OIP3. With a single 3.0 V power supply, the LNA, down-mixer, and up-mixer consume 5 mA, 30 mA, and 25 mA, respectively.

[Return to main document.](#)