

# Abstracts

## A 60 GHz-Band Low Noise HJFET Amplifier Module for Wireless LAN Applications (1996 [MCS])

---

*K. Maruhashi, M. Funabashi, T. Inoue, M. Madihian and M. Kuzuhara. "A 60 GHz-Band Low Noise HJFET Amplifier Module for Wireless LAN Applications (1996 [MCS])." 1996 Microwave and Millimeter-Wave Monolithic Circuits Symposium Digest 98. (1996 [MCS]): 137-140.*

A 60 GHz-band low noise amplifier (LNA) module has been developed based on 0.15μm AlGaAs/InGaAs heterojunction FET(HJFET) technologies. A two-stage MMIC amplifier was designed and fabricated, which exhibited a noise figure less than 3dB with a gain higher than 10dB over 59.5 to 61.5GHz range. For the module fabrication, two MMIC chips were mounted in a WR-15 waveguide housing. The four-stage amplifier module demonstrated a noise figure of 4dB and a gain higher than 24dB from 59 to 60GHz. To our knowledge, this is the best reported noise figure including a microstrip-to-waveguide transition loss, using GaAs-based MMICs operating at this frequency range. The measured output power for the module at 1dB gain compression point was 4dBm. Temperature test from -20 to 70°C revealed very small noise figure and gain variations of 0.35dB and 0.62dB, respectively.

[Return to main document.](#)