

WEDNESDAY MORNING, MAY 28, 1980

AMBASSADOR ROOM					
WELCOME AND KEYNOTE ADDRESS					
Chairman: L.R. Whicker					
0830 A-1	Welcome from General Chairman L.R. Whicker, NRL, Washington, DC 20375	—			
0840 A-2	Comments from Technical Program Chairman R.C. Van Wagoner, NRL, Washington, DC 20375	—			
0850 A-3	Welcome from MTT-ADCOM President S.F. Adam, H.P.Co., Palo Alto, CA 94304	—			
0900 A-4	Remarks from IEEE President L. Young, NRL, Washington, DC	—			
0915 A-5	Keynote Address—Technology Growth for the 80's as Viewed by DOD (R&T) Dr. Arden L. Bement, Deputy Under Secretary of Defense (Research & Technology)	—			
1000	Break				
AMBASSADOR ROOM			DIPLOMAT ROOM		
MICROWAVE POWER TRANSISTORS			MILLIMETER RECEIVERS AND COMPONENTS		
Chairman: Fumio Hasegawa			Chairman: John Smith		
1030 B-1	Improved Elementary Cell GaAs Power FET Structure Pierre Baudet, LEP, France	3	1030 C-1	140 GHz All Solid State Receiver with Noise Figure Less Than 6 dB DSB J. Putnam, A. Cardasmenos, P. Boyd, M. Blustine, TRG Div. of Alpha Ind.	17
1050 B-2	10 GHz-10W Internally Matched Flip-Chip Power GaAs FET Y. Mitsui, M. Kobiki, M. Wataze, K. Segawa, M. Otsubo, M. Nakatani and T. Ishii, Mitsubishi, Japan	6	1050 C-2	A 200-300 GHz Heterodyne Receiver N.R. Erickson, Univ. of Mass	19
1110 B-3	A 6 GHz-25W GaAs MESFET with an Experimentally Optimized Pattern A. Higashisaka, K. Honjo, Y. Takayama and F. Hasegawa, Nippon, Japan	9	1110 C-3	Cryogenic 90 GHz Receiver for Airborne Radiometry B. Vowinkel, J.K. Petonen, W. Reinert, R.I.U., Bonn, W. Germany	21
1130 B-4	100W CW Microwave Bipolar Transistor David C. Anderson, Power Hybrids	12	1130 C-4	Noise Measurements of W-Band (75-100 GHz) CW GaAs Gunn and Silicon IMPATT Oscillators John Ondria, TRG Div. of Alpha Ind.	24
FORUM ROOM			TUDOR ROOM		
MICROWAVE ACOUSTICS AND MAGNETOSTATIC WAVES			MICROWAVE ENGINEERING FOR EXPORT		
Chairman: Dennis Webb			Chairman: Edward A. Wolff		
1030 D-1	The Implementation of Surface Acoustic Wave Devices in Avionics Systems W.J. Edwards and W.C. Eppers, WPAFB (Invited Paper)	29	1030 E-1	U.S. Export Procedures R. Garnitz, Dept of Commerce	45
1055 D-2	System Aspects of Surface Acoustic Wave Convolvers J. Cafarella, MIT Lincoln Labs, (Invited Paper)	30	1050 E-2	Import and Export Commodity Codes and Data W. Fletcher, U.S. Intl Trade Comm	46
1120 D-3	Efficient Thin Film InSb/LiNbO ₃ Convolver K. Yamanouchi, S. Mitsui, K. Shibayama, Tokyo Univ.	31	1110 E-3	Supplier Reliability: A Prerequisite for Export Expansion S. Abrahamson, Control Data	47
1140 D-4	Low Loss Multipole SAW Resonator Filters E.J. Staples, J. Schoenwald, J. Wise, T. Lim, Rockwell	34	1130 E-4	Critique of Microwave Export Performance T. Saad, Sage	50
1200 D-5	Adjustable Magnostatic Surface Wave Directional Coupler J.P. Castera, P. Hartemann, Thomson-CSF, France	37	1150 E-5	Exporting Microwave Components and Instruments B. Weinschel, Weinschel Eng.	51
1220 D-6	Simple Magnetostatic Delay Lines in Microwave Pulse Compression Loops K.W. Reed, J. Owens, C. Smith, R. Carter, U. Texas, Arlington	40	1210 E-6	Exporting Microwave Systems J. Bunker, Microwave Assoc.	55
			1230 E-7	Japanese Exports of Microwave Equipment	56

WEDNESDAY AFTERNOON, MAY 28, 1980

AMBASSADOR ROOM			DIPLOMAT ROOM		
MILLIMETER WAVE POWER GENERATION Chairman Apostle G. Cardasmenos			HIGH POWER DEVICES & TECHNIQUES Chairman H Goldie		
1400 F-1	MM Wave Gunn Oscillator with Distributed Feedback Fin-Line Circuit H. Hoffman, AEG-Telefunken, West Germany	59	1400 G-1	High Power X-Band MIC Diode Phase Shifter M Kuroda, K Hirai, S. Kamihashi, Toshiba, Japan	81
1420 F-2	Multidiode Ka-Band OSC, Using Hybrid Planar Circuit Design F. Sickling, H. Meinel, AEG-Telefunken, West Germany	62	1420 G-2	RF Energy Compressor Z D Farkas, SLAC, Stanford	84
1440 F-3	Gunn Diode Combining at U-Band Y Ma, D Sun, Hughes	65	1440 G-3	The Stability of Magnetrons Under Short Pulse Conditions B Vyse, H. Levinson, M-O Valve Co., England	87
1500 F-4	MM-Wave Microstrip Amplifier Using InPh Gunn Giodes D Rubin, NOSC	67	1500 G-4	A Novel Approach to the Design of a High Power Automatic Impedance Measuring Scheme C.J. Hu, U Colo	90
1520	Break		1520	Break	
1600 F-5	The Behavior of a Pulsed MM-Wave (70 GHz) Impatt Diode Oscillator During Laser Illumination H Gerlach, R Wellman, HDL	70	1550 G-5	Mode Coupling and Power Transfer in a Coaxial Sector Waveguide with a Sector Angle Taper A W Flitiet, L R Barnett, J M. Baird, BKD and V L Granatstein, NRL	93
1620 F-6	V-Band High Power Impatt Amplifier Y Ma, C Sun, E M Nakaj, Hughes	73	1610 G-6	Circular-Electric Mode Waveguide Couplers and Junctions for use in Gyrotron Traveling-Wave Amplifiers L.R. Barnett, J M Baird, A.W. Flitiet, BKD and V.L. Granatstein, NRL	96
1640 F-7	Performance of 94 GHz Coherent Pulsed Impatt Transmitters M D Simonutti, D C English, F.J. Bernues, Hughes	75	1630 G-7	Recent Advances in Gyrotrons H. Jory, R. Symons, P. Ferguson, J. Shively, J. Moran, Varian	99
			1650 G-8	Gain of the Gyrotron Amplifier with High Circular Waveguide Mode and Cyclotron Harmonic Number S. Ahn, J. Choe, NRL	102
FORUM ROOM			TUDOR ROOM		
MICROWAVE SYSTEMS—1 Cochairmen P Greiling & F Ivanek			MICROWAVE FILTERS AND MULTIPLEXERS Chairman: Ralph Levy		
1400 H-1	A Monolithic GaAs Decision Circuit for Gbit/s PCM Transmission Systems M Peltier, G Nuzillat, M Gloanee, Thomson-CSF, France	107	1400 J-1	Synthesis of Commensurate Comb-Line Band-Pass Filters with Half-Length Capacitor Lines S.B. Cohn, S B Cohn Assoc.	135
1420 H-2	Digital Generation of Wideband linear FM Waveforms F W Hapwood, R C Tracy, Westinghouse	111	1420 J-2	Asymmetric Realization for Dual-Mode Bandpass Filters R Cameron, ESA and J Rhodes, U Leeds, England	138
1440 H-3	6 GHz 16 QAM MIC Modulator with Phase Linearity Improved T Takano, M. Niori, Y Tokumitsu, K Ozawa, Kawasaki, Japan	114	1440 J-3	Bandpass Filters Using Parallel-Coupled Strip-Line Stepped Impedance Resonators M Makimoto, S Yamashita, Matsushita, Japan	141
1500	Break		1500 J-4	General Extracted Pole Synthesis Technique with Application to Low Loss TE ₀₁₁ Mode Filters J.D Rhodes, U Leeds, England and R J Cameron, ESTEG	144
1520 H-4	High-Power Upconversion for SSB-AM Signals E. Loiser, K. Schuenemann, Inst Hft Tech Univ, Braunschweig, Germany	117	1520	Break	
1540 H-5	Instantaneous Bearing Discriminators with Omnidirectional Coverage and High Accuracy S. Rehnmark, Anaren	120	1550 J-5	Design of MIC Broadband Contiguous Multiplexers J Dean, Filtronic, England and J Rhodes, U Leeds, England	147
1600 H-6	The Tiro-N Microwave Sounder Unit P N Swanson, W M Harris, E J Johnston, F S Soltis, JPL	123	1610 J-6	A Low Cost Multiplexer for Channelized Receiver Front Ends at Millimeter Waves K Breuer and N Warontzoff, AIL Eaton	150
1620 H-7	Two Microwave Complex Weighting Circuits M.J. Fithian, E-Systems	126	1630 J-7	Microstrip Variable Band-Pass Filters Using Varactor Diodes S. Toyoda, Osaka Inst. Tech., Japan	153
1640 H-8	Calculation of Impedance Variations in Electronically Beam-Steered Active Lens Antennas for Space Based Radar D W Griffin, U Adelaide, S Australia	129	1650 J-8	Advances in the Analytical and Computer-Aided Design of Optimum Equalizers for High Frequency RF and Microwave Solid State Amplifiers W Ku, Cornell	156

THURSDAY MORNING, MAY 29, 1980

AMBASSADOR ROOM			DIPLOMAT ROOM		
HIGH-POWER SOLID-STATE CIRCUITS Chairman: Don Parker			SATELLITE COMMUNICATION SYSTEMS IN EUROPE (Invited Session) Chairman: P. DeSantis		
0830 K-1	A High-Power X-Band Diode Amplifier R.J. Pankow and R.G. Mastroianni, Norden	159	0830 L-1	Communication Satellite Payloads: A Review of Past, Present and Future ESA Developments M. Lopriore, ESTC, Netherlands	189
0850 K-2	X-Band Pulsed Solid-State Transmitters S.E. Hamilton, R.S. Robertson, F.A. Wilhelm, M.E. Dick, Hughes	162	0900 L-2	GaAs FET's in Present and Future Communication Satellite Programs J. Turner, Plessey, England	192
0910 K-3	Efficient, Higher-Order-Mode Resonance Combiner M. Dydyk, Motorola	165	0930 L-3	Microwave Technology Developments in Italian Space Program M. Massani, Selenia, Italy	193
0930 K-4	A Corporate Structure for Combining Power from 3rd Oscillators S. Mizushima and M. Ashiki, Shizuoka Univ., Japan and J. Kondoh, Cornell	168	1000	Break	
0950	Break		1030 L-4	West German Microwave Activity State Of The Art in Satellite Communications H. Brand, U. Erlangen, Fed. Rep. Germany	195
1020 K-5	An Improved Trapatt Oscillator Circuit R. Davies, P.L. Booth, B.H. Newton, Phillips, England	171	1100 L-5	Some Advances in French Solid State Components and Technologies for Space Applications J. Magarshack, L.E.P., France	198
1040 K-6	Influence of Non-Ideal Circulator Effects on Negative-Resistance Amplifier Design B.D. Bates, P. J. Kahn, U. Queensland, Australia	174	1130 L-6	Microwave Activity for Satellite Communication in Sweden L. Afzelius, Ericsson, Sweden	200
1100 K-7	Pulsed Power Performance of GaAs FET's at X-Band S. Temple, Z. Galani, J. Dormail, R. Healy, S. Hewitt, Raytheon	177			
1120 K-8	A K-Band, 1 Watt GaAs FET Amplifier J. Sore and Y. Takayama, Nippon, Japan	180			
1140 K-9	Thirty-Two Diode Waveguide Power Combiner S. Hamilton, Hughes	183			
FORUM ROOM			TUDOR ROOM		
GUIDES AND COMPONENTS Chairman: T. Itoh			FERRITE APPLICATIONS Chairman: A. Yarranton		
0830 M-1	A Metal-to-Dielectric Waveguide Transition with Application to Millimeter-Wave Integrated Circuits T.N. Trinh, J. Malherbe, R. Mittra, U. Illinois	205	0830 N-1	Parallel Component μ_z of Partially Magnetized Microwave Ferrites M. Igarashi, Tokai Univ. and Y. Naito, Tokyo	229
0850 M-2	Trapped Image Guide for Millimeter-Wave Circuits T. Itoh, U. Texas, Austin and, B. Adelseck, AEG-Telefunken, W. Germany	208	0850 N-2	Planar Meanderline Ferrite Phase Shifters with Multi-Layer Ferrite/Dielectric Imbedding E.R. Bertil Hansson, Chalmers Univ. Tech., Sweden	232
0910 M-3	A Method for Reducing Radiation Losses at Bends in Open Dielectric Structures M. Desai and R. Mittra, U. Illinois	211	0910 N-3	New Nonreciprocal Devices in a Coplanar Waveguide Y. Naito and Y. Yamanaka, Tokyo Inst. Tech., Japan	235
0930 M-4	Coupling Characteristics of Dielectric Waveguides of Rectangular Cross-Section T.N. Trinh and R. Mittra, U. Illinois	214	0930 N-4	Magnetostatic Surface Wave Signal-to-Noise Enhancer S.N. Stitzer, H. Goldie, J.D. Adam, P.R. Emage, Westinghouse	238
0950	Break		0950	Break	
1020 M-5	Resonant Frequency of Dielectric Resonators in Homogeneous Media R. Bonetti and A. Atia, COMSAT	218	1030 N-5	A New Accurate Equivalent Network for Stripline Y-junction Circulators E.R. Bertil Hansson, K. Gunnar Filipsson, Chalmers Univ. Tech., Sweden	241
1040 M-6	Analysis and Application of the Scattering Mechanism in an Abruptly Ended Rod Dielectric Waveguide P.H. Gelin, M. Peterzi, J. Citerne, P. Kennis, U. Sci. Tech. Lille, France	220	1050 N-6	Characterisation of Planar Wye Shaped Resonators for use in Junction Circulator Hardware W.T. Nesbit, Lochend, Scotland and J. Helszajn, Heriot-Watt Univ., Scotland	244
1100 M-7	The Complex Pointing Vector, and the Fractional Current on the Upper Surface of a Microstrip Line L. Lewin and T. Rinehle, U. Colo	223	1110 N-7	A New Type Circulator for Millimeter Integrated Circuits Y. Naito, M. Nuraguchi, A. Tsuji, Tokyo Inst., Tech., Japan	250
1120 M-8	A 40 GHz Microstrip Array Antenna W. Menzel, AEG-Telefunken, W. Germany	225			

THURSDAY AFTERNOON, MAY 29, 1980

AMBASSADOR ROOM			DIPLOMAT ROOM		
MILLIMETER WAVE IC's Chairman: Nick Jansen			SATELLITE BROADCASTING IN JAPAN (INVITED SESSION) Chairman: K Suetake		
1330 Q-1	Characteristics of Unilateral Fin-Line Structures with Arbitrarily Located Slots L.P. Schmidt, T. Itoh, Univ. Texas and H. Hofmann, AEG-Telefunken, W. Germany	255	1330 P-1	Main Transmit and Receive Station in Japanese BSE Program N. Imai, Y. Otsu and T. Tanaka, R.R.L. Min. Posts and Telecomm., Japan	281
1350 O-2	A Solution of the Earthed Fin Line with Finite Metalization Thickness A. Beyer, I. Wolff, Univ. Duisburg, W. Germany	258	1355 P-2	Performance Characteristics of Transportable Type—A Earth Station for Japan's Experimental Broadcasting Satellite System (BSE) S. Nishimura, S. Betsudan, M. Nakanishi, Mitsubishi, Japan, Y. Konishi, NHK, Japan, S. Hoshino, M. Takahashi, Nippon, Japan	284
1410 O-3	Cutoff Frequencies in Fin Lines Calculated with a Two-Dimensional TLM-Program T. Shih, W.J.R. Hoefer, Univ. Ottawa, Canada	261	1410 P-3	14/12 GHz Band Mobile-Type Earth Station for Japanese Broadcasting Satellite Communication H. Hayashida, S. Hikosaka, Y. Yamashita, I. Sato, H. Shimayama, Nippon, Japan	287
1430 O-4	Advances in Printed Millimeter-Wave Oscillator Circuits L.D. Cohen, AIL Div. Eaton	264	1425 P-4	Receive-Only Stations for Broadcasting Satellites Experimental S. Kikukawa, M. Kajima, T. Chiba, Y. Sasaki, Toshiba, Japan, S. Hoshino, Y. Imahori, Nippon, Japan	290
1450	Break		1440 P-5	Satellite Broadcasting Receiver—Present and Future Y. Konishi, NHK, Japan	293
1520 O-5	E-Plane Components for a 94 GHz Printed-Circuit Balanced Mixer P.J. Meier, AIL Div. Eaton	267	1500	Break	
1540 O-6	Phasing Type Image Recovery Mixers R.H. Oxley, P.L. Lowbridge, N.D.R. Sheperd, AEI Semi., England, M.J. Ming, J.E. Curren, GEC, England	270	1530 P-6	Development of 12 GHz TWT for Broadcasting Satellite K. Yamamoto, NHK, Japan, K. Sugimori, Toshiba, Japan, T. Kimura, Nippon, Japan	296
1600 O-7	Low Cost MM-Wave Dielectric Loaded Mixer J.A. Paul and P. Yen, Hughes	274	1550 P-7	A Cross-Shaped Horn and a Square Waveguide Polarizer for a Circularly Polarized Shaped Beam Antenna for a Broadcasting Satellite N. Toyama, NHK, Japan	299
1620 O-8	Millimeter-Wave IC Components Using Fine Grained Alumina Substrate H. Yatsuka, M. Ishizaki, H. Komizo, Fujitsu, Japan	276	1610 P-8	Operational Achievements with Japanese Broadcasting Satellite for Experimental Purpose (BSE) S. Shimizu, K. Arai, Nat. Space Devel. Ag., Japan	302
			1640 P-9	Evaluation of Service Area in the Satellite Broadcasting by the BSE Y. Yamamoto, Min. Posts and Telecomm., Japan, S. Sonoda, NHK, Japan	305
FORUM ROOM			TUDOR ROOM		
GUIDED WAVE OPTICS AND INTERACTIONS Chairman: Thomas Giallorenzi			BIOLOGICAL APPLICATIONS AND EFFECTS Chairman: Elliot Bostow		
1330 Q-1	Guided-to-Radiation Mode Conversion in Heterostructure Planar Waveguides and Its Application to a Light Modulator H. Onodera, I. Arai, M. Nakajima, J. Ikenoue, Kyoto Univ., Japan	311	1330 R-1	Rationale for New ANSI C95 Recommended Safety Level with Respect to Human Exposure to RF Electromagnetic Fields A.W. Guy	335
1350 Q-2	An Optically Coupled Microwave Switch R. Kiehl and D. Drury, Sandia	314	1400 R-2	Electromagnetic Energy Deposition in an Inhomogeneous Block Model for Near-Field Irradiation Conditions I. Cattorjee, M.J. Hagmann, O.P. Gandhi, Univ. Utah	337
1410 Q-3	A Field Strength Measurement System Using an Integrated Optical Linear Modulator H.I. Bassen, BRH, C.H. Bulmer and W.K. Burns, NRL	317	1420 R-3	Microwave Effects on the Ocular Lens J. Stewart-Dehann, J.R. Trevithick, M. Creighton, L. Larsen, J. Jacobi, Univ. West Ontario and WRAIR	341
1430 Q-4	Nonreciprocal Effects in an Open Dielectric Waveguide with Grating Structures K. Arai, B.S. Song, T. Itoh, Univ. Texas	319	1440 R-4	A Microstrip Microwave Biological Exposure System A.W. Friend, NMRI and H. Howe, Jr., Microwave Assoc.	345
1450	Break		1500	Break	
1510 Q-5	An Approximate Analysis of Rib Waveguides H. Shigesawa, M. Tsuji, K. Takijama, Doshisha Univ., Japan	322	1530 R-5	Dual Mode Microwave System to Enhance Early Detection of Cancer K.L. Carr, Microwave Assoc., A.L. El-Mahdi, J. Shaeffer, Eastern Va. Med. Sch.	347
1530 Q-6	Analysis of Chirped Grating Lenses S. Forouhar, W.S.C. Chang, Univ. Cal., La Jolla	325	1550 R-6	Microwave Applicators for Localized Hyperthermia Treatment of Malignant Tumors R.W. Paglione, F. Sterzer, RCA, J. Mendecki, E. Freudenthal, C. Botstein, Montefiore Hosp.	351
1550 Q-7	Microwave Model of Blazed Dielectric Gratings for Integrated-Optics Applications T. Tamir, Polytech. Inst., N.Y.	327	1610 R-7	A 2450 MHz Slab-Loaded Direct Contact Applicator with Choke G. Kantor, D.M. Witters, BRH	355
1610 Q-8	Finite Element Analysis of Optical Waveguides N. Mabaya, P.E. Lagasse, Univ. Ghent, Belgium	329	1640 R-8	A Microstrip Antenna for Medical Applications I. Bahi, S.S. Stuchly, Univ. Ottawa, Canada and M.A. Stuchly, RPB, Canada	358

FRIDAY MORNING, MAY 30, 1980

AMBASSADOR ROOM			DIPLOMAT ROOM		
GaAs FET CIRCUITS Chairman: Eliot D. Cohen			COMPUTER AIDED TECHNIQUES Chairman: Walter H. Ku		
0830 S-1	A Monolithic GaAs I.F. Amplifier for Integrated Receiver Applications D.R. Decker, A.K. Gupta, W. Petersen, D.R. Chen, Rockwell	363	0830 T-1	Computer Modeling of Monolithic GaAs I.C.'s R. Van Tuyt	393
0850 S-2	Super Low Noise Packaged GaAs FETs for Ku Band T. Suzuki, Y. Kadowaki, M. Ito, M. Nakatani, T. Ishii, Mitsubishi, Japan	367	0900 T-2	Performance Optimization of Millimeter Wave Mixer Circuits L. Casner, J. Paul, Hughes	395
0910 S-3	A 12 GHz 140°K Low Noise GaAs FET Amplifier Y. Fujiki, S. Fukuda, J. Haga, K. Okata, Nippon, Japan	370	0920 T-3	Frequency Scaling for Computer-Aided Fourier Analysis of Mixer Diode Operation H.C. Lin, Univ. Maryland, N.A. Papanicolaou, J. McClintock, Martin Manetta	398
0930	Break		0940 T-4	MLS Simulation Facility J. Beneke, C.W. Wightman, Calspan	401
1000 S-4	Optimum Large-Signal Design of Fixed-Frequency and Varactor-Tuned GaAs FET Oscillators C. Rauscher, NRL	373	1000	Break	
1020 S-5	A Highly Stabilized 9-14 GHz GaAs FET Oscillator Using a Dielectric Resonator Feedback Circuit T. Mori, O. Ishihara, M. Nakatani, T. Ishii, Mitsubishi, Japan	376	1030 T-5	Analysis and Sensitivity Evaluation of 2P-Port Cascaded Networks J.W. Bandler, M.R.M. Rizk, McMaster, Canada	404
1040 S-6	Ultra Low Chirp GaAs Dual-Gate FET Microwave Oscillators R.S. Pengelly, J. Joshi, Plessey, England	379	1050 T-6	Accurate Models for Microstrip Computer-Aided Design E. Hammerstad, O. Jensen, Univ. Trondheim, Norway	407
1100 S-7	An Oscillator at K-Band Using a Dual Gate GaAs MESFET S. Chu, T. Chen, HP	383	1110 T-7	Computer Aided Optimization of Microwave Filter Networks for Space Application C.M. Kudsa, Com. Dev., Canada, M.N.S. Swamy, Concordia Univ., Canada	410
1120 S-8	GaAs IC Direct Coupled Amplifiers D. Hornbuckle, HP	387	1130 T-8	A New Computer Aid for Microwave Filter Design G. Szentirmai, L. Besser, Compact Eng.	413
1140 S-9	Synthesis of Distributed Networks with Applications to Design of Ultra-Wideband GaAs MESFET Power Amplifiers W. Ku, Cornell Univ. and H. Willing, NRL	390			
FORUM ROOM			TUDOR ROOM		
MICROWAVE MEASUREMENTS Chairman: H. George Oltman			FIELD THEORY Chairman: L. Wilson Pearson		
0830 U-1	Density-Independent Moisture Metering in Fibrous Materials Using a Double Cut-Off Gunn-Oscillator W. Hoppe, W. Schilz, W. Meyer, Phillips, W. Germany	419	0830 V-1	Frequency Selective Surfaces with Applications in Microwaves and Optics R. Mittra, C.H. Tsao, W.L. Ko, Univ. Illinois	447
0850 U-2	A General Approach to the Resonance Measurement of Asymmetric Microstrip Discontinuities V. Rizzoli, Univ. Bologna, Italy	422	0850 V-2	Calculation of Quasi-Static Characteristics of Microstrip on Anisotropic Substrate Using Mapping Method M. Horno, Univ. Sevilla, Spain	450
0910 U-3	Accurate and Automatic Noise Figure Measurements N. Kuhn, HP	425	0910 V-3	Analysis and Application of a New Waveguide Structure with Dielectric Loading A. Fukasawa, K. Hosoda, T. Sato, OKI, Japan	453
0930 U-4	Precision Automated Reflectometer Using Air-Line References Spans UHF Through Millimeter Ranges P. Lacy, Wiltron	428	0930 V-4	A Hybrid Method for Paraxial Beam Propagation in Multimode Waveguides E.F. Kuester, D.C. Chang, Univ. Colo.	456
0950	Break		0950	Break	
1020 U-5	Transmission Phase Measurements with a Single Six-Port G.P. Riblet, MDL	431	1020 V-5	Exact Analysis of Shielded Microstrip Lines and Bilateral FinLines A. El-Sherbiny, Ain Shams Univ., Egypt	459
1040 U-6	A Dual Six-Port Automatic Network Analyzer H.M. Cronson, L. Susman, Sperry	434	1040 V-6	Microstrip Analysis on Anisotropic and/or Inhomogeneous Substrate with the Finite Element Method M. El-Said, A.A. Ahmed, Cairo Univ., Egypt	465
1100 U-7	Optimizing the Design of the Six-Port Junction M. Rafail, W. Joines, Duke Univ.	437	1100 V-7	Waveguide Treatment of the Suspended Microstrip Line with Tuning Septums Using the Spectral Domain Approach & The Finite Element Method K. Sachse, A. Sawicki, Univ. Wroclaw, Poland	468
1120 U-8	A Least Squares Solution for Use in the Six-Port Measurement Technique Glenn F. Engen, NBS	440	1120 V-8	Attenuation in Microstrip Transmission Lines with Very Lossy Substrates B.W. Jervis, R.M. Pannell, Dept. Comm. Eng., England	471
1140 U-9	A 0.01-18 GHz Wide Dynamic Range Precision Vector Ratio Meter Fritz K. Weinert, Weinschel Engr. Co., Inc.	442			

FRIDAY AFTERNOON, MAY 29, 1980

AMBASSADOR ROOM			DIPLOMAT ROOM		
MICROWAVE IC COMPONENTS Chairman Ed Denlinger			MICROWAVE SYSTEMS-2 Chairman Gerald Schaffner		
1330 W-1	A Spiral Microwave Directional Coupler for MIC Application K Shibate, Kitami Inst Tech, Japan, K Hatori, Res Inst of App Elec, Japan, Y Tokumitsu & H Komizo, Fujitsu, Japan	477	1330 X-1	A Comprehensive Characterization of FET Power Amplifier Modules C Wong, J Bender, Raytheon	493
1350 W-2	Wideband High Directivity in MIC Proximity Couplers by Planar Means F C DeRonde, L E P, France	480	1350 X-2	A 25W, 5 GHz GaAs FET Amplifier for MLS Y Takayama, K Honjo, Nippon, Japan	496
1410 W-3	Planar Multiport, Quadrature-Like Power Dividers/Combiners A Saleh, Bell Labs	483	1410 X-3	Very Linear X-Band MIC Bipolar VCO with a 100 MHz FM Rate R.G. Winch, J.L. Matson, Teledyne	499
1430 W-4	The Traveling Wave Power Divider/Combiner A Bert, D Kaminsky, Thomson-CSF, France	487	1430 X-4	Short-Range Microstrip Diplex Doppler Radar Sensor Using a Baritt Diode B M Armstrong, R Brown, E J Duffin, J A C Stewart, Queen's Univ, Belfast, Ireland	501