

**G. G. TSHCHEBR'YA, N. M. MOROZOV
AND M. I. TYOMKEEN**

L. Ya. Karpov Physico-Chemical Institute

The kinetics of conversion of carbon monoxide in different concentrations in the reaction mixture were investigated over a ferric oxide-chromia catalyst at atmospheric pressure and temperatures of 390–483°. The experimental data of this study are in good agreement with the data calculated by use of Equation 24, which is based on the assumption that the reaction occurs in two steps.

The results calculated by use of Equation 24, modified for continuous operation, are compared with published experimental data.

The Nature and Causes of Aging of Chromia-Ferric Oxide-Zinc Oxide Catalyst

**R. A. BOOYANOV, M. A. ANDROOSHK'YEV
AND L. G. KARAKCHEEYEV**

*Institute of Catalysis of the Siberian Division
of the Academy of Sciences of USSR*

The properties of fresh and of completely spent samples of a chromia-ferric oxide-zinc oxide catalysts, used in dehydrogenation of n-butylenes and of divinyl, was determined by physical methods. The samples have a chromia-spinel structure. The phase compositions of the fresh and the spent samples do not show any substantial differences. Specific catalytic activities of the fresh and of the spent samples were found to be equal. The loss of activity and aging of the catalyst are associated with a decrease of specific surface due to recrystallization.

Isotherms and Heats of Adsorption of Vaporized Benzene on Argillaceous Minerals

**V. T. BIKOV, V. T. GOR'KOVSKAYA
AND B. A. FROLOV**

Far Eastern State University

The isotherms and differential heats of adsorption of vaporized benzene on montmorillonite, kaolinite, metahalloysite, and ferrihalloysite were determined at a temperature of 20°, using an adsorption calorimeter equipped with a heat exchanger.

The results show that the saturation volume of adsorbed benzene vapor decreases with increasing evacuation temperatures of each mineral, except for kaolinite—where the reverse is true.

With kaolinite and metahalloysite, the differential heat of adsorption curves pass through a maximum point, whereas with montmorillonite and ferrihalloysite, the curves continuously rise. With increasing evacuation temperatures, mobility of

adsorbed benzene molecules changes relative to their mobility in liquid state. The shape of the entropy curves provides the information regarding the benzene adsorption mechanism over the argillaceous minerals investigated.

Structure of Aluminum Oxides

L. M. PL'YASOVA AND L. M. KÉFELEE

*Institute of Catalysis of the Siberian Division
of the Academy of Sciences of USSR*

A study of the phase composition and structure of the products of thermal decomposition of aluminum hydroxides at temperatures of 300–950° reveals evolutionary character of transformation of the crystal lattice of aluminum oxide. The multiplicity of Al_2O_3 forms is discussed, based on the results of X-ray analyses. It is concluded that two polymorphic modifications of aluminum oxide exist: one, comprising the densest cubic packing of the oxygen ions, is formed at a low temperature; the other one, the corundum form, comprising the densest hexagonal packing of the oxygen ions, is formed at a high temperature.

Determination of Specific Surface of Solids by Thermal Desorption of Argon

**N. E. BOOYANOVA, G. B. GOODKOVA
AND A. P. KARNAOKHOV**

*Catalysis Institute of the Siberian Division
of the Academy of Sciences of USSR*

An improved chromatographic technique of thermal desorption is described to determine specific solid surfaces of 0.01 to 600 m²/g, and greater. By use of this technique, simultaneous adsorption on six catalyst samples can be carried out, regardless of their individual pretreatment history. Use of this method, in conjunction with an integrator for determination of the areas, enables surface measurement of 12 samples in a 6-hour working period. Adoption of this rapid technique is recommended to research and industrial laboratories.

Mathematical Optimization of Platforming Process

**YU. M. JOROV, G. M. PANCHENKOV,
S. P. Z'YEL'TZER AND O. A. TEERAK'YAN**

I. M. Goobkeen Institute for Industrial Petrochemicals and Gases in the City of Moscow

Based on pertinent kinetic considerations, a mathematical description of platforming process was developed. The analysis takes into account the effects of operating variables, composition of the catalyst, and the type, composition, and boiling