

## An efficient branch-and-bound algorithm for finding a maximum clique with computational experiments

Etsuji Tomita · Toshikatsu Kameda

Published online: 14 October 2008  
© Springer Science+Business Media, LLC. 2008

### Erratum to: J Glob Optim (2007) 37:95–111 DOI 10.1007/s10898-006-9039-7

In Graph column of Table 6 at p. 110 (Appendix), [Line 4] “hamming16-2-4” should read as “johnson16-2-4”.

Corrected version of the table is given below.

**Table 6** Fahle’s user time for DIMACS benchmark graphs [sec]

Graph	<i>Our</i> $T_1$	<i>Fahle’s</i> $T_7$	$T_7/T_1$
brock200_1	23.96	28.82	1.203
brock200_4	1.47	1.73	1.177
hamming8-4	3.07	4.05	1.319
johnson16-2-4	1.21	1.51	1.248
p_hat300-2	1.04	1.25	1.202
p_hat1000-1	1.66	2.18	1.313
p_hat1500-1	15.57	20.77	1.334
san400_0.5_1	719.16	924.5	1.286
sanr200_0.7	5.02	5.96	1.187
sanr400_0.5	3.50	4.07	1.163

The online version of the original article can be found under doi:[10.1007/s10898-006-9039-7](https://doi.org/10.1007/s10898-006-9039-7).

E. Tomita (✉) · T. Kameda  
Department of Information and Communication Engineering, The University  
of Electro-Communications, Chofugaoka 1-5-1, Chofu, Tokyo 182-8585, Japan  
e-mail: tomita@ice.uec.ac.jp

T. Kameda  
e-mail: kam@ice.uec.ac.jp