

[illegible]




hxi
Millimeter Wave
Products



RENAISSANCE
Renaissance Electronics & Communications LLC

Components

- Low Noise Amplifiers
- Power Amplifiers
- Mixers and Detectors
- Gunn Oscillators and VCOs
- Frequency Multipliers
- PIN Switches and Attenuators
- Isolators and Circulators
- Power Dividers and Combiners
- Switches - Electromechanical



Integrated Assemblies

- Receiver Multicouplers
- Switch Metrics
- ATCA and μ TCA Based Integrated Assemblies
- Up/Down Converters
- Pulse Radar, Radio Links
- Front Ends
- Millimeter Wave Radio Links
- HDTV Transceiver



www.rec-usa.com / www.hxi.com

An advertisement for Anritsu. The background features a close-up of a woman's face, looking upwards. Overlaid on her face and the background are various icons representing different communication technologies: a satellite dish, a globe, a network diagram, a smartphone, a camera, a microphone, a speaker, a lightbulb, and a gear. The text is in a clean, sans-serif font. The top line reads 'Over 100 years of' in a smaller font. The second line reads 'Advancing' in a large, bold font. The third line reads 'the World's' in a smaller font. The fourth line reads 'Communications' in a bold font. The fifth line reads 'History' in a smaller font. Below this, the website address 'www.anritsu.com' is displayed. At the bottom, the Anritsu logo is shown, consisting of a stylized 'A' followed by the word 'Anritsu' in a bold, sans-serif font. Below the logo, the tagline 'envision:ensure' is written in a smaller, sans-serif font.

[illegible][illegible][illegible][illegible]



RT LOGIC

A **KRATOS** Company

RF CHANNEL SIMULATOR



- ✓ Realistically test modems, transmitters, and receivers under punishing RF and complex motion conditions - without ever leaving the lab
- ✓ The T400CS RF Channel Simulator adds dynamic, phase continuous, Doppler shift, delay, path loss, AWGN, multipath, phase noise, and interference to signals used in terrestrial and/or space communications
- ✓ Instantaneous bandwidths to 250 MHz, 1-4 or more channels, 3us to 1.2s dynamic delay. Interfaces from IF to Ka-bands; Interface with AGIS STK



www.rtllogic.com | (719) 598-2801 | email: t400cs1@rtllogic.com



Over
100 years of
Advancing
the World's
Communications
History

www.anritsu.com

Anritsu
envision : ensure

Our RF & Microwave Products Give You An Unfair Advantage

Over 0.7 To 60 GHz Hybrid Power
Modules Provide Output Power
Up To 30 Watts CW Class A
And 50 Watts CW Class AB.
Other Modules Available From 4 To 48 GHz.

"S" Series Solid State
0.7 To 18 GHz,
1 To 120 Watts.
For Immunity And
Wireless Testing.

RF Solid State Amplifiers Up To
1,000 MHz, And 50,000 Watts.

CW And Pulsed Traveling Wave
Tube Amplifiers, 1 To 45 GHz,
Up To 10,000 Watts.

For More Information, Visit www.arnoldlux.com Or Call Us At 215-723-8181.

rf/microwave instrumentation



hxi

**Millimeter Wave
Products**



RENAISSANCE

Renaissance Electronics & Communications, LLC

Components

- Low Noise Amplifiers
- Power Amplifiers
- Mixers and Detectors
- Gunn Oscillators and VCOs
- Frequency Multipliers
- PIN Switches and Attenuators
- Isolators and Circulators
- Power Dividers and Combiners
- Switches - Electromechanical




Integrated Assemblies

- Receiver Multicouplers
- Switch Matrices
- ATCA and μ TCA Based Integrated Assemblies
- Up/Down Converters
- Pulse Radar, Radio Links
- Front Ends
- Millimeter Wave Radio Links
- HDTV Transceiver





www.rec-usa.com / www.hxi.com



Wainwright Instruments GmbH

since 1979

RF & Microwave Filters

Standard and Custom Designs

100 kHz to 26.5 GHz

Covering all Wireless Standards

Lowpass
Highpass
Bandpass
Band Reject Filters
Notch Filters
Duplexer
Duplexer
Multiplexer

Tunable • Digitally Tunable
Chebychev • Cauer • Cavity • Helical

	RoHS Conformity	ISO 9001	
	Our filters are	ISO 14001	
	RoHS compliant	OHSAAS 18001	
		PIM-Testing	

www.wainwright-filters.com
info@wainwright-filters.com

