



**We are** now members of a global <u>steel</u> family with 7 <u>steel joist</u> and 3 <u>steel deck</u> manufacturing facilities in the United States and Mexico.

**We are** now part of a company with over 60 years of <u>steel industry</u> experience.

We are manufacturing the industry-leading USD United Steel Deck brand of deck products.

**We are** confident that we will continue to provide the quality of customer service you have come to expect for over 40 years.

# We are CMC Joist & Deck.



Nicholas J. Bouras, Inc., United Steel Deck, Inc., The New Columbia Joist Company and ABA Trucking Corporation have joined forces with Commercial Metals Company to form **CMC Joist & Deck.** We will continue to offer the same professional sales, engineering and customer service along with the same high quality steel joist and deck products.

We are a team of professionals dedicated to meeting your expectations as well as your steel needs.

We are CMC Joist & Deck.

CMC Joist & Deck wishes everyone a safe, healthy and joyous holiday season.

For further information on any of our products or for the nearest CMC Joist & Deck sales representative, contact us at:

CMC Joist & Deck 25 DeForest Avenue Summit, NJ 07901 1.800.631.1215 www.cmcjd.com

CMC Joist & Deck - Divisional Office 440 Knox Abbott Drive Suite 250 Cayce, SC 29033

CMC Americas 6565 N. MacArthur Blvd., Suite 800 Irving, TX 75039











– Rick Welcher, Myers&Company Architectural Metals Inc, USA

# Structures that Do Business



COLLABORATE - import the analysis model and/or the architectural model



**DELIVER** - produce construction and fabrication drawings



FABRICATE - transfer data with MIS and CNC



ERECT - plan and manage in 4D

Tekla Structures is a building information modeling (BIM) software that streamlines the delivery process of design, detailing, fabrication, and construction organizations. While integrating openly with other 3D models, its strength lies in connecting the partners in the process. Thousands of Tekla Structures users in more than 80 countries have successfully delivered BIM-based projects across the world. Read more at www.tekla.com!

**TEKLA** Structures

CONTACT TEKLA: 1-877-TEKLA-OK


www.tekla.com







#### **December 2007**



#### international projects

#### 20 A Royal Addition

BY SHAHÉ SAGHARIAN, P. ENG A modern, angular addition to Toronto's Royal Ontario Museum uses steel to augment the existing historic structure.

#### 25 A Garden of Steel Flowers

BY MAURICIO GUTIÉRREZ VILLA Hollow structural shapes help Medellín's Botanical Gardens blossom into a new icon for the city.

#### 30 Building in Beijing

BY MARK SARKISIAN, P.E., S.E., NEVILLE MATHIAS, P.E., S.E., AND AARON MAZEIKA, P.E.

Steel provides the support for two new highprofile atriums in China's capital.

#### 36 Essential Elements

BY KEN JONES

London's new  ${\rm O_2}$  Arena uses a steel roof, erected with an innovative lifting operation, to top what was designed to be Europe's most acoustically advanced concert venue.

#### steelwise

#### **41** Pushing the Envelope

BY JAMES C. PARKER, P.E., ALEC S. ZIMMER, P.E., AND CHRISTOPHER M. HEWITT

Careful attention to façade attachment details pays off in the long run.



#### quality corner

#### 45 Listening to the Customer

BY SHEILA ALEGRIA, KIM SWISS, AND BOBBI MARSTELLAR, P.E.

Feedback from AISC Certified companies is making a difference in daily operations for AISC's independent auditing company.

#### steel bridge news

#### 49 Quick Response

BY AARON FRANKLIN, P.E., MAZEN WAHBEH, PH.D., P.E., DANIEL SPEER, P.E., AND MARTIN POHLL, P.E., S.E. A Caltrans-led construction team was able to quickly repair a damaged Bay Area interchange following a major explosion.

#### 55 Beauty and the Beast

BY DENNIS GOWINS, P.E.

In taming congestion, Orlando's Lake Underhill Bridge widening project will be beautiful—and beautifully effective.

#### 59 A Tale of Two Yanktons

BY DAN SHARP

A new steel span over the Missouri River replaces a National Historic Register bridge to route auto traffic between South Dakota and Nebraska.



#### departments

- 6 EDITOR'S NOTE
- 9 STEEL INTERCHANGE
- 13 STEEL QUIZ
- 18 NEWS & EVENTS
- 19 LETTERS

#### resources

- 61 FABRICATION PRODUCTS
  AND SOFTWARE
- 64 MARKETPLACE
- 65 EMPLOYMENT

ON THE COVER: Botanical Gardens, Medellín, Colombia. Photo courtesy Dario Eusse Tobon.

MODERN STEEL CONSTRUCTION (Volume 47, Number 12). ISSN 0026-8445. Published monthly by the American Institute of Steel Construction, Inc., (AISC), One E. Wacker Dr., Suite 700, Chicago, IL 60601. Subscriptions: Within the U.S.—single issues \$3.50; 1 year, \$44; 3 years \$120. Outside the U.S.—single issues \$5.50; 1 year \$88; 3 years \$216. Periodicals postage paid at Chicago, IL and at additional mailing offices. Postmaster: Please send address changes to MODERN STEEL CONSTRUCTION, One East Wacker Dr., Suite 700, Chicago, IL 60601.

AISC, Inc. does not approve, disapprove, or guarantee the validity or accuracy of any data, claim, or opinion appearing under a byline or obtained or quoted from an acknowledged source. Opinions are those of the writers and AISC is not responsible for any statement made or opinions expressed in MODERN STEEL CONSTRUCTION. All rights reserved. Materials may not be reproduced without written permission, except for noncommercial educational purposes where fewer than 25 photocopies are being reproduced.







# StruCad V13 is here!

StruCad V13 is the latest release from AceCad Software

Benefiting from advanced new modeling technology this latest version of StruCad delivers a unique array of powerful drafting tools coupled with a flexible range of accurate output options. StruCad facilitates your entire work process from estimating and detailing, analysis and revision control through to fabrication management and erection.

- Advanced new modeling technology for faster project detailing
- Enhanced automatic drawing generation and latest standards for CNC output
- Automatic reporting, listing, marking and revision control
- Leading integration with design, analysis and fabrication management systems
- Maximum collaboration facilitated between project teams via StruCad freeware

StruCad provides a single information model that will enable you and your supply chain partners to access, exchange data and complete your structural steel projects with maximum efficiency and ultimate confidence.

For more details on AceCad Software's complete range of products for the structural steel industry and to be one of the first to see StruCad V13 and the many significant additions and enhancements included in this exciting release, please contact us to schedule a no obligation demonstration now on: **610 280 9840** 



Model courtesy of Cadtec Draughting Limited

### editor's note



**AS I LISTENED TO BILL CLINTON DELIVER THE KEYNOTE ADDRESS AT THE RECENT GREENBUILD CONFERENCE,** I couldn't help but think about how much I could charge for tickets for a conversation between Clinton and Dan DiMicco, CEO of Nucor Steel.

While Nucor under DiMicco has been a huge proponent of a strong and sustainable environment (and has some notable green success stories), DiMicco is a huge opponent of the Kyoto Protocol. As I understand his objection, the problem with Kyoto is it has the effect of increasing the cost of U.S. manufacturing. As a result, a certain percentage of U.S. manufacturing will move offshore to places like China, where the factories produce more than nine times as much pollution. Therefore, in an interesting twist, the net result of Kyoto is not just a drain on the U.S. economy, but also a net increase in carbon emissions worldwide.

Clinton presented an opposing viewpoint during his presentation. He believes that reducing energy consumption and greenhouse gas emissions actually makes U.S. manufacturing more competitive and will have the result of bringing more business to the U.S., therefore further reducing carbon emissions worldwide. To make his case, he uses Denmark as an example of where strong environmental regulations have spurred economic growth.

Ever the pragmatist, Clinton stresses that the sustainability movement needs to be "operationalized"—that sustainability can't be presented as "a bottle of castor oil but also must have an economic benefit." As part of his "Greening America's Schools" program, his foundation is providing seed money to show that operation savings will pay for green retrofits, that the cost to make a building more energy-efficient is more than offset by the savings that result from that energy efficiency. "In 18 months, people will accept that buildings should be energy-neutral. Within five years, we'll be talking about energy-positive buildings."

During the same session in which Clinton spoke, George David, CEO of United Technologies, pointed out that "going green doesn't cost more, it saves money." I like that approach. At *Modern Steel Construction*, we've taken a similar approach. We use soy-based inks because they're not only environmentally sensitive, but also economical. We're thinking about switching to a recycled paper stock not just to help the environment, but because it's also 9% lighter, which will reduce our postage costs. We've introduced a digital edition so people who don't want a paper copy can read the entire issue (ads included) online at www.modernsteel.com.

Likewise, the digital edition means less fossil fuel consumption from shipping the magazine.

Our parent company, AISC, has taken green even further. Our offices use energy-efficient lighting and we have occupancy sensors on the light switches. Offices all have recycling boxes. As a benefit, AISC offers its employees the opportunity purchase public transit cards with pretax dollars—and more than 96% of AISC's headquarters staff commutes by public transportation. We've moved to using eFax (where our faxes come to our Outlook inboxes) instead of paper faxes. We've introduced ePubs, where members can access Engineering Journal, design guides, and about 15,000 pages of technical information online rather than purchasing paper copies that need to be printed and sent through the mail. We don't print out and store membership applications and subscription renewal forms; instead we accept electronic files that we store on our servers—no paper needed (an economic benefit not just from less paper use, but also from less printer maintenance and supplies). And, of course, we're trying to make NASCC: The Steel Conference as green as possible (more on this in the coming months).

Of course, we're not alone. Steel mills have reduced energy consumption and greenhouse gas emissions by more than a third. A number of fabricators have re-lamped for energy efficiency and are looking to incorporate daylighting into their shops. Recycling is de rigueur. In fact, there's even a session at the upcoming Steel Conference (April 3–5 in Nashville) called "Greening the Shop"—visit www.aisc.org/nascc for more information. (And talking about recycling, steel of course is the most recycled material in the world and all of the wide-flange rolled in the U.S. uses more than 95% recycled material. Steel is recycled, recyclable, and reusable.)

What are you doing to be green at your company? Drop me an email at melnick@aisc.org or log on to **www.modernsteel.com**, click on "reader feedback" and post a comment to start a conversation.

SCOTT MELNICK
EDITOR



#### **Editorial Offices**

One E. Wacker Dr., Suite 700 Chicago, IL 60601 312.670.2400 tel 312.896.9022 fax

#### **Editorial Contacts**

EDITOR & PUBLISHER Scott L. Melnick 312.670.8314 melnick@modernsteel.com

MANAGING EDITOR Keith A. Grubb, P.E., S.E. 312.670.8318 grubb@modernsteel.com

ASSOCIATE EDITOR Geoff Weisenberger 312.670.8316 weisenberger@modernsteel.com

#### **AISC Officers**

CHAIRMAN Rex I. Lewis

VICE CHAIRMAN

David Harwell

TREASURER Stephen E. Porter

SECRETARY & GENERAL COUNSEL David B. Ratterman

PRESIDENT Roger E. Ferch

VICE PRESIDENT John P. Cross, P.E.

VICE PRESIDENT Louis F. Geschwindner, Ph.D., P.E.

VICE PRESIDENT Roberta L. Marstellar, P.E.

VICE PRESIDENT Scott L. Melnick

#### **Advertising Contact**

Account Manager Louis Gurthet 231.228.2274 tel 231.228.7759 fax gurthet@modernsteel.com

For advertising information, contact Louis Gurthet or visit www.modernsteel.com

#### Address Changes and Subscription Concerns 312.670.5444 tel

312.893.2253 fax admin@modernsteel.com

#### Reprints

Betsy White The Reprint Outsource, Inc. 717.394.7350 w.betsy@verizon.net



SEE WHAT'S GOING UP.



Once you've experienced the power of SDS/2, you can see what's going up much more clearly. Design Data is moving above its last 25 years and the groundbreaking advancements we pioneered with SDS/2. The new innovations we're building into the next generation of SDS/2 will heighten your productivity and connect you to your partners in exciting new ways. Check out the foundation we've built at www.sds2.com/history and get ready to see what's going up at Design Data.

www.sds2.com

800.443.0782

402.441.4000

e-mail: info@sds2.com



## You need the best pit crew in the business



Rugged Machines Designed by Engineers Experienced in Structural Fabrication



Pro Customer Service team keeping you in the Race with Parts and Solutions



Knowledgeable Software Professionals who help Drive your toughest BIM projects

From start to finish, you need to run a consistently strong race.

Fast lap times really don't mean much if you break down along the way.

A driver is only as good as his design team and pit crew - it's the same with shop equipment.

Go with the team that races with you on every lap and delivers winners: Peddinghaus – Award Winning Design, Unbeatable Parts and Service.

Your Pit Crew during your Toughest Projects.



## POWERING YOU TO THE WINNER'S CIRCLE SINCE 1903

# steel interchange

**IF YOU'VE EVER ASKED YOURSELF "WHY?"** about something related to structural steel design or construction, *Modern Steel Construction's* monthly Steel Interchange column is for you! Send your questions or comments to solutions@aisc.org.

#### **Historic Lattice Columns**

We are examining an existing building constructed roughly in 1919. The columns in the building consist of double-angle flanges with lattice steel webs. We are trying to determine allowable loading for the column but have been unable to find any documented information. Any help would be appreciated.

I am not sure what type of documented information you are looking for. You may be able to find discussions in old textbooks, but I don't think that you will find capacity tables. The design of such compression members usually started with the calculation of the basic section properties and determination of the unit compressive stress. The elements also had to be joined together to act as a unit. To act as a unit, the buckling resistance of the individual element has to be at least as great as that of the member as a whole.

Kurt Gustafson, S.E., P.E.

#### **Evaluation of an Existing Structure**

I am working on an addition to a 1922 steel-framed building. When I check the columns using ASD (unreinforced concrete encased,  $F_a = 18000 - 70L/R$ ), many are overstressed. However, the results appear to be better using LRFD.

Is there anything in the AISC specification that would require that we use ASD and not LRFD to check the existing structure? Is it reasonable to apply today's load and resistance factors to historic steel?

There is nothing in the AISC specification that defines what load approach must be used in the analysis, design, or evaluation. Either method is acceptable as long as you stay consistent in the load and capacity sides of the design equations. Current requirements are often applied to existing structures. See Appendix 5 of the 2005 AISC specification for more information on evaluating existing structures.

Kurt Gustafson, S.E., P.E.

#### **Shear Stud Requirements**

Is there a minimum height requirement for studs used in the design of composite beams?

Section I1.3 of the AISC specification requires that studs shall not be less than four stud diameters in length after installation. Section I3.2c of the AISC specification requires that, when formed steel deck is used, after installation the studs shall extend not less than 1½ in. above the top of the steel deck. See Chapter I of the AISC specification for other stud requirements.

Amanuel Gebremeskel, P.E.

#### **Crane Runway Forces**

Where are "crane runway horizontal forces" addressed in the current AISC specification? This was formerly covered in Section A4.3 of the 1989 ASD specification. If it is not

## addressed in the new specification, where do I need to go to find these requirements?

The AISC specification no longer stipulates load requirements. Instead, loads and load combinations are now covered by the applicable building code or the ASCE 7 load standard. Crane loads are covered in Section 4.10 of ASCE 7-05.

Kurt Gustafson, S.E., P.E.

#### **Expansion Joint Location**

What is the maximum length permitted between expansion joints in a steel building?

There is no one specific requirement for permitted length between expansion joints in a steel building. The determination of when expansion joints should be introduced in a building structure is dependent on many factors including the configuration of the structure, type of use, and climatic conditions, among others. You may want to look at Technical Report No. 65, Expansion Joints in Buildings, published by the Federal Construction Council (1974). Key points from this reference are summarized in the 13th Edition AISC Steel Construction Manual beginning on page 2-31. The full document can be read online and is also available for purchase at www.nap.edu/catalog/9801.html.

Kurt Gustafson, S.E., P.E.

#### **Reduction for Splice Length**

In the 3rd Edition AISC LRFD manual, footnote "e" in Table J3.2 requires that a 20% reduction is taken on bolt patterns in tension splices where the bolt pattern length measured parallel to the line of force is greater than 50 in.

Is any tension connection considered a splice? I am evaluating diagonal tension members in a truss that connect to the top and bottom chords as well as vertical members. Does this reduction apply?

The underlying requirement is to reduce the available shear strength by 20% of an end-loaded bolt group that exceed 50 in. in length due to the uneven load distribution between such bolts. The connections you describe are likely such a case and, if the joint length exceeds 50 in., you do have to use the reduced capacity. The footnote was probably written with the term "splices" because it was rare to have connections other than splices of this length in an end-loaded configuration.

Amanuel Gebremeskel, P.E.

#### Seismic Retrofit of 1931 Building

I am doing a seismic retrofit for a structure designed and built in 1931. I guess it must be A7 steel. Could you let me know what values  $F_v$ ,  $F_u$ , and  $R_v$  should be used?

In 1931 most structural steel for buildings was designated as ASTM A9 rather than ASTM A7, which was applicable to bridge steel at the time. The tensile strength of ASTM A9 was stipulated as 55,000 psi to 65,000 psi and the minimum yield point as ½ T.S. or not less than 30,000 psi.

## steel interchange

FEMA 356, which is a prestandard and commentary for the seismic rehabilitation of buildings, defines default lower-bound material strengths for ASTM A9 as a tensile strength of 55 ksi and yield strength of 30 ksi.

There would have been no  $R_y$  (nor  $R_p$ ) defined for the material at the time, as these factors were only recently developed. FEMA 356 also provides factors to translate lower-bound steel properties to expected-strength steel properties. The factor given for steel produced prior to 1961 is 1.10 for both the tensile strength and the yield strength.

Kurt Gustafson, S.E., P.E.

#### Single Angle Design

Can you help me clarify the design of a single unequal leg angle in bending utilizing the new AISC specification? A very common situation for longer span masonry brick openings is to use an  $L6\times3\frac{1}{2}\times\frac{5}{16}$  LLV. Do you have an example or some clarification on the design?

Section F10 of the 2005 AISC specification addresses the design of unequal leg angles in bending. If the angle has lateral torsional restraint, the design can be carried out using equation F10-1. If there is no such restraint, the second paragraph of page 282 in the commentary to Section F10.2 provides some guidance for how to approach that problem. Equation F10-6 is applicable with that commentary.

Amanuel Gebremeskel, P.E.

#### **Bolt Torque/Tension Equation?**

I understand that the torque required for bolt installation in a slip-critical joint depends on the bolt class, the bolt diameter, and the faying surfaces properties. Can you tell me what equation to use to determine the torque required developing the required tension in the bolt?

No. Bolt installation is defined by the tension required in the bolt, not the applied torque. There is no defined torque/tension relationship, as this can vary considerably depending on the project conditions and must be calibrated if a torque-based method is to be used to provide pretension in bolts. The RCSC Specification for Structural Joints Using ASTM A325 or A490 Bolts (a free download at www.boltcouncil.org) defines procedures for proper installation of high-strength bolts. Both the calibrated wrench method and the twist-off-type tension control bolt assembly method are

torque-based methods. Note the special requirements for calibration that apply, particularly for the calibrated wrench method.

Kurt Gustafson, S.E., P.E.

#### **Required Bolt Length**

I am relocating a structure where there is not proper documentation of existing conditions, and I am unable to determine the required length of the structural bolts.

We have the connection drawings of the columns and beams, and the thickness of the splice plate. I want to know what should be the length of the bolt and length of the threaded portion, taking into consideration the height of the nut and the thickness of the washer.

In addition to the information you summarized, you will also need to assess what loads the connections are required to transfer, that appropriate use of washers and nuts is followed, and whether the threads are required to be excluded from the shear plane. The length of bolt used must, at a minimum, allow for the end of the bolt to be flush with the outside face of the nut so as to have the threads adequately engaged. Furthermore, the washer requirements will depend on the bolt, hole, and base material types, as well as the method of installation.

The RCSC Specification for Structural Joints Using ASTM A325 or A490 Bolts (a free download at www.boltcouncil.org) provides a good source of information on these subjects. The Commentary to Section 2.3 provides general guidance on proper selection of bolt length. An AISC Engineering Journal paper by Carter (second quarter, 1996) provides a more detailed treatment of the subject. This paper is available at www.aisc.org/epubs.

Amanuel Gebremeskel, P.E.

The complete collection of Steel Interchange questions and answers is available online. Find questions and answers related to just about any topic by using our full-text search capability. Visit Steel Interchange online at **www.modernsteel.com**.

Kurt Gustafson is the director of technical assistance and Amanuel Gebremeskel is a senior engineer in AISC's Steel Solutions Center. Charlie Carter is AISC's chief structural engineer, and Lou Geschwindner is AISC's vice president of engineering and research.

Steel Interchange is a forum to exchange useful and practical professional ideas and information on all phases of steel building and bridge construction. Opinions and suggestions are welcome on any subject covered in this magazine.

The opinions expressed in Steel Interchange do not necessarily represent an official position of the American Institute of Steel Construction, Inc. and have not been reviewed. It is recognized that the design of structures is within the scope and expertise of a competent licensed structural engineer, architect or other licensed professional for the application of principles to a particular structure.

If you have a question or problem that your fellow readers might help you solve, please forward it to us. At the same time, feel free to respond to any of the questions that you have read here. Contact Steel Interchange via AISC's Steel Solutions Center:



One East Wacker Dr., Suite 700 Chicago, IL 60601 tel: 866.ASK.AISC • fax: 312.803.4709

solutions@aisc.org

## Swimming in jobs?



#### Taking on a greater number of jobs creates challenges

When you take on a greater number of simultaneous jobs, you've simply got more to manage—more drawings, revisions, and change orders, more material to purchase, more stock to keep track of, more production priorities to organize, and more assemblies to ship. FabTrol MRP, the global leading software for managing steel fabrication, can keep you from drowning.

#### Having the right tools in place to manage growth helps

Lindsay Allen, who is Operations Manager for Brisbane Steel Fabrications in Australia, says, "FabTrol MRP software has not only helped us to take on larger jobs, it has helped us to keep jobs separate and manageable—allowing us to take on an even greater number of larger jobs." To find out how FabTrol MRP can help you manage growth, call us today at (888) FABTROL.

#### A better way to manage rapid growth

Read a case study to learn how Brisbane Steel Fabrications has managed rapid growth at www.fabtrol.com/growth



FabTrol Systems, Inc. • 1025 Willamette St., Suite 300, Eugene, OR 97401 U.S.A. • (888) FABTROL • www.fabtrol.com



# A WINNING PLAY BY TWO OF BENTLEY'S KEY PLAYERS

BENTLEY'S WINNING TEAM PROVIDES THE MOST COMPREHENSIVE, INTEGRATED SOLUTIONS FOR THE STRUCTURAL INDUSTRY.

One of these solutions is a complete connection design for building and plant applications with RAM Connection.

Not only do we offer a complete analysis and design solution for your structures but now the design of your connections can be performed integrated with your structural model.

Visit www.Bentley.com/IntegratedConnection to find out more or contact us at 1 800 Bentley or structural@bentley.com







## steel quiz

**LOOKING FOR A CHALLENGE?** *Modern Steel Construction's* monthly Steel Quiz tests your knowledge of steel design and construction. Most answers can be found in the 2005 *Specification for Structural Steel Buildings*, available as a free download from AISC's web site, **www.aisc.org/2005spec**. Where appropriate, other industry standards are also referenced.


It's all about the AISC Seismic Provisions in this month's Steel Quiz, developed by AISC's Steel Solutions Center. Sharpen your pencils and go! You can download a copy of the AISC Seismic Provisions at no charge at <a href="https://www.aisc.org/2005seismic">www.aisc.org/2005seismic</a>.

- What limiting width-thickness ratio should be used for a member subjected to axial compression plus flexure?
- What area is used to check for shear yielding and shear buckling on a round HSS?
- What is the difference between nominal strength, design strength, and allowable strength?
- 4 True/False: When evaluating an existing steel structure, the available strength of the structural members and connections must be assessed based on the AISC specifi-

- cation that was in effect at the time of the original construction.
- **True/False:** If a steel building structure is classified as Seismic Design Category C and an *R*-Factor of 3 is used, the design need not comply with the detailing requirements of the AISC Seismic Provisions.
- 6 Can finger shims be used in slip-critical connections?
- **True/False:** When considering flexural yielding on a W-shape, the available strength is based upon the plastic section modulus (*Z*<sub>v</sub>).

- Is it permitted to use thermal cutting to make bolt holes?
- When checking the bearing strength at bolt holes, how are the various bolts in the connection required to be checked, given that edge distances vary?
- 10 Is a pipe the same thing as a round HSS?

TURN PAGE FOR ANSWERS



## steel quiz

**ANSWERS** 

Design of members for combined forces is covered by Chapter H of the 2005 AISC specification. The axial and flexural design parameters are considered independently and combined per the applicable equation. Thus the applicable limiting width-thickness ratio for uniform compression from Table B4.1 is used in determining  $P_c$ , and the applicable limiting width-thickness ratio for flexure from Table B4.1 is used in determining  $M_c$ .

2 One-half of the gross area of the round HSS based on the design wall thickness is used in the shear check, which also includes parameters for shear buckling based on the diameter of the HSS. See Section G6 of the 2005 AISC specification for details.

3 Nominal strength is the unreduced strength of a structure or component (without the resistance factor or safety factor applied) determined in accordance with the AISC specification. This is an estimate of the load that would be achieved in laboratory testing. Design strength is the nominal strength multi-

plied by the resistance factor, used with the LRFD load approach. Allowable strength is the nominal strength divided by the safety factor, used with the ASD load approach.

4 False. The available strength of members and connections can be determined from applicable provisions of the current AISC specification. See Appendix 5 of the 2005 specification for evaluation of existing structures.

**5 True**. Table 12.2-1 of ASCE 7-05 permits structural steel buildings in seismic design categories A, B, and C to not be specifically detailed for seismic resistance if an *R*-factor of 3 is used in the design. Steel building structures classified as seismic design category D, E, or F are required by ASCE 7-05 to be detailed per the AISC *Seismic Provisions*. Note also that if *R* is taken greater than 3 in categoires A, B, or C, the structure must be detailed per the AISC *Seismic Provisions*.

**6 Yes.** However, the shims must also meet the faying surface require-

ments. For finger shims up to ¼ in. in slip-critical connections with standard holes, no reduction is necessary. Above ¼ in. thickness, the slip resistance is reduced to that for short-slotted holes. See Section J3.2 and J3.8 of the 2005 AISC specification for details.

**True**. As defined in Section F2.1 of the 2005 AISC specification, the nominal flexural strength for yielding is  $M_n = M_p = F_y Z_x$ . For those familiar with previous versions of the ASD approach, note that this similar concept of plastic distribution was hidden in the specification, which permitted a 10% increase for compact shapes  $(F_b = 0.66F_y)$  in lieu of  $F_b = 0.60F_y$ ). This increase was provided assuming that the lower-bound shape factor  $(Z_x/S_x)$  for a W-shape is 1.1 (the range is from 1.1 to 1.4, approximately). The 2005 AISC specification permits the use of the actual  $Z_x$  for the specific shape.

**Yes.** Section M2.5 of the 2005 AISC specification states that "thermally cut holes shall be permitted with a surface roughness profile not exceeding 1,000  $\mu$ in. (25  $\mu$ m) as defined in ASME B46.1. Gouges shall not exceed a depth of  $\frac{1}{16}$  in. (2 mm)." Thermally cut is defined as cut with gas, plasma, or laser.

Pror connections, the total bearing resistance is taken as the sum of the bearing resistances of the individual bolts. In other words, the bearing resistance at each individual bolt hole is determined, and the sum of these is used to determine the available strength of the connection for this limit state.

10 As defined in the 2005 AISC specification, an HSS is a hollow structural section, which includes square, rectangular or round shapes produced in accordance with a pipe or tubing product specification. Don't confuse this definition with the actual ASTM specifications for the particular material types. Pipe used for structural steelwork, as defined in Section A3 of the 2005 AISC specification, is ASTM A53 Grade B ( $F_y$  = 35 ksi); round HSS is ASTM A500 Grade B ( $F_v$  = 42 ksi) or Grade C ( $F_v$  = 46 ksi).

Anyone is welcome to submit questions and answers for Steel Quiz. If you are interested in submitting one question or an entire quiz, contact AISC's Steel Solutions Center at 866. ASK.AISC or at **solutions@aisc.org**.



# **FABSUITE**

STEEL FABRICATION MANAGEMENT SOFTWARE

# Big enough to meet your needs ... Small enough to know your name ...



- + ESTIMATING
- **♦ INVENTORY CONTROL**
- PROJECT MANAGEMENT
- **◆ COMBINING (MULT/NEST)**
- BAR CODING INTERFACE
- + PRODUCTION CONTROL
- ♦ PURCHASE ORDERS

P.O. Box 5366, Williamsburg, VA 23188

ORDER ENTRY



#### **LEADER IN CONNECTION DESIGN SOFTWARE SINCE 1984**

# DESCON


# The Ultimate Advantage in Connection Design

Excellent Quality \* Easy to Learn \* Simple to Use \* Outstanding Technical Support

#### **DESCONWIN \* DESCONBRACE**

AISC SPECIFICATION 2005 \* SEISMIC PROVISIONS 2005 ASD \* LRFD \* METRIC (SI) \* IMPERIAL


SHEAR AND MOMENT CONNECTIONS \* COLUMN AND BEAM SPLICES \* BRACED FRAME CONNECTIONS
PREQUALIFIED SEISMIC MOMENT CONNECTIONS





Omnitech Associates, Inc.

www.desconplus.com



# OLD NEW ORLEANS CAN BE USED TO BUILD THE NEW NEW ORLEANS.

The photo to your left is where this story begins, but happily not where it ends.

Because we recycle steel. Our ball-and-socket sheet piles are made from recycled steel. And it's all cast and hot-rolled right here in the United States.

So those submerged cars can be turned into new steel piles to make the levees stronger.

Giving new life to old steel. Not to mention New Orleans.

www.nucoryamato.com



#### news & events

**CERTIFICATION** 

#### AISC to End Sponsorship of Metal Building Certification Program

The American Institute of Steel Construction (AISC) and the Metal Building Manufacturers Association (MBMA) have jointly decided to end AISC's sponsorship of the Metal Building Certification Program effective December 31, 2008, or 12 months from the date of the final participant's 2008 audit, whichever comes later.

"AISC is focusing its certification efforts on its revitalized fabrication, erection, and bridge certification programs," explained Roger Ferch, president of AISC. The termination of this program is not a reflection its quality or importance, but rather reflects a concentration by AISC on its core market and participants. "The timing of the transition is designed to give MBMA time to transition to a new sponsor," Ferch explained.

"MBMA is currently in the process of selecting a new sponsor/administrator for the program, and anticipates that the transition to the revised metal building certification program under this new sponsor will be seamless, and that there will be no interruption in a company's certification," explained Bill Savitz, chairman of MBMA.

The Metal Building Certification Program began in 1989. The program is often referenced in project specifications and is designed to assure that certified companies have the manufacturing and engineering capabilities necessary to design and fabricate a quality metal building system.

Both Ferch and Savitz stressed that the two organizations have valued their relationship and expect to continue working together on a variety of future projects. Currently, the two organizations are working jointly on a tapered member design guide as well as seismic research.

For more information on the current program and a list of participants, please visit www.aisc.org/metalbuilding. For more information on metal buildings, please visit www.mbma.com.

### CONFERENCES

# Register Now for The Steel Conference!

Register now for the 2008 North American Steel Construction Conference! More than 3,000 engineers, fabricators, erectors, and detailers are expected to register for The Steel Conference, which will take place April 2-5 in Nashville, Tenn. See the advance program in this issue or visit www. aisc.org/nascc for a complete schedule of conference events and instructions for preregistration.

With nearly 90 technical sessions, The Steel Conference is the industry's premier education event. It provides structural engineers, steel fabricators, erectors, and detailers with practical information and the latest design and construction techniques. The conference is a key networking opportunity. Its extensive trade show features products and services ranging from fabrication machinery, galvanizing, and connection products to detailing and engineering software. The conference also incorporates the Structural Stability Research Council's Annual Stability Conference. Online registration is available through March 27, 2008. After March 27, registrations will be taken on-site, but at higher rates.

#### **BOOKS**

#### New Handbook for Civil and Environmental Engineers Addresses Risk and Reliability Analysis

When it comes to the planning, design, construction, and management of engineering systems, risk and uncertainty are unavoidable. The consideration of the risk involved in any situation, project, or plan becomes an integral part of the decision-making process. Risk and Reliability Analysis: A Handbook for Civil and Environmental Engineers presents key concepts of risk and reliability that apply to a wide array of problems in civil and environmental engineering.

The authors begin with an overview of the art of making decisions in the presence of uncertainty and then explain the fundamentals of probability that will be applied throughout the book. In the second part of the book, the authors discuss various techniques used in probability distributions and parameter estimation. A third section of the book considers different aspects of uncertainty analysis, especially risk analysis and risk management, providing instructive examples. The final group of chapters

addresses reliability analysis and design, focusing particularly on the important area of water distribution networks.

Ample illustrations and detailed reallife examples make *Risk and Reliability Analysis* essential reading for present and future engineers in the fields of civil, environmental, biological, and agricultural engineering, as well as the watershed sciences.

To order, call 800.548.ASCE (2723) or visit **www.pubs.asce.org**. The ASCE member price is \$120.00.

#### Correction

The detailer for the Springwater Trail (McLoughlin Blvd.) Pedestrian Bridge in Portland, Ore. (November, p. 75) was AISC Member Graphics for Steel Structures, Inc. AISC Member Fought & Company, Inc. was the fabricator for the project. We regret any confusion caused by the error.

#### **ONLINE RESOURCES**

# Annual Meeting Presentations Online

In response to a large number of requests by attendees, the speaker presentations from the 2007 AISC Annual Meeting are now available for download by AISC members. The presentations include:

- ✓ Attracting and Retaining A Quality Workforce (Andrew Patron from FMI Management)
- ✓ Immigration Reform Update (Patrick Cont from Strum & Cont)
- ✓ Four Generations (Cam Marston from Marston Communications)
- ✓ Moving Your Business a Generation Ahead (Wayne Rivers from the Family Business Institute)

The downloads are only available to members. To access the files, visit www. aisc.org and click on the Membership tab, then click on the Annual Meeting Sessions link.

**AWARDS** 

#### Walterio Lopez and Rafael Sabelli Win 2008 T.R. Higgins Award

Buckling-restrained braced frames (BRBFs) are an increasingly popular new steel seismic load resisting system that has demonstrated efficiency and exceptional seismic performance. Based on their groundbreaking paper "Seismic Design of Buckling-Restrained Braced Frames," Walterio Lopez and Rafael Sabelli are being honored with the T.R. Higgins Lectureship Award. "BRBFs have the potential to significantly impact the structural steel market in seismic regions," explained Louis F. Geschwindner, AISC's vice president of Engineering and Research.

A new paper based on the work will be presented for the first time at the 2008 NASCC: The Steel Conference in Nashville April 2-5, 2008. For more information on the conference, visit www.aisc.org/nascc.

Their work has already been published by the Structural Steel Education Council and has helped BRBFs to be accepted in ANSI/AISC 341-05 Seismic Provisions for Structural Steel Buildings and in the

letters

Weight vs. Cost

Scott Melnick's recent comments about weight vs. cost invoke a long-standing sore point with me. It has often taken hours of discussion and many design alternatives to prove the point.

One argument that I have not been able to get much traction with is the concept of pounds per *cubic* foot of building volume: As floor-to-floor heights increase, whether they are trading floors in high-rises or roofs over warehouses, weight per square foot will increase since the columns are longer with no increased floor area to compensate. In very tall buildings this can easily add one pound per square foot.

Now that I am on the developer's side of the table, I have been able to defend the consultant when he/she gets beaten up on the pounds per square foot numbers.

It would be interesting to learn whether others have considered this concept. Maybe we can start something. Keep up the good work.

Irwin Cantor Tishman Speyer International Building Code. Included in their paper is a detailed component design of two typical BRFB configurations and the development of testing protocols. In addition, a discussion of gusset-plate design and its influence on acceptable frame behavior is provided.

The T.R. Higgins Lectureship Award,

which includes a \$10,000 cash prize, is presented annually to an outstanding lecturer(s) and author(s) whose technical paper or papers are considered an outstanding contribution to the engineering literature on fabricated structural steel. For more information on the T.R. Higgins Award, visit www.aisc.org/higgins.

Ficep with

"Wireless Technology"

Now Offers the Fastest Single Spindle Drill Line on the Market Today!



That's right! Ficep has pushed the technology and performance level of single spindle drills to a new level by incorporating many proven technological features that are part of their multiple spindle CNC drilling lines. Some of the productivity features that are now part of the new Victory 11 are:

- Positive ball screw spindle feed to use carbide tools for unbelievable feed rates.
- ◆ 2,000 RPM spindle speed.
- Wireless remote control enhances floor-to-floor productivity by 30%.
- ◆ Self contained design eliminates the need for trailing cables, wires, hoses, etc.
- ◆ Integrated chip collection system.

#### All this and more at an extremely attractive price!

Give us a call to find out how you can substantially reduce your man hours per ton for an investment equal to the **annual cost of one employee.** 



2301 Industry Court Forest Hill, Maryland 21050 410-588-5800 • 410-588-5900 fax www.ficepcorp.com



# A modern, angular addition to Toronto's Royal Ontario Museum uses steel to augment the existing historic structure.

IN 2001, THE ROYAL ONTARIO MUSEUM (ROM) IN TORONTO EMBARKED ON A MISSION TO REJUVENATE AND EXPAND ITS HISTORIC FACILITY. The first order of business was to establish an international design competition, one that would attract renowned architects from around the globe. Studio Daniel Libeskind (SDL) was eventually selected to design the project, and six years later, ROM's Michael Lee-Chin Crystal addition has come to fruition. The new angular structure is adjacent to, and also overlaps, ROM's classic facade.

From the onset, it was clear that structural steel was the right material for the job, as it was the only solution that could make the vision conceived on the famous "Libeskind napkin sketch" a reality. The engineering team recognized that the

irregularity of the structure would amplify gravity forces and needed to be as light as possible. The site limitation also required minimum construction staging space and quick erection. Arup and SDL team members who had already experienced SDL's Denver Art Museum, a project with similar structural demands (April 2007, p.30), shared the lessons learned with the rest of our group, including the owner and construction manager.

#### **Design Stage**

Early in design, a process was implemented between the architects and the structural engineers that provided a virtual space where the steel members had to "live" and established "no-fly zones" for the rest of the building systems to work around. The architectural modeling work was carried

out using Form-Z software, and then the plans were imported into AutoCAD where individual floor and diagrid elements were modeled by the structural engineers. The architects used this line work to review the structure and coordinate with their design.

Once the geometry was finalized, the line work was imported into finite element design and analysis programs. At the preliminary stages, GSA (a structural analysis software package developed by Arup) was used for its capability to provide a better graphic interface with other software being used. In the final production stage, SAP 2000 was used for its compatibility with X-steel (now Tekla Structures), which the team predicted would be implemented during detailing. After ironing out a few translation and communication issues between the different software

products used, this process proved to be extremely valuable.

At the preliminary stages, custom-built skewed tube sections were specified at various locations, including the corners where the diagrid planes met. By collaborating with the fabricators, we learned that the fabrication of these custom sections was not going to be economical and timely. Although it was the correct response to provide box sections that were torsionally stiff and achieved concentric corner details, it was evident that the local market demanded the use of sections that were readily available. It was obvious that the custom-made box sections had to be redesigned to allow the use of readily available wide-flange sections.

#### **Detailing Stage**

The file transfer protocol that was adopted during the design stage was complementary to the protocol adopted during detailing and fabrication stages. The team added one more step to the file exchange process. Once the structural steel elements were designed in SAP, the geometry and the section properties were forwarded to the detailer. The detailer then imported the line work into Tekla

Structures, where the single-line work was converted to actual extruded sections. The extrusions were rendered and then exported into Form-Z for compliance review. Once the geometry was coordi-

nated, the changes were fed back into the structural design and analysis program in order to revise the design and load paths. The extra efforts made during the detailing stage eliminated almost all problems during fabrication.

#### **Fabrication**

The fabrication process was, in a word, intriguing. The complex geometry required that many members be framed into a single node from many different directions. Shop personnel had to be equipped with laptops in order to visualize the 3D models of the nodes and execute their work. One of the more complex nodes required a shop drawing that was 5 ft wide by 8 ft long with more than forty views of the node. This process proved yet again that extra time spent in the shop pays off during erection.

Since the structure was irregular, a conventional grid system could not be established. A general grid system was in place that identified the diagrid and floor planes with their corresponding crystal form. However, an unconventional naming system was also adopted to identify the various connection locations that could not be referenced to the grids. Metaphoric names such as "Owl's head," "Thore's brother's broken leg," (named for an SDL team member), "Stair of wonder," and the "Pinnacle" were used to reference these locations.

#### **Construction Engineering**

The construction managers identified the proper construction sequence to enable other trades to move into the building and start their work while the steel structure was partially erected. But the team was concerned that the partially erected steel structure might not behave as modeled and designed, and hired Halsall to carry out the construction engineering and to provide the necessary staging sequence to reflect the schedule needs.

Halsall's job was to ensure that the partially erected structure did not experience

The extra efforts made

during the detailing

stage eliminated

almost all problems

during fabrication.

overstressing due to locked-in forces, as well as to predict the behavior of the partially erected sections to avoid misalignments for later erection. Roughly fourteen different partially built analysis models were created

that addressed the partially erected structure and the sequencing of shoring installation and removal. Additional steel elements had to be introduced to compensate for the missing floor diaphragms, and shoring had to be added to maintain the geometry of the partially erected sections. It was crucial to maintain the building's geometry due to the proximity of the new structure to the ROM's existing 1914 and 1933 buildings on three sides of the site, as well as to accommodate the cladding that had already started the detailing process.

This process worked flawlessly. A number of monitoring targets were added all around the structure and checked at various stages of erection and after each concrete floor was constructed. The building structure behaved as predicted at all different stages of construction. The erection



Aerial view of the Royal Ontario Museum.


#### **Fabrication Bidding**

At the design development stage, the team visited several local steel fabricators to understand their capacities and capabilities. It was evident that close interaction was needed between the steel fabricators and the design team, so employing a fabricator that was geographically close to the team and the project was a very important consideration.

With this knowledge in hand, the team tendered the project to four pre-qualified steel fabricators. The bidders were tasked with providing a guaranteed maximum price, ideas on fabrication and erection, and a detailed schedule of deliverables to expedite the steel work.

All four bids demonstrated excellent understanding of the work and had various approaches to detailing and building this structure, but only one firm could be chosen. Immediately after awarding the steel contract, the A/E/C team and the fabricator began the design interaction and implementation process. The challenge was to detail and fabricate the steel in order to have it ready for erection as soon as the sub-grade work was complete.





Left, top: Interior spaces prominently feature the structure's unusual geometry.

Left, bottom: Due to the complexity of the structural nodes like this one, shop personnel had to be equipped with laptops in order to visualize their work in 3D.

was completed with minimum modification on-site, and few coordination issues arose.

At times, the challenges appeared overwhelming. Despite this, the building team was able to create the landmark architectural icon that the ROM envisioned. And given the effort that went into the steel work, some of the complex steel structures were left exposed, giving museum patrons a glimpse of the skeleton.

Shahé Sagharian was Halsall's project principal for the ROM Michael Lee-Chin Crystal addition.

Royal Ontario Museum, Toronto

#### **Architect**

Studio Daniel Libeskind, New York/B+H Architects, Toronto -Joint Venture

#### **Structural Engineer**

Arup, London Halsall Associates Ltd., Toronto

#### **Construction Manager**

Vanbots Construction, Markham, Ontario



**ProSteel 3D** is your complete solution for design, drawing production and fabrication. Completely customizable, **ProSteel 3D** is proven technology that saves time and increases profit in all aspects of steel construction. This intelligent steel modeling application works within AutoCAD.

- True 3D modeling of structures and connections
- Automatic creation of 2D details, 2D plans, layout drawings, shop drawings and BOM
- Easily generates stairs, ladders, cages, trusses and combined curved and user shapes
- CNC Communication to Peddinghaus, Controlled Automation, Ocean Machinery Vernon Tools and Studmeister
- Communicates with analysis software
- Special functionality for offshore construction, lattice tower generation, pressure vessel design and light gauge construction









WWW.STRUCSOFTSOLUTIONS.COM 1-877-810-7575



# 1/2 the price! 1/2 the floor space! 2x the versatility!

CNC layout and drilling of

- ✓ beams and channels
- ✓ flat bars and base plates
- ✓ square and rectangular tubes
- ✓ round tubes and pipes
- ✓ tapered and pre-cambered beams
- stair stringers and welded connections

Drills 1/4" to 2" diameters
Drills steel up to 10" thick
Easy import of CAD detailed
drawings

**Built by Peddinghaus** 




# AVERGER CNC BEAM DRILL LINE

Made in the USA CAUTION

### Call for a FREE Video & Brochure

DX 860 Metal Deck Fastening System





# Hollow structural shapes help Medellin's Botanical Gardens blossom into a new icon for the city.

T USED TO BE THAT WHEN YOU THOUGHT OF MEDELLÍN, COLOMBIA, YOU THOUGHT OF CRIME. But the twenty-first century version of Colombia's second-largest city paints a different picture. For the last decade or so, local administrators have focused on boosting the city's image and have poured significant funding into public parks, convention centers, libraries, and public transportation. In the process, Medellín has also become a city of avant-garde architecture—much of it using structural steel.

A new canopy shelter at Medellín's Botanical Gardens is perhaps one of the most representative icons of the city's recent improvement. Set on a small piece of native jungle in the heart of the city, the old Botanical Gardens were practically abandoned, with old enclosures that didn't attract local or foreign visitors and were

deemed not worth restoring. However, the current local government—particularly in response to increased environmental awareness and conservation efforts—decided to transform the place into one of the most important landmarks of the city, one that would bring in tourists and also provide a base for scientific research.

#### In Harmony with Nature

With the new \$2.2 million (USD) canopy enclosure (part of an overall renovation of the Botanical Gardens), the architects created a monument to nature, harmonizing the design with local natural symbols; bee hives and orchids—Colombia's national flower—served as inspiration for the project. The new enclosure covers an open plaza area and is constructed in the form of 10 huge steel "flowers," each made up of multiple hexagons. From the sky, the

structure appears as a giant honeycomb in the middle of the jungle.

The enclosure is 59,000 sq. ft (5,900 sq. ft per flower), making it suitable for large outdoor events, and the flower structures are modular, allowing for future expansion. Each flower is 50 ft tall and weighs 62,000 lb.

The flower structures were fabricated with round HSS of diameters between 2 in. and 12¾ in. in ASTM A500 Grade C steel. Each flower was composed of more than 700 steel elements of various sections, diameters, lengths, and directions, creating a very intricate detailing process in terms of the welded connections.

The roof of the enclosure was made from standing seam tile, galvanized and pre-painted, and modified polycarbonate. On the inside, each flower was covered with immunized cypress wood slats with large





**Above:** From the air, the steel canopy appears as a giant honeycomb.

**Left:** Constructed of round HSS of varying sizes, the steel flowers consist of more than 700 members each.



CUSTOM BUILT

TO THE HIGHEST STANDARDS.
YOURS.



**SuperStruct** tubular sections hold up to the strictest design standards without holding them back.

- Manufactured in a variety of shapes and sizes to your specifications
- Large sizes from 12" up to 48" squares and rectangles
- Lengths up to 55'
- Wall thickness 5/16" to 1"
- Excellent column strength and torsional properties
- Aesthetically appealing



800-825-6668 • www.valmont.com • Valley, Nebraska

Contact Jeff Simons at Valmont Tubing toll-free at **1-800-825-6668** ext. 3811 or **ijs4@valmont.com** to learn more on the design possibilities of HSS SuperStruct.

gaps between the slats, allowing visitors to view the steel structure. Due to Medellín's humid, tropical climate, the coating used for the structure was an epoxy base with finished epoxy paint.

The project's most significant challenge was that of time; it was necessary to complete the project within five months. And of course, construction took place during the most brutal rainy season of the last several years. The schedule was impossible to modify, as the structure had to be completed in time for the Feria de las Flores (Flower Festival), where the Botanical Gardens play an significant role.

#### **Already a Winner**

In April, the Botanical Gardens project was awarded the Colombian design prize Lápiz de Acero (Steel Pencil) for the best project of the year in terms of quality, aesthetics, and harmony with its surroundings, as well as for its practicality, environmental friendliness, and functionality.

With the Botanical Gardens and other projects over the past few years, Medellín has gone a long way in changing its late 20<sup>th</sup> century image and aims to present itself to the world as a city full of dynamic, architecturally significant—and steel-framed—buildings.

Mauricio Gutiérrez Villa is a mechanical engineer with ESTACO S.A. in Medellín, Colombia.

#### Owner

City of Medellín

#### Architect

Plan B and JPRCR

**General Contractor/Structural Engineer/Fabricator/Erector**ESTACO S.A.

#### **Software**

AutoCAD, STAAD.Pro


#### **Photography**

Dario Eusse Tobon

Steel Fabricators, Bridge Fabricators and Contractors can now...

Buy Direct from a Manufacturer, packed and labeled per your specifications!

Complete Project Support from Start to Finish





# NOW MANUFACTURING ALL ROD PRODUCTS



## Tie Rod Assemblies



- **Anchor Bolts**
- Sag Rods
- **Swedge Bolts** 
  - Threaded Rod
- Plate Washers
- Tie-Rod Assemblies

Manufacturing to **ASTM Standards:** 

A449, F1554

(Grades 36, 55,

105), A354, A307,

A193 B7, as well as Stainless Steel.

Hot Dip

Galvanizing



Full Assembly & Product Marking is available on every order!

#### **OWNER**

- Direct from manufacturer service
- Experienced knowledgeable staff
- Total project support
- Virtually no dependence on others
- 100% MELTED & MFG USA STEEL

#### **PURCHASING AGENT**

- Fast accurate quotes
- Orders confirmed in timely manner
- One stop for ALL structural bolts
- Kegs labeled with PO# &/or Job# for easy receiving

#### **ERECTOR OR JOB-SITE**

- Custom keg labeling & packing
- Testing done prior to shipment
- Ship by sequence for large projects
- Delivery anywhere in the USA & Overseas
- Overnight expediting service to anywhere in the USA
- Tone Wrench sales, service & support





Heavy Hex Bolts (A325, A490)

TC (Tension Control) Bolts (F1852 & F2280)

**Low Carbon Bolts (A307)** 



**MADE WITH PRIDE** 

St. Louis Screw & Bolt

2000 Access Blvd •

Phone: 800-237-7059

Fax: 314-389-7510



**Electric Tone Wrenches** 

Sales, Service, Repair Hex & TC (Tension Control)

Email: sales@stlouisscrewbolt.com

Web: www.stlouisscrewbolt.com



# ONE MAN'S TRASH IS ANOTHER MAN'S CORPORATE HEADQUARTERS.

When Boldt Construction decided to build

an environmentally friendly corporate headquarters, it's only natural they asked for help from Vulcraft. As a part of Nucor, the world's largest recycler, our joists and decking are made from recycled steel. So we not only provided the support Boldt's Southern Headquarters needed, we helped Boldt apply for Oklahoma's first ever LEED certification. Although, the real reward was helping to prove that supporting big business and the environment are not so different after all.

www.vulcraft.com



# **Building in Beijin**

BY MARK SARKISIAN, P.E., S.E., NEVILLE MATHIAS, P.E., S.E., AND AARON MAZEIKA, P.E.

#### Steel provides the support for two new high-profile atriums in China's capital.

IT'S NO SECRET THAT CHINA'S ECONOMY HAS BEEN ON THE RISE IN RECENT YEARS, AND PROMINENT STRUCTURES HAVE BEEN GOING UP AT A RAPID PACE. And as expected, this construction surge has provided some unique structural design opportunities, especially in the country's larger cities. Two recently completed projects in Beijing, both designed by Skidmore, Owings & Merrill LLP, illustrate this phenomenon. The first, the New Beijing Poly Plaza, is a composite office tower incorporating the world's largest steel cable net-supported glass façade. The second is Beijing Finance Street, a mixed-use development consisting of 700,000 m<sup>2</sup> (7.5 million sq. ft) of framed office, retail, and residential space. The centerpiece of this development is a retail mall enclosed by a 300-m (980 ft) skylight supported by architecturally exposed steel trusses.

#### **New Beijing Poly Plaza**

Taking a look at the New Beijing Poly Plaza, the project is prominently located at a major intersection along Beijing's second ring road, northeast of the Forbidden City. The site's primary orientation is northeast towards the intersection and beyond to the client's existing headquarters building. The triangular form minimizes the perimeter surface area exposed to the elements, while a series of atria provide additional interior surface area to give office areas maximum access to daylight. The result is a simple "L" shaped office plan that cradles a large atrium. The exterior walls

of the atrium are comprised of minimal glass membranes supported on two-way cable nets in order to maximize visual and solar transparency. In order to accelerate the construction schedule—and to accommodate the complex geometry of the building form—SOM selected a composite structural system employing both reinforced concrete and structural steel. The base building structural system consists of three reinforced concrete cores acting compositely with structural steel moment resisting frames. Floor framing consists of structural steel trusses at 13.5-m (44.2 ft) spans and rolled sections at 9-m (30 ft) spans. Moment resisting frame beams and columns used ASTM A913 grade 65 steel imported from Europe, while locally produced steel was used in gravity framing.



While conceptually simple, cable-net systems may still be considered an exotic solution for the structural support of glass curtain walls. However, the completion of several major walls around the world has established a proven track record of an achievable scale and level of transparency. Planar two-way cable systems support and stabilize glass façades through the resistance to deformation of the two-way prestressed net. Gravitational loads from the glass elements are carried through the attachment nodes to the vertical cables, and up to a transfer structure in the base building above. Lateral deformations due to wind and seismic loadings are resisted by the tendency of each of the horizontal and vertical cables to return to its straight line configuration between supports, while being subject to a perpendicular force. The flexible nature of a planar cable-net under lateral loading means



that the critical design goal is limiting deflection through adjusting axial stiffness of the cables, as well as the cable pre-stress. Deflection limits of L/40 to L/50 are generally set for the design loading condition (typically, a 50-year wind event) to protect the integrity of the glass and sealants and to minimize a perception of weakness by the building's occupants.

For more on cable-net walls, please see "Getting Started with Cable-net Walls" from the April 2007 issue (available in the Archives section at www.modernsteel.com).

#### The Challenge

The New Beijing Poly Plaza project is 110 m (360 ft) tall with a 90-m-tall (300 ft) atrium enclosed by a cable-net glass wall, 90 m high by 60 m wide (300 ft by 200 ft). The scale of this wall greatly exceeds those that have been built before, introducing specific challenges that are not critical in smaller walls. SOM's preliminary analysis showed that the cable-net spans were too large to be economically achieved using a simple two-way cable-net design. We determined, however, that the cable-net could be achieved by subdividing the large cable-net area into three smaller zones by folding the cable-net into a faceted surface, and introducing a relatively stiff element along the fold lines. The faceted cable-net solution allows the individual sections of the cable-net to span to a virtual boundary condition at the fold line, effectively shortening the spans. Rather than introduce a beam or truss element to stiffen the fold line, a large-diameter cable under significant pre-stress was used. The largest of these primary cables is 275 mm (11 in.) in diameter and consists of a parallel-strand cable bundle of 199 individual 1x7 strands (a strand consisting of six wires twisting around a single straight wire), each strand being 15.2 mm (0.60 in.) in diameter. The largest cable is pre-stressed to 17,000 kN (3,800 kips) and experiences a maximum in service loading of 18,300 kN (4100 kips) during a 100-year wind event. Using the faceted design solution, the typical horizontal and vertical cables are limited in diameter to 34 mm and 26 mm (1.3 in. and 1.0 in.) respectively. The composite base building structure proved well-suited to the cable-net installation, as two of the three reinforced concrete cores were located at the sides of the cable-net to act as stiff boundary conditions resisting the cable pretension forces, and also providing an ideal location to access the cable anchorage points and to facilitate tension-



ing operations. The remaining boundary conditions were provided at the bottom of the net by the concrete structure at ground level, and at the top by a three-story-tall structural steel truss spanning 60 m (200 ft) between the top of the two cores.

#### "Rocker Mechanisms"

By introducing the large-diameter diagonal cables, one problem is created while another is solved. As the base building structure is subject to seismic and wind loads and experiences inter-story drifts, connecting a point on one floor slab to another point 45 m (150 ft) higher up the structure with an axially stiff element, the diagonal cable behaves as a brace and tries to resist the base building drift. Thus analyzed, the brace forces were too great to be resisted by the main cables or the attachments to the base building structure. However, when the base building drifts in a direction that causes one diagonal cable to go into tension (tries to lengthen), the other cable that forms part of the "V" con-

figuration goes in compression (tries to shorten). A pulley analogy was developed that allowed the "V" cables to be considered as a single element, with rotation at the base of the V allowing the length increase of one cable to be offset against the length decrease of the other cable. This allows the base building to drift without significantly increasing or decreasing the level of prestress in the main cables. The pulley analogy was realized in a buildable form as a cast "Rocker Mechanism." By crossing the cables and connecting to the rocker casting arms, the need to provide

curved pulley surfaces and curved sections of the main cable were eliminated. Each of the two rocker mechanisms consisted of six unique steel castings, each weighing up to 8 tonnes (18,000 lb), with solid material thicknesses of up to 800 mm (32 in.).

#### Construction

The installation of the cable-net wall required that the base building structure be topped out before any cable installation operations could occur. The base structure was constructed with the structural steel floor framing following several stories behind the concrete cores. Once the boundary elements were in place, the installation of the rocker mechanisms began. Each of the castings were hoisted into place, then connected together to form the mechanism. With the rocker mechanisms temporarily shored in place, the main V cables were installed and tensioned. Using technologies developed for the installation of cable-stayed bridge cables, each of the 199 strands were tensioned in a carefully planned sequence to result in an even distribution of force in the final condition. With the V cables installed and tensioned, the smaller cablenet cables were then loosely located in place and incrementally tensioned up to the design pretension level, then the glass support nodes were tightened and the glass was installed and sealed.


#### **Performance**

The critical service level load condition (the 50-year wind event) was determined through careful wind engineering studies performed by Beijing University. The wind studies included a traditional rigid model of the building massing, as well as that of the surrounding building fabric, and an aero-elastic wind tunnel study performed on a flexible model of the actual cable-net configuration. This latter study used wires and a membrane to replicate the anticipated dynamic response of the cable-net system. This study, likely the first of its kind to be performed on a cablenet curtain wall system, was used to verify and modify, where appropriate, the results of the rigid model. Analysis and testing shows that the New Beijing Poly cable-net wall behaves very much as conceived. The results from the static non-linear (large displacement) analysis clearly show that the strategy of subdividing the wall into facets with shorter individual spans was indeed successful. This strategy allows the overall displacements to meet the L/45 deflection limit between hard boundary conditions established for the project, while maintaining the economic viability of the project.

#### **Architect and Structural Engineer** Skidmore, Owings & Merrill LLP, San

#### Local Design Institute

Beijing Special Engineering Design & Research Institute, Beijing, China



#### **Beijing Finance Street - F9 Retail Project**



The buildings in this carefully planned development are decidedly modern, reflecting Beijing's strong position in international commerce. Beijing Finance Street's many architectural and landscape elements are all clustered around a park, which is the project's core. Opening onto the park is the Great Urban Atrium. This crescent-shaped building—the most engaging component of the project, with a sharply slanting roof and exposed diagonal trusses—provides a vibrant indoor urban space and, being adjacent to the park, enhances the complex's role as a gathering place.


#### "Butterfly Trusses"

The roof of the cavernous 300-m-long (980 ft) atrium retail space is intended to establish a theme of transparency that is present throughout the development. Exposed structural steel "butterfly trusses" are key components. Each is formed by tipping two planar single-kingpost trusses towards each other, resulting in a three-dimensional "V" kingpost butterfly truss. Spanning up to 30 m (100 ft), the single-kingpost trusses provide a long-span solution using a minimum number of structural elements. As the top chord of each truss is effectively pointsupported at its ends and at one point within the span (at the 3/3 point along the length of the truss when viewed in plan), bending forces on the top chord are significant. Large-diameter steel circular hollow sections, specified per American Petroleum

Institute standards for pipe sections, were used to resist the combined axial and bending forces resulting from this truss configuration. The lack of bracing elements between the top and bottom chord, as well as the visual weight of the 457-mm-diameter (18 in.) pipe truss top chords relative to the 25-mm- to 37-mm-diameter (1 in. to 1.5 in.) cable bottom chords, results in the appearance of slender parallel beam elements spanning the atrium.

The reinforced concrete retail buildings that support the retail roof are subdivided into independent structures with a maximum dimension of 90 m (300 ft). The structures were also subdivided by the natural building break that occurs at the atrium. As a result the roof needs to span between six independent structures. A typical solution to this type of relative movement issue is to provide sliding supports at one end of each of the trusses. However, due to the slope of the roof trusses, the high end of the trusses are supported atop freestanding columns that extend up to 11 m (36 ft) above the roof of the supporting concrete structure. This condition reduces the applicability of a sliding detail.

Ultimately, the high-end columns were also the source of the design solution to the "dynamic" support issue. By providing articulated ball-and-socket joints at the top and bottom of the high-end columns, the columns and trusses become components in a three-pinned arch roof system. Relative move-




ment between the supporting structures is accommodated by the articulation of the joints. When the supporting buildings move closer together and further apart along the axis of the roof trusses, the enclosed angle at the apex of the roof closes and opens. The glazing system is jointed to allow this rotation without damage. When the relative movement between supports is perpendicular to the axis of the truss, the top of the high-end columns effectively moves with the low-end support point due to the diaphragm bracing in the plane of the sloped skylight. The bottom of the high-end columns conversely moves with the high-end support point. This causes the south wall of the roof system to rack in-plane.

The glazing for the south wall is supported in horizontal courses that are allowed to slide relative to each other as the columns rack. Due in part to the dynamic nature of the support conditions, the kingpost truss arrangement was developed to result in the three-dimensional truss configuration that has additional out-of-plane stiffness. Lateral forces induced in each of the roof sections are transferred to one of the supporting structures (through the low-end columns) by the use of diaphragm bracing rods.

# FloorVibe v2.0 It's like having an in-house floor vibration expert!

FloorVibe v2.0 helps solve problems with floor vibrations due to human activity in offices, residences, health clubs, convention centers, and buildings housing sensitive scientific equipment.



Just some of the benefits include:

- FloorVibe v2.0 gives you the expert advice you need such as what live loads to use, how to estimate damping, and much more.
- ✓ Has databases for hot-rolled sections and castellated SmartBeams.
- ✓ Handles all joist types including composite joists.
- ✓ Provides a complete design report for ease in checking.
- Automatically generates notes and warnings.
- ✓ Criteria based on the AISC/CISC Design Guide 11: Floor Vibrations Due to Human Activity.

For more information or to order, visit www.floorvibe.com, e-mail tmmurray@floorvibe.com, or call Structural Engineers, Inc. at 540-731-3330. FloorVibe v2.0 is only \$345 per copy and Design Guide 11 is \$30 per copy. Price includes technical support.

www.floorvibe.com

#### Construction

Originally designed to allow for the fabrication and tensioning of each of the butterfly trusses at ground level, the truss design could accommodate the lifting and installation of each three-dimensional truss without any requirement for shoring. However, after construction of the reinforced concrete supporting structures was completed, the contractor elected to install a scaffolding system filling the full volume of the retail atrium, allowing each of the truss top chords to be installed independently with continuous gravity support along its length. The truss elements were then connected together, and the steel cable bottom chords were installed and tensioned in-situ.

#### **Architect and Structural Engineer**

Skidmore, Owings & Merrill LLP, San Francisco

#### **Local Design Institute**

China Academy of Building Research, Beijing

Mark Sarkisian is a partner, Neville Mathias is associate director, and Aaron Mazeika is an associate with Skidmore, Owings & Merrill LLP in San Franciso.

# NASCC THE STEEL CONFERENCE

2008 Annual Stability Conference

# Nashville, Tennessee April 2-5, 2008

#### Who attends?

More than 3,000 structural engineers, steel fabricators, erectors, detailers, educators, and others involved in the design and construction of fabricated steel attend the conference each year. In addition to conference seminars, attendees have many networking opportunities, including the annual Fabricator Workshops, where fabricators can exchange ideas in a non-competitive envi-

#### What about the exhibit hall?

This year's exhibit hall features more than 400 booths with more than 160 exhibitors demonstrating the latest products. You'll find fabrication equipment, detailing software, connection products, safety equipment, engineering software, and coatings. Equipment manufacturers typically provide full demonstrations of their equipment—steel beams are cut, punched, and drilled right on the exhibit-hall floor! The exhibit hall is open April 2-4, 2008.

#### What will I learn?

Learn about topics ranging from composite steel joists to sharing digital models to designing to avoid floor vibration. Some sessions focus on technical engineering issues, while others focus on fabrication, erection, or detailing. Following up on our successful program offering "Top Hits from Top Profs," this year we're also offering "Essays from Experts." In this new series of lectures, we've asked some of the top professionals to present a topic they find interesting. Speakers include Larry Griffis on wind, Duane Miller on welding, Robert McNamara on damping, and Ron Hamburger on simplifying design. The conference also offers a pre-conference short course on BIM and a postconference short course on the design of low- and mid-rise buildings.

## For more information, visit www.aisc.org/nascc

sponsored by



#### NASCC: The Steel Conference is a premier

education event aimed at providing structural engineers, steel fabricators, erectors, and detailers with practical information and the latest design and construction techniques. More than 60 technical sessions offer a variety of educational opportunities:

Sharing Digital Models Between Steel and Cladding Contractors

Detailing in High Seismic Regions The Advanced Bill as a Deliverable

BIM for Low-Rise Steel Projects 3D Software and Complex Hip and

Valley Roof Systems

Getting Dimensions: Will 3D Modeling Help?

Got Stiffness?

Latest Developments in Steel Plate Shear Walls

Designing Deck Diaphragms for **Ductile Systems** 

Part One: An Introduction to Earthquake Engineering and Seismic Codes—Ductility

Part Two: An Introduction to Earthquake Engineering and Seismic Codes—Seismic Provisions

Part Three: An Introduction to Earthquake Engineering and Seismic Codes—Tips and Examples

AESS and the New Canadian Matrix: A Category Approach

Effects of Post-Tensioned Concrete Slabs on Composite Steel Beams

Engineering Ethics: You Be The Judge Steel Solutions for Low-Floor-to-Floor

Multi-Story Residential Housing Rules of Thumb for Steel Design Composite Steel Joists—Standards and

Code of Standard Practice Quality Assurance for Engineers

Around the Bend: How to Specify Curved Steel

AISC Certification: Considerations for Special and Not-So-Special Inspection

AISC Certification: Keeping It Simple and Effective

Solving the Recruitment, Retention, and Training Dilemma

Decreasing Your Insurance and

**Bonding Costs** Shop Scheduling

Fabricator Roundtable

New Technology for Fabrication

**Business Valuation for Fabricators** 

Greening the Shop: Strategies for Managing Your Environmental **Footprint** 

Constructability and Teamwork Procedures and Processes to Manage

The History and Status of HSS Stability Design in North America

Five Useful Stability Concepts

AISC Certification: New Directions and Continual Improvement

Immigration Issues in Hiring

Teamwork!

Marketing for Erectors: A Call for Professionalism

Simple—But No Simpler

Designing with Damping

Lessons Learned

Something About Wind

**Practical Erection Details** Risk Management for Detailers

Non-Destructive Examination and

Special Inspection

Deep Deck Floor Systems

Designing Low-Cost Steel Structures

The Steel Design Specification: A

Designer's Perspective

Effective IT Strategies to Improve Your Bottom Line

and much more!

# **Essential Elements**

BY KEN JONES



London's new O<sub>2</sub> Arena uses a steel roof, erected with an innovative lifting operation, to top what was designed to be Europe's most acoustically advanced concert venue.

#### THERE'S BEAUTIFUL MUSIC COM-ING FROM GREENWICH, LONDON.

More specifically, it's coming from the new O<sub>2</sub> Arena. Built within London's existing Millennium Dome structure, the recently opened arena provides London with a 22,000-seat state-of-the-art entertainment venue. Designed to be the most technically and acoustically advanced concert arena in Europe, it also plays host to multiple sporting events.

#### **Geometry and Design**

The spherical surface of  $O_2$  Arena's roof has a radius of 1,145 ft and is exactly parallel to the surface of the dome canopy above. (The project's structural engineer, Buro Happold, also designed the original award-winning cable-net structure of the Millennium Dome itself, now called The  $O_2$ .) The structure comprises intersecting

planar trusses of depths varying between 13 ft and 36 ft. The radial trusses cantilever by up to 72 ft beyond perimeter trusses that form a ring inside the roof support bearings and cores. The slender roof edge is dressed with a smooth "bullnose" cladding detail that undulates and seemingly floats in space over the upper concourse.


Buro Happold created a three-dimensional structural model of the project using Microstation, and Structural design analysis was carried out using STAAD.Pro. The ductwork and catwalk systems were fully integrated and coordinated into the design from the outset. The fabricator, Watsons Steel, then progressed with the steelwork production drawings using the 3D model as a starting point. During the initial stages of connection design, Watsons seconded an engineer to work in the Buro Happold offices, which aided the full understanding

of the critical joint issues from the project's early stages.

#### **The Roof**

Constructing a building within a building created many challenges. For starters, the seating bowl design limited the space available for the new roof construction beneath the existing dome canopy; a minimum 16.5 ft of clearance between the new arena roof and the existing structure was required for building environment and smoke management considerations. The use of standard cranes was clearly not an option because of the proximity of the existing dome structure.

The whole roof was built at ground level, including all catwalks, services containment, ductwork, gondola winch platform, perimeter bullnose, gutters, fall-arrest systems, and acoustic cladding. It was built on



a series of temporary trestles and then lifted by the strand-jacking method in a virtually completed condition. Working at this low vertical level maximized access and speed of construction and also improved safety.

Roof support was accomplished using only eight bearing points; the roof "floats" above the upper seating bowl and upper circulation concourse. It was lifted by strand jacks acting on the eight permanent support bearing points. The contractor chose to lift the roof in one piece, although the original concept allowed for raising it in several discrete, independently stable pieces, thereby enabling the progressive construction of the building frame below.

Each of the concrete cores at the eight points was designed so that the roof "slotted" into a gap in the core, allowing the roof to be lifted from directly above the bearing point. In two of the cores, several sections of floor slab were eliminated so that the roof steel could move vertically up past the floor edges. These were added at a later date. At four of the cores, quadruped support frames fitted into a free gap. They were hung from the end of the primary truss nodes as a means of lifting them to the top of the cores. Once the roof was positioned at the correct level, the quadrupeds were rotated and dropped onto the top of the core to support the roof.

#### **The Lift Operation**

Temporary steel lifting frames, with strand-climbing jacks, were positioned at the head of each core and used to lift the roof. All the jacks were controlled from a central computer, enabling them to be operated individually or simultaneously. Due to a lack of space above the temporary lifting frames, climbing jacks, rather than top-mounted jacks, were used.

Buro Happold worked closely with Watsons Steel and specialist lifter PSC Fagioli on the design of the lifting frames, the lift sequences, monitoring, and method statements. Some of the concrete cores were slender, with tall temporary steel frames mounted on them. Detailed non-linear buckling analysis of the combined roof, lifting frame, and core assemblies was carried out, together with independent checks on the design of the frames themselves, using the analysis results. Developments to the design of the lifting frames were made to ensure a rigorously checked and safe overall build sequence.

Lifting the roof safely required tight dimensional control and monitoring during the operation. The strands needed to remain within only 1 in. of vertical in order to avoid excessive lateral loads to the lifting frames, especially as the strands shortened at the top of the lift. In addition, the roof needed to remain almost perfectly horizontal, within a band of 1.2 in., so that the trusses and connections were not overstressed by a temporary condition in the process.

The lift operation was split into two stages—an 36-ft lift and a 52-ft lift—giving a total roof elevation of 88 ft. Each stage took three night shifts to complete, allowing other construction work to continue throughout the day. Particular care was taken on "lift-off" when the temporary frames rapidly picked up their full load and the roof swung free. During this step, a swing of only 0.40 in. to the north was experienced, which was testament to the accuracy of the construction, positioning,

and robustness of the temporary lifting frames. In the three weeks between the two lift operations, the strand jacks were locked off and packs inserted as a precaution to control any tendency toward lateral movement. The roof hung on its strands while work continued to complete the final cladding envelope work, such as movement joint in-fill sections.

The lift progress was hampered by the need to constantly correct for level after every few jack strokes, in order to remain within the required tolerances. Problems with survey monitoring points and survey equipment were encountered periodically, but were overcome. Maintaining a balanced force within a pair of jacks at a single suspension point caused consternation at times. To combat this, movements were surveyed, plotted, and monitored for all core lift points (using survey targets mounted near the top and bottom position of the strands), as well as for some of

#### By the Numbers

Arena roof steel: 2,800 tons

Main span: 421 ft

Approx. roof area: 186,000 sq. ft

Seating capacity: 22,000

Primary truss depth: 36 ft (max.)

Primary truss chord: 30-in.-diameter by 2.2-in.-thick tubes

Building height: 154 ft

Roof lift weight: 4,400 tons

the slender concrete cores. An automated surveying system was used so that measurements could be taken regularly, allowing the lift to proceed as quickly as possible.

Building the temporary lifting frames was a feat in and of itself, involving smaller jacking processes to push the 12-ton lift beams to within 5 ft of the underside of the existing cable net.

#### **Design Features**

As predicted and expected, large vertical structural deflections occurred at the time of lift-off from the ground level trestles. This formed an important and unique challenge for the structural design, one that is not often encountered in this way. To accommodate this movement, an extensive network of joints in the steelwork and cladding was incorporated. Steelwork joint movements were monitored before, dur-



**Above:** The roof structure was built at ground level on a series of temporary trestles.

**Below:** The roof structure in its final postion.





Each of the concrete cores at the eight points was designed so that the roof "slotted" into a gap in the core, allowing the roof to be lifted from directly above the bearing point.

#### **AutoSD STEEL DETAILING**

Detailing the Future using AutoCAD® 14 - 2008, AutoCAD LT 2000 - 2007 and IntelliCAD®. For detailing structural and miscellaneous steel, roof frames, embeds, beams, columns, bracing, stairs, stair rails, wall rails, ramp rails, ladders, hip and valley, creating erection drawings and general editing using AISC or CISC shapes.

Beam to Beam, Beam to Column and Vertical brace to Column connection matching. Extract CNC data to DSTV files. Extract BOM for import into Fabtrol and E.J.E. material manager.

Five packages to choose from. Select the ones right for you.

Visit Our Website at www.autosd.com For more information or To download Free demo.



- \* No Maintenance Fees
- \* Free Technical Support
- \* Money Back Guarantee
- \* Free Demo Disk

#### AutoSD, Inc.

8203 Lizelia Rd Meridian, MS 39305 601-679-5800 E-mail: ray@autosd.com ing, and after the initial lift, and this work showed the structure to have behaved as planned, with joints opening or closing by the predicted amount.

The catwalks and network of rigging beams at the level of the truss bottom chords are configured to support the complex sports lighting requirements and concert rigging demands. A maximum rigging load of 110 tons plus 22 tons of center-hung scoreboard can be suspended in the roof. In addition, the roof is "future-proofed" for possible external conditions, such as wind and snow, in the event that the dome canopy is removed.

The scoreboard can be fully retracted into the roof volume using the winch platform at the center of the roof to make way for in-the-round event configurations. Buro Happold continues to work with and advise the client on specific concert rigging requirements.

#### **Roof Cladding**

The cladding is tuned for optimum acoustic performance for break-out, break-in, and reverberation time. It is designed to be the most acoustically advanced venue in Europe. The cladding is also used as a "stressed skin"

structure, in order to economize on the steel weight in the purlin members.

Cladding build-up options were tested against prescribed acoustic performance requirements, and the resulting deck weighs a hefty 14 psf, including an 8-in.-deep steel profile decking with acoustic absorption panels fixed to the soffit of each trough.

A large (approximately 52 ft by 46 ft) cladding and purlin trial panel was built, which proved to be extremely useful for many reasons:

- ✓ To check buildability of warped cladding fixed to spherical-faceted purlins
- As a physical fit-up test for complex purlin-to-truss steelwork bracket connections (also a function of spherical geometry)
- ✓ As an aid to test options for the cladding movement joints and edge support trim
- ✓ To develop and hone a safe method of cladding installation
- To force coordination and collaboration between all parties in advance of the main fast-track build (cladding contractor, steelwork contractor, main contractor, cladding designer, acoustics engineer, structural engineer, and procurement parties)



The end result is the  $O_2$  Arena, Europe's most acoustically advanced concert venue.

✓ To "de-risk" the construction process (faster, safer, etc.)

The panel, although large, is certain to have paid for itself many times over in terms of improved overall project performance and product quality.

### **Tight Space, Tight Schedule**

All told, the O<sub>2</sub> Arena is a stunning venue with a special and unique design. The construction and lifting of the roof by controlled strand jacking of the whole 4,400-ton assembly was skillfully and safely achieved to a tight schedule, despite the challenges of construction within an existing building.

Ken Jones is Structures Group Director with Buro Happold's Bath, UK, office.

### Owner

Anschutz Entertainment Group, London

#### **Architect**

HOK Sport, London

### **Structural Engineer**

Buro Happold, Bath, UK

#### Contractor

Sir Robert McAlpine, London







## TERMINATOR

DUAL COLUMN
MITER SERIES BAND SAWS

TERMINATOR





- ✓ Huge sawing capacity
- ✓ Two models 30" and 42"
- ✓ Fast and accurate cuts every time

### **Unbeatable Features:**

- ✓ Dual column design for exceptional accuracy
- Miters both directions
- ✓ Large 10HP motor drives 2" band saw blade
- ✓ Long blade life
- ✓ Simple to operate
- ✓ Positive clamping
- ✓ Digital feedback
- **✓** Built by Hyd-Mech

### Call for a FREE Video & Brochure





### **Pushing the Envelope**

BY JAMES C. PARKER, P.E., ALEC S. ZIMMER, P.E., AND CHRISTOPHER M. HEWITT

### Careful attention to façade attachment details pays off in the long run.

ONE OF THE MOST CHALLENGING DETAILS FACING STRUCTURAL DESIGNERS IS THE SUPPORT OF A BUILD-ING FAÇADE. The complexity of this attachment is not to be overlooked, and the entire design team should be engaged in developing a strategy for supporting the façade system in order to prevent unplanned changes and problems in the field. The structural designer should then strive to develop slab edge and spandrel beam designs that are consistent with this strategy.

### **Building Envelope Systems**

Before devising a support strategy, it is important to understand the function of the façade system. There are three basic concepts for exterior walls to mitigate water infiltration: reservoir walls, barrier walls, and cavity wall systems. While each system is designed to keep water out of a building, each approaches the problem differently. Understanding the type of system that the structural frame is supporting is important for determining appropriate goals for the structural support.

Older masonry bearing wall buildings employ the reservoir system. In traditional thick stone and brick bearing wall buildings, the walls act as reservoirs and allow a certain amount of water infiltration into the wall. The walls are thick enough to prevent an unacceptable amount of water from entering the interior space, and the water later escapes by weeping and evaporation. Though good in its day, this system is heavy and is no longer considered to be cost-effective.

Most modern commercial walls are constructed as either barrier or cavity systems. Barrier wall systems are just that—barriers designed to keep water out of the wall and to rely on the exterior surface and joint seals to prevent (or mitigate) water infiltration into the building.

Alternatively, cavity walls have a drainage plane and waterproofing barrier behind the exterior cladding and a means to divert water

Reservoir Barrier Cavity

Exterior wall systems for mitigating water infiltration.


out of the wall. Water that makes it past the cladding runs down the drainage plane and out of the wall through weep holes at the base or at flashing joints. AISC's Design Guide 22 and its seminar on façade attachments to steel frames give attachment strategies to accommodate the challenges of each of these wall systems.

### **Design of Slab Edge Conditions**


In designing slab edge conditions, there are two fundamental approaches: Either the slab cantilevers over the spandrel beam to carry any loads applied to the overhang, or the designer does not count on the slab as a cantilever, and loads applied to the overhang are carried by a structural steel plate or assembly attached to the spandrel beam. Generally, using the slab to carry the loads as a cantilever will be more economical than relying on the spandrel beam alone, but the slab must have sufficient strength to carry the load without increasing the thickness of the floor slab system. Otherwise, a bent plate or other steel assembly must be designed to transfer façade loads to the spandrel beam. Several examples of these appropriate details are included in the design guide and seminar.

### Pour Stops and Bent Plate Edge Details


The use of a light-gage metal pour stop as part of the façade support system is generally limited to slabs that have a clear overhang less than 12 in. and slabs that have sufficient strength to sup-



Typical forces at slab edge conditions.



Design loads on light-gage metal pour stops or bent plates.



port superimposed loads. Typically, in this type of slab edge, the façade attachment will be made directly into the slab or spandrel beam and will not engage the pour stop. Accommodating such an approach may become difficult at corners and column joints. When used, the light-gage metal pour stop should be designed for the wet weight of concrete, concrete fluid pressure on the vertical leg, and 20 psf of live load. When these conditions are such that a light-gage element can not accommodate the loads, the designer must employ the use of a bent plate at the slab edge. The bent plate may be designed to be a pour

As Strong as the Steel We Inspect. The Robert W. Hunt Company, and its parent Bureau Veritas, have over 300 years of combined experience providing structural steel inspection services. From the most high-profile projects to simple source inspections, The Robert W. Hunt Company is the partner of choice for clients worldwide. Inspection and Consulting services for: • Construction • Fabrication • Repair • Forensics • Erection Bridge Inspectors of choice for Departments of Transportation nationwide Robert W. Hunt Company A Bureau Veritas Company 1.888.CWI.WELD (1.888.294.9353) www.us.bureauveritas.com weldingexpert@us.bureauveritas.com stop, a means to attach the façade, and a means to transfer the façade loads to the primary structure.

### **Design of Spandrel Beams**

As one might suspect, spandrels must have sufficient strength and stiffness to resist the applied loads, but must also be designed to accommodate architectural and practical limitations of the system. For strength, the spandrel design must consider:

- → superimposed floor loads
- → loads arising from weak-axis bending
- → torsion on the member and its connections
- → offsets between the centerline spandrel and of the column
- → eccentric façade loads

For serviceability, the spandrel design must consider:

- → deflection due to superimposed dead loads and live loads
- → rotation of spandrel beams and façade supports
- → long-term creep of composite sections
- → relative displacements of the structural frame with respect to the façade
- → tolerances of the façade and structural frame

And, for practical reasons, the spandrel design must consider:

- → overall depth and flange width
- → the interferences with the slab edge and the connections
- → interferences with window heads
- → interferences with mechanical systems such as ducts and piping
- → interferences with shade pockets or other architectural features
- → flange interferences with the façade system
- → clearances for fireproofing and façade elements
- → constructability of the spandrel


Because composite spandrel beam sizes are often controlled by post-composite deflections, cambering composite spandrel beams does not tend to reduce the beam weights for most façade systems. Cambering adds to the tolerances that the design of the façade system must accommodate, and it should typically be avoided for spandrel beams.

#### Wind and Seismic Loads


For the base building components, the structural engineer of record can often use a simple and conservative design when planning for façade wind and seismic loads without adding undue cost. Negative wind pressures on the wall, combined with gravity load eccentricities, will often control the design of the façade attachment, particularly those attachments made to the bottom flange of the spandrel beam as shown in the below figure. The IBC requires components and cladding to be designed for seismic forces and the attachments to accommodate relative seismic displacements, which can be large. These requirements should not be overlooked and can control wind loading for heavy wall systems.

#### **Kickers and Roll Beams**

When façade loads are eccentric to the supporting spandrel beams, significant eccentricity exists on a cantilevered slab. There are a number of strategies that the designer can use to help to resist the torsional moments imposed on the spandrel beam. Commonly, either a roll beam or a kicker is provided to restrain the beam against rotation. Each system has advantages and disadvantages. In addition to their role as a torsional brace, kickers can also be used as an effective solution for resisting façade forces applied between floor levels; however, they require coordination with the architectural and mechanical systems, which can limit their use. Roll beams ensure a rectangular grid of girders and beams, but designers must be sure to design their connections to the spandrel beams to have some level of moment resistance. Both approaches, however, are effective ways to restrain torsion on spandrel beams and thereby reduce spandrel beam rotations.




Façade attachments must be designed to resist lateral and gravity loads.





Roll Beam



Façade systems and related details must account for fabrication and erection tolerances.

### **Accommodating Tolerances and Adjustments**

Every façade attachment design must allow for adjustment to accommodate tolerances and deflections. Steel framing tolerances are generally larger than façade tolerances, and the designer must be careful to provide sufficient adjustability in the design to accommodate these tolerances, which may accumulate. A good attachment detail will provide the means to:

- → adjust the slab edge in or out relative to the spandrel beam,
- → adjust the location of the façade system in or out relative to the slab edge,
- → adjust the location of the façade system up or down relative to the slab edge,
- → and adjust the location of the attachments both vertically and horizontally.

Designers must also provide sufficient clearances between the steel frame and the façade that accommodate tolerances, relative movements and rotations, thermal insulation, fireproofing, and access to install the façade component.

#### **Forces from Restraint**

The façade system must be designed to accommodate relative movement between stories, and when that movement is restrained the restraining element is highly loaded. When possible, it is best to avoid restraint altogether. When it can not be avoided, restraint forces can be difficult to predict because of cracking, creep, and attachment stiffness. It is also important to be cautious of the potential for inadvertent restraint caused by friction, movement, or other sources, which can have dire consequences when not accounted for.

### **Conclusions**

Designing façade systems can be a challenging effort. The process should be approached with an earnest understanding of its complexity, and by initiating a dialogue among the structural engineer, architect, façade system designer, and contractor to arrive at the most practical and economical solution for a project. With open communication and the appropriate degree of care, most façade attachment problems can be avoided from the start, making the project successful for the entire construction team.

James Parker is a senior principal and Alec Zimmer is a senior staff engineer at Simpson Gumpertz & Heger, Inc. Chris Hewitt is a senior engineer wtih AISC.



Sharon Stairs Sharon Stairs Sharon Stairs



Please visit us at www.sharonstair.com to download all Details & Specifications



1481 Exeter Road Akron, Ohio 44306

> 1-800-792-0129 sales@sharonstair.com



Sharon Stairs Sharon Stairs Sharon Stairs



This SteelWise qualifies for 1 PDH (0.1 CEU) through AISC's "Extra Credit" program. To purchase your extra credit, log on to www.aisc.org/ extracredit and take the online quiz. Need more CEU credits? Register for the AISC seminar "Façade Attachments to Steel Frames," coming to a city near you! Visit www.aisc.org/seminars for details.



- Plasma
- Drilling
- Oxy-Fuel
- Piece Marking

www.peerlessusa.com

quales

### Listening to the Customer

BY SHEILA ALEGRIA, KIM SWISS, AND BOBBI MARSTELLAR, P.E.

### Feedback from AISC Certified companies is making a difference in daily operations for AISC's independent auditing company.

IN OCTOBER 2006, QUALITY MANAGEMENT COMPANY (QMC) DID SOMETHING THAT MANY COMPANIES ARE TOO AFRAID TO DO: We started asking our customers (fabricators and erectors) for feedback. Early in 2006, our team set a goal to improve the level of service we provide to our program participants. Since customer satisfaction is often described as the gap between what the customer expects and what they get, we knew we first had to make understanding their expectations a priority.

Program participants are mailed a survey annually with their certificate. The survey is designed to measure customer satisfaction related to the audit, the on-site auditor, and the QMC staff. In the first year of the program, QMC received more than 400 completed surveys (a response rate of more than 50%!) containing extremely substantive and thoughtful comments. From them, we have gained valuable insight into how our customers think, and more importantly, what they expect of us.

The surveys have become an integral part of our continuous improvement process. As an ISO 9001:2000 certified company, QMC is required to monitor and measure the performance of our quality management system. One of those measurements per-

tains to customer satisfaction. How do we know that we are meeting our customer's requirements and expectations? We review each and every survey comment—more than 600 through the end of September 2007. Then we look for trends and determine which ones are actionable. (For a more detailed look at our survey process, see the figure at right.)


### **Areas for Improvement**

The majority of concerns we've received to date have to do with communication, auditor issues, or audit scheduling. (For a complete breakdown of the topics, see the pie chart on the next page.) We can't deny the fact that our clients would like to hear from us more often. There are times in the certification process that participants have felt ignored or concerned that their materials were lost in cyberspace.

We have also received a lot of comments regarding the differences among auditors, in particular that an auditor observed or commented on something within a company's quality system that the previous year's auditor did not. We do our best to keep these variations to a minimum by providing individual and group training for our auditors. However, we consider the uniqueness of our auditors to be an asset. They have different strengths and areas of expertise and can provide our program participants with a fresh perspective each year.

Other comments relate to the pace of the audit, some indicating that it went too slow, while others felt rushed. With so much to cover in just one or two days, it can be difficult to get the pace just right while still making sure that the experience is a beneficial one. Our auditors can adjust their pace almost immediately, so be sure to speak up during the audit if you are concerned.

Material submission requirements made the list as well. Many of the program participants felt it was unnecessary to resubmit their quality documentation every year, and we couldn't agree more! Beginning in October 2007, participants are only asked to submit their materials every third year, when a full audit is scheduled. Material submission requirements are outlined in the renewal packets.




**Quality Corner** is a monthly feature that covers topics ranging from how to specify a certified company to how long it takes to become a certified company. If you are interested in browsing our electronic archive, please visit **www.aisc.org/QualityCorner**.

### WHITEFAB

**BIRMINGHAM, AL** 


PHONE: 205-791-2011 FAX: 205-791-0500 EMAIL: sales@whitefab.com WEBSITE: www.whitefab.com

### ROLLING AND BENDING SPECIALIST






FULL LINE CNC MACHINING



1,000 TON PRESS BRAKE 30'-0" BED (20'-0" BETWEEN HOUSINGS)
ALSO - 1/2" X 20'-0" SHEAR; PLATE ROLLS; CUT TO LENGTH LINE



Survey comments by category.

Audit scheduling received a significant amount of feedback, specifically how clients would prefer to pick their audit date. We agree that this would be ideal; however, attempts at this in the past have proven more costly and time consuming and still we had unhappy customers. We currently schedule the audits for the fabricator program four months ahead of time, which we hope can give ample time to prepare for the audit. (For more information on audit scheduling, please see the September 2007 Quality Corner at www.aisc.org/qualitycorner.)

### **Taking Action**

As it turns out, collecting the data is the easy part. It's taking action that presents the real challenge. We knew when we implemented the program that we couldn't ask for feedback unless we were prepared to act on it. We react to the comments we receive and trends we identify in the following ways:

- → Call or e-mail to the program participant to further discuss their comments.
- → Implement a new process.
- → Modify an existing process.
- → Incorporate feedback anonymously into auditor performance evaluations.
- → Include as an agenda item at auditor training.

Some concerns and ideas can be addressed or implemented immediately, while others take time. As a direct result of the survey responses, we've made the following changes over the past year:

- → When Corrective Action Requests (CARs) are closed, an e-mail is sent to the program participant.
- → When materials are received, a postcard is sent to the program participant.
- → Auditors are required to send their audit agendas and introduction letters to QMC.
- → Auditors are required to obtain confirmation from program participants that their audit agenda has been received.
- → Audit materials are no longer required for Annual audits (AR1/2), only Initial and Full audits.

- → A new, comprehensive list of documentation required for certification has been created. This list is mailed annually with the renewal packet and is also available in the Resources section of the OMC website at www.qmconline.com.
- → We revised our customer appreciation survey for surveys mailed after October 1, 2007.
- → QMC has increased the number of days that auditor training takes place to allow more time for "calibration."
- → An "Auditors Forum" now exists where auditors can post messages, ask questions, and share their thoughts with one another.
- → We have redesigned our audit report so our auditors can communicate their findings more efficiently.

Some of these points can be considered the proverbial low-hanging fruit, but we never underestimate the significance that a small change can make. As for our long-term goals, we are currently exploring our customer service program in its entirety, from mailing the invoice to mailing the certificate, in an effort to close the remaining cracks and ultimately improve our overall satisfaction scores. Plans are also underway for revamping both the

QMC web site and the AISC web site (www.aisc.org).

In October 2007, we began mailing a new version of the survey to our customers. Please look for it in the mail with your certificate. It's a little shorter than the first version and concentrates more on the specifics of how and when we communicate with our program participants. For those of you that have taken the time to submit a survey to QMC: Thank you! We hope that you will continue to take the time to do so each year, not only because it enters


you in a drawing to win a free audit, but also because what you say is essential to our continuous improvement. If you have an idea or concern, please don't wait for the annual survey. You can contact us at any time: certinfo@QMConline.com or 312.670.7520. We look forward to hearing from you!

Sheila Alegria is client services coordinator, Kimberly Swiss is manager of certification administration, and Bobbi Marstellar is vice president with Quality Management Company.

% "completely" and "mostly" satisfied		2007		
		10	2Q	3Q
Total # of respondents	76	105	104	115
Overall satisfaction with your AUDIT this year		99%	99%	100%
Overall satisfaction with QMC		95%	94%	97%
How satisfied are you with QMC staff with regard to:				
courteousness	95%	100%	98%	100%
program knowledge	96%	97%	96%	97%
explanation of deadlines and requirements		96%	95%	92%
ability to resolve problems		95%	92%	89%
how quickly your call was answered		88%	85%	83%
how quickly you received a reply to your e-mail		85%	79%	80%
frequency of phone and e-mail communication	82%	88%	85%	88%

### The drilling machine of "X-Y positioning 3 drills" method

Three drills (left/right/top) travel 2 dimensionally while the workpiece is firmly held by vises · · · this original method of Daito enables unrivaled speed and accuracy.



(in) Beam Width CSD 1050 1350 1570 40 51 1/2 59 Max Min 6 8

CSDI1050 **M** 

DAITO U.S.A., INC.

1470 Elmhurst Road, Elk Grove Village, IL 60007 Tel: 847-437-6788 http://www.daitousa.com

### **Revised Printing Now Available**

### Unlock the Code

### The Seismic Code.

The International Building Code seismic design requirements are no longer exclusive to California — unlocking the door for the new national design criteria.

Knowing your technical requirements and seismic provisions can get puzzling. The AISC *Seismic Design Manual* gives you the key to unlocking the building code in a format that is already familiar to you.

With easy-to-understand illustrations rendering every detail for these systems, the *Seismic Design Manual* guides you through the specifics of when seismic load and design requirements are essential.

The Manual highlights the ANSI/AISC 341-05 Seismic Provisions for Structural Steel Buildings and ANSI/AISC 358-05 Prequalified Connections for Special and Intermediate Steel Moment Frames for Seismic Applications. The 2005 Seismic Provisions are the first to combine ASD and LRFD into a unified format. You will have all the tools you need in one source for the seismic design of structural steel.

The new *Seismic Design Manual* is available at \$175.00 for AISC members and \$350.00 for non-members. To order your copy — or to learn more about joining AISC — visit www.aisc.org/publications today!

### SEISMIC DESIGN



MANUAL

AMERICAN INSTITUTE
OF
STEEL CONSTRUCTION
INC.

AND THE

STRUCTURAL STEEL EDUCATIONAL COUNCIL



www.aisc.org

866.ASK.AISC

There's always a solution in steel.

DECEMBER 2007

### **Quick Response**

BY AARON FRANKLIN, P.E., MAZEN WAHBEH, PH.D., P.E., DANIEL SPEER, P.E., AND MARTIN POHLL, P.E., S.E.

### A Caltrans-led construction team was able to quickly repair a damaged Bay Area interchange following a major explosion.

**THE MACARTHUR MAZE ISN'T AS FUN AS IT SOUNDS.** It's a nickname for a network of major interchanges east of the San Francisco-Oakland Bay Bridge that distributes traffic to East Bay freeways. The Maze connects Oakland, Berkeley, and San Francisco via five major highways, whose combined average daily traffic is approximately 80,000 vehicles.

Earlier this year, the Maze was the site of a major accident that made national headlines. At 3:41 a.m. on April 29, 2007, a tanker truck, carrying 8,600 gallons of fuel and traveling southbound from I-80 to I-880, overturned and exploded. According to police reports, the accident occurred when the driver changed lanes and the fuel shifted from one side to the other, tipping the truck. The explosion and fire occurred on the bridge deck of southbound I-880 and beneath the connector ramp from the Bay Bridge to eastbound I-580. The heat from the free-burning gas fire caused the steel box beam bent cap at Bent MB19, as well as spans 18 and 19 on I-580, to buckle and collapse onto the I-880 connector ramp directly below. The estimated high temperatures were in excess of 1,500 °F, which caused the steel to soften and forge under its own weight. This col-

lapse closed both the southbound I-880 and eastbound I-580 connectors, interrupting San Francisco-Oakland Bay Bridge traffic.

The collapsed portion of I-580—a total of 160 ft long and 51 ft wide—encompassed the steel girders on both sides of the bent (MB19) as well as the bent cap itself. The failed spans had six steel girders with a 45-ft-wide concrete deck. Luckily, the I-880 connector sustained less damage.

The California Department of Transportation (Caltrans) management and government officials reacted immediately and decisively to prioritize reconstruction. Within hours, senior bridge officials were meeting to set priorities, and engineers were on-site assessing damage. By the end of the first day, Governor Arnold Schwarzenegger declared a State of Emergency and procured federal support for emergency reconstruction funds.

Immediately after removal of debris and stabilization of the structure, steel and concrete samples were obtained. After testing, Caltrans engineers determined that the I-580 superstructure, which remained standing, was not heat damaged, with exceptions at the upper columns. Caltrans engineers also determined that the I-880 structure had suffered minimal damage.

Eight days later, after shoring from below and minor repairs were completed on the I-880 connector, Caltrans reopened it to traffic. As a result, the primary items of work required to replace the collapsed section were the girders, bent cap, and deck. Caltrans engineers realized that rebuilding quickly would hinge on the availability of materials and obtaining the right contractors. On the day of the accident, Caltrans officials mobilized a worldwide search to assess steel availability and fabrication capabilities. This information, gathered within two days, became a critical guide for engineers selecting the reconstruction alternatives.

\*\*Continued on p. 51\*\*



Two spans of I-580 collapsed onto the I-880 connector ramp directly below.



The steel box beam bent cap spanning the I-880 connector collapsed in the estimated 1,500 °F fire.

### TRAVELIFT CRANES



#### STEEL HANDLING SOLUTIONS

Mi-Jack features specialized hauling and lifting equipment, custom tailored to each job and capable of carrying loads from 15 - 350 tons.



Creative, common sense approach in developing unique and logical solutions to difficult material handling problems.

### REMANUFACTURED CRANES AVAILABLE

For more info, call: Mike Lanigan Jr. at 1-800-6-MI-JACK

3111 West 167th St., Hazel Crest, IL 60429 email: info@travelift.com • www.mi-jack.com

A MESSAGE FROM THE

### **Executive Director**



On October 31, the House Transportation and Infrastructure Committee approved legislation to authorize \$2 billion in spending for repairs and reconstruction to the most struc-

turally unsound bridges in the U.S. The bill was drafted by committee chairman Congressman Jim Oberstar (D-MN) in response to the I-35 bridge collapse in Minnesota that killed 13 people and injured at least 140. Chairman Oberstar originally proposed a \$25 billion initiative, partially funded by a five-cent fuel tax for automobiles over three years. However, that amount has been scaled back to \$2 billion in light of political opposition from the Senate and White House, both of which are fearful that the new tax would contribute to the highly politicized issue of growing fuel prices. The approved \$2 billion amount is a fraction of the Department of Transportation's estimate that \$65 billion is needed to address all critical bridge deficiencies.

The bill now waits to be considered and voted upon by the full House of Representatives and has yet to be introduced in the Senate.

Best Regards, Conn Abnee NSBA Executive Director

#### **National Steel Bridge Alliance**

One East Wacker Drive, Suite 700 Chicago, IL 60601-1802 www.nsbaweb.org www.steelbridges.org

#### **Conn Abnee Executive Director**

Phone: 606.724.2347 Cell: 312.804.1524 abnee@nsbaweb.org

#### **Mike Moffitt Director of Engineering Services**

1228 S. 4th Street St. Charles, IL 60174-4019 Phone: 630.443.8090 moffitt@nsbaweb.org

#### **Jody Lovsness Marketing and Membership** Coordinator

11708 Jackson Road Omaha, NE 68154 Phone: 402.758.9099 Fax: 402.778.9499 lovsness@nsbaweb.org


#### Calvin R. Schrage Regional Director (west)


5620 Harding Drive Lincoln, NE 68521 Phone: 402.466.1007 Fax: 402.466.1027 schrage@nsbaweb.org

#### William F. McEleney Regional Director (east)

45 Pasture View Lane Cranston, RI 02921-2732 Phone: 401.943.5660 Fax: same as phone mceleney@nsbaweb.org

### **Regional Directors' Territories**





continued from p. 49

Caltrans determined steel girders like those in the original design would be the preferred option—if the steel could be located quickly. They initially considered precast concrete girders, but decided against this idea because it would require foundation enhancement to support the additional weight.

From the time of the collapse on Sunday until the following Thursday, damage to the bridge structures was evaluated, a design was developed, and contract documents and plans were developed. To meet this schedule, designers had to make quick decisions, taking into consideration several factors. These included:

- → Quick design that could be easily fabricated with currently available materials.
- → Fast fabrication time to minimize structure closure.
- → Shoring design of the lower structure to provide a platform for reconstructing the upper structures.
- → Two different designs, with both concrete and structural steel bent caps, providing alternatives to further speed-up the reconstruction.

The engineers anticipated that the contractor would need a straightforward and simple design to complete the project in the time frame required, and made several engineering judgments during the design phase with assistance of fabrication experts, allowing delivery of a fast and safe design. The design team investigated prefabricated rolled shapes versus built-up sections; however, the required rolled shape sizes were not known to be readily available and would have required several weeks for fabrication. Hence the team decided to proceed with built-up sections. In addition, to reduce the number of stiffeners required for local buckling checks and to reduce the amount of welding required on built-up girders, the web thickness was increased. The flange plates were kept to one size only to simplify fabrication. The web depth was adjusted to ensure that the overall depth would not require adjustment of the existing bearings that were to be reused.

Constant communication played a large role in the success of this project. Daily status meetings with project managers and key Caltrans management cleared hurdles that would have caused costly delays. On the shop floor, Caltrans maintained a constant presence of quality assurance inspectors, which proved to be critical to the success of steel girder fabrication. Designer availability at all hours of the day allowed ma-

### **Quick Turnaround**

The implementation of significant changes to typical construction contracts contributed to the MacArthur Maze project's success. Caltrans, the owner, was motivated to complete the project safely and in record time. It issued a construction contract specifying that its engineers would have only 24 hours to respond to all submittals and requests from the contractor (typical response times range from several days to several weeks, depending on the submittal type). To provide a comprehensive yet expedited review, Caltrans significantly increased the manpower of the review teams. Reducing response time to a single day clearly demonstrated Caltrans' commitment to be responsive.

Within two hours of awarding the general contract award, the steel fabricator was also determined. Caltrans immediately initiated contact to begin discussing the fabricator's first critical path item before fabrication could start: approval of welding and shop plans. Within 24 hours of contract award, Caltrans had placed a senior reviewer full-time at the fabricator to provide immediate guidance for welding and shop plans. In order for Caltrans to meet the one-day review times, Caltrans engineers directly solicited draft copies of all welding submittals. In this way, Caltrans provided the fabricator immediate feedback, often before the official copy was even submitted.

On May 10th, three days after the contract was awarded, Caltrans and the general contractor conducted a pre-welding meeting with the fabricator. During this meeting, Caltrans provided Stinger Welding with review comments on their Welding Quality Control Plan, to which the fabricator was able to respond immediately. By the end of this meeting, Caltrans officials were satisfied with the fabricator's plan; that same evening, fabrication began.



INSTALL CLOSE-MESH GRATING AT LOW COST!

ATTACH GRATING with slots as narrow as 3/8" — without cutting or drilling — with the new G-Clips Close-Grip slimbodied grating fastener.

And G-Clips' Close-Grip fasteners let you quickly attach close-mesh grating with hand tools — dramatically lowering installation costs.

- 316 Stainless fights corrosion
- Resistant to vibration loosening
- Won't damage beams, paint or coatings
- NO welding or hot work required.

Attaching close-mesh grating is no longer a problem. (Our other fasteners, available in 316 stainless, galvanized carbon steel, aluminum and CuNi alloys, make short work of all popular gratings.) Call today for a sample kit and a free catalog.



P. O. Box 6438, New Orleans, LA 70174 **800-227-9013** 

www.gclips.com • Email: sales@gclips.com




Built-up sections were fabricated with thicker web plates to minimize the number of stiffeners required. Flange plates were kept constant to simplify fabrication. The bridge reopend to traffic in only 25 days.

# Having problems hiring and retaining skilled layout and fitting personnel?

Chances are you're like every other fabricator in today's market who answers "YES."

Ficep, the world's recognized technology leader in structural steel and plate fabrication systems, has made the first quantum leap in this process since the introduction of the beam line concept in the 60's.



Now you can go directly from a Tekla or X Steel 3-D model into Ficep's proprietary software where we automatically generate the CNC program for not just the holes but also the scribing data for all the required layout locations without any manual programming!

The CNC program is automatically generated with our proprietary software for processing on Ficep's CNC beam drilling and plate lines. This will contain not just holes but also the scribe lines for all four surfaces and part numbers to *locate and orientate* the required detail to the main member.

If your company wants to be an industry leader going forward and take the next quantum step in the reduction of your man hours per ton while solving the challenge of hiring and retaining layout personnel, give us a call. You will be truly amazed by our technology and how it will positively impact your operation!



2301 Industry Court
Forest Hill, Maryland 21050
410-588-5800 • 410-588-5900 fax
www.ficepcorp.com

terials engineers to quickly work through any issues that came up. On-site, Caltrans inspectors quickly elevated and addressed any issue that could potentially delay fabrication. At the height of fabrication, there were several QA inspectors covering fabrication and quality around the clock.

Another key factor to the project's success was a new Caltrans process that was recently implemented where "fit-for-purpose" decisions could be made. This process is managed by a materials engineer who is dedicated to the project and charged with seeking proposals from the fabricator and contractor, making a fit-for-purpose determination on the contractor's proposal and gathering input and concurrence from the appropriate authorities. With this process, when it is in the best interest of Caltrans to accept the contractor's proposal, a decision can be rapidly made and documented. Thanks to this new program, Caltrans was able to use material with minor deviations, but that were nonetheless acceptable to all parties.

Governor Schwarzenegger had described the Maze collapse as "the worst damage to our transportation infrastructure since the Loma Prieta Earthquake." However, in just 25 days, traffic was reopened in time for the Memorial Day weekend. In less than a month, the design and construction team was able to erect a bridge that met current stringent guidelines.

Aaron Franklin is a senior engineer and Mazen Wahbeh is a senior principal with Mactec Engineering. Daniel Speer is a supervising bridge engineer and Martin Pohll is a senior bridge engineer (seismic specialist) with the California Department of Transportation.

### Owner/Designer

California Department of Transportation (Caltrans)


#### **General Contractor**

C.C. Myers, Rancho Cordova, Calif.

#### **Fabricator**

Stinger Welding, Coolidge, Ariz. (AISC/NSBA Member)

### Differences Between Certification and Inspection Can Be Like **Apples** and **Oranges**



That's the philosophy behind the American Institute of Steel Construction's Quality Certification program for structural steel fabricators and erectors. Our independent auditing company, Quality Management Company, LLC, is ISO 9000:2001-registered. QMC's on-site audits confirm that companies have the personnel, knowledge, organization, equipment, experience, capability, procedures, and commitment to produce the required quality of work.

What does "AISC Certification" mean to you? A quality management system implemented for AISC Certification can reduce the scope or eliminate the need for structural tests and special inspection. To find out more visit www.aisc.org/buildingofficials.

### Who is AISC?

AISC is a standard-setting organization responsible for writing the *Specification for Structural Steel Buildings*. More than 20,000 U.S. designers are members of AISC and almost every structural engineer has a copy of the *Steel Construction Manual*.

### What else can AISC do for me?

The AISC **Steel Solutions Center** is a free service that answers technical questions about structural steel. Just call **866.ASK.AISC** or e-mail **solutions @aisc.org**.

### Try us on for size!

AISC now offers an affiliate membership for building inspectors and code officials. In addition to discounts on publications, conferences, and seminars, affiliate members have access to more than 12,000 pages of online technical information—anytime you need it, 24 hours a day, 7 days a week. AISC is offering a **complimentary** one-year affiliate membership to building inspectors and code officials who join before December 31, 2007 and mention seeing this ad. To receive your free membership, e-mail your mailing address to **membership@aisc.org**.







In today's fast-paced, competitive design and construction industry, success is often a matter of access to the right information at the right time. The Steel Solutions Center makes it easy for you to explore traditional and innovative solutions enabling you to find, compare, select and specify the right system for your project. From typical framing studies to total structural systems, including project costs and schedules, we can provide you with up-to-date information for your next project – **FOR FREE!** 



The Steel Solutions Center can help you visualize your project in steel – call 866.ASK.AISC or e-mail **solutions@aisc.org**.

For a sample of what The Steel Solutions Center can do for you, visit **www.aisc.org/solutions**.



### **Beauty and the Beast**

BY DENNIS GOWINS, P.E.



### **CONGESTION CAN BE A BEAST ON ORLANDO'S STATE**

**ROAD 408.** Just ask any of the more than 150,000 daily commuters who pay a toll to use the major artery to and from downtown. Increased demand, backups at toll plazas, and a general lack of mainline capacity create 55 hours of delays per motorist annually.

To sooth the bottleneck, the Orlando-Orange County Expressway Authority has undertaken a \$450 million improvement program to widen 12 miles of S.R. 408 from Hiawassee Road to Goldenrod Road. Program improvements include the reconstruction of the Holland East and Holland West main toll plazas and the installation of express E-PASS lanes, so that customers may travel at the posted highway speed instead of creeping along. Once complete, the overhaul is expected to significantly condense commute times and increase the corridor's overall capacity by 50%. S.R. 408 will be well-positioned to handle the more than 215,000 daily commuters projected by 2025.

The final leg of the current S.R. 408 improvement program calls for widening the Lake Underhill Bridge from eight to 12 lanes, increasing the bridge's traffic capacity by 50%. The Expressway Authority, which plans, builds, maintains and operates a network of five tolled expressways in the Orlando metropolitan area, is funded completely by tolls. It has taken extra steps to respect the surrounding neighborhoods of its customers by ensuring the milelong project will be both highly functional and highly attractive.

#### **Beauty Comes at a Price**

Lake Underhill Bridge is punctuated with two pylons with faux cable stays resembling a cable-stayed bridge. Dramatic night-time lighting will be added to spotlight the structure, which has been dubbed Orlando's new eastern gateway. Complementing this structure to the east will be the Conway Road Bridge. This highly curved steel box girder structure will be framed by four pylons in

combination with highly landscaped planter walls.


HNTB was selected as the prime consultant to provide final engineering and construction plans for the Lake Underhill widening project, which runs from Crystal Lake Drive to Conway Road. At the request of the Expressway Authority, the original design featured two "braided ramp" bridges, each more than 2,400 ft long. They were to be a combination of steel plate girders and AASHTO prestressed girders. The steel plate girders were to span the ramps below and yield a braided ramp configuration. The braiding concept was intended to eliminate traffic weaving between the Crystal Lake Drive and Conway Drive ramps.

The low bid for the project came in at \$105 million—too much, according to the Expressway Authority. It rejected the bids and directed HNTB to redesign the project without the braided ramp bridges.

Because it impacted other aspects of the adjacent projects currently under construction, completion of the Conway Road Bridge was the only milestone built into the new design. The Expressway Authority's request for a new design could have jeopardized the project's schedule, but HNTB established an aggressive one-year schedule for the redesign and hoped for a better bidding environment than the original project bid, which occurred just a few weeks after Hurricane Katrina. When the firm delivered the redesign, bidding was tight with the low bid being within 1% of the engineer's estimate.

Scrapping the initial design proved to be a very cost-effective decision for the Expressway Authority. Less than 18 months later, HNTB presented a new design with a new price tag: \$77.9 million—more than \$25 million less than the original bid. This past March, designs for the Lake Underhill widening project were completed. The project includes:

→ Expanding one mile of S.R. 408 from six to 10 lanes.



- → Widening Lake Underhill Bridge to 12
- → Modifying the ramps at Crystal Lake Drive and Conway Road Interchanges.
- Widening the mainline bridges at Crystal Lake Drive and Lake Underhill Road.
- Creating a parallel 1,700-ft pedestrian bridge spanning the lake that will be the missing link in connecting a series of trails in the area.

Bids for the redesign were opened on May 8, 2007, and construction began this summer. The project is scheduled for completion in early 2010. More than 290 tons of steel will be used in the fabrication of the structure.

### **Putting it into Context**

At least \$10 million of the project's budget will be spent on aesthetics and to preserve the fiber of the surrounding community. As such, the Expressway Authority was at liberty to incorporate design elements that might not have been considered on a tighter aesthetics budget. For example, in lieu of curved plate girders for the Conway Road Bridge, they chose curved steel box girders, which traditionally are more expensive.

The Authority also approved the additional expense of enclosing the area beneath the deck between the steel box girders to give the appearance of a single steel box. This will provide a smooth appearance

At least \$10 million of the project's budget will be spent on aesthetic elements to integrate the bridges into the surrounding communities.

to motorists traveling below.

The bridge is a highly curved two-span structure with an overall length of 270 ft. The curvature's tight 280-ft radius and spiral transitions presented a complex geometrical challenge. The use of two steel trapezoidal box girders yielded both a technical and aesthetically pleasing solution.

The Expressway Authority's decision to put the Lake Underhill project in a context-sensitive design is part of a national and statewide trend in transportation planning. It requires the input of all stakeholders to develop a transportation facility that fits its physical setting and preserves scenic, aesthetic, historic, and environmental resources, while also improving mobility and safety.

Throughout the entire S.R. 408 widening project, the Expressway Authority has incorporated sound walls, eye-pleasing retaining walls, tiered landscaped planter walls, improved lighting, decorative bridge treatments, colored concrete, and extensive landscaping. Architects even borrowed design elements from Orlando's downtown neighborhoods. For example, the battered pylons featured at each bridge in the program reflect the battered columns found on the front porches of bungalows throughout downtown neighborhoods. Sedate colors, aesthetic wall treatments, and high-quality lighting fixtures follow the community's standards.

The Expressway Authority used the Florida Department of Transportation's Interstate 4 urban design criteria as a foundation for the S.R. 408 improvements. Criteria include:

- → Placing emphasis on adjacent properties and cross streets.
- → Reflecting the character of the surrounding neighborhood in the design of retaining and sound walls.
- → Providing good lighting for pedestrian safety under bridges.
- → Landscaping, so the focus is on the veg-



### THE NEW HMD9048 SWIVEL BASE DRILL.

It's tough to line up precise center points especially in horizontal or upside down positions with a magnetic drill. But not with our new swivel base model. Get it close and engage the magnet. Release the swivel's quick unlock handle. Line up the pilot over the center point and lock the swivel. It's that simple and only takes seconds. Hougen makes the tough holes easy, again.



800-426-7818 • www.hougen.com



### Value Engineering Returns \$1.85 Million to Florida County

A VALUE ENGINEERING REDESIGN BY FINLEY ENGINEERING GROUP, INC., COMBINED WITH COST-EF-FECTIVENESS MEASURES TAKEN BY ZEP CONSTRUCTION, will return \$1.85 million to Lee County, Fla. on the Estero Parkway Flyover project.

Finley's redesign replaces twin, castin-place concrete box girders with a single, four-steel box girder design. This solution provides significant economic benefits with the elimination of a large falsework support system, reduced construction time, reduced foundation design requirements, and simplified construction.

The new Estero Parkway Flyover, 561 ft long with spans of 340 ft and 221 ft and approximately 116 ft wide, will alleviate traffic on the parkway and nearby I-75 in the Estero community, which is southeast of Fort Myers. It will complement the widening of Corkscrew Road while providing a link to areas east and west of I-75. It will also provide an alternate east-west route for travelers using the Tamiami Trail and I-75.

"By using shallower steel girders, it allows for the use of smaller grades, so it won't require as much fill on each approach," said Robert Clark, Jr., president of steel fabricator Tampa Steel. "The contractor can also erect the bridge in longer sections, which means fewer obstructions in the roadway."

The redesign also calls for a staged temporary tower support scheme to optimize the efficiency of the steel section, which allowed the steel bridge solution to be competitive against the initial cast-inplace concrete design.

In addition, the driving public benefits from the redesign through reduced traffic maintenance requirements. The redesign also enhances overall project safety with the elimination of falsework over the Interstate and reduces risks associated with a constrained traffic pattern through the falsework system.

The \$1.85 million refund to the county is significant because the county is responsible for funding the flyover, and in the wake of a tax cut passed down by the state, the money will help the county meet its budgetary commitments.

"We're obviously pleased," said Donald Deberry, P.E., public works operations manager for Lee County. "We always appreciate working with engineers and contractors who are willing to take a second look at projects and find ways to give the public more bang for their buck."

"We see this as a great example of what can happen with value engineering when the owner, contractor, and engineer come together to create a design that takes the contractor's strengths into account and utilizes the best material for the challenges of the project," says Craig Finley, president of Finley. "In this case, the redesign from concrete to steel had an overall positive effect on the cost, schedule, and efficiency of the bridge. With construction budgets as tight as they are, there's no room for waste in any of these areas."

etation, not the walls.

→ Minimizing the use of chain-link fence. The design of the S.R. 408 expansion program also follows the vision of the Downtown Orlando Community Redevelopment Agency (CRA). As part of its Downtown Orlando 2020 Vision plan, the CRA touched on downtown gateways that announce: "You have arrived."

The Lake Underhill project is symbolic of the entire city. In planning the project, the Expressway Authority obviously thought well beyond the scope of its right-of-way. By considering the community along its corridor, the design moves far

beyond asphalt and concrete to respect the people who live and work along this road, as well as those who drive on it. The entire community will benefit.

Dennis Gowins is structures leader for HNTB Corp. and structural project manager for the State Route 408 Lake Underhill widening project.

#### Designer

HNTB, Orlando, Fla.

### Fabricator/Detailer

PDM Bridge, Palatka, Fla. (AISC/NSBA Member)



### **Got Bridge Work?**

### Structural Steel In-Stock.

Metals USA has a wide variety of structural steel products in grades commonly used in bridge construction including AASHTO M270 GR 36, 50 and 50W, and ASTM A36, A500, A572, A588, A709 and A992.

All Metals USA structural materials including plates, bars, angles, pipe & tube and sections come complete with mill test reports and are shipped promptly nationwide, usually within days of your order.



www.metalsusa.com



ACTIVE MEMBER

Ohio Valley Region Jim Wisbon jwisbon@metalsusa.com 800-569-5830

Notheast Region Jim Urban jurban@metalsusa.com 800-523-3340

Western Region Beverlea Bons bbons@metalsusa.com 800-284-7321 Project Supply Jim Collins jcollins@metalsusa.com 800-523-3340

Mid Atlantic Region Gary Mobley gmobley@metalsusa.com 800-334-4511

Southeast Region Mickey Marshall mmarshall@metalsusa.com 800-277-0476

Steel & Service the Metals USA Way.





### A Tale of Two Yanktons

BY DAN SHARI



### A new steel span over the Missouri River replaces a National Historic Register bridge to route auto traffic between South Dakota and Nebraska.

PRETTY SOON, THERE WILL BE A NEW WAY TO GET FROM NEBRASKA TO SOUTH DAKOTA—AND VICE VERSA, OF COURSE. Construction began this summer on a new, 1,590-ft, welded steel-plate girder bridge over the Missouri River between Yankton, S.D. and South Yankton, Neb. It is the first bridge over the Missouri River to be designed in-house by the Nebraska Department of Roads (NDOR).

The bridge is being constructed approximately 900 ft west of the Meridian Bridge, the current span between the two towns. The 84-year-old, two-level, steel truss bridge carries U.S. Route 81 motorists via a single lane on the top level. Northbound traffic is underneath, on a single lane orginally intended for a railroad line that was never built.

Constructability was the primary concern when preliminary design began, and the added attention to that aspect resulted in a very efficient, cost-effective design. With assistance from National Steel Bridge Alliance, NDOR was able to evaluate the capabilities of fabricating shops in the surrounding states to determine the maximum length and height of girder sections to use. It was determined that the maximum-depth girder that area shops could handle

was 10 ft, and the maximum length for a girder section was 160 ft. With a six-span, haunched girder design, using 280 ft for the four interior spans and 235 ft for the two end spans, a 166-ft girder section was needed in the end span from the abutment to the first field splice. All of the other girder sections could be 130 ft, 140 ft, or 150 ft. An optional field splice in the 166-ft section was provided to reduce the section length to less than 130 ft, if the contractor chooses to use it.

The superstructure is made up of seven lines of girders spaced at 11-ft 4-in. centers. The hybrid girders, which incorporate ASTM A709 Grade HPS70W steel for the flanges and Grade 50W steel for the webs, are 10 ft deep at the piers and 6.5 ft deep at midspan. The maximum flange plate thickness used was 2 in. to take advantage of increased market competition in the supply of Grade HPS70W 2 in. thick and under. These limits helped determine the best span arrangement to use for the bridge.

Preliminary plans were sent to the steel fabricating shops for review and comment. The only comment received was that it was a very clean and efficient design and should be very competitive with any other girder option. Common practice in Nebraska is to design both concrete and steel options for girder bridges with spans greater than 50 ft, unless site conditions or other restrictions prohibit it. In the case of the Meridian Bridge replacement, the state prepared both sets of plans and received three bids—all for the steel option; no bids were received for a concrete girder option.

Once completed, the bridge deck will provide for two traffic lanes in each direction on a 74-ft clear roadway with an 18-ft painted median. The anticipated completion date is November 2009; however, the contractor expects to finish almost a year early because of the steel design.

The old bridge, meanwhile, is on the National Historic Register and will be maintained for use as a pedestrian bridge, connecting existing and planned foot and bike trails.

Dan Sharp is a bridge engineer with the Nebraska Department of Roads.

#### Designer

Nebraska Department of Roads

### **Fabricator**

PDM Bridge, Eau Claire, Wisc. (AISC/NSBA Member)

# Voortman Corporation The leading supplier of

high performance fabrication machinery for the structural steel industry.

For the processing of structural steel **beams, flats, angles** and plates, Voortman offers unrivaled solutions.



V600



V630



**VB-range** 



V806M

drilling systems • punching & shearing systems • cambering machines • band saws • beam coping systems • beam welding machines • plate processing machines • shot blasters • stock systems



V550



7505





V250



V2000

Voortman USA Corporation • Unit F 450 South Spruce St. • Manteno IL, 60950 USA T: +1 (0)815 - 935 3010 • F: +1 (0)815 - 935 2201 info@voortmancorp.com





### **FABRICATION PRODUCTS**

Company	Products Offered	Product Description
Advanced Fabricating Machinery		
www.advancedfab.com 603.642.4906	Tube fabrication equipment	Advanced Fabricating Machinery provides tube/pipe bending and beam cambering equipment.
Anchor Lamina, Inc. www.anchorlamina.com 800.652.6462	Heavy-duty drills	Lamina hydraulic drills are powerful and portable. Quick-change heads drill and tap up, down, or sideways from 13/16 in. to 4 in. They are reliable and low-maintenance, and meet U.S. and global standards.
Behringer Saws, Inc. www.behringersaws.com 888.234.7464	Automatic bandsawing systems	Bandsaw machines and material handling systems deliver 50% faster average cutting times for higher productivity and throughput.
Bug-O Systems, Inc. www.bugo.com 800.245.3186	Components for hand-held tools	BUG-O Systems, Inc., a division of Weld Tooling Corporation, manufacturers of a system of drives, carriages, rails, and attachments designed to automate welding guns, cutting torches, and other hand-held tools.
Cambco, Inc. www.cambcoinc.com 713.781.9702	The Original Cambering Machine	Structural steel beam cambering machines that camber beams as large as a W44x285, W40x397, or W36x441. Eight basic models plus six conveyor-fed versions are available to meet any cambering need. Totally self-contained, they may be moved or stored when not in use.
CMLUSA, Inc Ercolina www.ercolina-usa.com 563.391.7700	Megabender 030	Ercolina's patented mandrel system adapts easily to the Rotary Draw Bender Model MegaBender 030, without modification, to produce high-quality bends on tubes and hollow profiles.
	050KD Economy Top Bender	Ercolina 050KD is ideal for bending pipe, tube, squares, rectangles, solids, and other profiles. Hex mount patented tooling system tooling allows rapid changeover.
	CE35 Angle Roll	Ercolina angle rolls are capable of bending a wide range of profiles and materials to centerline radii as small as four times the diameter of the work piece.
COMEQ, Inc. www.comeq.com 410.933.8500	ROUNDO, AMERICOR, GEKA, and PRIMELINE	Distributor of metal fabricating machinery including ROUNDO angle, section, beam, 3-roll, and 4-roll plate bending rolls; AMERICOR angle, 3-roll, and 4-roll plate bending rolls; GEKA ironworkers and automated punching systems; PRIMELINE press brakes and shears; and more.
	LKF-450 multi-purpose beveling machine	Bevels, deburrs, and chamfers steel, stainless steel, nonferrous metals, brass, and plastic. Faster and cleaner than angle grinders, the unit has a fine adjustment feature for the preparation of weld seams.
CS Unitec, Inc. www.csunitec.com 800.700.5919	ECO 50-AK portable magnetic drill	Lightweight, portable, 2-speed, high-performance magnetic drill has a hole-cutting capacity of 2-indiam. and a twist drill capacity of <sup>7</sup> / <sub>8</sub> -indiam. An automatic cooling/lubrication system is built into the arbor. Ideal for structural steel and other metals.
	ARMOR-PLATED Unibroach	Ideal for drilling applications in structural steel and other hard metals. These cutters allow drilling at high operating temperatures with more power and RPM. Available in 1-in., 2-in., and 3-in. depths with diameters from 7/is in. to 5 in.
	PL50 air-reciprocating saw	Pneumatic reciprocating saw for demanding applications, including cutting metal, timber, and fiberglass. Accepts either ½-in. or ¾-in. hand or machine hacksaw blades with nosepiece change. Rugged construction and built-in lubrication system for long life.
Daito USA www.daito-seiki.com	Band saws and miter saws	Band saws and miter saws for industrial and structural steel. Our band saws and miter saws come in a variety of sizes up to 20-in. capacity.
847.437.6788	Drill presses	Drills designed for structural steel use.
Design Data www.dsndata.com 800.443.0782	SDS/2	Design Data's SDS/2 is a 3D computer modeling software product designed for the structural steel industry. SDS/2 allows steel detailers, fabricators, engineers, and erectors to access the same 3D model from anywhere in the world simultaneously.
	General purpose saws	Cut-off, contour, and miter band saws are available for sawing a variety of materials with capacities to 17-in. x 17-in. rectangles. They are an economical solution for low volume operations.
DoALL Sawing Products	Vertical contour saws	Vertical band saws have a throat depth up to 36 in. and a maximum work height to 20 in., depending on the model. They are for mitering, contour cutting, disk cutting and more.
www.doallsawing.com 888 DoALLSAW	Miter cutting saws	Available in tilt-frame or swivel head configuations, miter cutting saws feature rectangluar capacities to 26 in. $\times$ 39½ in. with angle cutting capacities to 60°.
	Product power saws	Horizontal saws for production sawing have automatic operation and numeric control and feature solid, heavy-duty construction. This provides more rigidity and reduces vibration for superior finishes and exceptional accuracy.
E.J.E. Industries, Inc. www.ejeindustries.com 724.228.8841 800.321.3955	Structural Material Manager	The system manages material lists by providing weights, surface areas, paint/primer requirements, bolt counts, shipping tickets, and estimating reports. Its Nesting Module optimizes cut-lists, and the CAD interface eliminates re-typing.
	Coreshield self-shielding flux cored wires	Combining outstanding strength, superior weld characteristics, high deposition rates, low spatter, easily removable slag, and low fume production, Coreshield wires consistently rate the highest welder appeal in their class.
ESAB Welding & Cutting Products www.esabna.com	Atom arc covered electrodes	The original iron powder low-hydrogen electrode still sets standards for high-production radiographic quality welds in mild and low alloy steel with its smooth metal transfer and excellent mechanical properties.
800.ESAB.123	ESAB 653cvcc power source	This multi-process, three-phase power source is designed for heavy-duty industrial DC welding applications. Ideal for Mig, flux cored wire, submerged arc, and stick electrode welding or carbon arc gouging.
	Mobilefeed wire feeder	This arc voltage wire feeder for use with DC, CC, or CV power supplies features a permanent magnet drive motor and a totally enclosed, impact-resistant case that protects against contaminants
FabCAD, Inc. www.fabcad.com 866.427.2454	FabCAD Premium	An AutoDesk-powered ornamental/miscellaneous detailing system. The program automatically draws railings, fences, and gates with complete dimensions and bill of materials. FabCAD Premium also includes a 10,000-part design library of ornamental castings and forgings from nine industry suppliers.
FabSuite LLC www.fabsuite.com 757.645.0842	FabSuite	A package of fabrication management programs that includes: estimating, combining (mult/nest), inventory, production control, project management, purchasing, order entry, and bar coding interface.
	FabSuite - Project Management	A stand-alone program, packaged for independent steel detailers. It includes: project contacts, design and detail drawing logs, transmittals, RFIs, change orders, journal entries, check list, and task list.
FabTrol Systems, Inc. www.fabtrol.com 541.485.4719	Fabrication software	FabTrol MRP is the global leading steel fabrication software for managing estimating, drawings, materials, production, and shipping.



		TABRICATION FRODUCTS
Company Eassin USA Inc.	Products Offered	Product Description
Faccin USA, Inc. www.faccin.com 813.664.8884 905.407.4606	Bending rolls	Faccin is the world leader in the production of heavy-duty bending rolls for plate, angle, and structural shapes. Special options automate the rolling of wind tower structures and offer maximum output. Also a manufacturer of heavy-duty flange rolls and dished head equipment.
Ficep Corporation www.ficepcorp.com 410.588.5800	CNC plate processing systems	The Ficep plate processing systems address the operations of drilling, punching, milling, tapping, countersinking, marking, and final part cutting without manual intermediate material-handling processes.
	CNC angle processing lines	The current Ficep product line of CNC angle fabrication systems comprises 12 different models. Typical operations include punching, drilling, marking, and notching (on not only angles, but also flats and channels).
	CNC drilling lines	The Ficep lines incorporate drilling and scribing on all surfaces. The scribing capability interfaces with Tekla Structures for downloading of the scribing data required for fitting from their 3D model.
	CNC robotic coping	The Ficep robotic coping systems feature both oxy-fuel and plasma. The full robotic torch motion features full motion even for such tasks as weld prep on the web and flanges.
Franklin Manufacturing, Inc.	Model AFC5108-12FB × 196 Angle Fabricator	Three-axis angle fabricator (6 × 6 × $\frac{1}{2}$ - 8 × 8 × 1-in. maximum angle, 12 × 1-in. flat bar, C12 at 20.7 channel capacity). Triple gag tooling and optional plasma cutting. Punching capacity: 100-130 tons. Maximum: 1½-indiameter hole.
	Model HD-145 × 44 Drill System	CNC three spindle drill system with 300-750 lb/ft conveyor system. High-speed spindles. DVST file compatible with Windows XP. Saw integration. Engineered material handling.
www.fmi-solutions.com 256.332.6654	Model PF196 × 72G Plasma/ Punch Plate Fabricator	With triple gag tooling and plasma cutting. Optional conveyor and gantry systems. Multi-grade ASTM A36. 60-72 psi maximum shear strength. Maximum tonnage is 196 tons. Maximum hole diameter is 2 in. 400 amp plasma. Various nesting options. Windows XP.
	Heavy-Duty F5-2 Series Hydraulic Punch Presses and Power Units	Sixteen standard web/flange models from 30-275 tons, eight standard models from 30-100 tons. With coupling nuts, wrenches, and handlebars. Hardened replacement die pockets.
Hougen Manufacturing, Inc. www.hougen.com 810.635.7111	Portable mag drills	Lightweight and easy to use on the job site. Fifteen models make holes from 7/16 in. to 3-1/16 in. diameter and up to 3 in. deep.
	Rotabroach annular cutters	Require less horsepower, last longer, and drill cleaner holes than conventional methods. Available in diameters from $\frac{7}{16}$ in. to 4 in., and up to 6 in. depth of cut.
	Sheet metal hole cutters	Two series of sheet metal hole cutters make clean, burr-free holes in sheet metal and thin materials. Heat-treated, precision ground geometry makes them last longer than hole saws.
	Punch-Pro portable electro- hydraulic hole punchers	Completely self-contained. No external hoses or hydraulic pumps to carry. Plug into any 120v outlet and punch holes in seconds.
Jesse Engineering Company www.JesseEngineering.com	Pipe benders	Simple and rugged hydraulic pipe benders for pipe fabrication from 2-in. to 10-in. pipe.
253.922.7433	Pipe saddle and hole cutters	Heavy-duty roller bed-style pipe cutting machine for cut to length, bevel, and Y, T and K joints in 2-in. to 36-in. pipe.
	SkyWelder	The JLG SkyWelder for boom lifts consists of a 7,500-watt generator installed in the engine compartment with leads running through the boom to the platform where a 280-AMP Miller is installed.  JLG Ultra boom lifts have platform heights ranging from 120 ft to 135 ft. They have 1,000 lb of restricted
JLG Industries, Inc. www.jlg.com 877.JLG.LIFT	Ultra boom lifts	platform capacity, 500 lb of unrestricted capacity, and the largest work envelope in the industry.
	JLG scissor lifts	JLG rough terrain scissor lifts feature standard 4-wheel drive, proportional lift up and lift down, and a 4-ft manual extension deck as standard equipment. Maximum capacities are up to 2,250 lb.
	JLG telehandlers	JLG telehandlers have lifting capacities up to 12,000 lb. and lifting height to 55 ft. There are four brands, each with unique features. They include JLG, SkyTrak, Lull, and Gradall.
Kaltenbach, Inc. www.kaltenbachusa.com 800.TALK.SAW	Sawing, drilling, and coping machinery	Manufacturer/supplier of machinery for the structural steel fabricator and steel service center, specifically: band and circular sawing machinery; 3-axis CNC drilling lines; structural plate processing machinery; 8-axis fully robotic coping cells; fully CNC punch and shear lines; plus associated material measuring and handling systems.
Lista International Corp. www.listaintl.com 800.722.3020	Storage systems	Lista International Corp. designs and manufactures innovative, efficient, modular storage and workspace systems: drawer storage cabinets, industrial and technical electronic workbenches, Storage Wall Systems, accessory systems, and other unique solutions. With custom solutions that exactly suit the user's specific storage needs and free design services, we maximize space to make businesses more productive
	FabriGear	Automatically loads, feeds, lasercuts, and unloads round and rectangular pipe as well as I-beam and other structural shapes. Can handle pipe up to 11.8 in. in diameter and over 49 ft long.
Mazak Optonics Corporation www.mazaklaser.com 847.252.4500	SpaceGear	Triple-mode laser. Fabricates sheetmetal and plate up to 7/8 in. thick. Cuts pre-formed parts—stamped, hydroformed, and spun. Processes round and rectangular pipe as well as I-beam and other structural shapes.
	HyperGear	Processes up to 1-in. mild steel using patented intelligent features designed to automatically provide optimum setup, maintenance notification, and fastest cutting speeds for every material type and thickness—all without operator intervention.
	SG-U44	Compact triple-mode production laser. Performs high-speed 2D processing of sheet metal and plate up to $\frac{1}{2}$ in. thick, 3D cutting of pre-formed parts, and 3D-rotary cutting of tube, pipe, and structural.
MG Systems & Welding, Inc. www.mg-systems-welding.com 262.255.5520	MPC2000	The MPC2000 is a large-gantry, precision multi-process cutting machine enhanced with programmable PL-1 lifters. Powerful AC drives provide high performance and productivity. Heavy-duty construction allows 24/7 operation.
	EdgeMax	The EdgeMax sports a rugged unitized steel table/frame, full-capture bearing assemblies, and a low-mass aluminum beam driven by dual brushless AC motors, which provides fast acceleration, precise motion, and a very stable cutting platform. It meets the needs of various fabrication markets from HVAC, general fabrication, and precision Hy-Definition cutting.
Mobilis Systems, Inc. www.smsteel.com 866.618.3878	Mobilis modular software suite for steel fabricators	Software suite covering estimating, nesting, production follow-up, shipping, material management, and job costing. Modules can be implemented at your own pace, as your needs evolve, to step toward greater profitability
Multiquip, Inc. www.multiquip.com 800.421.1244	DLW-300ES welder/generator	A mid-size 300-amp welder/10kW generator with a 100% duty cycle at 280 amps. The arc force dial lets the operator fine-tune the arc to the desired quality.
	Moonlight balloon lights	Portable lighting systems that emit glare-free 360° white light up to 100 ft from the light source. The balloons don't require a fan to maintain inflation
	GA Series generators	Outputs from 2.5 to 9.7 kW and they power a wide variety of jobsite tools. Each utilizes 100% copper windings and brushless alternator designs for superior voltage regulation



### **FABRICATION PRODUCTS**

Company	Products Offered	Product Description	
	One-stop shopping for struc-	Major importer and distributor of steel fabricating machinery, including CNC beam lines, press brakes, iron-	
Ocean Machinery www.oceanmachinery.com 800.286.3624	Ocean Avenger CNC Beam	workers, plasma cutters, waterjets, hydraulic punches, etc.  Processes all steel profiles, including beams, channel, angle, tube, pipe, and plates. It drills the heaviest/	
	Drill Line	thickest steel profiles, eliminates manual layout of holes and marks, and drills holes at over 200 holes per hour.	
	Ocean Liberator CNC Beam Coping Machine	Cuts and copes all steel profiles, including, beams, channel, tube, angle, plate, etc. Up to 44-in. beams, 6-in. thickness.	
	Ocean Terminator Dual Col- umn Dual Miter Band Saw	The terminator band saws are designed to cut structural steel profiles up to 42 in. They feature dual column construction and miter cutting both ways, with large 2-in. saw blades, ensuring fast accurate cutting.	
Peddinghaus Corporation www.peddinghaus.com 815.937.3800	Drill, plate processing, saw, and material handling equipment	Peddinghaus manufactures the following products in the U.S.: three models of structural steel drilling machines; seven models of heavy plate processing systems; four models of heavy-duty production band saws; three models of Anglemaster machines for angle iron and flat stock detail production; and automated material handling systems.	
Scotchman Industries, Inc. www.scotchman.com 800.843.8844	ShearMaster 610	Designed to shear 1-in. $\times$ 12-in. base plates and up to $\%$ -in. $\times$ 16-in. and $\frac{1}{2}$ -in. $\times$ 24-in. flat stock. This shear can be used in small-run applications or a high production environment.	
	Scotchman Advanced Feed System	Comes complete with a powerful, user-friendly control panel, which allows you to set up to 99 different programs using fractions, decimals, inches, or metric. The system automatically moves your material to position and cycles the machine.	
Peerless Industrial Equipment Corp. www.peerlessusa.com 920.231.4100	Daito CNC Drill Lines	Daito offers the most automated drill line systems in the world including drilling, marking, sawing, coping, and beveling in an integrated system with one operator.	
	Daito CNC Robot/Plate Coping	Daito's innovative coping robot can be placed in-line with other machines or can stand alone. The flexible system employs both plasma and oxy-fuel. The robotic arm is motioned for all tasks including weld-prep and plate processing for plate up to 48 in. wide.	
	Peerless Band Saws	Peerless began manufacturing saws in 1901 and now offers a full line of cut-off saws, contour saws, miter cutting saws, and power hacksaws.	
	Peerless Ultra-Fab Plate Processors	Plasma, oxy-fuel, drilling, tapping, and plasma piece marking with tables of virtually any size.	
Simonds International www.simondsinternational.com 800.343.1616	Bandsaw blades	Professional grade carbide-tipped, bi-metal, and carbon bandsaw blades enhance faster cutting and increased production through the toughest materials	
SteelCad Consulting Corp. www.steelcad.com 800.456.7875	SteelCad	SteelCad offers a variety of steel detailing modules, starting at the basic structural package—which offers beams, columns, and bracing along with built-in connection design—to the fabricator package, which offers CNC and production control capability. You are free to build a package that is right for you at a price you can afford.	
Steelware, Inc. www.steelware.com 864.294.1206	Steel detailing package	Steelware is a complete steel detailing package for both miscellaneous and structural steel. The miscellaneous section includes a very extensive and versatile stair and railing element. Also included are the cage ladders, plain ladders, angle frames, embedded angles, and considerably more. The structural section contains beams, columns, horizontal bracing, vertical bracing, and their associated components (i.e., end clips, auto coping, web holes, shear tabs, base and cap plate, etc.).	
StrucSoft Ltd. www.strucsoftsolutions.com 877.810.7575	ProSteel 3D	Intelligent steel modeling within AutoCAD offers connection design capability and interface to popular analysis applications and CNC machines.	
	Concrete anchors and shear connectors	Headed weld studs are available in low carbon or stainless steel. Ranging in diameters from $\frac{1}{4}$ in. to 1 in. diameter. Used in composite construction and embedment plates in reinforced concrete. Conforms to AWS, AISC, and AASHTO specifications	
Tru-Weld www.truweldstudwelding.com	Deformed bar	Deformed bar anchors are available in mild and stainless steel. Ranging in diameters from $3/8$ in. to $3/4$ in. diameter with lengths up to $60$ in. configured straight or bent.	
800.321.5588	Threaded studs	Fully threaded, partially threaded, and collar studs are available in low carbon plain finish, copper plated, zinc plated, nickel plated, and stainless steel	
	Stud welding equipment	Stud welding machines and accessories. New and used equipment along with a large rental fleet. Parts and service for all brands of stud welding equipment	
UNIST, Inc. www.unist.com 616.949.0853	UNIST Thru-The-Tool Micro- Fluidization Systems	UNIST Thru-The-Tool Micro-Fluidization Systems are positive displacement lubrication systems designed to apply lubricants small amounts to the tool-work interface in structural steel drilling applications. UNIST Thru-The-Tool systems are designed for use both in portable and CNC drilling for steel fabrication. The systems employ a "low air-pressure drop" technology, which maintains a consistent amount of air and fluid flowing to the tool tip throughout the entire duration of the cut to keep materials cool and evacuate chips.	
Vernon Tool Company www.vernontool.com	Pipe cutting machines	An oxy-fuel and plasma cutting machine for 2-in. to 84-in. OD structural members.	
760.433.5860	MasterTube Plasma Profiler	Cutting machine for 1 in. to 6 in. round and rectangular structural tubing for ornamental and miscellaneous steel construction.	
Voortman Corporation www.voortmancorp.com 815.935.3010	CNC pipe cutting systems	Plasma and gas cutting systems for pipe, square, and rectangular tubing from 2 in. to 84 in.	
	CNC drilling lines	Up to 50 in., all with high-speed drilling using carbide tooling. Spindle speed up to 2,500 rpm and 30 ipm feed rate. Layout/detail marking from 3D detailing to the material can now be included with the standard system. These machines can be incorporated into the Voortman FMS system to run unmanned as required.	
	CNC band saws	Many models up to 50 in. wide with mitering capability up to $\pm$ 0. Stand-alone systems or in combination with a CNC drill line. Saw measuring system that includes the measuring stop and also rollerfeed can be added to the system. The systems can be driven directly from DSTV to provide automation and a paperless cut list.	
	CNC plate processing	High-speed carbide plate drilling systems, combination punch, and high-speed plate drilling systems. Punching and shearing systems with miter shear capability. Automated plate systems that can run unmanned with stock loading systems. Plate plasma/gas cutting and drilling systems up 8 ft in width with automated load unload.	
Wheelabrator Group www.wheelabratorgroup.com 800.845.8508	Wheel blast equipment, automated air blast equipment, and equipment modernization programs	Wheelabrator Group manufactures a full range of wheel-type shot blast machines, mass finishing equipment dedicated to the demands of the industry, and automated airblast solutions. Technically advanced and designed for ease of maintenance, Wheelabrator Group machines range from standard versions to fully customized and integrated systems. Wheelabrator Plus professionals will inspect your current blasting equipment and conduct a thorough assessment that includes reviewing the latest modernization options to determine if any productivity, cost savings, safety, or environmental improvements could be realized as a result of upgrading to newer technology.	

### marketplace

### AISC CERTIFICATION DONE THE ATEMA WAY

### What are Fabricators saying about Atema?

- "Not only did Atema help us prepare for our audit, they also helped us make the better business decisions. "
- Midwest Based Fabricator
- "I was able to understand the requirements and develop a clear path to meet the requirements and improve my business."
- Southern based Fabricator
- "Thanks Atema! We did not receive any Corrective Actions and now we're certified!"
- Northeast based Fabricator

Call: 312-861-3000 information@atemainc.com www.atemainc.com



### Quebec Detailing Connection 100 Detailers available

Superior management from "Old School" veterans, combined with the latest technology for simple to complex projects, with tight delivery schedules.

Contact Robert Beauchamp at 1-866-677-6161

email@datadraft.com Web Site: www.quebecconnection.com

### Are you thinking of becoming AISC Certified?

### **Quality Management Company can help!**

Writing your own Quality Manual may be easier than you think. QMC Online (www.qmconline.com) has a multitude of free resources that can save you time and money preparing your documentation required for AISC Certification. At QMC Online, you'll find:

- A downloadable sample quality manual geared to both large and small fabricators, that includes instructive comments from QMC
- Sample procedures with guidance on how to write them effectively
- Required references that meet current codes and standards for your library
- Answers to over 100 frequently asked questions
- Samples of internal audits and more

Make QMC Online your first stop when considering AISC Certification, or call 312.670.7520.

### AISC Quality Certification

Our **hands-on** experience...
Our **on-site** guidance and training...

Together they make getting and using AISC Certification much faster, easier and more economical.

### **JAMES M. MOONEY & ASSOCIATES**



### Call 941-223-4332 or 941-485-7172 immoon94@aol.com

Experience Counts in AISC Certification...Just Ask Our Clients

### A&P DETAILING AND DESIGN, S.A.

STRUCTURAL & MISC. STEEL DETAILING

### Tekla Structures 3D Modeling Services MATERIAL TAKE-OFF AND JOB ESTIMATES

> 62-03 ELIOT AVE, MIDDLE VILLAGE, NY 11379 L. ARANA 646.315.5951/718.554.3094 larana@apdetailing.com www.apdetailing.com

### WANTED

QUALITY-CONSCIOUS, GOAL-ORIENTED, AND PROACTIVE STRUCTURAL STEEL FABRICATORS COMMITTED TO QUALITY WANTED FOR AISC QUALITY CERTIFICATION PROGRAM. AISC is looking for capable fabricators of any size interested in reinforcing their positive reputation within

size interested in reinforcing their positive reputation within their local market by implementing a quality management system addressing all aspects of their business processes. Candidates must be willing to subject themselves to a rigorous annual third-party independent audit. Successful candidates will become AISC Certified, proving to specifiers, contractors and owners that they have the personnel, experience, equipment and knowledge to deliver a quality product. All interested applicants please contact AISC at 312.670.7520 or certinfo@aisc.org.

### Glenn Ihde & Company Structural Steel Detailing Tekla Structures 3D Modeling Services

QPP Firm – Professional Engineer and NISD Certified Detailers on Staff
Competitive Rates – Quick Turnarounds – All Sizes and Types of Projects Fabrication
Equipment Control Data – Electronic Drawing File Transfers
Staffing to Meet Project Requirements – AISC & NISD Member
4500 W Eldorado Pkwy, Suite 1700, McKinney, Texas 75070

www.gihde.com glenn@gihde.com T-972-964-3310 F-972-867-2198

### marketplace

### **CURVED WF BEAMS**

**USE DIAMOND CURVE!** 

40% More Ductility, Minimizes Distortion Structural, Architectural

### MARKS METAL TECHNOLOGY

10300 SE Jennifer, Clackamas, OR 97015 Info@MarksMetal.com www.marksmetal.com 800.526.1031

### WE BRING METAL TO LIFE





### 100 TEKLA Structure Licenses WITH TECHFLOW

Applying 3D Technology For Detailing **24x7** 

Phone: 770.495.1446

Fax: 770.495.1448

email: techflowus@techflowengg.com

Website: www.techflowengg.com

### employment

**AceCad Software** offers a competitive salary along with 100% paid health and dental benefits, 401K, a total of 6 weeks paid time off per year.

Position: StruM.I.S. Software Sales Consultant

### **Duties and responsibilities:**

- Researching Potential Sites/Prospects
- Organizing campaigns in coordination with Marketing Department
- Presenting Company, Software and Solution Services
- Maintaining Relationships with the Customer base
- Traveling Required
- Provide technical support on StruM.I.S. to our customers in North and South America

Candidates will require excellent written and verbal communication skills, with the ability to multi-task. Attention to detail, enthusiasm and the will to succeed are necessary to fulfill this demanding role, but knowledge of the Structural Steel Industry is essential.

2-3 years experience using fabrication software for the steel industry is required.

#### Equal opportunity employer.

Please apply in writing with an up-to-date resume to **sales@strucad.com** 

### RECRUITER IN STRUCTURAL/MISCELLANEOUS STEEL FABRICATION

**ProCounsel,** a member of AISC, can market your skills and achievements (without identifying you) to any city or state in the United States. We communicate with over 3,000 steel fabricators nationwide. The employer pays the employment fee and the



interviewing and relocation expenses. If you've been thinking of making a change, now is the time to do it. Our target, for you, is the right job, in the right location, at the right money.

### **PROCOUNSEL**

Toll free: 866-289-7833 or 214-741-2014 Fax: 214-741-3019 mailbox@procounsel.net To advertise, call 231.228.2274 or e-mail gurthet@modernsteel.com

### TEKLA STRUCTURES DETAILING MANAGER

CAL WEST STEEL DETAILING is looking for an experienced Tekla Structures Detailer/Checker to run our Tekla Structures Department.

Ideal Candidate would have multiple years of Detailing and Checking Experience with several years of Tekla Structures Experience. Cal West offers Excellent Pay, Great Benefits including 401K and a Relocation Allowance. A Starting Bonus will be paid to the right candidate.

Cal West Steel Detailing
4495 Stoneridge Drive, Pleasanton, CA 94588
Or email to: bobs@cwsteeldetailing.com

### **Structural Steel Division Manager**

Top 25 ENR General Contractor is seeking an experienced Structural Steel Division Manager. Qualified candidates must have 15 years experience in structural steel erection in commercial building and or heavy highway, preferably both. Must have the capability to develop new business, estimate, project manage, and recruit key personnel. Ideal candidate will provide leadership, team building, develop talent, and create a successful atmosphere.

Offered are competitive compensation and benefits, Matching 401K, and a successful organization. Interested candidates please email resumes to: **cbecker@fortcalumet.com** 

### Structural & Misc. Steel Fabrication

Our organization has been recruiting for the Structural and Misc. Steel Fabricating industry for over 20 years. Current positions include:

- Project Manager
- General Manager
- Quality Control

- Plant SuperintendentsChief Draftsman
- Estimators
- DetailersCheckers

Please send resume to: Richard Stauffer

United Employment Associates, P.O. Box 8, East Texas, PA 18046 phone: (610) 437-5040 fax: (610) 437-9650 e-mail: rstauffer@unitedemployment.com www.unitedemployment.com



### **LOOKING FOR A NEW START IN 2008?**

#### Are you a structural engineer looking for a different path?

We specialize in matching great structural engineers with unique opportunities that utilize their talents, help them achieve their goals, and have a lot more FUN!

### Why have SE Solutions help you find a unique opportunity?

- We have over 25 years of experience working with structural engineers.
- We have relationships with people responsible for hiring decisions with engineering companies all over the United States.
- We will save you time and provide additional information and help during the process of finding a new job that you couldn't find anywhere else.

Call us TODAY to learn more about how we can help you!

#### SE Solutions, LLC

Main Office **Brian Quinn, P.E.** (616) 546-9420

West Coast Office Lisa Willard, EIT (805) 482-8436

www.FindYourEngineer.com

### AISC Engineering & Research Dept.

Staff Engineer

If you are looking for an entry-level position, have good people skills, and like new challenges, AISC has an opportunity available. AISC is now seeking applicants for a Staff Engineer position in the AISC Engineering & Research Dept. This is a unique opportunity to work with issues in structural research as well as steel fabrication. You will work with the top educators in the North American steel design and construction industry and will be in a position to establish yourself as an expert in steel design. The position will allow you to use your technical training to develop and promote research and industry issues that benefit the entire structural engineering community and structural steel industry.

Applicants should have a BS degree, with a structural emphasis, in architectural or civil engineering, and must be qualified to work in the U.S. AISC provides a great working environment offering professional development opportunities and a competitive salary and benefits package.

Send resumes to C. Becker at **becker@aisc.org** 



**Ramar Steel**, a member of AISC, is one of western New York State's most reputable structural steel fabricators and erectors. Ramar is located in Rochester—on the shores of Lake Ontario and within the Finger Lakes region of the state. We are seeking experienced, talented and motivated steel industry professionals to support our plant expansion and sales growth. We are currently seeking:

- Detailer minimum 2-3 years structural steel detailing experience (Tekla / XSteel preferred)
- Project Managers to manage multiple fabrication and erection projects
- Fabrication Manager Hands-on professional to oversee shop operation of 15-20
- Estimators Minimum 5 years structural steel estimating experience required

Ramar Steel offers excellent pay, generous medical, dental and life insurance benefits, 401K, profit sharing and bonuses.

Send resumes to mar@ramarsteel.com or fax to 585.263.2734.

### Have You Visited the NEW

### **Modern Steel Construction**

web site?

### www.modernsteel.com

### **BIM Modeler**

Progressive structural engineering firm seeks a structural 3-D Building Information Modeler interested in an opportunity to join an innovative team involved with adopting a more advanced technological approach to designing, documenting and constructing building facilities across the country.

Responsibilities will include working with design and construction teams in a 3D environment to design and coordinate multi-discipline building design projects and assist the interoperable flow and use of 3D models to the construction team. Qualifications include 3-5 years Tekla detailing or Revit modeling experience and fluency in Autocad.

Submit resume and project biography to Structural Consultants, 3400 E. Bayaud Ave. #300, Denver, CO 80209, fax 303-333-9501. Email: joe@sci-denver.com.

### Project Manager/Detailers/Checkers

**SteelStar Corporation** is an aggressively growing detailer/fabricator/erector (16-20 Million/Annually) in the Denver Metro area along the beautiful Front Range of Colorado.

#### Project Manager (\$65-95K Annually)

We are currently seeking an aggressive and skilled project manager with experience in low to mid rise commercial/industrial, miscellaneous and architectural/ornamental metals projects from 500-2000 Tons.

The successful candidate must have a minimum of five years experience in construction project management. Requirements to include, but are not limited to; excellent computer/technical skills, organizational skills, scheduling skills and documentation skills as well as great communication and customer service skills. Most important of all, the successful candidate must have a great attitude! An Associates or Bachelors degree is required; this may be waived in lieu of experience. Relocation to Colorado Required. Must have excellent references and project track record.

#### Detailers/Checkers (\$15-\$35 Per/Hour)

We are currently seeking (3) skilled Tekla (Xsteel) and (4) AutoCAD/AutoSD detailers & checkers with experience in low to mid rise commercial/industrial, miscellaneous and architectural/ornamental metals projects up to 2000 Tons.

The successful candidate must have a minimum of (3) year's structural and/ or miscellaneous steel detailing experience. Requirements include, but are not limited to; excellent computer/technical skills and Tekla or AutoCAD experience. Most important of all, the successful candidate must have a great attitude! Relocation to Colorado Required. Candidate must be able to provide excellent references and drawing examples. All candidates must be currently eligible to work in the United States.

We offer the security of a financially stable company, profit sharing, competitive wages, relocation reimbursement, medical benefits, 401K, paid holidays and paid leave time, and most of all, a fun place to work with opportunity for advancement. Please send resume to: SteelStar Corporation, P.O. Box 218 - Dacono, CO 80514 Attn: Employment - Fax 303.828.4092 or email employment@steelstar.com. Visit us @ www.steelstar.com.

# THE FUTURION TO THE NUMBER NOW

### RISA-BD VERSION 7

The new features in RISA-3D Version 7, from the implementation of the latest design codes to a faster, more robust sparse solver, enable engineers to work more productively and stay ahead of the competition.




### AISC 13TH EDITION STEEL CODE


RISA-3D Version 7 incorporates the new Direct Analysis Method of the AISC 13th Edition. This version allows users to design for either the ASD or LRFD requirements of this new steel code.

### ACCELERATED SPARSE SOLVER

RISA-3D Version 6 used a Skyline solver, which is the current industry standard. The new accelerated sparse solver offered in RISA-3D Version 7 can solve models up to 100 times faster, making RISA-3D the future of structural analysis.

The Concourse J of the Miami International Airport took nearly 11 minutes to solve and required more than 600 MB of storage space using the current industry standard solver technology. The accelerated sparse solver in RISA-3D version 7 solved the same model in 6 seconds and required only 2MB of storage space. That's more than 100 times faster!





### SOLID ELEMENTS

RISA-3D Version 7 now offers 8-node solid elements which opens a whole new range of modeling and analysis possibilities. This new element combined with RISA-3D's automatic meshing features opens up a whole new world of modeling and analysis possibilities!

Integration with RISAFoundation and Revit Structure 2008 as well as the implementation of the 2005 NDS wood code make RISA-3D Version 7 the right choice for today and for the future.

Try RISA-3D today and see how good structural engineering software can be!





### REGISTER NOW FOR SOFTWARE TRAINING



### **WEB-BASED SOFTWARE TRAINING** FOR ETAB



### Steel Design for AISC360-05/IBC2006

This three-hour online course is intended for ETABS users who want to become more familiar with the new steel design provisions that have been adopted into the AISC360-05/IBC2006 code. We will cover topics related to steel beam and column design, including the direct analysis method, effective length method, calculations of nominal strength and design of members with combined forces.

Fee: \$300

Thursday, January 24 9:00 am - 12:00 pm (Pacific Time) Thursday, February 7 2:00 pm - 5:00 pm (Pacific Time)



### **ETRES** Concrete Shear Wall Design

This three-hour online course covers topics related to shear wall design using ETABS, including meshing. Other topics to be discussed include uniform reinforcing, simplified tension/compression reinforcing, design for torsional effects in shear walls, and flexural and shear design for piers and spandrels.

Fee: \$300

Thursday, January 24 2:00 pm - 5:00 pm (Pacific Time) Thursday, February 7 9:00 am - 12:00 pm (Pacific Time)

> To register, visit www.csiberkeley.com Reserve your space today!



### **COMPUTERS & STRUCTURES, INC.** Software for Structural and Earthquake Engineering

1995 University Avenue, Berkeley, CA USA 94704 tel: 510/649-2200 fax: 510/649-2299 email: info@csiberkeley.com web: www.csiberkeley.com