

MSC

MODERN STEEL CONSTRUCTION

September 2008



Angular Atrium Anchors New Museum

IN THIS ISSUE
School Projects
Steel Joists
Steel Bridge News



"CUSTOMers"

Custom Projects.

Custom Thinking.

Think CMC Joist & Deck.

We provide fast and accurate detailing, no excuses approval process management and rapid RFI resolution. We strive to understand our CUSTOMers' specific job requirements and together we diligently work towards a unique solution.

Our experience paves the way.



CMC Joist & Deck

"Manufacturers of



United Steel Deck products"

For further information on any of our products or for the nearest CMC Joist & Deck sales representative, contact us at:

CMC Joist & Deck
11777 Katy Freeway, Suite 305 North, Houston, TX 77079
deborah.hoover@cmc.com
www.cmcjd.com



CMC Joist & Deck Manufacturing Facilities:

JOIST: Hope, AR • Starke, FL • Iowa Falls, IA • Juarez, MX • Fallon, NV • New Columbia, PA • Eastover, SC DECK: Peru, IL • So. Plainfield, NJ • Rock Hill, SC

Presenting projects by Tekla customers worldwide:

Structures that Stand Out



1: Swan Bell Tower, Australia

2: Torre Agbar, Spain

3: Hotel Hilton, Finland

4: Hearst Tower, USA

5: "The Tower", United Arab Emirates

6: Panorama Tower, Finland

7: Financial Center, China

8: Khalifa Sports City Tower, Qatar

9: Burj Dubai, United Arab Emirates

10: 30 St Mary Axe, United Kingdom

11: Menara Telekom, Malaysia

12: Rose Rotana Suites, United Arab Emirates

13: Willis Building, United Kingdom

14: Finnforest HQ, Finland

15: China Central Television Building, China

16: Padua NET Center building, Italy

17: Denver Art Museum, USA

Tekla Structures is Building Information Modeling (BIM) software that streamlines the delivery process of design, detailing, fabrication, and construction organizations. The software easily integrates with other systems such as architectural, MEP process layouts as well as analysis and design solutions. Use the same model to save time and ensure quality projects. Thousands of Tekla Structures Users have successfully delivered BIM-based projects in more than 80 countries around the world. For more information call 1.877.TEKLA.OK



TEKLA®


www.tekla.com



September 2008

MSC

MODERN STEEL CONSTRUCTION



university projects

25 Artistic Achievement

BY MARIO ELCID, P.E., AND
BOB VARGA, AIA, LEED AP

The arts campus at Western Michigan University finds the "missing link" with a dynamic new building that complements and enhances its neighbors.

29 A New Link to Learning

BY BRENT BANDY, P.E., LEED AP
An expanded bridge on Georgia State University's campus brings two library buildings together as one.

33 Moving In

BY NAT OPPENHEIMER, YEGAL SHAMASH, AND
BEN ROSENBERG

Dickinson School of Law, formerly an independent entity, will soon have its own building on the Penn State campus.

k-12 projects

36 Facilitating Creativity

BY TERRY TSANG, S.E., AND GARY GIDCUMB, R.A.
Eye-catching architecture and innovative structural design are all but requirements when building a school geared toward the arts.

museum projects

41 A Model Museum

BY LISA MINAKAMI, P.E., AND
DERRICK ROORDA, P.E., S.E.

Extensive 3D modeling helped to create and navigate the framing for a new art museum in Virginia.

steelwise

45 Stability Analysis: It's not as Hard as You Think

BY CHRISTOPHER M. HEWITT, S.E.

The Direct Analysis Method is a good choice for stability design—and with a little guidance, it can be a relatively simple process.

quality corner

49 The Quality Diet: Building A Healthy Business

BY TIMOTHY J. FOLKERTS

Implementing a corporate quality system is much like dieting—and there's a lot more to both of these processes than you might think.

business issues

55 A Fair and Balanced Offer

BY TIM R. JOHNSON

Framing a job offer properly can be the difference between landing a top-notch candidate and scaring him away.

industry innovations

57 Supporting Role

BY PERRY S. GREEN, PH.D., AND
TIM HOLTERMANN, P.E.

Erecting steel joists without proper bridging can cause it all to come crashing down.

steel bridge news

61 Remember the Red River Valley

BY LARRY A. ERICKSON, P.E.

Part replacement span, part revitalization tool, a new bridge over the Red River of the North connects two Upper Midwest towns in North Dakota and Minnesota.

departments

- 6 EDITOR'S NOTE
- 9 STEEL INTERCHANGE
- 12 STEEL QUIZ
- 19 NEWS & EVENTS

resources

- 64 NEW PRODUCTS
- 66 MARKETPLACE
- 67 EMPLOYMENT

topping out

70 Notes from an E in an A/E World

BY ASMA MONIN

Being an engineer at an A/E firm involves lots of challenges—but also plenty of opportunities that might not be available at an engineering firm.

ON THE COVER: The Art Museum of Western Virginia in Roanoke. Photo: Randall Stout Architects, Inc.

MODERN STEEL CONSTRUCTION (Volume 48, Number 9). ISSN 0026-8445. Published monthly by the American Institute of Steel Construction (AISC), One E. Wacker Dr., Suite 700, Chicago, IL 60601. Subscriptions: Within the U.S.—single issues \$6.00; 1 year, \$44; 3 years \$120. Outside the U.S.—single issues \$9.00; 1 year \$88; 3 years \$216. Periodicals postage paid at Chicago, IL and at additional mailing offices. Postmaster: Please send address changes to MODERN STEEL CONSTRUCTION, One East Wacker Dr., Suite 700, Chicago, IL 60601.

AISC does not approve, disapprove, or guarantee the validity or accuracy of any data, claim, or opinion appearing under a byline or obtained or quoted from an acknowledged source. Opinions are those of the writers and AISC is not responsible for any statement made or opinions expressed in MODERN STEEL CONSTRUCTION. All rights reserved. Materials may not be reproduced without written permission, except for noncommercial educational purposes where fewer than 25 photocopies are being reproduced. The AISC and MSC logos are registered trademarks of AISC.






The power to innovate

Fabrication Information Modeling - in the palm of your hand

Offering an integrated model based software solution
for all the activities of a steelwork fabricator.



Greater profitability

Increased productivity

Faster decision-making

Team co-ordination

Combining StruCad with StruM.I.S. .NET enables competitive advantages for all involved in a structural steelwork supply chain. Advanced model based technology simultaneously links all departments and project team members with a database of fabrication information.

StruCad

The Worlds Leading 3D
Structural Steel Detailing System

+

StruM.I.S.NET

The Ultimate Management Information System
For Steelwork Fabricators

AceCad
SOFTWARE

W: www.strucad.com

T: 610 280 9840

E: sales@strucad.com

editor's note



IF YOU'RE UNDER 40, CHANCES ARE YOU DON'T KNOW FROMY ROSENBERG. Under his quiet guidance, AISC has developed an extensive—and impressive—array of programs for both students and faculty. And while some of the programs pre-date him, his efforts have fostered and grown these important activities.

If you were a civil engineering student during the past two decades, you were probably invited to participate in your school's student steel bridge building competition. And if you did, chances are good that you met Fromy at the competition. This wonderful program pits teams of students against each other in the design, fabrication, and erection of a one-tenth scale bridge. The bridges are designed to be erected in just minutes—and also have minimal deflection when loaded with 2,500 pounds of weights. About 2,000 students participate in this program annually—or nearly 36,000 during Fromy's career!

Probably the most visible presence AISC has on college campuses comes in the form of steel teaching sculptures. These 8-ft-high forms (some are as tall as 15 ft) include most common structural shapes and connections and allow students to see and touch what they learn about in the classroom. The sculptures are donated by local AISC member fabricators and during Fromy's tenure, nearly 150 of these beautiful artworks have been installed.

AISC's most popular program for students, though, is its discounted manual program. Recognizing the importance of every engineering student having a steel manual and also the limited budgets that most students have, Fromy administers a program that works with faculty members and not only discounts the purchase price of the manual but also doesn't charge for shipping (quite a consideration when you consider the weight of the manual!).

One of Fromy's big success stories has been the advent of a program AISC conducts in conjunction with the Association of Collegiate Schools of Architecture. This eight-year-old design competition lets teams of students explore a variety of design issues related to the use of steel in design and construction. The program continues to grow and this year approximately 320 students from 30 universities participated.

Of course, Fromy's efforts aren't all directed just at students. Fromy has also been involved in AISC's Adopt-A-School program, where fabricators, producers, and service centers work closely with a specific school. And he's directed our faculty workshop program and administered our scholarship program. In addition, Fromy has put together an extensive set of teaching aids (which, while targeted to the university setting also have applicability in the professional office). To learn more about all of these programs, simply visit www.aisc.org and click on learning opportunities.

Fromy has recently retired, and the entire AISC and steel community will miss him.



SCOTT MELNICK
EDITOR

MSC

MODERN STEEL CONSTRUCTION

Editorial Offices

1 E. Wacker Dr., Suite 700
Chicago, IL 60601
312.670.2400 tel
312.896.9022 fax

Editorial Contacts

EDITOR & PUBLISHER
Scott L. Melnick
312.670.8314
melnick@modernsteel.com

SENIOR EDITOR
Geoff Weisenberger
312.670.8316
weisenberger@modernsteel.com

DIRECTOR OF PUBLICATIONS
Areti Carter
312.670.5427
areti@modernsteel.com

GRAPHIC DESIGNER
Kristin Egan
312.670.8313
egan@modernsteel.com

AISC Officers

CHAIRMAN
Rex I. Lewis
VICE CHAIRMAN
David Harwell
TREASURER
Stephen E. Porter
SECRETARY & GENERAL
COUNSEL
David B. Ratterman
PRESIDENT
Roger E. Ferch, P.E.

VICE PRESIDENT
Charles J. Carter, P.E., S.E.

VICE PRESIDENT
John P. Cross, P.E.

VICE PRESIDENT
Louis F. Geschwindner, Ph.D., P.E.

VICE PRESIDENT
Scott L. Melnick

Advertising Contact

Account Manager
Louis Gurthet
231.228.2274 tel
231.228.7759 fax
gurthet@modernsteel.com

For advertising information, contact Louis Gurthet or visit
www.modernsteel.com

Address Changes and Subscription Concerns

312.670.5444 tel
312.893.2253 fax
admin@modernsteel.com

Reprints

Betsy White
The Reprint Outsource, Inc.
717.394.7350
bwhite@reprintoutsource.com

SDS/2
DESIGN DATA



ONE CHANGE LEADS TO 1,000 OTHERS.



Only SDS/2 lets you make them simultaneously.

Even the smallest adjustment to a structure can send detailers scrambling to recalculate hundreds, if not thousands, of connections. With the connection intelligence of SDS/2, every time you make one change, the system automatically identifies every affected connection throughout the structure. Even the fabrication drawings and reports are automatically updated. SDS/2's connection intelligence improves productivity and accuracy, delivering a great return on your software investment. Contact Design Data today for more information.

www.sds2.com

800.443.0782

402.441.4000

e-mail: info@sds2.com

What have you been searching for today?

FIND 10 THINGS A FABRICATOR SEARCHES FOR WORD SEARCH PUZZLE

Clues & answers @ www.fabtrol.com/search



Stop searching and find answers instantly with **FabTrol MRP** software



How much time do you spend searching for answers?

A change order has you hunting to see if the material has been cut. The erector calls and wants to know if a certain assembly has shipped. A production mistake has you searching the stockyard for a replacement bar. Meanwhile, you're looking everywhere for the phone number of a new contractor. If you find the answers by noon, then you can start what you intended to do this morning.

Make it a habit to never waste time looking for answers

Steel fabricators notoriously spend a lot of time tracking down details. One of the seven habits of highly successful fabricators is to minimize the time spent searching for details. The key is to put the right tools in place to ensure that the information you need is quickly accessible. To learn how FabTrol MRP can help you stop searching and find answers instantly, call **(888)FABTROL**.

A better way to manage fabrication

Download our free e-book

**The Seven Habits of Highly
Successful Steel Fabricators**

www.fabtrol.com/success

FabTrol MRP

A better way to manage

FabTrol Systems, Inc. • 1025 Willamette St., Suite 300, Eugene, OR 97401 • (888) FABTROL • Fax: (541) 485-4302 • www.fabtrol.com

Estimating ■ Drawing Management ■ Material Management ■ Production Management ■ Shipping

IF YOU'VE EVER ASKED YOURSELF "WHY?" about something related to structural steel design or construction, *Modern Steel Construction's* monthly Steel Interchange column is for you! Send your questions or comments to solutions@aisc.org.

KL/r Modified for Single-Angle

A question and answer on this subject appeared in the January 2008 Steel Interchange (reprinted below). LeRoy Lutz, a member of the AISC Specification Task Committee covering the design of members, was kind enough to provide the following supplementary discussion pertaining to the design of single-angles: Single-Leg Angles per E5.

This is a response to the comment made with regard to single-angle slenderness in section E5 of the AISC *Specification* in the January 2008 issue of MSC.

- First, I was unsure what the designer meant when he indicated calculating KL/r_z (I presume that he meant L/r_z). One considers the KL/r to be an equivalent L/r_z when designing.
- The 0.95 and $0.82L/r_z$ limits given in E5 (a) and (b) are in the paragraph that addresses unequal-leg angles with the long leg projecting and does not apply to equal-leg angles.
- The limits of 0.95 and $0.82L/r_z$ for equal-leg angles would occur when the KL/r is at about the upper limit of 200, so that there would be no need to check those limits for equal-leg angles. For unequal-leg angles with the short leg projecting, those limits would occur well beyond an L/r of 200.

Here is a short summary for stocky and slender equal-leg angles:

- For an L3×3×¼ equal-leg angle with L/r_z of 30 (and L/r_x of 19), the KL/r (i.e. L/r_z) calculated from (a) would be 86.2 and from (b) would be 75.2. The axial load design at these values of slenderness would account for strength reduction based on the load's eccentricity reduced some by the end restraint (as compared to a pinned-end member).
- For an L3×3×¼ equal-leg angle with L/r_z of 160 (and L/r_x is 101), KL/r (i.e. L/r_z) calculated from (a) would be 158 and from (b) would be 146. The axial load design at these values of slenderness account for a slight strength increase due to the end restraint and reduction based on the load's eccentricity (as compared to a pinned-end member).

LeRoy Lutz

Original question/answer from the January 2008 Steel Interchange:

For a single-angle compression member, I followed AISC specification section E5 to calculate the modified KL/r . I also calculated KL/r_z , and it turns out to be greater than KL/r modified. Should I use the larger of the two (KL/r modified, or KL/r_z) in section E3?

If you are in compliance with E5 (including attaching the angle using the longer leg) then you can use the limits on L/r_z that are provided at the ends of the both sections (a) and (b). In the first case the limit is $0.95L/r_z$ and in the second case it is $0.82L/r_z$. In essence, with your condition, you are still designing for KL/r_z but with a K value of less than 1.0 because of the higher end restraints.

Amanuel Gebremeskel, P.E.

Flexural Capacity of Channels

Why are the maximum strong and weak axis bending stress values for channels limited to $0.6F_y$ and $0.66F_y$ respectively? The weak axis limit seems particularly conservative given that compact, doubly symmetric sections and plate have a $0.75F_y$ limit.

I am not sure which document you are looking at, but in the 2005 AISC *Specification* (available at www.aisc.org/2005spec) channels in strong axis bending have an ASD limit of $0.66F_y$ and $0.9F_y$ for weak axis bending if you approximate a lower bound shape factor and use S to make the comparison to older versions of ASD. The derivation for these is as follows:

For the weak axis, $M_n / \Omega = 0.9F_y Z_y / 1.5 = 0.9F_y (1.5S_y) / 1.5 = 0.9F_y S_y$. This derivation assumes that $Z_y / S_y = 1.5$, which is reasonable for weak axis bending. For strong axis bending a similar derivation using $Z_x / S_x = 1.1$ results in $M_n / \Omega = 0.66 F_y S_x$. These approximations assume a wide-flange cross-section.

Amanuel Gebremeskel, P.E.

Fillet Weld Strength

I am familiar with the method of determining the fillet weld strength using the ASD load approach, but I am having difficulty determining this strength when using the LRFD load approach.

For a simple ASD fillet weld (load at 90° to the fillet) the magic number is 0.9 kips/in. of weld, which is based upon 0.3*70 ksi electrode per 16th of weld.

I noticed in the 13th Edition Manual that the weld strength is increased when the load is at 90° to the fillet. I always thought a weld had the same strength whether a load was in the same direction, along the weld or perpendicular to the weld. The 13th Edition Manual seems to indicate that it is 50% stronger when loaded at 90°.

The increase for direction of load is covered in Section J2.4(a) of the *Specification*. Where the load is oriented at 90°, this amounts to a 50% increase and applies to both ASD and LRFD load approaches.

The weld value in the old versions of ASD was 0.928 kips per 1/16 in. of leg. This comes out to the same Allowable Strength in the ASD approach of the 2005 *Specification*. The Available Strength of Fillet Welded Joints is $0.60F_{EXX}$, regardless of whether the ASD or LRFD load approach is used. (See Table J2.5 of the 2005 *Specification*.)

If the ASD load approach is used, $\Omega = 2.00$, resulting in an Allowable Strength of $0.60F_{EXX}/2.00 = 0.30F_{EXX}$, then this resolves as follows: $(0.30)(70)(0.707)/(16) = 0.928$ kips per 1/16 in.

If the LRFD load approach is used, $\phi = 0.75$, resulting in a Design Strength of $(0.60F_{EXX})(0.75) = 0.45F_{EXX}$, then this resolves as follows: $(0.45)(70)(0.707)/(16) = 1.392$ kips per 1/16 in.

Note that the LRFD Available Strength is always 1.5 times the ASD Available Strength.

Kurt Gustafson, S.E., P.E.

steel interchange

Anchor Rod Push-Out

Section 2.9.1 of Design Guide 1 contains the following statement:

“When designing anchor rods using setting nuts and washers, it is important to remember these rods are also loaded in compression and their strength should be checked for push-out at the bottom of the footing.”

How does one go about calculating the push-out of the anchor through the bottom of the footing?

Another AISC source of information on the subject, Design Guide 10, *Erection Bracing of Low-Rise Structural Steel Buildings*, provides a discussion of anchor-rod push-out. See Section 4.2.7 in that publication.

Kurt Gustafson, S.E., P.E.

Fillet Weld for Single-Plate Shear Connection

My question has to do with single-plate connections to supports. Chapter 10 of the 13th Edition (page 10-101) states “the weld between the single plate and the support should be sized as $\frac{5}{8} t_p$, which will develop the strength of the plate.” Is this a minimum or maximum limit? Should we design the required weld size needed, and then compare to this value? This question stems from the 9th Edition Commentary on single-plate connections (page 4-53) where it stated the weld size need not exceed $0.75t$. Are these (2) requirements discussing the same subject? It seems that the 9th Edition is trying to make sure we have more web thickness than weld, but the 13th Edition Commentary is stating to use an exact amount of weld. Can you shed light on this?

You are correct that the requirement on page 10-101 in the 13th Edition Manual is intended to develop the plate. This means it is a minimum weld recommendation if the designer wishes to develop the strength of the plate, and is based on weld shear rupture. You do not need to calculate a weld size for load and compare. Rather, if the plate is adequate in shear, the weld size is then selected as $\frac{5}{8} t_p$ and will have adequate strength. The idea behind the older $\frac{3}{4} t$ requirement in the 9th Edition Manual was also the same, but it is an older approach based on weld yield that has been dropped in favor of the new approach.

Amanuel Gebremeskel, P.E.

L_p for Non-Compact Shapes

I have a question regarding a value in Table 3-2 of the 13th Edition Manual pertaining to the W21×48 (page 3-17). The listed value for L_p is 6.09 ft, whereas when I calculate the value myself (for a 50 ksi beam) I get 5.86 ft. Can you please review this value and let me know if this is an error?

The number listed in the table for the W21×48 is not an error. A W21×48 is non-compact, and the L_p for non-compact shapes, L'_p , is not calculated per Equation (F2-5). Remember that non-compact shapes are not capable of achieving the full plastic moment. Therefore, a point on the moment versus unbraced length curve is used to define the value M'_p for the shape. See page 3-4 in the 13th Edition Manual for discussion, and the Equation upon which the value of L'_p is based.

Amanuel Gebremeskel, P.E.

ASD or LRFD?

What is the AISC position on use of LRFD or ASD design? It appears that the equations in the 2005 AISC *Specification* can be utilized in the LRFD or ASD method by multiplying by the ϕ factor or dividing by the Ω factor. Is this correct, because people are telling me one cannot use the ASD method anymore? What about the IBC—do you know if they specifically require the use of LRFD?

The governing building code typically specifies load combinations. IBC (and ASCE 7) provide load combinations that can be used with either ASD or LRFD design approaches. IBC 2006 also references AISC 360-05 (the 2005 AISC *Specification*), which provides both ASD and LRFD methods of design.

Therefore, the answer to your question is that you can use either method when using the 2005 AISC *Specification*. Since AISC 360 uses the same equations for both methods, the only differences between LRFD and ASD will be due to variations in the load combinations from ASCE 7 or IBC. Just be sure to use the corresponding set of load combinations.

Amanuel Gebremeskel, P.E.

The complete collection of Steel Interchange questions and answers is available online. Find questions and answers related to just about any topic by using our full-text search capability. Visit Steel Interchange online at www.modernsteel.com.

Kurt Gustafson is the director of technical assistance and Amanuel Gebremeskel is a senior engineer in AISC's Steel Solutions Center. Charlie Carter is an AISC vice president and the chief structural engineer.

Steel Interchange is a forum to exchange useful and practical professional ideas and information on all phases of steel building and bridge construction. Opinions and suggestions are welcome on any subject covered in this magazine.

The opinions expressed in Steel Interchange do not necessarily represent an official position of the American Institute of Steel Construction, Inc. and have not been reviewed. It is recognized that the design of structures is within the scope and expertise of a competent licensed structural engineer, architect or other licensed professional for the application of principles to a particular structure.

If you have a question or problem that your fellow readers might help you solve, please forward it to us. At the same time, feel free to respond to any of the questions that you have read here. Contact Steel Interchange via AISC's Steel Solutions Center:



**Steel
SolutionsCenter**

One East Wacker Dr., Suite 700
Chicago, IL 60601
tel: 866.ASK.AISC • fax: 312.803.4709
solutions@aisc.org

Building strength through diversity.

Gerdau Ameristeel has created an environment of diversity and collaboration through consolidation, providing innovative solutions for the steel industry.

We encourage our employees to contribute creative ideas and to share best practices that further enable us to improve our processes and help solidify our position as the supplier of choice.



www.gerdauameristeel.com



GERDAU AMERISTEEL
TM

steel quiz

LOOKING FOR A CHALLENGE? *Modern Steel Construction's* monthly Steel Quiz tests your knowledge of steel design and construction. Most answers can be found in the 2005 *Specification for Structural Steel Buildings*, available as a free download from AISC's web site, www.aisc.org/2005spec. Where appropriate, other industry standards are also referenced.

This month's Steel Quiz was provided by the Steel Joist Institute. Sharpen your pencils...

It's all about the HOLE

The best tooling makes the best holes.



American Punch
Punches & Dies, Shear Blades, Portable
Punch Units, Magnetic Drills, Annular
Cutters and Structural Steel Drills

End of story.



1655 Century Corners Parkway, Euclid, Ohio 44132 800-243-1492 Fax: 800-261-6270
sales@americanpunchco.com www.americanpunchco.com

- 1 How can I locate the reaction at the end of an open-web steel joist at the center of a beam?
- 2 Are standard joists designed to resist any concentrated loads not at a panel point?
- 3 What special bridging requirements apply when the joist is detailed with bottom-chord bearing, or when a joist has a full-depth cantilevered end condition?
- 4 Can joists be designed for a moving point load at top and/or bottom chords?
- 5 True or False: KCS joists are designed so that a single 200-lb concentrated load can be placed between panel points without the need for reinforcing with an additional web.
- 6 Is a row of uplift bridging required for roof joists designed with 10 psf gross wind uplift and 15 psf dead load?
- 7 Can open-web steel joist size be controlled by the required fire rating?
- 8 What is the minimum bearing length when installing a K-Series joist that is detailed to have a 2½-in. R Type top-chord extension, and the connection detail shows the full length of the bearing seat and extension resting on the steel support?
- 9 What is the minimum bearing seat depth (height) for an LH-Series joist installed at a 1:12 slope?
- 10 What is the minimum number of rows of bridging required for a 26K8 with a span length of 46 ft-8 in.?

TURN TO PAGE 14 FOR ANSWERS

XTREMELY FLEXIBLE XTREMELY LEAN

ALL FROM ONE
***SMART
MACHINE***

***Cut Slots,
Rip Beams,
Piece Label,
Layout Marks***

***Cope, Notch
and Strip***

***Cut to Length
and Miter***

***Produce
AISC-Approved
Bolt Holes***

All these cuts were made in one pass,
on one machine, from one drawing
file, by one operator.

PythonX tackles all shapes - BEAMS, HSS, Channel, Angle and Plate. It eliminates material handling, eliminates errors, uses the least floor space, and slashes process time.

PythonX profits beat drilling + sawing every time. Learn how:


www.pythonx.com
for a free DVD call 905-681-9622

PythonX
SQUEEZING THE COST
OUT OF STRUCTURAL FABRICATION

A Product of

**BURLINGTON
AUTOMATION**

SDI and SJI Joint Seminars



If you are an engineer, architect or design professional, we invite you to attend one of our upcoming STEEL seminars jointly sponsored by the **Steel Deck Institute** and the **Steel Joist Institute**. Don't miss this unique chance to learn from steel deck and steel joist engineering professionals. You will be exposed to the most recent information on designing and specifying with steel deck and steel joists. These seminars will provide an opportunity to update, refresh or learn about building design with these efficient and time proven structural components.

EVENT HIGHLIGHTS:

- CEUs or PDHs awarded
- Copy of SDI Design Manual No. 31, Composite Deck Design Handbook, Roof Deck Construction Handbook, Designing with Steel Form Deck White Paper and SJI 42nd Edition Catalog provided each attendee
- Discount offer for new SDI Diaphragm Design Manual, DDM03 - Only available to seminar attendees
- Five seminar lectures including design of steel joists and deck for lateral diaphragm loads
- Continental breakfast and lunch included
- Question and answer opportunities

DATES:

BOSTON, SEPTEMBER 2008
CINCINNATI, OCTOBER 2008
JACKSONVILLE, NOVEMBER 2008

Register today at www.sdi.org
to learn more about specifying and
designing with steel deck and joists.



Steel Deck Institute

P.O. Box 25 • Fox River Grove, IL 60021 • (p) 847.458.4647

steel quiz

ANSWERS

- 1 Provide a note on the drawing such as, "Joist manufacturer to proportion the joist such that the working point is centered on the support." Note that the bearing depth may have to be increased to accomplish this. Conservatively, for every inch you increase the bearing depth, you get an extra inch of clearance to the end diagonal web. For K-Series joists, there is normally only 4 in. of clearance. For LH-Series, there are 6 in. For every additional inch you need, deepen the seats an inch.
- 2 No. Any additional loading should be taken into account when specifying the uniform loads. Otherwise, request that the joists be designed for a concentrated load at any panel point, or at any location along the joist top or bottom chord.
- 3 A row of diagonal bridging must be located near the support for lateral stability. This bridging must be installed as the joist is erected.
- 4 Yes. The joist design will be designed for the worst condition for each member in the joist for the load applied anywhere along the length of the joist.
- 5 False. Chord bending due to concentrated loads must be handled with an extra web member shop- or field-applied for K-Series (and KCS*), LH- and DLH-Series. *Note: KCS joists are a subset of K-Series joists.
- 6 Yes, using ASCE 7-05 load combinations:

In LRFD, net uplift = $0.9D - 1.6W = 0.9(15) - 1.6(10) = -2.5$ psf

In ASD, net uplift = $0.6D - W = 0.6(15) - 10 = -1$ psf
- 7 Yes. Several Underwriter's Laboratories (UL) designs have a minimum joist size, as well as minimum depth and weight per foot, maximum spacing, minimum bridging size, or minimum element size. In addition, when a UL design requires a reduction in the design stress level of a steel joist, the specifying professional must apply the proper stress level reduction in the selection process.
- 8 Five inches. The SJI *Standard Specification for Open Web Steel Joists, K-Series*, Section 5.3(b) states that the joist "shall extend a distance of not less than 2½ in. over the steel supports." This does not consider the joist extension. Because the R Type extended end is fully supported on the steel, it also must be considered when calculating the required bearing length for the installed joist.
- 9 Six inches. This is given in the table "Sloped Seat Requirements for Slopes 3/8:12 and Greater, LH- and DLH-Series Steel Joists" found in the Accessories and Details section of the 42nd Edition *SJI Catalog*.
- 10 Four rows. Reference SJI *Standard Specifications for Open Web Steel Joists, K-Series*, Table 5.4-1. Note that this joist span length is also in the red shaded area of the SJI Load Tables; therefore, one of these bridging rows nearest mid-span must be bolted cross bridging.

Anyone is welcome to submit questions and answers for Steel Quiz. If you are interested in submitting one question or an entire quiz, contact AISC's Steel Solutions Center at 866. ASK.AISC or at solutions@aisc.org.



Steel
SolutionsCenter

LEADER IN CONNECTION DESIGN SOFTWARE SINCE 1984

DESCON

The Ultimate Advantage in Connection Design

Excellent Quality * Easy to Learn * Simple to Use * Outstanding Technical Support


DESCONWIN * DESCONBRACE

AISC SPECIFICATION 2005 * SEISMIC PROVISIONS 2005



ASD * LRFD * METRIC (SI) * IMPERIAL

**SHEAR AND MOMENT CONNECTIONS * COLUMN AND BEAM SPLICES * BRACED FRAME CONNECTIONS
PREQUALIFIED SEISMIC MOMENT CONNECTIONS**

NEW
ANSI/AISC 358-05 IMPLEMENTED
RBS MOMENT CONN. DESIGN
SMF & IMF



NEW
ANSI/AISC 358-05 IMPLEMENTED
END PLATE MOMENT CONN.
4E, 4ES, 8ES SMF & IMF



Omnitech Associates, Inc.

www.desconplus.com

info@desconplus.com * 1-888-8DESCON * 1(510) 658-8328 * Fax: 1 (510) 595-0373



WHY OUR
NUTS & BOLTS
— ARE MORE THAN —
NUTS & BOLTS.

Even our simplest products are far from basic. Not only do we manufacture a wide range of high-strength construction nuts, bolts, and Tru-Tension™ assemblies, but beyond that we stock a variety of grades, sizes and finishes to meet your not so standard needs. On time. On budget. Plus, our fasteners are made in the U.S.A. and 100% traceable. So no matter where or when a question arises, we'll find the answer. Because the smaller the detail, the harder we work to take care of our customers.

It's Our Nature.®



— Visit www.nucor-fastener.com or call 1-800-955-6826 —

YOUR BENDING EXPERTS

Sun Valley Music Pavillion in Sun Valley, ID.
220,000# of pipe rolled ranging from 10" Sch80 to 10" XXH

STRUCTURAL & PIPE BENDING



**LOW DISTORTION
TIGHT RADII BENDS**



**SPIRAL STAIRCASES
AND STRINGERS**

Albina

Pipe Bending Co., Inc.

BENDING THE RULES™

12080 SW Myslony St.
Tualatin, OR 97062

Phone: (503) 692-6010 Fax: (503) 692-6020

Toll-Free: (866)ALBINA-8 (866) 252-4628

E-mail: info@albinapipebending.com

Website: www.albinapipebending.com



PROJECTS

Covering the Colts

On September, 7 the Indianapolis Colts will play their first game at brand-new Lucas Oil Stadium. Designed by architect HKS, Inc., the stadium seats 63,000 (and can be expanded to 70,000 when it hosts the Super Bowl in 2012). The playing field is 25 ft below street level, allowing fans unobstructed views from their easily accessed seats.

At the Colts' first game in its new home—against the Chicago Bears—fans will be sitting beneath an engineering milestone. The stadium's steel roof, designed by structural engineer Walter P Moore, is the first ever to divide lengthwise into two retractable panels—160 ft long × 600 ft wide and 2.9 million lb each—with each half sliding down the steep, gabled roof of the stadium into the open position. A 960-hp cable drum drive system moves the retractable roof panels up and down the sloped track in 9 to 11 minutes depending on wind conditions. (Structural steel was fabricated by AISC Member Hillsdale Fabricators/Alberici Constructors.)

The project also features a retractable end wall consisting of six glass panels that



Walter P Moore



HKS, Inc.

move to create an 85-ft-tall × 210-ft-wide opening. Each panel rides on a steel rail while the wall opens and closes, and is supported by two hardened steel wheels.

QUALITY NEWS

Indiana Fabricator Wins Free Audit

Indiana Steel and Engineering Corp., a fabricator in Bedford, Ind., has won Quality Management Company's drawing for a free audit.

Since October 2006, QMC has been administering a voluntary Customer Satisfaction Survey of AISC Certified Fabricators and Erectors upon receipt of their

certificate. The objective of the survey is to improve the certification process from invoicing to the audit to issuing the certificate, and companies that complete the survey are automatically entered into the drawing. QMC will draw for another free audit in six months, so keep those surveys coming in!

STEEL SHEET PILING

Best Practices for Installing Steel Sheet Piling

The North American Steel Sheet Piling Association (NASSPA) earlier this year announced the publication of its *Best Practices Steel Sheet Piling Installation Guide*. This updated and revised manual provides an authoritative guide to the methods of installing steel sheet piling.

The goal is to describe practices that ensure proper steel wall installation, and convey the importance of predicting the "driveability" of sheet piling sections following a thorough evaluation of all ground conditions. The manual presents an inventory of

the existing driving systems, from impact hammers to vibratory piling drivers and special systems, and also provides a description of driving methods, ancillary equipment (including guide frames), and all necessary procedures to follow when installing sheet pilings. Finally, some common installation problems are illustrated and several special aspects of driving are briefly outlined.

The guide can be downloaded from the NASSPA web site, www.nasspa.com. A hard copy is available upon request; call 866.658.8667.

HELP IS HERE.

Get the 75-year Steel Joist Manual, the current Specs and Loads Catalog and comprehensive technical digests on steel joist construction at steeljoist.org/help



PROJECTS

From the Shipyard to the Backyard

BY JAMES FALLS

Steel containers have been a mainstay in the world's shipping industry ever since 1956, when U.S. trucking entrepreneur Malcolm McLean loaded 58 steel containers aboard the tanker Ideal-X and transported them from Newark, N.J. to Houston.

But what happens to these containers when they are "retired?" At the end of its lifespan (typically eight to 12 years), a container is traditionally sold for scrap or, when it's cost-effective, shipped back to its country of origin. But today many retired containers are finding new life as garages or spare bedrooms. Known as intermodal steel building units (ISBU), these repurposed containers are being used to build strong, sustainable, and durable structures.

Some major shipping companies are selling their used containers for approximately \$1,200 each, and many containers are being sold over the Internet. A search for "shipping container" returned more than 100 advertisements for shipping containers in the U.S.; most of these are selling for around \$4,000 each.

The standard dimensions of a container are 8 ft in width, 8 ft-6 in. or 9 ft-6 in. in height, and lengths of 20 ft, 40 ft, 45 ft, 48 ft, and 53 ft (for a point of reference, a 40-ft container weighs approximately 10,580 lb and can hold approximately 65,000 lb). The containers are made from high-strength weathering steel, water-resistant, and designed to resist harsh oceanic environments, making them more than acceptable for use in building construction.

Dropping Anchor

Transforming an ISBU into a useable structure is fairly straightforward. Since they

are originally designed for efficient transportation, they can easily be relocated to a construction site. After delivery, holes for doors, windows, and other desired openings are cut in the sides. The ISBU is then lifted by crane onto the building foundation and securely welded to the foundation; when properly anchored, it can resist winds of up to 175 miles per hour. Commonly, several ISBUs are stacked on top of each other or placed side-by-side to form a large home or office building. The steel is insulated with a ceramic powder, making it rust-resistant and preventing mildew build-up. Exterior and interior finishes such as drywall, stucco, and wood are then attached to the steel frame as desired. At this point, the transformation from a sea-faring shipping container to a static structure is complete.

Mixed Use

ISBUs can be used to build a multitude of different structures. Architects use them to build custom homes and trendy bungalows of all sizes and shapes. The U.S. military uses them to set up temporary command centers and training facilities. ISBUs are also very useful as emergency shelters and temporary housing, as they can be delivered quickly and set up with little effort. Press boxes, concession stands, storage facilities, radar stations, and apartment buildings have also employed ISBUs.


In addition, several notable projects around the world have been constructed using these special steel boxes. Architect Peter DeMaria designed a two-story home using eight ISBUs in southern California; the 3,500-sq.-ft home was awarded the 2007

AIA Honor Award for Design Excellence/Innovation. And according to a recent article in *USA Today*, DeMaria plans to offer more of the container homes, at a starting price of \$150 per square foot—a bargain considering that traditional homes in the same area typically go for \$225 to \$250 per square foot.

In Whistler, Canada, home of the 2010 Winter Olympic Games, 294 rooms are being constructed to provide temporary housing for workers, media, and volunteers. Also, the Nomadic Museum, built in 2005 in New York to house a photography exhibit, used 152 shipping containers for its exterior walls. (Interestingly, the museum was dismantled and then rebuilt in Santa Monica, Calif. a year later and Tokyo the following year.) And in Bishkek, Kyrgyzstan, hundreds of containers are double-stacked to create the Dordoy Bazaar, a large wholesale and retail market; an estimated 6,000 to 7,000 containers stretch for more than a kilometer to make up one of the largest commercial centers in the region.

The use of shipping containers to build structures is still in its infancy, but with a little imagination and creativity it is possible to construct almost anything. So the next time you walk by a shipyard or rail yard and see an empty shipping container, don't assume it will be crossing an ocean; it might just turn out to be your neighbor's new kitchen.

James Falls is a senior civil engineering student at the University of Florida in Gainesville and a summer intern with AISC.



Photos: Andre Moyses/Christian Kienapfel



This 3,500-sq.-ft home in Redondo Beach, Calif., designed by Architect Peter DeMaria, uses eight ISBUs.

Third Quarter 2008 Article Abstracts



The following papers appear in the third quarter 2008 issue of AISC's *Engineering Journal*. EJ is available online (free to AISC members) at www.aisc.org/epubs.

Fracture Modeling of Rectangular Hollow Section Steel Braces

XIANG DING, DOUGLAS FOUTCH, AND SANG-WHAN HAN

Steel braced frames are widely used in all regions of the U.S. including those with high levels of seismicity. Rectangular hollow sections (RHS) are popular because of good section properties and ease of construction. A refined beam model has been developed which is efficient for use in finite element models of buildings. It accounts for local buckling and fracture in the brace and is shown to have good accuracy for nonlinear seismic analyses.

Topics: Seismic Design, Hollow Structural Sections, Stability and Bracing

Design Aid for Triangular Bracket Plates Using AISC Specifications

SHILAK SHAKYA AND SRIRAMULU VINNAKOTA

This paper presents a model to determine the nominal strength of a triangular steel bracket plate using the column strength equations in the AISC *Specification*. Also included are two design

tables for such bracket plates for two grades of steel. The nominal strengths obtained by using the relations developed by the authors are compared with the available experimental results and results from other available theoretical approaches. The authors' approach predicts results closer to the experimental results than the other theoretical approaches. Two example problems are worked to illustrate the use of the design tables.

Topics: Connections-Simple Shear, Columns and Compression Members, Steel

A Comparison of Frame Stability Analysis Methods in ANSI/AISC 360-05

CHARLES J. CARTER AND LOUIS F. GESCHWINDNER

Two simple unbraced frames are used to illustrate the application of the following four frame stability analysis methods:

- The Second-Order Analysis Method (ANSI/AISC 360-05, Section C2.2a)
- The First-Order Analysis Method (ANSI/AISC 360-05, Section C2.2b)
- The Direct Analysis Method (ANSI/AISC 360-05, Appendix 7)
- The Simplified Method (13th Ed. *Steel Construction Manual*, page 2-12; AISC *Basic Design Values* cards)

Topics: Analysis, Specifications, Stability and Bracing

Effects of Slab Post-Tensioning on Supporting Steel Beams in Steel-Framed Parking Deck Structures

BHAVNA SHARMA AND KENT A. HARRIES

AISC Design Guide 18, *Steel-Framed Open-Deck Parking Structures*, discusses

the use of cast-in-place post tensioned concrete slabs in steel framed parking structures. In Section 3.3.2.1 of Design Guide 18, the authors reflect on the manner in which the post-tensioning force is resisted by and affects the supporting beam: in a non-composite or composite manner. They conclude that the post-tensioning force is carried almost entirely in a composite manner (minus effects of shrinkage and elastic shortening). This conclusion is based on results of unpublished research and is corroborated by earlier design guidance. The objective of this field study is to quantitatively assess the effect that slab post-tensioning forces have on their supporting steel members.

Topics: Beams and Flexural Members, Composite Construction

Current Steel Structures Research

REIDAR BJORHOVDE

This regular feature of the *Engineering Journal* provides information on new and ongoing research around the world. Research projects are summarized on the following topics: structural behavior and strength under seismic loads, including special concentrically braced frames and energy dissipation characteristics of semi-rigid connections; cross-sectional stability of hot-rolled shapes; behavior and strength of steel columns with partial damage of the fire retardant coating; composite beams with precast hollowcore slabs; and plate girder research in Spain, including hybrid and stainless steel girders.

Topic: Research

INDUSTRY EVENTS

May the Best Welder Win

Sparks will fly—literally—at the AWS Skills Competition Weld-Off, an event testing students' welding skills. A component of the SkillsUSA Competition, the Weld-Off is among the highlights of the 2008 FABTECH International and AWS Welding Show, October 6-8 in Las Vegas.

Sponsored by the American Welding Society, it requires welders to demonstrate their skills by completing standard test weldments (plate and pipe), sheet metal projects in aluminum and stainless steel,

and a pressure vessel. Welds will be judged by AWS Certified Welding Inspectors for soundness and appearance. Written skills and welding code interpretation also will be considered.

Six finalists, selected from 24 student welders that participated in the SkillsUSA Championships in 2007 and 2008, will compete in the Weld-Off this year and only three will qualify to advance to the SkillsUSA U.S. Open Weld Trials in 2009. The U.S. Open Weld Trials Champion will represent the United States at the

WorldSkills Competition in Calgary, Alberta, Canada in 2009. The AWS U.S. Open Weld Trials winner will receive a four-year scholarship, sponsored by the Miller Electric Manufacturing Co., worth \$40,000 from the AWS Foundation, a four-year AWS membership, an AWS Certification, and up to \$1,000 in AWS publications.

For more on FABTECH International and AWS Welding Show and the AWS Skills Competition Weld-Off, visit www.fmafabtech.com.

news & events

UNIVERSITY RELATIONS

Student Bridges Shine in the Sunshine State

The University of Florida's Stephen C. O'Connell Center was full of students this past May 23-24, but the majority of them weren't Gators.

Civil engineering students from around the country, as far away as Hawaii, traveled to the Gainesville campus, as the school played host to the 17th annual AISC/ASCE National Student Steel Bridge Competition. This year's contest ended with the University of California, Berkeley taking first place. Cal's win ended North Dakota State University's bid for a three-peat; that school had won in 2006 and 2007. The University of Florida (UF) and the University of California, Davis took second and third place, respectively.

For the 42 participating universities, the goal of the competition was to design, fabricate, and build the most efficient 21-ft steel bridge that could support a vertical load of 2,500 lbs. Each bridge was ranked in six categories: construction speed, lightness, aesthetics, stiffness, economy, and efficiency. Teams spent the entire year and countless hours preparing for the competition.

Beyond the Bridge

For Florida students, however, designing an award-winning bridge was only part of the goal. As the host school, the larger

feat was figuring out how 42 bridges were going to be assembled and tested in only eight hours.

Nearly 650 students, professors, and professionals attended the competition expecting the competition to run smoothly and efficiently. What many of them didn't realize is that well before the rules were released in August of 2007—and before many students knew they would even be on a steel bridge team—UF students were already preparing for the 2008 competition. In fact, Dr. Tom Sputo, UF ASCE Faculty Advisor, began the long process in 2006 when he requested that UF be considered as the host of the 2008 NSSBC.

A small committee of dedicated students was assembled to plan, coordinate, and execute the competition. The students, with already busy schedules—juggling homework and oftentimes a job, as well as other responsibilities—added another demanding item to their plate, spending countless hours making hotel arrangements, setting up contracts with vendors, contacting professionals to be judges, and coordinating with the qualifying universities to make sure they were ready for the competition. Many of the venues, including the O'Connell Center and the Reitz Union Grand Ballroom,



were reserved two years in advance—even before the 2007 NSSBC, hosted by California State University, Northridge, took place.

Student Director of the competition and AISC summer intern James Falls described his experience: "You have to be dedicated and proud to host the best student engineering competition in the country. It was a tremendous amount of work but extremely rewarding when two years of hard work all comes together." Without question, he explained, the students in charge from year to year are the unsung heroes that make the competition possible.

Fromy Rosenberg, AISC's Director of University Relations, commented, "This is the premier competition for student engineers. It brings together everything students have learned in the classroom. Participating students practice basic steel

Photos: Bob Phelan/Missouri University of Science and Technology





design and fabrication and project scheduling and management, and gain hands-on appreciation for the strength and versatility of structural steel."

In order to reach the national competition, student teams nationwide competed in 18 regional competitions. The winners in those competitions were invited to compete in the national event. This year a total of 182 universities competed in the regional competitions.

The 2009 NSSBC competition will be hosted by the University of Nevada, Las Vegas, May 22-23, 2009—and yes, UNLV has already been preparing for months.

2008 NSSBC Winners

Overall

University of California, Berkeley
University of Florida
University of California, Davis

Construction Speed

SUNY College of Technology at Canton
 University of California, Berkeley
 University of Wyoming

Lightness

University of California, Berkeley
 Virginia Polytechnic Institute
 University of Florida

Aesthetics

Iowa State University
 South Dakota School of Mines
 University of Wisconsin, Madison

Stiffness

University of Missouri, Kansas City
 University of Wisconsin, Madison
 Seattle University

Economy

SUNY College of Technology at Canton
 University of California, Berkeley
 University of Florida

Efficiency

University of California, Berkeley
 University of California, Davis
 University of Florida

Full results of the overall competition and each category are posted on the official 2008 NSSBC web site, www.2008steelbridge.com.

Surface finishing adds the value



Surface Finishing • Shot Blasting

*Innovative solutions from the world's
leader in surface finishing*

www.rosler.us

RÖSLER
finding a better way ...

RÖSLER Metal Finishing USA L.L.C. • 1551 Denso Road • Battle Creek • MI 49037
Tel.: 269-441-3000 • Fax: 269-441-3001 • info@rosler.us

COBRACUT

ANNULAR CUTTERS

Cuts Faster. Works Harder. Lasts Longer.



AMERICAN PUNCH COMPANY

27101 Tungsten Rd., Cleveland, Ohio 44132
 800-243-1492 Fax: 800-261-6270

sales@americanpunchco www.americanpunchco.com

BENTLEY



RAM



STAAD



PROSTEEL



ALL THE KEY PLAYERS ON THE SAME TEAM.

YOURS.

In welcoming RAM, STAAD and ProSteel to the Bentley family, we're proud to expand our reach as the leader in structural solutions. Offering the most comprehensive suite of analysis, design, detailing and construction documentation tools anywhere, Bentley's flexible and scalable products will allow your team to work seamlessly throughout the entire project. Whether you're part of a small firm or one of the largest engineering firms in the world, with Bentley you'll have complete access to the best and most complete integrated solutions available. For the industry's broadest and most productive range of structural solutions, Bentley is your answer.

Contact us at +1 800 BENTLEY or structural@bentley.com

SEMINARS ON BENTLEY'S INTEGRATED CONCRETE OFFERINGS
COMING SOON TO A CITY NEAR YOU. VISIT [WWW.BENTLEY.COM/
CONCRETESEMINARS](http://WWW.BENTLEY.COM/CONCRETESEMINARS) FOR MORE DETAILS AND TO REGISTER.



Artistic Achievement

BY MARIO ELCID, P.E., AND BOB VARGA, AIA, LEED AP

The arts campus at Western Michigan University finds the “missing link” with a dynamic new building that complements and enhances its neighbors.

SOMETIMES, IT TAKES JUST THE RIGHT PIECE OF FURNITURE—OR PERHAPS THE RIGHT RUG—TO “TIE THE ROOM TOGETHER.”

Entire buildings can also play this role—on a grander scale, of course—as illustrated on the Western Michigan University campus in Kalamazoo.

The Richmond Center for Visual Arts (RCVA) completes the campus’ Miller Plaza Quad and adds a new, striking element to WMU’s School of Visual Arts. RCVA physically connects the Miller Parking Deck to the Dalton Center (which houses the music and dance departments) and provides a link to the south wing of Kohrman Hall, the future location for the School of Art. Conceptually, the completed Miller Plaza Quad imbues these connections, which will be used by students and visitors alike, with a broad visual art experience. And RCVA becomes a physical connector with the equally important function of allowing visitors to view and experience visual art at various scales and locations.

Designer Needs

The building uses form to express and delineate functions that the public at large will attend, such as student exhibits, main exhibits, and lectures. Although RCVA is a relatively small building, it had to meet rather high standards. One of the design challenges was to provide a high-quality and well-designed space on a budget considered tight for buildings achieving American Association of Museums (AAM) standards. To meet the budget, the design visually expresses typically concealed construction materials such as the structural steel system, which forms an integral part of the design and helps reveal the notion of “construction” to the art students inhabiting the space. All the structural elements become architectural finishes and work together to serve a specific visual purpose.

The exhibit areas are wrapped in a dynamic bent copper plane forming both the roof and south wall, allowing light to bleed in via north-facing clerestory glazing. The south exterior tilted wall in the exhibit hall seamlessly and gradually curves and transforms into a roof structure. Along that wall two rows of columns are placed to provide two structural functions and convey one visual intent. The outer sloped column line, with thinner columns spaced at 6 ft-8 in., supports the exterior copper wall, while the inner column line has larger columns and girders that are spaced at 20 ft on center and serve as roof support and are part of the moment frame lateral system. Horizontal angles are provided in the hidden cavity

between the outer and inner columns to appropriately transfer the wind loads from the wall into the moment frames.

We guided the structural design to achieve a specific contrast between the thin planar, more rhythmic character of the exterior wall and the heavier inner columns and girders. This approach turned out to be very beneficial from an economics standpoint, as the larger columns had to be designed to resist the wind loads as well as the seismic loads in the north-south direction due to the unique geometry of the building.

Not-So-Basic Structural Design

RAM Steel was used to design the basic gravity framing elements of the building. Its ability to take into consideration the size restrictions of limiting physical factors and visual design intent also proved useful. For example, in the east-west direction the column spacing is kept consistent at 20 ft on center for the majority of the building. In the north-south direction the columns’ spacing varies and ranges between 20 ft and 40 ft, which creates several framing scenarios where each bay has to be checked individually to meet the vibration criteria. W-Shapes are used to support the first floor slab above the partial basement, and the



Hedrich Blessing Photography



Laszlo Regos Photography

The south exterior tilted wall in the exhibit hall seamlessly and gradually curves and transforms into a roof structure.

second floor. Lightweight concrete was used for the second floor composite slab, while normal-weight concrete was used for the first floor composite slab to match the color and appearance of the slab-on-grade concrete around that location.

The complex geometry of the building's large second floor openings into the gallery area, sloped lecture halls, double-story entry space, and a tilted exterior wall and roof prompted a careful approach to designing the lateral system. RISA 2D and RISA 3D models were created to calculate the frames' stiffness, while a few specially designed spreadsheets were generated to ensure an appropriate and efficient distribution of the lateral forces while minimizing the effect of torsion. The lateral resisting system consists of moment frames in the north-east direction and vertical braces in the east-west direction. Horizontal braces were added within the floors, around openings, to help transfer the lateral seismic loads to the appropriate braces. Transfer vertical kickers were strategically placed between the exterior tilted wall and the moment frame columns to transfer wind loads from the building's skin to the main lateral force resisting system. The seemingly simplistic and partially exposed lateral system appears minimal and fits well with the overall design expression, but it conceals many more complex components within the architectural finishes.

Special Features

In addition to the basic structural steel members, the steel used in this building is heavily influenced by architectural requirements. Steel pieces are used to construct glass and steel display cases that showcase specially displayed pieces of art by the main donors. These boxes give the illusion that they are part of the building's main structural system, but in reality they complement the design and are purely architectural features.

WMU desired a very transparent front face for the building in order to draw the attention of students passing by on the plaza to what was happening inside the building. To that end, a very specific rhythm of expressed and concealed structure was set up to create larger "windows" into the building. For example, one of the main building columns on the east (front) building face is wrapped in an asymmetric metal panel skin that projected beyond the glass curtain wall. The lower part of the metal enclosure was widened to emphasize the asymmetry of the front entrance. Other

Now
You Can Do
**Curved
LRFD
Projects!**

THE PROVEN STEEL BRIDGE DESIGN SOLUTION.



www.mdxsoftware.com
(573) 446-3221

The leading software package for designing and rating curved and straight steel girder bridges for compliance with AASHTO ASD, LFD, LRFD specifications.

FREE 15-Day Trial!

See www.mdxsoftware.com for details.

columns on the same column line were left visibly exposed behind the glass to enhance the notion of "skin." In addition, the columns provide a visual frame for a large projection screen that descends from the ceiling into the lobby and can be viewed from outside the building.

The larger of RCVA's two lecture halls, located on the second floor, has a curved exterior that cantilevers outside of the first-floor borders. The open-space, cantilevered structure and curved exterior required for both lecture halls combined to provide additional challenges in keeping the steel framing as shallow as possible, as the allowable number of columns to be used in this space was limited. Several framing schemes were developed using RAM Steel, paying careful attention to the structural depth variations due to subtle framing changes. Continuous girders run over columns and are spliced at the zero moment transition point, helping to keep a shallow framing in the space, while filler beams are added within each bay helping to meet the required vibration criteria.

The new bridges that connect the building to the adjacent structures are another indicator of the level of detail and collaboration that makes the structural steel enhance the appearance of the project, and proves that design considerations were not limited to the interior of the building. For example, the bridge on the south side of the building connecting RCVA to the parking garage is supported by extremely narrow exposed galvanized wide-flange columns that are offset by deep side girders to draw the viewer's attention and focus to the bridge.

RCVA is a great example of what happens when art, design and structure come together to form an aesthetically appealing and extremely functional space. And steel plays a leading role in punctuating this design purpose, creating a bold, modern addition to a campus area that focuses on the arts. MSC

Mario Elcid is a structural engineer and a project manager; and Bob Varga is an architect and designer; both with SmithGroup.

Owner

Western Michigan University,
Kalamazoo, Mich.

Architect and Structural Engineer

SmithGroup, Detroit

General Contractor

CSM Group, Galesburg, Mich.



4 lines running around
the clock.

Shipping and receiving
around the clock.

Environmentally friendly
galvanizing.

Upon request we will
provide certification that
your project or compo-
nent was galvanized
without producing **ANY**
hazardous waste.

If you have a job in the
southeast or transiting
through the S.E.
Tennessee Galvanizing
will unload your steel,
run it, and reload while
your driver waits.

Saturday runs
with notice.



Alloy Zinc to threaded
rods and fasteners using
HOT DIP GALVANIZING for
time proven protection.

www.tennesseegalvanizing.com
1535 Industrial Blvd • PO BOX 609
Jasper, TN 37347
(423) 942-1020
TOLL FREE (877) 242-5848

PROVIDING THE KNOWLEDGE AND TOOLS TO BUILD THE FUTURE

OCTOBER 2-3, 2008 | HYATT REGENCY | ATLANTA, GEORGIA



Structural Engineers' **BUILDINGS** Conference & Expo

PLAN TO ATTEND!

The Structural Engineers' Buildings Conference & Expo is the only annual conference to focus simultaneously on the most up-to-date technical issues in the successful completion of buildings, and the necessary management issues to increase your business expertise. The conference program is focused on the most timely and important topics to today's structural engineer.

2008 Conference Themes:

Building Codes: Navigating Your Way through the Updates and Changes

Wind Design: Mitigating the Effects of Natural Hazards on the Built Environment

Industry Evolution: Market Changes Affecting Your Business

Business Management: Successful Strategies for Effective Leadership

Technical Innovation: Cutting Edge Building Design Techniques and Tools

Register **EARLY** and save \$100

www.SEBuildings.com

1.800.466.6275

SPONSORED BY

Autodesk



TEKLA

SDS/2
DESIGN DATA

IN ASSOCIATION WITH

Structural Engineer



PRESENTED BY



A New Link to Learning

BY BRENT BANDY, P.E., LEED AP

An expanded bridge on Georgia State University's campus brings two library buildings together as one.

WHEN I FIRST WALKED INTO THE GEORGIA STATE UNIVERSITY LIBRARY at the start of this project, I was transported back to my college days at nearby Georgia Tech. The smell of musty old books, the long rows of shelves, and the dim lighting evoked “knowledge” to me.

For today's students, however, natural lighting, the hum of a hard drive, and the smell of lattes are what opens their minds for learning. Georgia State, in downtown Atlanta, understood this and had a vision to make its library more inviting and up-to-date, with goals to:

- Update finishes, furniture, and building systems
- Increase reader seats and collaboration spaces
- Expand collection space by adding compact shelving
- Expand the narrow three-story steel pedestrian bridge spanning Decatur Street and link the library's north and south buildings (from the 1960s and 1980s, respectively), making them act and feel like a single building

BIM from the Start

Both the architectural and structural teams were committed to using the Revit platform on the \$17.5 million project, both for collaboration and production of documents. Walter P Moore was still in the early stages of implementing the new software when this project started. Despite the steep learning curve, we quickly saw the benefits of three-dimensional collaboration and coordination.


Modeling the existing concrete buildings and steel pedestrian bridge helped us to visualize and coordinate between old and new. Multiple schemes for the new link were explored for aesthetics, constructability, and cost. Three-dimensional views of the design helped the owner more easily understand the options. The construction manager and subcontractors used these same views to better comprehend and more accurately price the options, providing a clear direction at the end of schematic design that proved itself throughout the remainder of design and construction.

The chosen scheme for the new link was a downward vertical expansion of one floor, resulting in a four-story bridge, plus a horizontal expansion of 35 ft at the two lower bridge levels and 19 ft at the two upper levels. This resulted in the addition of about 11,000 sq. ft. The second level was supported at each side by trusses, while the middle portion of the floor was supported by a truss at the level above. A truss at the third level was already in place, so a similar truss was set alongside the existing to limit the impact on usable space. The new floors at levels five and six were supported by transfer girders at level four, which were in turn supported by the new trusses. This scheme maximized the usable open space between library levels two and four and optimized the structural load path to provide an efficient overall design.

Link Analysis

The original 15-ft-wide pedestrian bridge consisted of one-story trusses on each side, spanning about 75 ft and topped with two more stories of steel beam and column framing. The south end was attached to the south library structure, while the north was supported to the ground with a braced frame system on auger-cast pile foundations separate from the library's original north structure.


Our goal from the start was to avoid costly modifications to the existing walkway members and connections. We studied various structural




Walter P Moore

Above: Bridge erection was performed over a street, without shoring.

Center: The updated bridge included a vertical expansion of one floor, plus a horizontal expansion of 35 ft at the two lower bridge levels and 19 ft at the two upper levels.



Copyright Brilliance Photography



Walter P Moore

Above: A new mid-truss “sistered” alongside an existing truss.

Tons of Reasons to Plan on Steel.

Our network of steel service centers have broad & deep inventories of structural steel available to keep your project on track and budget.

Make Metals USA part of the team when planning your next project. Visit www.metalsusa.com for the service center nearest you.



Project Supply
Jim Collins
jcollins@metalsusa.com
800-523-3340

We Sell Service.

- Beams
- Tubing
- Plates
- Angles
- Channels
- Bars

Stock or
Processed

design concepts that minimized the impact on the existing trusses. The final design entailed three trusses:

- The west truss is two stories high and spans between two new steel columns that aren't attached to the existing structure.
- The new east truss sat directly below the existing east truss to pick up a portion of the new second floor. This new east truss was designed to have stiffness compatible with that of the existing east truss so that new floor live loads would cause no net increase in loading on the existing truss.
- Similarly, the new "mid-truss," adjacent to the existing west truss, was designed for deflection compatibility with the existing west truss.

A staged analysis of the system was performed to ensure that the different phases of construction and various loading combinations did not overload the existing trusses and supporting structure. The mid-truss was set alongside the existing west truss and stitched together to ensure that there were no vertical stresses in the floors at the construction joint between the old and new slabs. The trusses were not stitched until after all the other framing and concrete slabs had been cast, in order that the only load to be shared between trusses would be the live load.

The original geotechnical report classified the downtown site as Site Class E. The team requested a site specific hazard study as well as shear wave velocity testing in order to more accurately assess the site class, which paid off by reducing the Site Class to D and the Seismic

Design Category to B. The decreased detailing requirements and seismic forces helped reduce the required upgrades to the existing lateral system. The link expansion had very little impact on the eight-story concrete frame to the south, but the combination moment frame and braced frame at the north end was upgraded for the link expansion loads.

Constructability Challenges

Key to the project's constructability was the planning of the sequence of steel erection and the need to avoid shoring. The sequencing plan on the structural drawings specified that the trusses should be erected first, and the second and fourth floors should be erected next, which provided a working platform for the rest of the work over Decatur Street. While it would have been possible to keep the street open during construction, the contractor closed it for much-needed layout and staging space. Only after the remaining steel framing and concrete deck was placed could the connections between the new and existing structures be made. After all the structures were tied together, the cladding and finishes were attached.

Another constructability challenge was the deep foundations that were to be installed in the basement of the existing north library. The north end of the new link required new columns and foundations. The basement working clearance was only about 8 ft and required low-headroom equipment to install foundations. Auger-cast piles were chosen for this application since most of the founda-

Precision Low-Deformation Bending and Spiraling of Beams, Pipes and Tubes

- Induction Bending of Carbon, Stainless and Alloy Steel Pipes up to 42" Diameter
- Full Range of Capacities, Shapes, Sizes & Materials
- Conical, Elliptical, Helical, Compound Reverse and Tight Radii
- Delivery F.O.B. Your Door

Don't Assume It Can't Be Done Until You Talk To Us !

Toll Free: 1-800-563-BEND
(2 3 6 3)
Email: sales@bending.net
Web: www.bending.net



"Helix Bridge" Seattle, Washington
36" OD x 1.25" wall & 24" OD x 1" wall
cold bent to a multiple radius helix

ADVANCED BENDING TECHNOLOGIES



tions on the project were a standard installation. The steel framing at the lowest level was configured to take advantage of some significant overstrength in existing foundations and reduce the number of low-overhead foundations by about two-thirds.

Exposing the Structure

The design team initially leaned toward minimizing visibility of the structural systems, but the trusses were eventually turned into a signature element of the building. While the link's two-story open space over the road is dramatic in itself, the exposed pipe truss accentuates the height of the space. Once we had determined the diameter of the two-story truss web members, the architect did not want to wrap them in cementitious fireproofing and drywall, because they would become too bulky and obscure the views from both inside and outside. Also, because the truss web members connected right at the floor levels, pipe-to-pipe connections were made to eliminate gussets, which further enhanced the overall appeal of the system and minimized visual obstructions through the glass curtain wall.

Due to a very efficient design of the steel structure—resulting in a steel weight of 120 tons—the budget was able to accommodate the use of intumescent fireproofing on the web members of the exposed two-story truss. The wall thicknesses of some pipe member sizes were increased to reduce the required thickness of coating for the fire rating. The main shafts came to the site primed and painted with only the ends primed. The final coating was kept from the joints to keep the welding heat from damaging the intumescent paint.

Successful Transformation

Even with the exposed trusses, sleek connections, intumescent paint, difficult foundations, and other challenging existing conditions, the bridge project came in on time and under budget. The project team received an AIA award for collaboration using BIM technology. Both the owner and university community are thrilled with the “brand new” library. But most importantly, following the “scent of knowledge,” students flock to the library every day and fill all the reader seats by early morning.

MSC

Brent Bandy is a senior project manager and principal with Walter P Moore in Atlanta. He can be reached at bbandy@walterpmoore.com.

Architect

Leo A Daly, Omaha and Atlanta

Structural Engineer

Walter P Moore, Atlanta (lead)
Sykes Consulting, Atlanta

Steel Fabricator

SteelFab, Norcross, Ga. (AISC Member)

Steel Erector

Superior Rigging and Erecting Company, Inc., Atlanta (AISC Member)

Construction Manager

Holder Construction, Atlanta

Software

SAP2000
Revit Architecture

WHITEFAB

BIRMINGHAM, AL

PHONE: 205-791-2011

FAX: 205-791-0500


EMAIL: sales@whitefab.com

WEBSITE: www.whitefab.com


ROLLING AND BENDING SPECIALIST

TS 20 X 12 X 1/2


W 24 X 94 #



**HARDWAY
OR
EASYWAY
ON
NINE MACHINES**



**FULL LINE
CNC
MACHINING**



**1,000 TON PRESS BRAKE 30'-0" BED (20'-0" BETWEEN HOUSINGS)
ALSO - 1/2" X 20'-0" SHEAR; PLATE ROLLS; CUT TO LENGTH LINE**



Maximize Your Potential

Introducing the New V600 INTIMIDATOR from Voortman...

the fastest and most accurate carbide capable CNC drilling system available. Designed for steel fabricators who need big results but have limited floor space.

And thanks to Voortman's unmatched world-wide service and reliability, the new V-600 INTIMIDATOR is always ready to tackle any job.

For a DVD video and brochure, contact us at 1-815-468-6300 or visit us on the web at www.voortmancorp.com



Features & Benefits:

- Carbide Capable Drilling
- Automatic 5 Tool Changer
- 2500 rpm Constant Torque Spindle
- Ball Screw Positioning
- Servo Driven
- Wireless Connectivity
- Onboard Hydraulic system
- Onboard Compressor
- Internal Mist Coolant
- Non Contact Laser Measuring Web Probe
- Totally Guarded for Safe Operation
- No Umbilical Cord Required for Power, Air and Hydraulics



Moving In

BY NAT OPPENHEIMER, YEGAL SHAMASH, AND BEN ROSENBERG



Polshek Partnership Architects/ Crystal Computer Graphics Ltd.

Dickinson School of Law, formerly an independent entity, will soon have its own building on the Penn State campus.

A DECADE AGO, TWO PROMINENT PENNSYLVANIA INSTITUTIONS OF HIGHER LEARNING—the Dickinson School of Law (DSL) in Carlisle and Penn State University in State College—joined forces in a mutually beneficial relationship. Penn State got a law school (it didn't have one before), and DSL was able to take advantage of Penn State's resources as a preeminent research institution.

But there was one problem: The two schools were almost two hours apart. From the beginning, the two schools shared a vision to create a flagship building for DSL on Penn State's main campus. Almost 10 years after the initial merger, this vision will become reality, as DSL's new Lewis Katz Building will open in State College this December. (A new sister building, also named for Lewis Katz, is scheduled to open next year on the Carlisle campus).

Structurally, the sinewy new building in State College is essentially two long halves fit and joined together along the length. The north half is brick-clad with a flat roof and connects to the campus' mechanical and transportation core. The south half is clad with a curtain wall and stone and has a sloping roof that soars over 60 ft into the air at its eastern end. Containing the library, auditorium, courtroom, and café, the south half is the visual centerpiece of the building.

Staying Light

During schematic design, we decided to use steel framing with composite concrete on metal deck. Initially, the foundation system was designed as piles, due to State College's typical ground conditions, and the structure needed to be as light as possible in order to minimize the number of piles. In addition, the client wanted an efficient system that could meet the demands of the plan irregularities that made the design so unique. After looking at alternate systems, we chose a 4½-in. light concrete slab on composite metal deck system. This system provided the appropriate fire rating and was the lightest system that was flexible enough to address the challenge of the proposed layout. In this case, repetitive or prefabricated systems did not gain the advantage due to the non-repetitive layout.

During the design development phase we discovered that the local building soil conditions were suitable for spread footings; indeed, rock was found not far below the surface. We continued to use steel framing, as spans as long as 50 ft were necessary and, as noted above, the

normal cost-effectiveness of repetitive lightweight systems did not have an advantage here.

While very lightweight, the slab and deck system challenged us in two ways: vibration and noise. After sizing members for stress, deflection, and architectural constraints, we conducted a comprehensive vibration analysis on the structure and determined that several beams and girders needed to be increased in size due to vibration limitations. There was also concern about noise from mechanical rooms in the basement; three large classrooms with auditorium-style seating sit above the mechanical rooms. On the advice of the acoustical consultant, we chose a 7½-in. normal weight composite deck system at all bays above the mechanical room in order to minimize noise.

Keeping Up with the Architecture

As the building is visually striking, the exposed steel needed to be designed to meet this aesthetic. Round hollow structural sections (HSS) comprise a series of full-height columns along the south side of the building. Because all of these round HSS columns needed to be the same nominal diameter, we used ASTM A500 Grade C with a yield stress of 46 ksi instead of the more conventional Grade B, 42 ksi steel.

The most intriguing design challenge of the building was the 30-ft-high, two-story sloping ramp that carried a curtain wall and ran along the south face of the building. The view from the south side of the building, which faces the rest of the campus, is dominated by this curtain wall, and it was important to minimize the structure so as not to impede the view either from outside or from within. The ramp, which connects the two floors of the building's library, is cantilevered over the south entrances to the building. We designed a system to hang the ramp from the roof framing using a series of outrigger plates and hanger rods with clevises. Because the ramp support framing was exposed, plates allowed us to maintain the desired visual appearance. The 1-in.-diameter hanger rods, spaced at 10 ft on center, are cleanly connected with stainless steel pins to steel plates at the ramp floor structure and with clevises at the top. To carry the wind loads on the exterior curtain wall, a series of strong-back plates, also spaced at 10 ft on center, march up the ramp at a consistent offset from the hanger rods. Each strong-back consists of two vertical plates spanning the height of the curtain wall, separated by a small gap with spacer plates. The hanger rods carry gravity loads,

the strong-backs carry lateral wind loads, and both work together to provide a clean visual system.

Laterally Speaking

The building's lateral system is a combination of moment frame and braced bays. A multi-story interior skylight that runs along the boundary between the north and south halves of the building creates an open corridor with a desire for little visible structure within it. We used a series of connector HSS16x8 tubes to carry lateral loads between the two halves of the building to meet both structural and aesthetic requirements.

Framing Crisis Averted

Due to a necessary architectural design change during construction, we needed to develop a solution quickly when we found that one of our double-angle braces was blocking a relocated door to a café support room. Relocating this primary lateral frame was not an option. We looked at various solutions and eventually designed a combination moment frame and braced bay that essentially framed the door. The moment frame between the head of the door and the floor above is a series of W12x72s. There is also a miniature brace bay to the side of the door, safely enclosed within a wall. We were able to safely carry the

required lateral loads without disturbing the architectural design and carry out the redesign within a few days during standard shop drawing review.

Curbing Problems Early On

All involved parties agree that for a project of this size, the steel went up in a relatively uninterrupted pattern and with very few issues arising during erection. The detailer was able to build a very accurate BIM model of the entire frame at the beginning of the shop drawing phase. Although the creation of this model generated a significant number of RFIs, all parties understood that these early RFIs would largely eliminate more urgent ones later on in construction, and communication flowed smoothly between all parties.

The fabrication shop was methodical in forwarding erection drawings and shop standards. Once these were approved, a rapid but reasonable schedule was established and held by all parties throughout significant completion of shop drawings, whereby the detailer forwarded a standard number of sheets to the general contractor once a week, on Thursdays, and these were forwarded to RSA by Monday morning. Knowing that we would be receiving a package each Monday morning allowed us to turn the package around by the Thursday of the same week, back to the architect, with little disruption to the schedule.

By establishing and maintaining a constant flow of information, all parties were able to collaborate successfully and help each other get an otherwise complex steel project erected within schedule and budget. **MSC**

Nat Oppenheimer is a principal, Yegal Shamash is an associate, and Ben Rosenberg is a project engineer, all with Robert Silman Associates.

Owner

The Penn State Dickinson School of Law, University Park, Pa.

Architect

Polshek Partnership Architects, New York

Structural Engineer

Robert Silman Associates, New York

Steel Fabricator

Buffalo Structural Steel Construction Corporation, Titusville, Pa. (AISC Member)

Construction Manager/General Contractor

Gilbane Building Company, Providence, R.I.

Powder Primed Tubing

Now Available!

- Square 2" - 7"
- Rectangle 3" x 1 1/2" - 10" x 4"
- Round 2 NPS - 8 NPS
- Square, Rectangle & Round in a wide variety of gauges.

EPOX Z KOTE
Powder Primed Tubing

Cut it.
Weld it.
Paint it.
Ship it.

Are you ready to uncover more profit?

- Weld spatter doesn't stick
- No VOC's or harmful fumes
- No special welding procedures
- Reduces cleaning & preparation
- Compatible with powder & paint systems
- Save space, store EPOX Z KOTE outdoors!

ATLAS TUBE

DIVISION OF THE JOHN MANEELY COMPANY

USA 800-733-5683 CANADA 800-265-6912

MADE WITH PRIDE - IN AMERICA -

SALES@ATLASTUBE.COM WWW.ATLASTUBE.COM



helping you walk on water.

**When you use ESAB,
amazing things happen.**


With the harsh environments and demanding workloads of the bridge-building structural world, even everyday jobs aren't simple. Fortunately, your choice of a welding and cutting manufacturer is. As the global authority on welding and cutting, ESAB offers the broadest selection of world-class products that meet the tough demands of the industry. So no matter the size of the steel bridge you are building, choose ESAB for powerful solutions.

WELDING + CUTTING + AUTOMATION = BRIDGE-BUILDING SOLUTIONS



Facilitating Creativity

Eye-catching architecture and innovative structural design are all but requirements when building a school geared toward the arts.



BY TERRY TSANG, S.E., AND GARY GIDCUMB, R.A.

THE ARTS ARE THRIVING IN LOS ANGELES—and not just in Hollywood and the area's mega-studios. Central L.A., with the Walt Disney Concert Hall, Museum of Contemporary Art, and sprawling Music Center complex, has become a center for arts and culture in the area. And next year, the High School for the Visual and Performing Arts will bring an educational component to this nexus of creativity.

As part of the Los Angeles Unified School District's (LAUSD) 12-year, \$20 billion construction program, the high school stands at the north end of the Grand Avenue Cultural Corridor, within easy walking distance of the above institutions. The state-of-the-art campus, built to accommodate 1,800 students, will merge sustainability, security, and a dedication to the arts in a new cultural icon.

Elements of Design

To express the LAUSD's educational visions, designers created three sculptural expressions of form in the project: a theater tower, a main performance lobby, and a library.

The tower, visible from surrounding buildings and a neighboring freeway, cuts against the downtown landscape and proclaims the school's identity. Elevated above the theater, the tower is part of the theater building's two integrated structural systems. The main building is a concrete shear wall system with steel gravity framing, with the steel tower projected from the main roof via steel braces.

The primary lateral resisting system uses concrete shear walls resting on continuous footings or concrete grade beams, and steps down with various grade changes along the building. While the engineers worked with the architect to incorporate concrete as a design feature, structural steel was chosen for the main building's primary and secondary framing systems. The steel framing system accommodates the unique functional and spatial requirements of the theater, accounting for numerous floor elevations and irregularly-shaped platforms between the orchestra pit and the roof above the stage. The main seating area is formed by a series of bent steel composite girders ranging from W10 at shorter spans to W24 at the center of the space for increased headroom. These



Photos: HMC Architects

Steel being erected for the theater tower.

members slope and fan out to support a metal deck with concrete topping.

The "Grid-Iron" platform was constructed with a combination of steel channel-shaped beams and steel grating to accommodate the increased live load. The 60-ft-tall rigging wall, which supports the heavy arbors, was constructed with HSS members, forming a grid system (vertical and horizontal) to resist induced seismic force. Framing for acoustic reflectors and clouds employed round steel pipes, channels, tubes, and angles.

The Tower

The elevated tower is an unoccupied space with an enlarged box (referred to as the tower head) located 150 ft above the lowest building grade. Early in the process, the design team decided on a structural steel braced frame system as the basic lateral resisting method. The major structural objective was to keep the tower as light as possible, thus minimizing the unnecessary burden on and demand for the main building's lateral resisting elements. By virtue of the vertical massing, a result of an unoccupied tower head with a lighter mass, and the stiffness provided by the braced members and frames, the design minimized an extra lateral load at the top level, creating a "whiplash effect."

The tower structure consisted of W14 diagonal steel braces, columns, and beams. All steel members are connected concentrically at their work point with weld and gusset plates. The tower's columns are extended to the foundation 80 ft below and encased in concrete, working with the main building's concrete shear wall and acting as composite columns. This design resulted in an increased slenderness ratio and enhanced compression-and-

tension capacity. The positive load path for the tower's induced lateral load is to the shear wall and foundation below.

The Spiral

Hovering around the tower, a second architectural feature, called the "Spiral," projects from the main structural system high above the adjacent freeway crossing through downtown L.A. As with the tower, the major structural objective was to keep the design as light as possible. The spiral assembly consists of fabricated steel pipes, each 3 ft in diameter, with a series of transverse stiffener plates inside each pipe. The spiral's exterior cover is an 8-ft square section built with structural steel tubes and angles and clad with architectural metal panels. The pipe acts as a spine, providing the necessary support for the assembly. The pipe supports a series of steel outrigger beams cantilevered from the tower's structure and reinforced with added steel side plates on each side. These plates improve the weak axis bending and torsion resistance of the W27 outrigger beam for the induced lateral force seismic or wind, which can originate from any direction.

The Lobby

During the preliminary design phase of the lobby, several "stick models" were used to illustrate the architectural form, and a collaboration of aesthetics, function, and structural performance was achieved.

The lobby structure makes use of 10-in. square hollow structural section (HSS) members as the primary structural system, the skeleton of the form. HSS members are welded together to form a moment resisting connection. Secondary HSS members support the lobby's exterior wall and architectural metal panel glazing system.

Continuity steel plates, added to all joints of the HSS members and acting as a rigid box, ensure a direct and strong load path for the induced joint moment developed at the intersection of the HSS members. An upper-level horizontal ring truss system, referred to as the "donut," was constructed at the same level as the main building's primary roof elevation. The donut level consists of HSS members to provide diaphragm action and positive load transfer for the lobby's framing above the primary roof. All HSS columns and braces are embedded into the foundation concrete. Additionally, the insides of the lower portion of these HSS members are filled solid with non-shrink and non-metallic grout to increase their torsion resistance at the critical section.

BUILDING BRIDGES



Mi-Jack Travelift® MJ Series RTG Cranes Versatility, Performance, Productivity...

Mi-Jack Products has been engineering and manufacturing material handling equipment since 1954. Through superior design and engineering, the Mi-Jack Travelift® Rubber Tired Gantry Crane is recognized for its durability and reliability.

The "MJ" Series Travelift® crane boasts superior hoist, traverse, and drive systems along with re-designed cab and engine compartment, for better productivity, ease of maintenance and a lower operating cost. With custom dimensions (heights and widths) and capacities ranging from 20 to 150 tons, the Travelift® RTG crane is sure to handle all of your lifting needs.

Give us a call today and find out how the New MJ Series Travelift® crane can provide you the Versatility, Performance and Productivity you need: (800) 6-MI-JACK or visit us at www.MI-JACK.com

© Mi-Jack Products, Inc., 3111 W. 167th Street, Hazel Crest, IL 60429



New!!!
TREAD-GLOW
Photoluminescent
solutions to
fire egress



New!!!
**Perforated
Railing
Systems**

1481 Exeter Road
Akron, Ohio 44306
www.sharonstair.com
1-800-792-0129



The library's base is approximately 91 ft in diameter, with a total of 16 steel columns sloping to a top ring at varied angles.




Analyzing the Theater

The theater consists of three components: the main building, the tower, and the lobby. The engineering team developed a SAP 2000 3D finite element computer program to simulate the structural behavior of all three components to capture all possible structural demand for them. Three major computer runs included one for the lobby as a stand-alone structure, one for the tower with the main building only, and a third with the three components combined. Through this effort, the engineering team captured the entire loading envelope of the structural design.

Library Research and Design

Designers originally considered the form of the library as an asymmetrical, cone-shaped concrete structure. In design development, however, a more economical structural steel system emerged that would set the central campus quadrant apart from traditionally designed schools. The team used a 3D ETAB model to analyze the structure.

The primary lateral resisting system for the library is the steel special concentric braced frame (SCBF) on composite steel and concrete grade beams. The library's base is approximately 91 ft in diameter, with a total of 16 steel columns sloping to



Controlled Automation BTD-8X

The latest addition to our product line is a combined drill and plasma burning machine. Each machine is supplied in 8' working width and the length can be anything up to 124'. Drilling operations are performed using a 10 hp spindle with our own proven drilling technology. A high definition autogas plasma torch which cuts material up to 2-1/2" inches thick and a standard fitted autogas oxy-fuel torch cuts material up to 4 inches. An arc-writer marking system is also available for more defined part marking.

Material Capacity

Machine


- Maximum processing width: 8'
- Drill spindle:
 - Maximum hole diameter size: 1-9/16"
 - Maximum material thickness: 2-1/2"

Plasma torch:

- Maximum edge start: 2-1/2"
- Maximum pierce: 1-1/4"

Oxy-fuel torch:

- Maximum material thickness: 4"



Controlled Automation specializes in the manufacture of automated structural steel drilling, punching, and shape cutting machinery. We also build material handling systems to complement each type of machine we offer. As well as new machinery, we are the industry leader in retrofitting control systems and remanufacturing existing structural steel fabricating machinery. All machines and controls are designed and manufactured entirely in the United States of America. All software is developed and supported in the United States of America.

501-557-5109 • sales@controlledautomation.com • www.controlledautomation.com

a top ring at varied angles. The top compression ring is constructed with HSS members. The bottom tension ring is constructed with steel beams embedded inside the 4-ft, 6-in.-deep concrete grade beam. Round HSS was used for the bracing members of the SCBF, along with W14 members at the frame columns and beams. The complex interior layout of the library challenged the engineering team to provide secondary framing for the support of the compound, and interior walls and soffits were constructed with HSS members and angles with infill metal stud framing.

Testing and Inspection

Welding is the most critical and vital element for interconnecting the structural steel members in the lobby and tower structures. In a process with no margin for error, a new technique was used in the lobby to check the joint welding. With the understanding of the client and technical assistance from Smith Emery (the material testing lab representing LAUSD), joint welds were inspected by phased array ultrasonic inspection in addition to conventional ultrasonic techniques. This recommendation from the testing lab is a more user-friendly technique than conventional ultrasonic testing (UT), simple in principle but complex in practice. Increased restrictions on weld testing requirements were also needed with the steel in the tower. Inspection and testing was based on Table 6.3 of the America Welding Standard (AWS) - UT Acceptance-Rejection Criteria (cyclically loaded non-tubular connections) rather than the industry standard AWS D1 Table 6.2 (statically loaded non-tubular connections).

As with any complex project, solutions depended upon the input from various sources and open communication within the team. The early decisions of the engineering group facilitated the construction process and laid the groundwork for a successful, structurally innovative facility. The High School for the Visual and Performing Arts is on schedule to be completed next year, less than 30 months after the initial groundbreaking. MSC

Terry Tsang is a project manager and vice president with TMAD Taylor and Gaines, and Gary Gidcumb is an architect and associate principal with HMC Architects.

Owner

Los Angeles Unified School District

Architect

HMC Architects, Pasadena, Calif.

Designer of Record

Coop Himmelb(l)au, Los Angeles

Structural Engineer

TMAD Taylor and Gaines, Ontario/Pasadena, Calif.

Steel Fabricator and Erector

Maya Steel Fabrications, Inc., Gardena, Calif. (AISC Member)

Steel Detailer

SNC Engineering, Inc., Compton, Calif. (AISC Member)

General Contractor

PCL

Ficep with "Wireless Technology" Now Offers the Fastest Single Spindle Drill Line on the Market Today!



That's right! Ficep has pushed the technology and performance level of single spindle drills to a new level by incorporating many proven technological features that are part of their multiple spindle CNC drilling lines. **Some of the productivity features that are now part of the new Victory 11 are:**

- ◆ Positive ball screw spindle feed to use **carbide tools** for unbelievable feed rates.
- ◆ **2,000 RPM** spindle speed.
- ◆ **Wireless remote control** enhances floor-to-floor productivity by 30%.
- ◆ **Self contained design** eliminates the need for trailing cables, wires, hoses, etc.
- ◆ **Integrated chip collection** system.



All this and more at an extremely attractive price!

Give us a call to find out how you can substantially reduce your man hours per ton for an investment equal to the **annual cost of one employee.**



2301 Industry Court
Forest Hill, Maryland 21050
410-588-5800 • 410-588-5900 fax
www.ficepcorp.com



AISC Annual Meeting

The Broadmoor

AISC would like to thank the following sponsors
for supporting the 2008 Annual Meeting

Platinum

Nucor-Yamato Steel Company

Gold

**Stites & Harbison
W&W / AFCO Steel**

Executive

**National Steel Constructors
Peddinghaus Corporation**

Elite

**AISC Bender-Roller Committee
FabArc Steel
Gerdau Ameristeel**

Silver

**Bosworth Steel Erectors
Buckner Companies
Consolidated Systems Inc.
El Paso Machine & Steel
Peterson Beckner Industries, Inc.
Wheeling Corrugating**

Bronze

**Gooder-Henrichsen Company
Metals USA**

Golf Boxed Lunches

**Alpha Industries
Tekla**

Golf Tournament

**Alpha Industries
Corus
FabArc Steel**

A Model Museum

BY LISA MINAKAMI, P.E., AND DERRICK ROORDA, P.E., S.E.

Extensive 3D modeling helped to create and navigate the framing for a new art museum in Virginia.

MOVING TO NEW FACILITIES SEEMS TO BE PART OF THE 21ST CENTURY AMERICAN WAY OF LIFE. Offices, hospitals, and professional sports teams seem to do it all the time. But it's a rarer occurrence for art museums.

The Art Museum of Western Virginia in Roanoke, Va. is embarking on such a move. And, it's getting a new name. The new Taubman Museum of Art, the Art Museum of Western Virginia's new incarnation, will open this fall. The 82,000-sq.-ft facility will house the museum's permanent collection and greatly expand its exhibition and education spaces. As the city's most contemporary structure, it represents Roanoke's metaphorical gateway to the future for a city transforming its industrial- and manufacturing-based economy to one driven by information technology and services.

The new museum's forms and materials interpret the renowned beauty and drama of the Shenandoah Valley and the adjacent Blue Ridge and Appalachian Mountains. A dramatic, spacious atrium that rises to a peak of 75 ft is the hub of the entire facility, while angular exterior walls rise to support a curving roof whose various textures and forms emphasize the rocky surfaces found in the region's caverns, cliffs, and river gorges.

Scheming in 3D

Structural steel forms the curving roof forms and steel framing is featured as an architectural element in the atrium lobby. The floor levels, while irregularly shaped in plan, each have a con-

stant floor elevation, and were therefore framed using conventional methods. Initially, both steel and concrete floor systems were considered, but a large number of transfer girders and tight floor-to-floor height requirements resulted in steel being used for this portion of the project as well.

The curving roof forms and other complex surface geometries necessitated the use of a 3D modeling program in order to accurately convey the required member work points and geometry to the design and construction teams. Several programs were considered but the design team chose Rhino, which can create, edit, analyze, document, render, animate, and translate NURBS (non-uniform rational B-spline) curves, surfaces, and solids. It proved indispensable from schematic design, through the design stage and into construction administration, when various Rhino files were provided by DeSimone and project architect Randall Stout Architects (RSA) as part of the construction document package.

During schematic design, RSA used Rhino to investigate various geometric forms. These architectural models consisted of the curved exterior surfaces, which could be offset to define the top of the steel elevations. The museum's roof consists of several distinct curved surfaces, though each individual surface has a single radius, which greatly simplified construction and reduced fabrication costs. Despite the visual geometric complexity of the roof, its curving shape was achieved with a straightforward structural framing

Randall Stout Architects, Inc.


The Art Museum of Western Virginia's lobby atrium features nine architecturally exposed W14 structural steel columns that each slope 23° from vertical.

system; curved WT4×17 joists spaced at 6 ft supported a metal roof deck that curved in its weak direction. The WT4×17s in turn were supported by straight beams that framed into kinked girders.

Finding column locations that worked with the roof geometry, and that did not interfere with the gallery space below, was a challenge that resulted in numerous column transfers and cantilevered beams. To keep track of the multiple load path transitions running vertically down the building, a single RISA-3D model with both gravity and lateral members was created. Past project experience with RISA-3D had proven that it could accommodate unusual building geometries. Plus, member locations and orientations could be imported directly from Rhino using .dxf files. The composite floor slabs, in turn, were designed using RISAFloor, which seamlessly integrates with RISA-3D.

Share and Share Alike


During the detailing stage, the structural Rhino model was provided to the steel detailer, Superior Steel, who imported the steel members into the detailing program SDS/2. Due to the unique challenges posed by the building's geometry, the design and construction teams decided to submit and review "shop models" prior to the creation of shop drawings. After the steel detailer completed detailing a portion of the structure in SDS/2, the model was then



Randall Stout Architects, Inc.

converted back into a Rhino model and provided to the design team for review. The shop model review was primarily to review member geometries and to identify conflicts with architectural surfaces and building systems; verification of member sizes and connections were done later in the shop drawing phase. Both DeSimone and RSA formally commented on the shop models using Rhino's "dots" and "notes" features, in which members were "tagged" with text dots, directing the detailer to the appropriate comment in the Notes section. If geometry revisions were required by the design team, the affected structural members were remodeled, placed on a separate layer, and highlighted in red—the shop model version of the cloud and delta procedure used for 2D drawings, in which drawing changes are clouded and marked with a revision number.

Shop models were also reviewed by the glazing and cladding subcontractors, whose secondary support members attached to the structural steel. During each shop model review period, the design and construction teams, which were scattered across the country, conducted web conferences using Webex, a technology that allows participants to share and view each others' desktop applications. Webex enabled the architect, structural engineer, general contractor, steel detailer, and glazing and cladding subcontractors to simultaneously view a single shop




Randall Stout Architects, Inc.

The museum's exterior is intended to echo the surrounding area's geological features.

FROM 3D TO 2D

To fully convey the building geometry to the construction team, both RSA and DeSimone provided Rhino models in addition to conventional 2D drawings. RSA's Rhino models contained information such as the exterior surface geometries, mullion patterns, and top-of-concrete elevations. DeSimone's Rhino model contained solid and wireframe modeling of the roof and atrium steel members. The 2D structural drawings contained framing plans, column schedules, sections, and details as would be found in a typical construction drawing set. Only by also providing a Rhino model could geometries such as the curve of the WTs and the kink of the roof girders, be defined. Besides being a powerful visual tool, Rhino also proved useful in creating 2D axonometric views of the more complex geometric forms. (Using the "Make2D" command, Rhino can flatten a model's current view into a series of lines, which can then be imported into AutoCAD to create elevations and details.)



DeSimone Consulting Engineers.

model. In this manner, conflicts were identified and resolved quickly by all affected parties.

The Atrium, "Knuckle," and Theater Cantilever

The lobby atrium posed a unique structural challenge for DeSimone. It features nine architecturally exposed W14 structural steel columns that each slope 23° from vertical. To stabilize the atrium columns and essentially keep the atrium from tipping over, 2-in.- and 3½-in.-diameter pretensioned rods pull the peak of the atrium and tie it down to the rest of the structure. A continuous ring of HSS22×20 beams further stabilize the atrium columns and support the glazing system, which hangs from the ring using a series of pre-stressed cables that match the slope of the atrium columns. DeSimone performed a non-linear analysis of the roof diaphragm, which consists of 2-in.-diameter pretensioned cross-rods that span between the HSS22×20 beams. Pretensioned rods also span between the atrium columns to provide weak-axis lateral support.

Just northeast of the lobby atrium is a portion of the structure referred to as the "knuckle" in which a conical surface spans vertically between the second and third floor levels. This conical surface, along with several other unusually shaped exterior surfaces, uses ZEPPS, an engineered panel system created by A. Zahner Company, the cladding subcontractor. ZEPPS panels can take on any shape, curve, or bend and are prefabricated in the shop, eliminating the labor-intensive field fabrication associated with build-in-place systems. At the knuckle, the use of ZEPPS meant that a single conical panel needed to be attached to the primary steel structure, which greatly simplified construction and resulted in a better quality building envelope.

Another striking feature of the museum is the "theater cantilever" at the southeast corner of the building. As its name implies, the theater cantilever is supported at the second floor level by a series of W33 beams that cantilever dramatically over the exterior sidewalk. Transfer columns supporting the third floor framing sit on the tips of these canti-

levered beams, while HSS "arms" cantilever from the transfer columns to support the curved surfaces that wrap the theater cantilever. Similarly, complex load paths occurred throughout the building structure, requiring careful analysis and evaluation of expected construction sequences and vertical displacements.

MSC

Lisa Minakami is a senior project engineer and Derrick Roorda is a senior associate principal at DeSimone Consulting Engineers in San Francisco.

Owner

Art Museum of Western Virginia,
Roanoke, Va.

Architect

Randall Stout Architects, Inc., Los Angeles

Structural Engineer

DeSimone Consulting Engineers,
San Francisco

Steel Detailer, Fabricator, and Erector

Superior Steel, Knoxville, Tenn.
(AISC Member)

General Contractor

Balfour Beatty Construction, Fairfax, Va.

VERSATILE COPING ROBOT for Structural Steel

"Versacope" makes the difference!


DAITO's Versacope CR4816 coping robot is the most versatile/efficient partner of your business.

The distinctive features:

- ♦ Six [6] axes Robotic Arm
- ♦ Hypertherm HPR-260 Plasma
- ♦ Three [3] axes Oxy
- ♦ Rapid material feed system by pinch roller
- ♦ Precise material measurement by touch probe



Bevelling



Web Coping



Flange Coping



Haunching



Plate Processing




DAITO U.S.A., INC.

1470 Elmhurst Road, Elk Grove Village, IL 60007
Tel: 847-437-6788 <http://www.daitousa.com>

► **FASTRAK**TM BUILDING DESIGNER

FASTRAK is a market leading, proven solution for steel building design. Discover how **FASTRAK** can save you time and money. Register for a FREE demonstration at www.cscworld.com/fastrak/us

- The latest intuitive 3D interface for rapid model creation
- Unlimited geometrical building complexity
- Fully automatic gravity and lateral design in one model
- Automated detailed composite design
- Revit Structure integration



The software solution for structural engineers

Fastrak Building Designer is the most comprehensive, easy to use, dedicated software solution for general steel and composite building design. Complete physical design models are quickly created via an intuitive interface. Full model validation allows you to make changes with minimum effort. It produces fast, accurate, gravity and lateral design results, automated drawings, material lists and is BIM compliant. CSC is a world leader in the development of Building Design Solutions for structural engineers.



Tel: 877-710-2053

Email: sales@cscworld.com

www.cscworld.com/fastrak/us

CALCULATIONS

ANALYSIS

DESIGN

3D MODELLING

DRAWINGS

SUPPORT &
TRAINING

Stability Analysis: It's not as Hard as You Think

BY CHRISTOPHER M. HEWITT, S.E.

The Direct Analysis Method is a good choice for stability design—and with a little guidance, it can be a relatively simple process.

STABILITY IS FUNDAMENTAL TO DESIGN, YET IT CAN BE CHALLENGING TO understand, as many of the current provisions are new. The AISC *Specification* allows designers to use any method of stability analysis that considers each of the following:

- Second-order effects
- Flexural, shear, and axial deformations
- Component and connection deformations
- Member stiffness reduction due to residual stresses
- Geometric imperfections

Each of these effects is considered in all three stability design methods presented in the AISC *Specification* (the Effective Length Method in Section C2.2a, the First-Order Analysis Method in Section C2.2b, and the Direct Analysis Method in Appendix 7). The Direct Analysis Method is discussed here, as it offers an advantage: It eliminates the need to calculate *K*-factors in design. The *K*-factor, a long-standing feature of structural frame design, is well accepted as a means to implicitly capture many of these effects, in spite of its many limitations and underlying assumptions that are rarely satisfied in real structures.

The Effective Length Method is still permitted with minor changes in the AISC *Specification* and remains based in the use of *K*-factors in design. But after evaluating the Direct Analysis Method, you may see that it allows for a more transparent, intuitive, and often easier approach to design for stability.

Buckling

The most fundamental theoretical formulation in stability design and buckling of columns is the Euler formula, which defines the elastic axial buckling strength of a member as:

$$P = \frac{\pi^2 EI}{L^2}$$

The theory behind this strength equation assumes that the column is perfectly plumb and straight, behaves elastically, and has pinned ends that are restrained against lateral movement. These

assumptions all are commonly violated in real structures. In practice, columns lean due to fabrication and erection tolerances and are out-of-straight between braced points due to mill and fabrication tolerances. Residual stresses are present that cause inelastic behavior. Further, as a structure is loaded, deformations and drift also occur, adding second-order forces and moments. Not only must these effects be accounted for in design, but the fact that column buckling always involves both an axial force and bending effects also needs to be recognized.

Second-Order Effects

When flexure is introduced into an axially loaded member from the axial force acting through the sidesway of a frame and curvature of a member, this is referred to as a second-order effect. The analysis of the structure must be modified to capture the impact of these effects, as they will not be realized in a first-order design model of initially plumb frames and straight members. The primary effects to be considered are *P*-Δ moments, associated with the sidesway of the structure, and *P*-δ moments, associated with the curvature of each individual member as it deflects and deforms.

The moments generated by these effects can be captured in the analysis in several ways, and any method that a designer chooses to analyze a structure that captures each of the possible effects is acceptable. Therefore, it is equally permissible to analyze a structure by a direct, rigorous second-order analysis, or to use an approximate method of second-order analysis, such as the one presented in *Specification* Section C2.1b.

In the former case, the frame and member deformations are tracked directly within the analysis software as a part of the analysis. In the latter case, a first-order analysis is made and the resulting forces and moments are amplified using the variables *B*₁ and *B*₂ from the AISC *Specification*. *B*₁ captures the amplification of forces and moments due to the curvature or out-of-straightness of the member (*P*-δ), and *B*₂ captures the amplification of forces and moments from the drift of the frame (*P*-Δ). These effects are illustrated for a single column in Figure 1.



Christopher Hewitt is a project engineer with Forefront Structural Engineers in Chicago. He is a former senior engineer with AISC.




Figure 1. Basic model describing $P-\Delta$ and $P-\delta$ effects for a single fixed-base column.

Deformation of the Structure

Engineers are generally familiar with methods of calculating the deflections of members under load. While the structure can be analyzed conventionally for the deflections of individual members, it is important to be sure that these deflections are captured in a second-order analysis of the frame. As stated previously, it is equally permissible to analyze a structure by a direct, rigorous second-order analysis, or to use an approximate method of second-order analysis, such as the one presented in *Specification* Section C2.1b. It also is important to consider the effect of connection and panel-zone deformations in the analysis.

Residual Stresses

Residual stresses are introduced into structural shapes as a result of the pro-

duction process. Residual stresses include stresses due to temperature, as some elements of the hot rolled cross-section will cool faster than others, and also due to the effects of straightening that must be done to meet ASTM A6 tolerances. Areas with residual stress will yield prior to the overall yielding of the section, causing the column to lose some of its stiffness before reaching its theoretical buckling strength. The effects of residual stresses on member strength are accounted for in the column equations. However, the loss of stiffness due to residual stresses also will increase the frame and member deformations. This is accounted for in the Direct Analysis Method by using a reduced stiffness for all members in the analysis: multiplying the axial stiffness, EA , of all members by 0.8 and multiplying the flexural stiffness, EI , of all members by $0.8\tau_b$, where τ_b is the column stiffness reduction factor.

Geometric Imperfections

Geometric imperfections are inherent in all structures, and limits on these are found in the *AISC Code of Standard Practice* (plumbness of frames) and the ASTM standards for structural shapes (straightness of members). Frame out-of-plumbness is modeled directly in the Direct Analysis Method using notional loads acting laterally at each floor (alternatively, this can be done by direct modeling of the out-of-plumb frame geometry, if it is known).

A notional load is an equivalent lateral load of appropriate magnitude such that it

will generate a story shear in the structural model equivalent to the effect of the axial loads in a story acting in the deformed position, as illustrated in Figure 2. According to the *AISC Code of Standard Practice*, the permissible tolerance on out-of-plumbness of any individual column is no larger than $L/500$, and the notional load is specified to generate a story shear corresponding to this amount of out-of-plumbness. A horizontal notional load of 0.002 times the story gravity load in the horizontal direction is applied, with the 0.002 coefficient being equal to $1/500$ —the erection tolerance permitted by the *Code of Standard Practice*.

Leaning Columns

In any stability analysis, it is necessary to capture the destabilizing effects of columns that rely on the lateral frame for stability but are not a part of the lateral frame. These columns with pinned ends are commonly referred to as “leaning columns.” When modeling the frame, leaning-column effects can be captured either by developing a complete 3D model of the frame or by assigning a single equivalent leaning column carrying the summation of all of the gravity loads on all of the leaning columns in the structure, as a pin-connected part of a 2D frame. An example of how this might be modeled in a 2D analysis is shown in Figure 3.

Step-by-Step Analysis

Now that you know the basics, here is a simple step-by-step process to guide you as you use the Direct Analysis Method:




Figure 2. Equivalent loading using notional loads to represent the effect of geometric imperfections on a column.




Figure 3. 2D frame model that captures leaning column effects.

1. Create a model of the lateral frame being analyzed, including the leaning columns.
2. Reduce the stiffness of lateral framing members in your model.
 - a) **For a braced frame** modeled with pinned connections, this can be done by modifying the modulus of elasticity in your model to 0.8 times E (23,200 ksi).
 - b) **For a moment frame** (or a braced frame modeled with rigidly connected members), this can be done by modifying the modulus of elasticity in your model to $0.8\tau_b E$. As an alternative to applying τ_b , add a notional load of 0.001 times the gravity load to the notional load in step 3.*
3. Apply notional loads to all load combinations equal to 0.002 times the gravity load[†] on each story at the story level.**
4. Conduct a second-order analysis of the structure under applied loads, either by the Amplified First-Order Analysis approach (B_1/B_2) or by completing a direct, rigorous second-order analysis of the structure.
5. Reset your modulus of elasticity to $E = 29,000$ ksi and design the members using the equations in the AISC *Specification* to resist the forces that you have just determined, with $K = 1$.
6. Check drift limits for wind and seismic design.
7. Pat yourself on the back for doing a great job on your analysis! MSC

This topic is discussed in greater detail in a presentation by R. Shankar Nair, S.E., Ph.D.—the 2007 AISC T.R. Higgins Lecture—which can be viewed for free at www.aisc.org/boxedlunch.

Footnotes

* τ_b may be taken as 1 if $\alpha P_r < P_y$. This may, however, require iteration in the analysis if the member sizes change and the inequality reverses. Moment frames will often satisfy this inequality, allowing τ_b to be taken as 1.

[†]The term “gravity load” refers to either the LRFD gravity load combination or 1.6 times the ASD gravity load combination on each story.

** Per the AISC *Specification*, notional loads only need to be added to load combinations in which the notional load is larger than the lateral load on the frame. Thus, notional loads usually can be ignored in all but the gravity-only load combinations. However, if a designer wishes to simplify the design process, it is always conservative to include the notional loads.

START SPREADIN' THE NEWS.

THE GIRDER-SLAB® SYSTEM DELIVERS DRAMATIC SAVINGS IN COST, LABOR & TIME.

THE AQUA
LONG BEACH LONG ISLAND, NEW YORK



50 Projects either completed or under construction and 5.1 million SF of new projects in Development

The Girder-Slab® System combines the speed of steel with the low floor to floor heights of flat plate. Use your design team, choose your own subs.

For more information
call **888.478.1100**
or visit www.girder-slab.com





The combined advantages of structural steel and flat plate concrete

Recipient of the AISC Special Achievement Award.



Our first-stage processing is really a two-step process: Eliminate bottlenecks. Improve cash flow.

The best service available starts with our comprehensive structural steel inventory of more than 250,000 tons, and provides low-cost Just-In-Time delivery through our six Stocking/Processing service centers strategically located for your convenience.



We perform a variety of first-stage processing services using CNC machines for saw, flame, and plasma cutting, Wide-Flange-beam cambering, and rotary-shear splitting for cleaner, straighter Tees. And we support those services with in-house trucks making timely deliveries of pre-processed and stock sections.



For OEMs, fabricators, and local distributors, our services provide greater efficiency in reducing bottlenecks at your shop and in maximizing cash flow by making sure you don't store or finance your material any longer than necessary.



As an active participant in the AISC, Infra-Metals knows the materials needs and challenges you face.

- A. Wallingford, CT 800-243-4410
- B. Langhorne, PA 800-899-3432
- C. Baltimore, MD 800-235-3979
- D. Petersburg, VA 800-435-0850
- E. Tampa, FL 800-693-1361
- F. Hallandale, FL 800-432-1146
- G. Marseilles, IL 800-987-5283



Whether you're looking to avoid a production bottleneck or a cash flow pinch, contact your local Infra-Metals office today or visit www.infra-metals.com for a quote on your exact needs.



INFRA-METALS

Customer Satisfaction Built With Steel

The Quality Diet: Building A Healthy Business

BY TIMOTHY J. FOLKERTS

Implementing a corporate quality system is much like dieting—and there's a lot more to both of these processes than you might think.

LET'S FACE IT: QUALITY IS NOT ALWAYS AN EASY SELL.

Explaining the principles and techniques to people outside the field can be challenging. Convincing management to invest in the effort can require considerable perseverance. Sacrificing the hard cash you'll get from today's shipment for future good will is the sort of delayed gratification businesses aren't always ready to accept. At every turn there is pressure to cut corners, hide problems, and just go along.

When facing such challenges, it is helpful to remember one simple analogy: Succeeding with quality improvement is like succeeding with a diet.

Quality Pros/Corporate Dietitians

Quality professionals could be called corporate dietitians—there to guide businesses to healthier lifestyles.

A poor diet leaves a person vulnerable. Carrying around extra weight makes everything just a little more difficult and time consuming. Chronic problems like diabetes are aggravated by obesity. Hidden problems like high cholesterol caused by too much saturated fat or high blood pressure caused by too much dietary sodium can lead to sudden, life-threatening heart attacks. Of course, better nutrition isn't a cure-all for these problems but it certainly can limit the risks.

Similarly, poor quality leaves a company vulnerable. Inefficient procedures and management make everything just a little more difficult and time consuming. Chronic cost overruns due to poor quality of incoming materials and supplies sap competitiveness. Hidden problems in the quality of outgoing products can lead to sudden, bankrupting product recalls or lawsuits. Better quality isn't a cure-all for these problems but it certainly limits the risks.

With people, survival of the fittest has been mitigated somewhat. We have tamed the world around us and eliminated many natural hazards. We have family and friends to support us when we are sick or weak.

The corporate world is not so forgiving. When times are good, it is possible for a poorly performing company to survive. When times are bad, the wolves will descend, culling many of the weak and inefficient.

Potential Gains

Many people don't realize that the primary purpose of a diet should not be to lose weight. Instead, the primary purpose should be to improve health. Weight loss is just a pleasant, visible side

effect. In fact, the original motivation for the diet could be something besides weight loss; it could be reducing sodium, fat, and cholesterol, for example. Concentrating simply on one facet of the diet can lead to poor nutrition—insufficient vitamins, minerals, or protein for proper health. Taken to an extreme, concentrating exclusively on weight loss can lead to anorexia—a life-threatening condition.

For a corporation, the primary goal of a quality improvement initiative is improved corporate health. A single-minded effort aimed at cutting costs won't do. Neither will efforts aimed solely at increasing quarterly profits, eliminating defects, or pushing more products out the door.

While costs, quarterly profits, defects, and production all are important, pursuing any one too aggressively will only lead to problems. Excessive cost-cutting will leave a company anemic. Relentless pursuit of short-term profits often simply delays problems, as Enron learned. Reducing defects significantly is often possible, but making the products perfect becomes cost-prohibitive. Raising production without improving or at least maintaining quality can lead to loss of customer loyalty and sales.

Quality is not just about reducing fat but also about improving the true viability of a company.

Choosing an Approach

The potential approaches to dieting and weight loss are almost limitless: low fat, low carb, vegetarian, replacing meals with diet shakes, skipping dessert, eating lots of grapefruit, using diet pills advertised on late-night television, proprietary programs like Jenny Craig and Weight Watchers, fasting, gastric surgery, and liposuction.

Many approaches can be quite effective at both weight loss and improved health, some are mildly helpful, but a few are actually dangerous. You can go it alone or join a group. You can sign up for a brand name plan or create your own. You can mix and match several different approaches. You can get advice from an expert or buy a book or simply jump on the latest bandwagon.

Ideally, a person interested in improved health should work with a dietitian or nutritionist to develop the right plan. The expert can ensure the diet will help achieve desired goals while still providing the balanced nutrition required to maintain health.

Similarly, a company interested in quality improvement ideally should use quality professionals to develop the plan that is right for that company, because quality improvement choices are

Quality Corner is a monthly feature that covers topics ranging from how to specify a certified company to how long it takes to become a certified company. If you are interested in browsing our electronic archive, please visit www.aisc.org/QualityCorner.

as varied as diets: total quality management, plan-do-check or study-act, statistical process control, design of experiments, acceptance sampling, multi-vari plots, ISO 9001, TS 16949, lean, Six Sigma, lean Six Sigma, Dorian Shanin's Red X, W. Edwards Deming's 14 points, Joseph M. Juran's quality trilogy, and Philip Crosby's zero defects, to name several.

The right method, or combination of methods, will improve the viability of an organization by improving products and processes. The wrong approach could actually weaken an organization by diverting resources to the wrong problems.

Implementing the Plan

Even after a plan of attack has been chosen, success is still a long way off, and that success cannot be achieved by the dietitian. The dietitian can educate the client about nutrition issues. The dietitian can encourage the client to develop a support network. The dietitian can provide forms to track progress. The dietitian can applaud success

and watch for backsliding. The dietitian can set up weekly or monthly meetings to provide in-person feedback.

Ultimately, though, no matter how well-crafted the plan, it won't succeed unless the client acts on the plan. The client needs to be committed to improved health.

Quality professionals face the same sort of challenge. Corporate leaders might say they want improvement but not carry through with appropriate action. It is important to educate and encourage. It is helpful to get suppliers and customers on board. It is valuable to track progress—anything to provide motivation and keep focused on the ultimate goals. The quality professional provides his or her support, but without leadership buy-in to quality improvement, it can't and won't happen.

Potential Pitfalls

Quality improvement and dieting can encounter similar pitfalls. Once you recognize the following five potential pitfalls,

you improve your chances of overcoming them, allowing you to lead your organization to quality improvement and business health:

1. Lack of tact
2. Not understanding the system
3. Focusing on the short term
4. Yo-yo quality
5. False economy

Lack of tact: People don't like to be told they are fat, and bosses don't like to be told they are running a poor-quality operation.

With a receptive boss, a direct approach might work best but make sure you have a plan before you start pointing out problems. Even though a wise leader will acknowledge the truth and recognize that something must be done, he or she must be approached tactfully. Issues with suppliers or customers can often provide an opening to broach the subject.

At other times a stealth quality approach might be better. This is the equivalent of not telling your overweight spouse that you are now buying low-fat ground beef and diet desserts. After gains have been realized in small ways, the boss might be more receptive to learning about bigger improvement opportunities.

Not understanding the system: Weight Watchers uses a point system to monitor food intake. For example, one large apple is two points. If you aren't careful, it is easy to miscount points. If you make the mistake of counting one apple as one point several times, the diet will fail.

Similarly, small misunderstandings can lead to the failure of quality improvement initiatives. Whether it is miscalculation, miscommunication, miscalibration, or any number of other mistakes, quality plans have the potential to misfire if key ideas about the system are not understood.

Focusing on the short term: It is not uncommon to lose an unusually large amount of weight during the first week of a diet. This can set up unrealistic expectations and lead to later discouragement. It is also quite possible to stick faithfully to a plan, but see different amounts of weight loss each week. The dieter might be tempted to restrict calorie intake even more following a week of poor performance or to ease up after a week of exceptional performance.

Yo-yo quality: Many managers don't seem to have time to do things right the first time but they always seem to have time

FABSUITE

STEEL FABRICATION MANAGEMENT SOFTWARE

Find out why Fabricators Love FabSuite

**Call for your 30 Day FREE Demo CD...
(757) 645-0842**

Now There Are No Excuses!



- ◆ ESTIMATING
- ◆ INVENTORY CONTROL
- ◆ PROJECT MANAGEMENT
- ◆ COMBINING (MULT/NEST)
- ◆ BAR CODING INTERFACE
- ◆ PRODUCTION CONTROL
- ◆ PURCHASE ORDERS
- ◆ ORDER ENTRY



P.O. Box 5366, Williamsburg, VA 23188

757-645-0842

www.FabSuite.com

to fix things later. This is the equivalent of yo-yo dieting. You overeat and exercise too little for a couple months, and then you discover you've put on 20 pounds. For the next two months, you have to work three times as hard to lose those pounds and get back in shape. Maintaining steady progress all along is much easier overall than reacting to fix self-created problems.

False economy: Skipping lunch but then eating three candy bars in the afternoon because you are starving is not effective for dieting. Bragging about all the lunches you've skipped won't change the fact that you are still gaining weight.

Similarly, cutting costs in one division but passing along equal or greater costs to other divisions is not a viable business plan. The manager or vice president of the cost-cutting division might be able to brag about improvements but the improvements don't prevent the business from losing more money than before.

Lasting Success

Quality can't be temporary. Quality can't be just a slogan. Quality can't be the job of just one person or one department. Quality can't be subordinate to today's production quotas.

Ultimately, success means a fundamental change in corporate lifestyle. As long as the mentality is, "We just need to do this until we reach our goals," or, "We just need to do this until the boss gets a new pet project," then failure is never far away.


So, the next time you have one minute to explain what quality professionals do, tell them you are the corporate dietitian. You have the plans to make the company healthier by eliminating poor habits that sap profits. You champion improvements that make everyone look better. You study and educate and encourage and implement to make those improvements a reality. And you would be happy to share that knowledge with them anytime they want to know more.

MSC

Timothy J. Folkerts is a physics instructor at Barton County Community College in Great Bend, Kan. He earned a doctorate in physics from the University of California at Davis. Folkerts is a member of ASQ and a certified quality engineer and reliability engineer.

A longer version of this article first appeared in the May 2007 issue of Quality Progress. This excerpt is reprinted with permission.

Bar Grating Attachment MADE EASY!



P/N: GG-1A
shown above

G-Clips™ attach grating materials to structural members. Installed with simple hand tools, G-Clips are a low cost, fast and dependable way to fasten grating.

- ➔ G-Clips are available in galvanized carbon steel, stainless steel, copper-nickel alloy or aluminum.
- ➔ G-Clips do not damage structural members, paint or coating systems.
- ➔ G-Clips resist more vibration than other fastening methods.
- ➔ G-Clips make installations easy, fast and economical.

Model GG: This galvanized carbon steel grating fastener is economical and easy to install. It fastens bar grating to structural members with the structural flange in a horizontal plane.

Call Toll-Free:
800-227-9013



P.O. Box 6438, New Orleans, LA 70174
www.gclips.com • Email: sales@gclips.com

The Utmost in Beauty & Performance.

Crafted from top quality, all-weather 316 stainless steel, Sta-Lok® tensile rated rod systems are exceptionally versatile, durable, attractive and low maintenance. All Sta-Lok® rods are made to order with special tension fork end fittings that allow adjustability without bulky turnbuckles or exposed threads. Quick delivery and a 30-year track record of excellence make Sta-Lok® the reliable choice for your next project.

STA-LOK®
ROD ASSEMBLIES

Call for a free catalog
800-888-2418 or visit
www.feeneyarchitectural.com

feeneyarchitectural
PRODUCTS





HOW
SOLID STEEL
— | HELPED STRENGTHEN | —
OKLAHOMA
PIGSKIN.

Because Oklahoma weather is so volatile, the OU Sooners desperately needed an indoor practice facility. But the construction site was so small, there was no room to store the mammoth bowstring and long-span joists needed to support the building's roof. So when the Nucor Vulcraft Group was able to deliver the steel in precisely timed waves, we were able to help finish the project ahead of time. And give the Sooners the ability to practice through rain, sleet, snow and dark of night. 24/7 if need be. Sorry about that, guys.

It's Our Nature.®



— | Visit www.vulcraft.com | —

ocean CLIPPER

CNC ANGLE LINE FOR CLIP ANGLE PRODUCTION

Made in the USA



The most
affordable and
compact CNC angle
line in the world!



- ✓ Unique design uses a drill and punch combination
- ✓ Small footprint – no bigger than an ironworker
- ✓ Efficient use of angle – drop length 8-1/2"
- ✓ Process angles from 1-1/2x1x1/2x1/8" up to 6x6x5/8"
- ✓ Drill holes up to 2" dia
- ✓ Punch slots up to 1-1/4"
- ✓ Reduce your labor costs
- ✓ Speed up production and increase your output
- ✓ Increase accuracy – speed up your on-site erection
- ✓ Import directly from your CAD drawings (DSTV)
- ✓ Built and serviced by Peddinghaus

Call for a FREE Video & Brochure

Tel 800.286.3624 • 954.956.3131 • Fax 954.956.3199
www.oceanCLIPPER.com • www.oceanmachinery.com

Buy Direct, Packed to Order!



Our New Rigid Polyethylene Kegs RPK's for Short, will keep you safer at the jobsite and for your AISC audits. They can be resealed much easier than the traditional metal kegs. *No more bent lids!*

- No Rust
- Seamless
- Built in Handles
- Safer, no sharp edges
- Recyclable
- Durable
- Reusable
- Made in USA
- Re-purposed
- Easy Off /Easy On Lids w/gaskets

- ★ Heavy Hex Bolts (A325, A490)
- ★ TC (Tension Control) Bolts
- ★ Low Carbon Bolts (A307)
- ★ Anchor Bolts (F1554 gr. 36,55,105 as well as A449, B7, Stainless Steel)
- ★ Many Other Structural Fasteners



St. Louis
SL
1887
Screw & Bolt

St. Louis Screw & Bolt
2000 Access Blvd
Madison, IL 62269
Phone: 800-237-7059
Fax: 314-389-7510

www.stlouisscrewbolt.com
sales@stlouisscrewbolt.com

A FAIR AND BALANCED OFFER

BY TIM R. JOHNSON

Framing a job offer properly can be the difference between landing a top-notch candidate and scaring him away.

WHEN PURSUING GAINFULLY EMPLOYED CANDIDATES—those top-talent hires that mean so much to the success of a firm—framing the best possible offer is critical. Approaching those best-of-the-best with new employment opportunities virtually always requires both promotional possibilities and a compensatory increase.

Recruitment that includes relocation almost always requires a salary increase of 15% or more, I've found—especially in the current real estate market—and usually comes with a whole grab-bag of surprise challenges. That means the most viable hires needed for company growth and success are just next door, on the staff of local competitors. Attracting talent from nearby competition, however, is no simple task itself; it requires a careful approach. Perhaps most important is framing the best possible offer. Here's an example of a common mistake that is easily overlooked, and just as easily overcome when handled appropriately.

In pursuing a top-notch candidate, a client of mine recently faced the challenge of how to frame the best offer. (To protect the innocent—and myself—let's call the candidate Joe and the company Tobinelli Associates.) Joe was interested in working for Tobinelli Associates upon the first introduction, and viewed the position as a highly advantageous next step in his career. After several meetings, both Joe and Tobinelli Associates felt that there was an excellent connection on both cultural and personal levels. Everything seemed to align well in everyone's favor. Then, the offer went out. And Joe turned it down.

Joe rejected the position because of money, even though he was well within the targeted salary range and was not looking for an unreasonable increase. Tobinelli could have easily overcome this negative reaction had they managed the offer stage more effectively.

Early on in the recruitment process, Joe made it very clear that his principal interests were a fair salary boost and opportunity for increased responsibilities in a new position. Both interests weighed in equally. Tobinelli wasn't sure they could deliver completely on the salary side, and were looking to offer about an 8% increase. To make up for what they felt was a shortcoming, Tobinelli framed the position as a high management post with several staff reports and significant business development responsibilities. The intention was to make the job sound "big"—in fact, "bigger" than it truly was—so as to inflate the growth opportunity in place of a much higher salary.

After listening to this new pitch, Joe actually asked for *more* money than he originally wanted, because Tobinelli made the job seem like it entailed significantly more responsibility than Joe had initially anticipated. Tobinelli countered with a revised offer—more than they first intended to pay—but it still wasn't enough, because they had already cast the die for the position, and it was too late to amend the job description. Joe decided to stay with his current employer, in a position with fewer responsibilities, and at a lower salary than he could have accepted.

What could Tobinelli Associates have done differently? First, never oversell responsibility to balance out what may be a lack in immediate monetary compensation, because that will have an adverse effect and cause candidates to want more money. Instead, sell *opportunity*. Explain that the position pays a certain figure on day one, but enumerate the opportunities for career growth (and with that, compensation growth) months and years down the line.

There's more to it than money, of course. For example, Joe mentioned during the interview that he desired to pursue an MBA. Tobinelli could have focused on the fact that they offer an excellent tuition reimbursement plan, and could have also explained to Joe the additional opportunities that would have been available to him once he earned that degree. Tobinelli should have focused on strong short- and long-term selling points, rather than trying to play a balancing act with salary and responsibilities alone.

The bottom line is that, regardless of what many say, salary is going to be a primary issue when hiring managerial staff members. But the salary needn't always be delivered on the first day if a firm has benefits and culture that are attractive to prospective candidates. Hiring firms always need to listen to cues from candidates about non-salary desires and focus on ways to help a candidate parlay into greater responsibilities and higher salaries in the future. Frame offers carefully. With responsibilities on one side and salary on the other, don't overcompensate for one to make up for a lack of the other. The key to a properly presented offer is balance, and when a firm looks at all angles, there are certainly more than two sides that hold weight.

MSC

Tim Johnson is Project Operations Manager of the Engineering division at SullivanKriess, Inc., an executive search firm dedicated to the design-build industry. He can be reached directly at tjohnson@sullivankreiss.com. For more information, visit www.sullivankreiss.com.



“You can get the joists and decking to me faster?”

“Yep.”

“You talked to the engineer and got the RFI’s resolved?”

“Yep.”

“And now the erector needs the bowstring joists first.”

“Yep.”

**“OK, another small project, can I get
some 2" composite deck in three days?”**

“Yep. You’re golden.”

Welcome to a very different business conversation. When you call New Millennium about your joists and deck needs, this is what you will hear: What do you need? And when do you need it?

Challenge us. We’ll help you keep your delivery promises.

After all, that’s what every joist and deck conversation is ultimately about, keeping your customers happy. Yep, it is. Because when your customers are golden, so are you.

PLANT LOCATIONS: INDIANA | FLORIDA | OHIO | SOUTH CAROLINA | VIRGINIA

**Challenge us today at
www.newmill.com/challenge**



NEW MILLENNIUM
BUILDING SYSTEMS

Flexible to the Finish

SUPPORTING ROLE

Erecting steel joists without proper bridging can cause it all to come crashing down.

BY PERRY S. GREEN, PH.D., AND TIM HOLTERMANN, P.E.

ONE OF THE MOST IMPORTANT ASPECTS OF SAFE STEEL JOIST ERECTION IS PROPER BRIDGING. A joist may be unstable as soon as the hoisting cable is released, even if other applied construction loads aren't present. As such, three types of joist bridging play three different roles in creating stability: erection, construction, and permanent.

Erection bridging is required if the joist is not stable under the combination of its own weight plus the weight of the worker releasing the hoisting cable at the joist mid-point. Erection bridging is defined in the OSHA Federal Safety Standards, 29 CFR 1926.757, as "the bolted diagonal bridging that is required to be installed prior to releasing the hoisting cables from the steel joists." However, not all joists require erection bridging when being set into position on a structure.

The second bridging type—construction bridging—provides adequate lateral support for a joist and any construction loads on top of the joist while a permanent means of top chord lateral support, normally metal decking, is installed. Without proper lateral support, loads during construction can cause the joist to distort, roll over, or shift from its intended position, resulting in the ironworkers, joists, or construction loads—or all three—falling and causing injury and damage. Proper construction bridging can prevent such mishaps.

Finally, permanent bridging serves to permanently brace the top and bottom chords of the joist; it remains as part of the structural system for the life of the structure. In cases where the metal decking creates a sufficient diaphragm, permanent bridging isn't necessary at the top chord after construction is complete. One exception, however, is when a standing-seam metal roof is attached directly to a joist top chord. The Steel Joist Institute (SJI) has determined that this type of roofing system does not provide the required diaphragm strength, and permanent bridging is necessary for the joists to function properly.

For the joist bottom chord, permanent bridging is required. Since the bottom chord serves to laterally brace the joist web members—when modeled as pinned ends—it too must be braced laterally, even when it is in tension. Also, when joists are used in roof construction, they are frequently subject to a net uplift force, creating compression in the bottom chord. In this scenario, permanent bridging in the bottom chord will provide the necessary buckling resistance.

Let's take a closer look at all three types of steel joist bridging.

Erection Bridging

The SJI K-Series and LH- / DLH-Series Load Tables in the 42nd Edition *Standard Specifications Load Tables and Weight Tables for Steel Joists and Joist Girders* show the total safe uniformly distributed loads for standard products at various spans. As the span increases for a particular joist designation, the uniformly distributed

load-carrying capacity decreases. The Load Tables also indicate when the span becomes too great for a particular joist designation to be erected without erection bridging.

Table A, Erection Bridging for Short-Span Joists, in the OSHA *Federal Safety Standards* gives the minimum span for each short-span joist designation (e.g., 26K8) and indicates when erection bridging must be installed. If Table A indicates that erection bridging is not mandatory (NM), the joists can be spaced out, attached, and then bridged in accordance with Section 6 of the *SJI Standard Specifications for Open Web Steel Joists, K-Series*.

The required bolted diagonal erection bridging for K-Series joists must be installed as the row of bridging nearest the mid-span of the joist. The erection bridging must also be anchored to prevent lateral movement of the joist prior to the hoisting cables being released. This can be accomplished by securing the bridging to a fixed object such as a concrete or masonry wall, steel beam, or other stable portion of the structure. OSHA refers to this anchorage point as a "bridging terminus point."

Table B, Erection Bridging for Long-Span Joists, in the OSHA Standards gives the minimum span for each long-span joist designation (e.g., 32LH06) and indicates when erection bridging must be installed. If Table B indicates erection bridging as NM, the joists can be spaced out, attached, and then bridged in accordance with Section 105 of the *SJI Standard Specifications for Longspan Joists, LH-Series*.

The required bolted diagonal erection bridging for any LH-Series joist depends on its length. Where the span of the steel joist is less than 60 ft, the bolted diagonal erection bridging must be installed as the row of bridging nearest the mid-span of the joist. Where the span of the steel joist is between 60 ft and 100 ft, the required bolted diagonal erection bridging must be installed as the two rows of bridging nearest the third points of the joist. Where the span of the steel joist is 100 ft to 144 ft, all rows of bridging are considered erection bridging and must be completely installed. As stated in Section 105 of the LH-Series Specification, the bridging row(s) must be anchored to prevent lateral movement of the joist.

Since all erection bridging will in turn become construction bridging, the more stringent construction bridging criteria are used to establish the erection bridging forces, sizes, and connections.

Bridging for Construction Loads

After any required erection bridging is installed and the hoisting cables have been released, additional bridging rows required for construction bridging need to be installed before the application of additional construction loads. Under no circumstances should construction loads of any description to be placed on unbridged joists. As previously described, many joists are laterally unstable until the joists are properly bridged and the bridging and joists are properly anchored. The joists should be completely bridged im-

mediately after final placement and end attachment is completed in accordance with OSHA and SJI requirements.

Construction loads are defined in the OSHA *Federal Safety Standards* as “any load other than the employee(s), the joists, and the bridging bundles.” These loads include the weight of metal deck bundles and individual sheets being placed, the weight of multiple erectors placing the deck, and equipment loads such as welding machines and leads, hand tools, bridging for adjacent bays, etc. The OSHA Standards strictly prohibit placing construction loads on unbridged joists and give the proper procedure for landing bridging bundles on unbridged joists; see 29 CFR 1926.757 (e) (1), (2), and (3). It is critical that construction loads on any one joist be minimized, and it is advisable that the loads be placed as close as possible to the ends of the joist. There is an exception for the placement of a bundle of decking after the installation of at least one but not all bridging rows if certain stringent conditions are met. Any erector who allows construction loads to be placed on unbridged joists is in direct violation of the OSHA standards, as well as Section 6 and Section 105 of SJI’s K-Series and LH-/DLH-Series Specifications.

SJI *Standard Specifications for Open Web Steel Joists, K-Series*, Section 5.4 requires that each bridging connection resist a nominal (unfactored) horizontal force of not less than 700 lb. The spacing of the bridging rows is determined by the radius of gyration of the top chord about its vertical axis and shall not be less than $\ell/145$. Also, to meet this criteria the quantity of top chord bridging rows shall not be less than the number shown in Table 5.4-1. The number of rows of bottom chord bridging shall not be less than the number of top chord rows; the top and bottom chord bridging rows may be spaced independently.

SJI *Standard Specifications for Longspan Steel Joists, LH-Series and Deep Longspan Steel Joists, DLH-Series*, Section 104 requires that each bridging connection to the joist must be able to resist a horizontal force not less than that specified in Table 104.5-1. Where two attachment points to a joist are utilized, each attachment must be able to resist one-half of the bridging force given in the table. The spacing of the bridging rows shall be determined by the radius of gyration of the top chord about its vertical axis and shall not be less than $\ell/170$, and to meet this criteria the maximum spacing of lines of top chord bridging shall not exceed

the values in Table 104.5-1. The number of rows of bottom chord bridging shall not be less than the number of top chord rows; the top and bottom chord bridging rows may be spaced independently.

The bracing force that a joist imparts on the bridging is based on three assumptions: 1) an initial out-of-straightness in the chord of $\ell/920$; 2) a resultant total nominal bracing force of $0.0044P$ (in other words, the horizontal bridging rows must be continuous and each joist must be braced from both sides; therefore, the total bracing force is divided by two and rounded up to $0.0025P$, where P represents the chord axial force); and 3) there is an assumed construction stress in the top chord due to the chord axial force P . For K-Series joists, the bridging criteria are based on a top chord axial construction ultimate stress (F_{cr}) of 17 ksi. Due to the continuity of the top chord on either side of the bridging attachments, a K -factor of 0.9 is used in calculating the top chord slenderness ratio. Hence, for an ultimate Euler stress of 17 ksi and a K -factor of 0.9, the permissible slenderness ratio ℓ/r_y is limited to 145 for K-Series as given above. LH- and DLH-Series joists are similar, except that the assumed construction stress is taken as 12 ksi, and the resultant slenderness limit, ℓ/r_y , is 170.

Therefore, the nominal compressive force that accumulates in a horizontal bridging row is:

$$P_{br} = 0.0025 n A_t F_{construction}$$

where

$$F_{construction} = \begin{matrix} 17 \text{ ksi for K-Series joists, and} \\ 12 \text{ ksi for LH- and DLH-Series} \\ \text{joists, as noted above} \end{matrix}$$

$$A_t = \text{is the top chord area}$$

$$n = \text{the number of joists}$$

For horizontal bridging, n is taken as eight joist spaces because the construction loads tend to be localized, rather than spread uniformly over an entire bay. Also, the probability is low that all joists in a bay would exhibit the maximum out-of-straightness all in the same direction at any given time. For horizontal bridging, the bracing force P_{br} must be taken in compression. Diagonal bridging creates a load path whereby the forces are resolved at each braced joist space and do not accumulate. However, recall that the bracing force was divided by two on the presumption of continuous bridging on each side of the joist chord. Since continuity is not required of

diagonal bridging rows, and to allow the diagonal bridging force to be considered only in tension, n is taken as two for diagonal bridging.

The tables provided in the SJI specifications for bridging sizes are based upon the force P_{br} for the typical top chord areas for a given designation. Table 2.6-1a of the SJI *Code of Standard Practice* gives the maximum joist spacing for certain horizontal bridging sizes based on joist chord section numbers for K-Series joists and using $K = 0.9$ for the bridging design; Table 2.6-1b provides the same information for LH- and DLH-Series joists. Diagonal bridging is only subject to tension forces, and so the bridging size is governed by a slenderness limit (between connections) of 200, rather than by strength.

Recently, SJI has begun to investigate the difference between the assumed K-Series construction stress of 17 ksi versus 12 ksi for LH- and DLH-Series joists. Preliminary findings indicate that the construction stress has very little to do with the chosen joist series but is heavily influenced by both the span and depth of a joist. For a given span length and joist spacing, the construction load arguably will be the same regardless of joist depth, while the top chord construction stress will clearly be less for a deeper joist. On this basis, equations were developed for the newest SJI *Standard Specification for Composite Steel Joists, CJ-Series*, in which $F_{construction}$ and the top chord slenderness limit varies depending on the depth and span length as follows:

$$F_{construction} = \frac{\pi^2 E}{\left(\frac{0.9 \ell_{br}}{r_y} \right)^2} \geq 12.2 \text{ ksi}$$

$$\ell_{br} = \left(100 + 0.67 d_j + 40 \frac{d_j}{L} \right) r_y$$

but not greater than, $\ell_{br} = 170 r_y$

It is anticipated that a similar methodology may be adopted for the K- and LH-/DLH-Series joists in the future. However, they would not exactly match the CJ-Series equations, because the CJ-Series allows for an ultimate top chord construction stress in excess of 17 ksi. This is due to the fact that composite joist top chords are inherently smaller than comparable non-composite top chord sizes, and the maximum span to depth ratio is greater for composite than non-composite joists.

In certain design applications that use bottom bearing or square-ended joists, the product is designed to bear on the bottom chord. This produces a "top-heavy" condition. Therefore, their ends must be restrained laterally in accordance with SJI *Standard Specifications, K-Series*, Section 5.4(d) or LH- and DLH-Series Section 104.5(f). This is accomplished by means of an additional row of diagonal bridging placed at or near the bearing support ends of the joists as they are being erected. Where a bottom bearing joist is extended beyond its support to form a cantilevered end, a row of diagonal bridging near the support should first be installed. In addition, the structural drawings may indicate a row of diagonal bridging in the cantilevered portion to provide lateral stability. If the joists have bottom chords extended over and connected to a column, beam, wall, or other structure, the connection should be made in accordance with the structural drawings and/or instructions from the engineer of record.

Bridging for Permanent Loads

Top chord bridging serves a role as permanent bridging in the absence of a deck

diaphragm, as is the case with a standing-seam metal roof applied directly to the joist top chords. Sections 5.8(g) and 104.9(g) of the SJI *Standard Specifications* for K-Series and LH-/DLH-Series joists, respectively, provide the requirements for the horizontal bridging design. The compressive force equation is:

$$P_{br} = 0.0025nP$$

This equation is similar to the equation given above for construction bridging, but here, n is not limited to eight, and is equal to the total number of joists between end anchors. P represents the actual top chord design force, rather than the chord area times an arbitrary construction stress.

Bottom chord bridging is always permanent bridging, and either limits slenderness for bottom chords in tension or braces the bottom chord laterally for compression forces, such as those present in a net uplift loading case. Traditionally, and for simplicity in the field, the bottom chord bridging size is equal to the size as determined for the top chord.

When uplift forces are a design consideration, a row of bottom chord bridging

is required near each end of short-span joists in accordance with the SJI *Standard Specifications, K-Series*, Sections 5.6 and 5.11 and long-span joists in accordance with the SJI *Standard Specifications, LH-/DLH-Series*, Sections 104.7 and 104.12.

What's Next?

Future research on joist bridging requirements is likely to include a review of the construction stress levels, a unification of the K-Series and LH-/DLH-Series bridging requirements, and a better understanding of the accumulation of bridging forces when a net uplift loading condition is present. **MSC**

Perry S. Green is technical director of the Steel Joist Institute, and Tim Holtermann is chairman of SJI's Engineering Practice Committee and corporate engineering manager of Canam Steel Corp.

The SJI 42nd Edition Catalog containing the above referenced Standard Specifications and the Code of Standard Practice can be found at www.steeljoist.org.

ocean

TERMINATOR

DUAL COLUMN MITER SERIES BAND SAWS

ocean
TERMINATOR

beams channels pipe tube

Absolutely the Most Affordable DUAL COLUMN DUAL MITERING SAW for Structural Steel!

- ✓ Huge sawing capacity
- ✓ Two models – 30" and 42"
- ✓ Fast and accurate cuts every time

Unbeatable Features:


- ✓ Dual column design for exceptional accuracy
- ✓ Miters both directions
- ✓ Large 10HP motor drives 2" band saw blade
- ✓ Long blade life
- ✓ Simple to operate
- ✓ Positive clamping
- ✓ Digital feedback
- ✓ Built by Hyd-Mech

Call for a FREE Video & Brochure

Tel 800.286.3624 • 954.956.3131 • Fax 954.956.3199
www.oceanTERMINATOR.com • www.oceanmachinery.com

Hot Dipped Galvanizing

ON TIME and ON BUDGET



**North American
Galvanizing Company**

We make steel last longer




www.nagalv.com



NACE
INTERNATIONAL

(918) 488-9420



Remember the Red River Valley

BY LARRY A. ERICKSON, P.E.

Part replacement span, part revitalization tool, a new bridge over the Red River of the North connects two Upper Midwest towns in North Dakota and Minnesota.

WHEN MOST PEOPLE HEAR "RED RIVER," THEY LIKELY THINK OF THE BORDER BETWEEN TEXAS AND OKLAHOMA. But there's a second Red River—also serving as a border between two states—further north.

A major crossing of this "other" Red River was recently updated: the Main Avenue Bridge (Trunk Highway 10), which crosses the river between Moorhead, Minn. and Fargo, N.D. A combination of geometric and structural deficiencies, along with flooding issues, led the Minnesota and North Dakota Departments of Transportation to replace the existing bridge, which was constructed in 1936. While the bridge replacement was the project's initial focus, the new structure also became an integral component to the area's riverfront and Moorhead's downtown revitalization efforts.

A pedestrian promenade on the mid-span plaza provides views of the Red River and riverfront parks.

The result is a state-of-the-art, environmentally durable vehicular structure that is able to handle growing traffic volumes and addresses improvements to substructure movement. Developing a steel girder system was key to accommodating the possibility of "adding on" aesthetic enhancements that reflected a sense of connectivity between the two neighboring cities.

With five spans, the new 800-ft-long steel girder bridge incorporates several architectural enhancements, creating a recognizable regional landmark that melds engineering, art, and design. The project consisted of replacing the original bridge, reconstruction of roadway approaches in both cities, and reconstruction of Third Street in Moorhead as a riverfront parkway. The bridge also features a unique mid-span plaza, bridge-head plazas on either end of

The curved mid-span plaza girders sweep over the Red River, bearing only at the pier and framing into the bridge girders.



the structure, and grand stairs that provide a pedestrian connection to the riverfront.

Unstable Conditions

The selection of steel for the superstructure ultimately turned out to be the only possible solution, given the desire to provide an arched mid-span plaza—but to mention the need to hold up to the soil conditions in the Red River Valley. The Fargo-Moorhead area lies in a region of poor soil/construction conditions and is prone to geological instability of the riverbanks. In particular, the channel walls of the Red River and its tributaries are prone to slope failure and soil movement towards the river.

If the piers were to move slightly, steel would be easier to jack and reset the bearings. To offset potential movement of the piers, the bridge designers used larger, high-capacity 16-in. steel sheet piles. These were used at a higher pile spacing than usual to allow for soil movement between the piles. The bridge designer implemented unique design considerations for movement of the abutment and piers, which is not unusual for structures in this area.

Another precaution taken to address soil movement was to design the bearing

assemblies with a PTFE bearing system, the first of its kind used in the two bordering states. The stainless steel-plated sole plate was oversized in the longitudinal direction, allowing for bearing adjustment of the Teflon bearing plate in the event of slope movement.

A Pleasing Plaza

The 50-ft x 250-ft mid-span public plaza was a distinctive attribute to the river crossing. A steel girder system was selected, as it provided the ability to fabricate main girder members to fit the curvilinear outside shape of the plaza. The use of steel allowed the necessary flexibility in the shape, size, and visual appearance of the plaza. The plaza was designed as a curved shape so the girders would sweep over the Red River, bearing only at the piers and efficiently supporting the structure.

Another design feature of the public plaza was the use of stainless steel spires to create a series of vertical elements that augment the design of the public plaza and house vertical fiber-optic lighting. The aesthetic lighting supplements the roadway lighting and continually changes color to tie into seasonal or other themes, such as displaying a stylized “aurora borealis.”

The bridge has received numerous awards for its engineering complexity and thoughtful application of artistic and interpretive amenities. It is an iconic gateway for both cities and offers an enhanced urban environment and usage experience for travelers, while also serving as a gathering place for civic celebrations and community enjoyment.

MSC

Larry Erickson of SRF Consulting Group was the lead bridge engineer for this project and has been involved in the design of more than 280 bridges. He has managed several major river crossings during his 30-year career.

Owner

Minnesota Department of Transportation and North Dakota Department of Transportation

Designer

SRF Consulting Group, Inc., Minneapolis

Detailer



Tensor Engineering, Indian Harbor Beach, Fla. (AISC Member)

General Contractor


Industrial Builders, Inc., Fargo, N.D

Make Specifying Steel-to-Steel Connectors a Snap

- Online Connection Designer makes it easy to select the correct BeamClamp safety components from our complete line of high-strength, ductile iron fasteners
- Ideal for secondary steel connections and in-plant equipment
- Easy-to-install or adjust on site
- No welding or drilling required
- Will not weaken existing steel or harm protective coatings
- Guaranteed Safe Working Loads
- Corrosion-resistant



GrateFix secures steel grating to existing steel - available in hot-dipped galvanized and stainless steel finishes.



FloorFix positions raised pattern floor plates. Installs easily with one-side access. Hot-dipped galvanized finish.



BoxBolt® expansion anchor bolts for tubular steel connections including fire-rated curtain walls.



BeamClamp®

A KEE SAFETY PRODUCT

SAFE STEELWORK CONNECTIONS

YOUR ENGINEERING CONNECTION FOR STEEL CONSTRUCTION

BROWN

Consulting Services, Ltd.

Phone: 281-260-9749
Fax: 281-260-9771

Experienced Professional Engineers Registered Nationwide !

We work with:
Fabricators, Erectors, Detailers,
Architects & Building Owners

- Structural Steel Connection Design
- Stair and Railing Design
- Shop Drawing Review and Supervision
- Design Build Services
- Cold Formed Steel Design
- Curtain Wall Design
- Construction Dispute Resolution

SPECIALIZING IN CUSTOM STEEL CONNECTION DESIGNS

www.steelconnectiondesign.com


Call Toll-Free 1-800-851-5181 • Visit www.KeeSafety.com/BC

join us for the peddinghaus Oktoberfest

September 24 - 27, 2008
Peddinghaus Corporation
Bradley, Illinois




Join us as we introduce four new machines to the industry...that will give you the competitive edge!



Oktoberfest activities will include...

- Enjoy the opportunity to network with global fabricators in a relaxed business environment
- A "trade fair" venue featuring industry leaders in steel construction including software, detailing, and much more
- Four – yes *Four!* – New machines never before seen under power encompassing steel shapes: beams, columns, plate, flat stock, angle iron, channel and tube
- Enjoy authentic Oktoberfest music by a genuine Bavarian band
- Rousing entertainment highlighting your Oktoberfest experience



A lot has changed at Peddinghaus since Oktoberfest 2000...but not our commitment to our customers and industry partners!

Authentic Oktoberfest food, refreshments, and entertainment served all day – every day
Check out Oktoberfest details on www.peddinghaus.com

Peddinghaus

300 North Washington Avenue • Bradley, Illinois 60915
Phone 815-937-3800 • Fax 815-937-4003 • www.peddinghaus.com




Each month MSC's product section features items from all areas of the steel construction industry.

In general, these products have been introduced within the past six months. If you're looking for a specific product, visit MSC's online product directory at www.modernsteel.com/products. You can browse by product category or search on any term to help find the products you need, fast.

Hanging from the Rafters

Chicago Clamp Company's new Framing Clamp System assists with framing roof openings and supporting loads above or below roof decks, making it suitable for installing HVAC equipment, exhaust fans, vents, and skylights. Because no welding or specialized tools are required, it can be easily installed and relocated. With a 1,000-lb capacity per end clamp, it consists of end clamps, T-brackets, and perforated channels. Using the system in a typical framing application, four end clamps are attached to two parallel bar joists or beams. Each end clamp slides over the top of the joists and occupies a space that is 1¼ in. high by 3 in. wide between the joists and corrugations of a standard roof deck. In most applications, four T-brackets are used to anchor a perpendicular set of perforated channels. Four perforated channels are usually required and are positioned between a pair of end clamps or T-brackets. Perforated channels are available in lengths up to 10 ft.

For more information, visit www.chicagoclampcompany.com or call 708.343.8311.



Two-in-One

Peddinghaus Corporation's Drill/Cope Tandem System combines the capacities of two machines into one effective shop fabrication process. All AISC structural shapes, including beams, columns, angle iron, channel iron, and HSS square and rectangular tubes, as well as thick plate and flat stock, can be processed in this system. This tandem machine can perform all typical functions of today's fabrication shop, including precise hole drilling, beam scribing, and all thermal coping and cut-off functions including bevels, flange thinning, and interior cuts. The powerful drive/positioning system provides capacity to split beams into tee sections and thermally cut haunches and beam castellations.


For more information, visit www.peddinghaus.com or call 815.937.3800.



Waterproof

Sealex, Inc.'s ImmerSeal pre-cured sealant is ideal for a wide range of metal building applications where a water-tight seal is required, including: expansion joints, roof-to-wall transitions, roof steps, ridge details, and other high-movement conditions. The sealant requires no mechanical fasteners, is resistant to UV degradation and weathering, has excellent movement capability, and is compatible with all types of metals and coatings commonly used in the metal building industry.

For more information, visit www.sealexinc.com or call 231.348.5020.




All products submitted are considered for publication, and we encourage submittals related to all segments of the steel industry: engineering, detailing, fabrication, and erection. Submit product information via e-mail to Geoff Weisenberger (weisenberger@modernsteel.com). To be included in MSC's online products directory, contact Louis Gurthet (gurthet@modernsteel.com).

Streamlining the Detailing Process

Design Data's SDS/2 steel detailing software features built-in intelligence to automatically design connections using a 3D model with a multitude of options for beams, columns, bracing, and joists. With the release of SDS/2 Version 7.1, SDS/2 users will notice some exciting new features that will help streamline processes and increase functionality. The software now allows users to add curved members with connection design and add clevises and turnbuckles into the 3D model. Members can now be grouped and detailed together with the bill of material, and it is also easier to copy and paste member information, such as connections and specifications, from member to member. This new version also features additional reports, including Status Report by Proximity, which will help the user to determine which members may be affected when a member is revised. In addition, SDS/2 will now design welded connections for vertical braces and will support sloping columns.

For more information, visit www.sds2.com or call 800.443.0782.



Increased Mobility

Hougen Manufacturing's new Model HMD904S Swivel Base Portable Magnetic Drill marks a major performance improvement to the versatile HMD904 model. The S series features a new drill body-to-magnetic base coupling that provides both a pivot axis for up to a 1½-in. arc of side-to-side motion and a straight-line axis that permits up to 1¾ in. of front-to-back movement. After the magnetic base has been engaged, the added axes allow operators to fine tune the drill position and precisely locate hole center points. The new unit incorporates a lockdown mechanism that, unlike similarly equipped models, makes releasing and securing the pivot and slide coupling simple, fast, and virtually effortless. A single-actuation handle with short stroke travel both unlocks and securely retightens the swivel base coupling.

For more information, visit www.hougen.com or call 810.635.7111.



On the Edge

Perimeter Protection Product's reusable guardrail system, for use on steel and concrete building projects, eliminates the waste and costs of the currently used angle iron OSHA posts. The system consists of a base plate and post. The base plate can be welded to the structural beams in the fabrication shop or in the field.

The posts are then screwed into the base plates in the field and support a wire cable at the perimeter of the building. They can be easily removed and reused on future buildings. The base plates become part of the building and at the roof level can be uncovered for future use as tie-off points with our fall arrestor accessory. The system eliminates 87% of workers' exposure to the edge of the building during installation and removal of the system.

For more information, visit www.PerimeterProtectionProducts.com or call 732.469.5626.



avoid someone who is standing over you. Somehow, in an exclusively engineering world, I felt sheltered from the mundane and miscellaneous world of architectural detailing. In an A/E firm, the lines between the architect's and engineer's responsibility become skewed and fuzzy. I have taken on more design responsibility in my work with A/E firms. I have been asked to look at curtain wall details, interior partition wall details, and ceiling details. I have even detailed and sized framing for bathroom vanities. This partially comes from an industry-wide misunderstanding that all elements having any sort of gravity load are a structural responsibility. We all know that everything thousands of feet above the earth's surface has gravity loads, but I am not designing everything thousands of feet above the earth's surface. (I can't help thinking that if I weren't sitting within just a few feet the architect, somehow they would find a way to frame the architectural details.)

Additionally, structural engineers in an A/E firm take on more responsibility because, unlike engineering companies, there are no contracts outlining the project role and responsibility of the structural engineer. Engineering companies can ask for more money to design elements that were not initially called out in their contract. For example, if you're dealing with non-structural elements—as in the case of the bathroom vanity—the architects would figure out how to address the issues without structural input, or they would renegotiate the contract. Either way, this process keeps elements that are not part of the building frame design—and are traditionally allocated to architects—from landing in the structural engineer's lap.

Having said all this, I must point out that it is perhaps a generalization based on my personal experiences. I recognize that variances exist among individual engineering and A/E firms. In the end, the management and the culture of the firm you are working with will strongly dictate your experience. A willing and supportive management goes a long ways and is definitely not a disadvantage. A culture that appreciates and recognizes what you have to offer as a structural engineer is always a benefit.

MSC

ACHIEVE AISC CERTIFICATION

Not sure where to start?

Call ATEMA for assistance with:

- Document preparation
- On-site training
- Internal audits

Assessment
Training
Executive
Management
Assistance



ASSOCIATE
MEMBER

Call: 312.642.8362

E-mail: information@atema.com

www.atema.com

AISC Quality Certification

Maximize profit and performance with Certification

- On-site guidance and training
- Increase productivity
- Reduce drawing and shop errors
- Reduce/eliminate field back charges
- No hidden charges



ASSOCIATE
MEMBER

JAMES M. MOONEY & ASSOCIATES

Call 941.223.4332 or 941.485.7172

jmoon94@aol.com

Structural Steel Detailers • www.gihde.com



GLENN IHDE & COMPANY
STRUCTURAL ENGINEERS & DETAILERS

972.964.3310

QPP Firm • Competitive Rates • Professional Engineer & NISD Cert. Detailers • Quick Turn-arounds • Equipment Control Data • All Sizes & Types of Project Fabrication • Electronic Drawing File Transfers • Staffing to Meet Project Requirements



ASSOCIATE
MEMBER

Have TEKLA Detailing Software experience?
We want you! Contact: glenn@gihde.com

CURVED WF BEAMS

USE DIAMOND CURVE!

40% More Ductility, Minimizes Distortion
Structural, Architectural

MARKS METAL TECHNOLOGY

10300 SE Jennifer, Clackamas, OR 97015

Info@MarksMetal.com

www.marksmetal.com 800.526.1031

WE BRING METAL TO LIFE

Are you thinking of becoming AISC Certified?

Quality Management Company can help!

Writing your own Quality Manual may be easier than you think. QMC Online (www.qmconline.com) has a multitude of free resources that can save you time and money preparing your documentation required for AISC Certification. At QMC Online, you'll find:

- A downloadable sample quality manual geared to both large and small fabricators, that includes instructive comments from QMC
- Sample procedures with guidance on how to write them effectively
- Required references that meet current codes and standards for your library
- Answers to over 100 frequently asked questions
- Samples of internal audits and more

Make QMC Online your first stop when considering AISC Certification, or call 312.670.7520.



ASSOCIATE
MEMBER

100 TEKLA Structure Licenses WITH TECHFLOW

**Accelerating Detailing Revolution
24x7**

Commercial Projects

- Schools • Malls • Casinos • Stadiums • Churches
- Office Buildings • Hospitals • Airports • Hotels
- Car Parking Structures

Industrial Projects

- Petrochemical Refineries • Duct Work • Conveyors
- Offshore Structures • Power and Process Industry
- Cement Plants

3820 Satellite Boulevard, Suite 100, Duluth, Georgia, USA

Phone: 770.495.1446 **Fax:** 770.495.1448

Email: techflowus@techflowengg.com

Website: www.techflowengg.com

Quebec Detailing Connection

100 Detailers available
Stations of 3D modelers for:

Superior management from "Old School" veterans, combined with the latest technology for simple to complex projects, with tight delivery schedules.

Contact **Robert Beauchamp** at 866.677.6161

email@datadraft.com

Web Site: www.quebecconnection.com

WANTED Steel Erection Companies

GOAL-ORIENTED AND PROACTIVE STRUCTURAL STEEL ERECTION COMPANIES COMMITTED TO QUALITY WANTED FOR AISC QUALITY CERTIFICATION PROGRAM. AISC is looking for capable erectors interested in getting on bid lists, increasing client confidence, and setting themselves apart from their competition. With over 100 participants and counting, find out why erectors all over the country are becoming AISC Certified. Contact AISC at 312.670.7520 or certinfo@aisc.org today.

RECRUITER IN STRUCTURAL/MISCELLANEOUS STEEL FABRICATION

ProCounsel, a member of AISC, can market your skills and achievements (without identifying you) to any city or state in the United States. We communicate with over 3,000 steel fabricators nationwide. The employer pays the employment fee and the interviewing and relocation expenses. If you've been thinking of making a change, now is the time to do it. Our target, for you, is the right job, in the right location, at the right money.



PROCOUNSEL

Toll free: 866-289-7833
or 214-741-2014
Fax: 214-741-3019
mailbox@procounsel.net

Advertise in Steel Marketplace!

Contact: Lou Gurthet
Gurthet Media Sales, LLC
telephone: 231.228.2274 **fax:** 231.228.7759
e-mail: gurthet@modernsteel.com



SUPREME GROUP

Supreme Group is one of the largest steel fabricators in Canada, with the resources and position to be able to serve present and future robust Canadian and Northwestern U.S. market opportunities. We have branches located in Alberta, Saskatchewan, British Columbia and Oregon.

Supreme Steel Ltd., located in Edmonton Alberta, has an immediate need for Steel Estimators, Project Managers, Detailers, Checkers and Coordinators. In addition to an attractive base salary, we offer a comprehensive benefit package including medical/dental/vision and a company matched Registered Retirement Savings Program. Submit your resume to rita.raposo@supremesteel.com. For more information on these and other opportunities visit www.supremegroup.ca.

Have You Visited the
Modern Steel Construction
Online Product Directory?
www.modernsteel.com/products

Detailer/Checker

Minimum 3 years experience required. Proficient in autocad, DetailCad experience desired. Must have good communication skills, goal and detail oriented. Live in beautiful Albuquerque. Pay is DOE, we are a drug-free workplace.

Email resume to southwestironwor@qwestoffice.net.



Estimator



L&M Industrial Fabrication has been delivering high-quality steel and specialty metal products to its structural and industrial customers for over 35 years. Through steady growth produced by investment in the industry's best people and automated equipment, we have become a trusted business partner to some of the Pacific Northwest's most noted companies. Located in Oregon's beautiful mid-valley, we are a short drive from the Portland metropolitan area.

We have an immediate opening for an experienced structural Estimator to build upon our recent investments in Fabtrol and an automated beamline. The ideal candidate will be a driven, self-motivated person who enjoys meeting deadlines and working in a fast-paced, competitive environment. Excellent computer skills and strong analytical skills required. This position offers the ability to contribute to our company at a high level.

Interested candidates should fax their resumes to 541.752.0019 or email to fritz@lmsteelfab.com.

STRUCTURAL ENGINEERS – UNIQUE OPPORTUNITIES

QUESTION: How would your life improve if you could find the perfect job that would help you achieve your professional as well as personal goals?

ANSWER: It's different for every person, but at SE Solutions, we help you find the answer so you can be PASSIONATE about your work and have a lot more FUN! We also specialize in helping structural engineers looking to use their background in unique and different ways.

WHAT HAVE OTHERS SAID? Please go to www.FindYourEngineer.com/casestudies to learn more on how we have helped other engineers find a great job that improved their quality of life. Their personal stories say it better than we can.

ABOUT SE SOLUTIONS: We are a specialty recruiting company run by structural engineers. In our 27 years of experience working with structural engineers, we have built relationships with companies all over the U.S. which allows us to match up your talents with the right company.

Call us TODAY to learn more about how we can help you find a job you will love!

Main Office
Brian Quinn, P.E.
(616) 546-9420

West Coast Office
Lisa Willard, EIT
(805) 482-8436

www.FindYourEngineer.com

iesweb.com

Easy Structural Software
for

Beautiful People

www.iesweb.com

AISC Steel Solutions Center Advisor

"There's always a solution in steel."

One of the most interesting parts of any structural engineer's job is the conceptual design phase, agreed?

Now imagine a job where you can spend most of your time working with decision makers in developing conceptual solutions for their steel construction projects while also spending time assisting in answering a wide variety of technical questions on structural steel. Imagine working at AISC.

As an Advisor in our Steel Solutions Center, you'll be able to share your structural design experience and creativity to help other professionals like yourself in the design and construction industry develop innovative conceptual solutions for their steel construction projects. You'll also use your current talents and experience to answer technical questions that come in from the construction and design decision makers. All the while, you'll be trained on a wide variety of topics in the industry to help you become a future leader in the structural steel community.

Work among our staff of experienced engineers and marketing professionals, and connect with a fascinating group of industry leaders to develop the knowledge, resources, and expertise you'll need to provide the best answers and technical assistance to the design and structural steel community we serve.

We offer an excellent salary and benefits package, along with an awesome working environment, flexible working hours, and professional development opportunities.

To be considered for this position, you must have a BS degree in Engineering, along with a minimum of 3 years experience as a consulting structural engineer or construction project engineer and proficiency with structural design software.

AISC is committed to employing only U.S. citizens or those authorized to work in the U.S. To apply for this position, please send your resume and cover letter with your desired salary requirements to: HR@AISC.org

Join AISC and become part of the solution.



A W&W STEEL COMPANY

Is seeking a

Quality Assurance Manager

Experience in the structural steel industry required, as well as a working knowledge of AISC Quality Program. Must be a certified weld inspector. NDE Level III ASNT. Certification in UT & MT preferred.

Complete benefits package includes: Health, life and disability insurance, paid vacations and holidays, Sect. 125 plan, and 401k plan.

Please send resume to:
AFCO Steel
Attn: Human Resources
P.O. Box 231
Little Rock, AR 72203
Fax: 501-340-6215
e-mail: bsnyder@afcosteel.com

EEO M/F/H/V

Structural & Misc. Steel Fabrication

Our organization has been recruiting for the Structural and Misc. Steel Fabricating industry for over 20 years. Current positions include:

- Project Manager
- Plant Superintendents
- Chief Draftsman
- General Manager
- Estimators
- Quality Control
- Detailers
- Checkers

Please send resume to:

Richard Stauffer

United Employment Associates, P.O. Box 8, East Texas, PA 18046

phone: (610) 437-5040 fax: (610) 437-9650

e-mail: rstauffer@unitedemployment.com www.unitedemployment.com

EXHIBIT AT NASCC: THE STEEL CONFERENCE

April 1-4, 2009 • Phoenix, AZ

Join over 180 other exhibitors at the premier event for more than 3,000 structural engineers, steel fabricators, erectors, detailers, educators, and others involved in the design and construction of structural steel!

Contact: Renae Gurthet, National Sales Manager

Telephone: 231.995.0637

Cell: 231.631.4614

E-mail: rgurthet@rgenterprises.us.com

Experienced Structural Steel and Light Iron CAD Detailer for fabricator-erector. Must be able to field measure. Will also involve project managing responsibilities. Complete benefits, including profit sharing.

American Architectural Iron Co.

P.O. Box 459

East Boston, MA 02128

Phone: 617.567.0011

Fax: 617.567.9054

Quality Systems Auditor Wanted

Contract Auditor wanted to audit Quality Management systems, to AISC steel fabrication and erection certification criteria. Applicant must be willing to travel. Typical workload is 10-12 audit days per month, not including travel time. Audits are mostly in North America (90%), but also throughout the world (Asia, South America, Europe, Middle East). Prefer applicant with background in steel construction (fabrication or erection) and Quality system auditing, ASQ/CWA/CWI certifications a plus. International travel experience and multi-lingual abilities preferred but not required. Auditors must be fiscally responsible, income up to \$70,000 per year, depending on audits completed.

Please forward cover letter and resume to Pat Thomashefsky at patt@qmconline.com.

SENIOR PROJECT MANAGER

Eastern PA based AISC Steel fabricator/erector servicing projects in NY, NJ, PA & CT seeking an experienced P.M. with at least 10 years experience, preferably with Engineering Degree. Full benefit pkg., bonus potential, pension, 401k plans, health benefits, relocation expense considered.

Apply online at: rkeating@msisteelco.com or send resume to:

Metropolitan Steel Ind. Inc.

601 Fritztown Road

Sinking Spring, PA 19608

Have You Visited the
Modern Steel Construction
Online Product Directory?
www.modernsteel.com/products

Chicago Metal Rolled Products Saved \$24,000 of Weld Splices with One-piece "S" Curves.



Chicago Metal created 16 reverse curves of W33x169# beams, cold bent on the x-x axis, each without a \$1,500 weld splice. A total of 310 tons of curved beams form the wavy roof of the Ratner Athletic Center at the University of Chicago, winner of the AISC Engineering Award of Excellence.



Contact us about cost-saving suggestions on *your* next project requiring curved structural steel.

CHICAGO METAL ROLLED PRODUCTS COMPANY 1-800-798-4504

Chicago, IL • Kansas City, MO • www.cmvp.com • sales@cmvp.com



NOTES FROM AN E IN AN A/E WORLD

BY ASMA MOMIN

Being an engineer at an A/E firm involves lots of challenges—but also plenty of opportunities that might not be available at an engineering firm.

WHEN MANY OF MY ENGINEERING FRIENDS

ask me what I like about working for an A/E firm, the first thing that comes to my mind is that I prefer to work with architects rather than engineers. I am only half joking. What I am getting at is this: I prefer having the architect as a *colleague* rather than a *client*. I have a lot more influence on projects with regards to schedules, among other things.

I remember my first job at a structural engineering firm. I was working on multiple projects with multiple architectural firms, and they all had short deadlines. Of course, everyone wanted everything yesterday, and when the architect is your client you do not have the luxury of telling them their project is not on the top of your list but you'll get to it eventually. You cannot negotiate schedules by stating the obvious: that you are working on another project, for another architect, at another firm. I remember the principal at my engineering firm telling me that you can't say "no" to the architect's schedule, nor can you even allude to working on any other projects.

What do you do, then, when the architects have impossible schedules, and you have to meet impossible deadlines? There's not much you can do. You are working on a tight deadline and waiting for the architect to send you their background. And as soon as they send it, they change it. Honestly, when it comes to sharing information and files,

I do not even remember how I managed to coordinate my projects at an engineering firm. I must confess that, in addition to coffee, the ability to readily access the updated architectural/mechanical files is a necessity for me.

Along the same lines, I like the opportunity to be able to walk across the office to discuss plans, sections, and details in person. I get more answers that way. It is hard to avoid a person standing over you. I don't have to drive across town for coordination meetings, I don't have to coordinate over the phone and guess what they are looking at, and I don't have to play phone tag. I save a lot of time not running after the information. This goes not only for architectural coordination but also for mechanical and other disciplines, which brings me to my next point.

Someone told me that diversity brings an opportunity to grow and learn. This is definitely the case at an A/E firm. Through conversations and discussions with other disciplines, I am more exposed to a global building perspective that is very different than the microscopic world of structural engineering. At an engineering company, it is easy to get sucked into the idea that a building begins and ends with structural engineering. The projects get into the books when the structure is ready to be designed and off the books when the structure is built. Everyone is talking, eating, and walking *structure* all the time. But in an A/E firm, you are constantly engaged in solving interdisciplinary problems, and therefore you become more aware of how your structure affects other disciplines. In A/E firms, I have been involved with the construction process at more levels than at straight-up engineering firms. It has been an enlightening experience that helps you become a better engineer.

At this point, you must be wondering what, if anything, I miss about working for an engineering firm. At times, I do miss certain things. Many of the A/E firms I have come across do not have large structural departments, and structural engineering is not their core business. Many people would argue that this correlates to job security. I must confess that I have heard of a few A/E firms laying off engineering departments during rough periods. However, I am not too concerned with that. It is in the best interest of an architectural firm to have an in-house engineering department. Not only is it a selling point to the clients, but it also keeps profits that would otherwise go to another company, in-house.

The abundance of structural resources available at an engineering company far exceed that of an A/E firm in terms of people, books, seminars, and technology. The structural departments of A/E firms I have worked with housed, at most, six engineers. I miss the abundance of structural minds and the plurality of structural opinions that you find in a structural engineering firm. There was always someone there with whom I could discuss project-related issues and concerns. Partially because it is the core business, there is a bigger appreciation for engineers and their contributions at an engineering firm.

There is also something to be said about being too available to the architects. As I mentioned, it is hard to

continued on page 65



Asma Momin is a structural engineer with A/E firm Page Southerland Page, LLP in Dallas. She can be reached at amomin@pspaec.com.

Have an opinion you'd like to share in "Topping Out"? Send your feedback to Geoff Weisenberger, senior editor, at weisenberger@modernsteel.com.

COMPUTERS & STRUCTURES, INC.

SOFTWARE FOR STRUCTURAL AND EARTHQUAKE ENGINEERING

**CSI is now an
ISO-9001
certified company.**



For more information about ISO-9001, please visit www.csiberkeley.com



COMPUTERS & STRUCTURES, INC.
TECHNOLOGY FOR A BETTER WORLD


1995 University Avenue, Berkeley, CA USA 94704
tel: (510) 649-2200 fax: (510) 649-2299
email: info@csiberkeley.com web: www.csiberkeley.com

Simplify Design

Spend less time modeling and more time designing with RISA-2D. The intuitive interface, robust solver and easy-to-use design tools allow you to quickly set up your model and get results faster.



It's the perfect tool to help you streamline your work process and simplify day-to-day tasks. Why do more when RISA-2D helps you get more done in less time.

RISA-2D



*Steel design per the
Direct Analysis method
of the AISC 13th Edition*

*Use RISAFoot within
RISA-2D for integrated
spread footing design.*



*RISA-2D now supports
wood and Glulam
design per NDS 2005*

***Try RISA-2D today and see how good
structural engineering software can be!***

WWW.RISA.COM

800.332.RISA

RISA
TECHNOLOGIES

© 2008 RISA Technologies