FM 21-31

DEPARTMENT OF THE ARMY FIELD MANUAL

TOPOGRAPHIC SYMBOLS

This copy is a reprint which includes current pages from Change 1.

HEADQUARTERS, DEPARTMENT OF THE ARMY
APRIL 1961

CHANGE No. 1 HEADQUARTERS DEPARTMENT OF THE ARMY WASHINGTON, D.C., 31 December 1968

TOPOGRAPHIC SYMBOLS

FM 21-31, 19 June 1961, is changed as follows:

Page 7. Figure 7.1 is added after figure 7.

Large Scale Medium Scale Small Scale

Figure 7.1. Direction of Flow. Shown only when direction of flow of stream or canal is not apparent.

†

Page 9. Figure 13, the title is changed to read "Dissipating Stream."

Small Scale

Page 9. Figure 13.1 is added after figure 13.


Medium Scale

Figure 13.1. Disappearing Stream.

Large Scale

Page 9. Figure 15 is superseded as follows:

Figure 15. Large Falls.



Page 10. Figure 18 is superseded as follows:

Figure 18. Navigable Canal, In Operation.

(a) Narrow. (b) Wide.

Large Scale Medium Scale Small Scale

Page 10. Figure 19 is superseded as follows:

Figure 19. Abandoned Canal, Containing Water.

(a) Narrow. (b) Wide.

Large Scale Medium Scale Small Scale

| Abandoned Canai | Abandone


Page 24. Figure 70.1 is added after figure 70.

Medium Scale Small Scale

Figure 70.1. Limits of Ice, Sea Ice, Pack Ice.


Page 27. Figure 75.1 is added after figure 75.

Figure 75.1. Scattered Trees.




Page 29. Figure 82 is superseded as follows:

Figure 82. Definition of Coastal Terms.



Page 30. Figure 84 is superseded as follows:


Figure 84. Reef or Ledge. Labeling indicates whether the reef is of rock or coral. The extent of uncovering of reefs at hydrographic datum is shown by labeling.



Page 30. Figure 84.1 is added after figure 84.

Figure 84.1. Submerged Reef or Ledge.


(a) Small area. (b) Large area.



Page 30. Figure 86 is superseded as follows:

Figure 86. Bare Rock, Exposed at Mean High Water.


(a) Bare rocks. (b) Bare rocks, dangerous to navigation.



Page 31. Figure 89 is superseded as follows:


Figure 89. Sunken Danger, Other Than a Rock or a Wreck.

(a) Identified danger, depth unknown. (b) Unidentified danger, depth known.




Page 32. Figure 91 is superseded as follows:

- Figure 91. Soundings. A sounding is the measured depth of water at the hydrographic datum. The unit of measure may be fathoms, feet, meters, or fathoms and feet in combination, as indicated in the legend.
 - (a) Soundings. (b) Soundings in fathoms with fractional values in feet.



Page 44. Figure 124, the symbol "(c) International," is added to the legend line and illustration as follows:



Page 86. Paragraphs 23.1 and 23.2 and figures 243 through 332 are added as follows:

23.1. Joint Operations Graphics

- a. Purpose and Scope. Joint Operations Graphics are produced in both ground and air versions. The ground version is designated as Series 1501; the air version is designated as Series 1501 AIR. Both versions are designed to provide common base graphics for use in combined operations by the ground and air forces of allied nations. The topographic information is identical on both the ground and air versions.
- *b. Unit of Vertical Measure.* On the ground version, elevation and contour values are shown in meters. These values are converted to foot units on the air version.
- c. Aeronautical Information. Both versions contain identical information regarding aerodromes and obstructions to pilotage. The air version contains additional information concerning aids to air navigation.
- d. Shaded Relief. Both versions contain an identical representation of shading, to provide a rapid recognition of slope and landforms. The shading also serves as a means of correlating contours and elevations, with emphasis on the more significant terrain features.
- e. Elevation Tints. Both versions contain a representative system of color tints which depict areas of the same elevation range. A key box on each version indicates the elevation ranges and their corresponding color tints.
- *j. Symbols.* The following approved symbols for Joint Operations Graphics are in addition to, or different from, the standard medium-scale symbols shown in figures 1 through 242:




Figure 243. Highest Known Terrain Elevations. The highest known terrain elevations are shown within each 15-minute square as an aid to air navigation. The larger digit represents thousands of feet; the smaller digit represents hundreds of feet.



(2) Vegetation. The following symbol is different from the medium-scale symbol shown in figure 74:

Figure 244. Woods-Brushwood; Forest.



(3) Roads in foreign areas. The following figures show the approved symbols for roads in foreign areas:

Figure 245. Hard Surface, All-Weather Road, Two or More Lanes Wide. (a) Principal route. (b) Secondary route.




Figure 246. Hard Surface, All-Weather Road, One Lane Wide. (a) Principal route. (b) Secondary route.




Figure 247. Loose or Light Surface, All-Weather Road, Two or More Lanes Wide. (a) Principal route. (b) Secondary route.




Figure 248. Loose or Light Surface, All-Weather Road, One Lane Wide. (a) Principal route. (b) Secendary route.




Figure 249. Loose Surface, Fair or Dry Weather Road. (a) Principal route. (b) Secondary route.




Figure 250. Cart Track. (a) Principal route. (b) Secondary route.




Figure 251. Footpath, Trail. (a) Principal route. (b) Secondary route.




Figure 252. Road Interchange, Access, Cloverleaf.




Figure 253. Dual Highway.



Figure 254. Distance Along Roads. Distances between selected populated places, road intersections, and road and railroad intersections are shown.



(4) Populated places and landmark features. The following figures show the approved symbols for populated places and landmark features which are different from, or in addition to, the symbols shown in figures 179 through 222:

Figure 255. Large Developed Areas. The outlined area generally shows that portion of a developed or urban area which comprises a dense concentration of structures. The limits of the outlined area have no relationship to political or administrative boundaries.



Figure 256. Native Settlement (Kampung or Kampong).




Figure 257. Walled City. The heavy black line represents walls surrounding cities or parts of cities. The word "walled" is shown in parentheses below the place name except when the wall coincides with the outlined limits of the developed area.



Figure 258. Landmark Features or Objects. Landmarks are those features which, because of their size, height, shape, or location, serve as means of positive orientation. They are readily recognizable from the air or on the ground. All landmark features are identified by explanatory labeling.




Figure 259. Outlined Landmark Areas. This symbol is used to show areas which are so different in nature or appearance from the surrounding terrain that they serve as outstanding landmarks. The nature of the area is explained by labeling.





Figure 260. Powerline With Pylons. Pylon symbols are shown at points of directional change, and on straight portions as often as necessary to emphasize the hazard to air navigation.



(5)	The following symbols for boundaries	differ from the	ose shown in figures	236 through 241:
Figure 261.	Primary Administrative Boundary.			
Figure 262.	Secondary Administrative Boundary.			
Figure 263.	Tertiary Administrative Boundary.			
Figure 264	Reservation Boundary.			
118410 2011	,			
	,			1 7

(6) Aerodromes. The following figures show the approved symbols for aerodromes on the 1501 and 1501 AIR Series:

Figure 265. Aerodrome (Military or Civil); Runway Pattern and Field Limits Known. Length of runway and field limits are shown to scale. Absence of the code letter "S" or "U" indicates hard surface runways.




Figure 266. Aerodrome; Runway Pattern Unknown, Field Limits Known.



Figure 267. Aerodrome; Runway Pattern Known, Field Limits Unknown. Length of runways shown to scale.



Figure 268. Aerodrome; Runway Pattern and Field Limits Unknown.




Figure 269. Seaplane Base (Military or Civil).




Figure 270. Seaplane-Emergency. This symbol is used to show emergency seaplane landing sites which have no facilities or for which complete information is not available.





Figure 271. Heliports.



(7) Radio navigation and communication facilities. The following figures show the approved symbols for aeronautical, radio navigation and communication facilities:

Figure 272. OMNI Range (Omnidirectional Range). Identified as VOR (very high frequency omnidirectional range), VORTAC (very high frequency omnidirectional range Tactical Air Command), or TACAN (tactical air navigation). The compass rose (magnetic bearing circle) is oriented to magnetic north and centered on the station. Name of the facility is shown in rectangular box.




Figure 273. Radio Range (RNG).




Figure 274. Visual-Aural Range (VAR).




Figure 275. Radio Beacon (R Bn). May also be labeled NDB for nondirectional radio beacons.




Figure 276. Consol Beacon.




Figure 277. Direction Finders (DF).




Figure 278. Radar Beacon (RACON-EUREKA).




Figure 279. Broadcast Station (BS). Name of facility is shown in rectangular box.




Figure 280. Ocean Station Vessel.





Figure 281. Multiple Radio Facilities. This symbol is used when two or more facilities are located in close proximity. The types of facilities are identified by the appropriate abbreviations.



(8) Controlled airspace. The following figures show the approved symbols for controlled airspace identification:

Figure 282. Air Defense Identification Zone (ADIZ).

- (a) Portion of graphic covered by ADIZ.
- (b) Entire graphic covered by ADIZ.




Figure 283. Buffer Zone. Name of zone is indicated by labeling.

- (a) Portion of graphic covered by Buffer Zone.
- (b) Entire graphic covered by Buffer Zone.






Figure 284. Berlin Control Zone. This symbol is used to show the 20 statute mile radius Berlin Control Zone and associated air corridors. The label BERLIN CONTROL ZONE is positioned immediately outside the dashed symbol.



(9) Magnetic variation data. The following figure shows the approved symbol for magnetic variation data:

Figure 285. Isogonic Line.



(10) Visual aids and obstructions. The following figures show the approved symbols for visual aids and obstructions to aerial navigation:

Figure 286. Aeronautical Rotating or Oscillating Light. Symbol is shown as: (a) If located on aerodrome; (b) If in isolated location.




Figure 287. Aeronautical Rotating Light With Flashing Code Identification Light. Symbol is shown as: (a) If located on aerodrome; (b) If in isolated location.




Figure 288. Aeronautical Rotating Light With Course Light and Site Number. Symbol is shown as: (a) If located on aerodrome; (b) If in isolated location.




Figure 289. Aeronautical Flashing Light. Symbol is shown as: (a) Located on aerodrome; (b) In isolated location.




Figure 290. Aeronautical Light With Flashing Code Identification. Symbol is shown as: (a) Located on aerodrome; (b) In isolated location.




Figure 291. Marine Light With Characteristics of Light. The abbreviations used to show the characteristics are: F (Fixed), Fl (Flashing), QK (Quick Flashing), I QK Fl (Interrupted Quick Flashing), Occ (Occulating), Alt (Alternating), Gp (Group), R (Red), W (White), G (Green), B (Blue), U (Unwatched), SEC (Sector), and Sec (Second). Marine lights are white and alternating lights are red and white unless otherwise labeled. Symbol is shown as:

(a) Land light; (b) Lightship.




Figure 292. Visual Ground Signs (Shore and Landmarkers). Symbol is shown as: (a) Arrow pointing to location of sign; (b) Actual location of ground sign.




Figure 293. Obstruction. This symbol is used to show structures which extend 200 feet or more above the surrounding terrain. The height of the structure above ground is shown immediately below the symbol in parentheses, and the elevation of the top of the obstruction above sea level is shown immediately above the symbol. The nature of the obstruction, i.e., building, smokestack, etc., is shown by labeling. Symbol is shown as: (a) Obstruction; (b) Radio facility obstruction.




Figure 294. Group Obstruction. Two or more obstructions in close proximity are shown by this symbol. The elevation and height of the highest feature in the group is shown.



23.2. Pictomaps

a. A pictomap is a map on which photographic imagery of a standard photomosaic has been con-

verted into interpretable colors and symbols.

b. The components of the pictomap consist of three basic color tones photographically extracted from a photomosaic, masked and drafted symbols, and names data. At the large scales used for city maps (1:5,000 to 1:12,500), the light tones and shadows on the photographic image serve to delineate many of the map features. At scales of 1:25,000 and 1:50,000, however, most planimetric features are shown by drafted symbols, printed in specified colors.

c. Tones. The three basic color tones used for area features are as follows:
(1) Landtone, a buff-like color tone which represents uncovered earth.

(2) Vegetone, green tones which represents densities of vegetation.
(3) Shadowtone, a black-green tone which represents shades and shadows.

d. Symbols. The following pictomap symbols are different from the standard large-scale symbols shown in figures 1 through 242:

Figure 295. Main Roads and Through Streets On City Maps.




Figure 296. Roads and Streets On City Maps: (Those not shown by symbol in fig. 295.)



Figure 297. Hard Surface, All-Weather Road, One or More Lanes Wide (1:25,000 and 1:50,000 Scales). Number of lanes is indicated by labeling.




Figure 298. Loose or Light Surface, All-Weather Road, One or More Lanes Wide (1:25,000 and 1:50,000 Scales). Number of lanes is indicated by labeling.




Figure 299. Point of Change in Number of Lanes (1:25,000 and 1:50,000 Scales).



Figure 300. Loose Surface, Fair or Dry Weather Road (1:25,000 and 1:50,000 Scales).



Figure 301. Street (i:25,000 and 1:50,000 Scales). Streets are shown by a solid white line .02" wide, or if wider, drawn to scale.



Figure 302. Track (1:25:000 and 1:50,000 Scales).



Figure 303. Trails (1:25,000 and 1:50,000 Scales).



Figure 304. Route Marker. (a) National or Federal. (b) Secondary or State. (c) Provincial, Communal or other.




Figure 305. Railroad. All railroads are shown by this symbol with number of tracks indicated by labeling: (a) Railroad; (b) Railroad spur.




Figure 306. Railroad Station. (a) Position unknown. (b) Position known.




Figure 307. Tunnel, Road and Railroad. (a) Road tunnel. (b) Railroad tunnel.




Figure 308. Railroad Overpass, Underpass. (a) Railroad overpassing road. (b) Railroad underpassing road.





Figure 309. Fills. Fills are symbolized when they are landmark in nature and an impediment to cross-country movement.






Figure 313. Small Dam. This symbol is used to show small dams of either earthen or masonry construction.



Figure 314. Escarpment. The continuous line represents the point of abrupt change in slope. Tick marks point downslope.





Figure 315. Buildings (1:25,000 and 1:50,000 Scales). Buildings outside the built-up areas which are not shown by the pictotone process are shown as: (a) Small buildings; (b) Larger buildings shown to scale.










Figure 317. Mosque.



Figure 318. Shrine. (a) Christian. (b) Moslem.





1

Figure 320. Windmill.




Figure 321. Located or Landmark Object. Object identified by labeling.



Figure 322. Telephone or Telegraph Line.




Figure 323. Ski Lift.



Figure 324. Powerline.




Figure 325. Tank. All types of small tanks which are not shown by the pictotone process are shown by this symbol and labeled as to contents.




Figure 326. Triangulation Station. The symbol represents a described horizontal control point which is marked on the ground and which was established by triangulation or traverse of third or higher order accuracy.



Figure 327. Bench Mark. The symbol represents a described vertical control point established by survey methods of third or higher order accuracy.



Figure 328. Spot Elevation (a) Checked elevation established by closed lines, including spirit level, stadia, and vertical angle methods. (b) Unchecked elevation determined by unchecked field surveys.




Figure 329. Highest Elevation on Pictomap. The highest elevation on the pictomap is shown as: (a) Checked; (b) Unchecked.




Figure 330. Contours. (a) Index. (b) Intermediate. (c) Supplementary.



Figure 331. Lake or Pond. (a) Small. (b) Large.




Figure 332. Small Reservoir. Larger Reservoirs shown as "b" of figure 331.



By Order of the Secretary of the Army:

W. C. WESTMORELAND, General, United States Army, Chief of Staff.

Official: KENNETH G. WICKHAM, Major General, United States Army, The Adjutant General.

Distribution: To be distributed in accordance with DA Form 12-11 requirements for Map Reading.



FIELD MANUAL

No. 21-31

HEADQUARTERS, DEPARTMENT OF THE ARMY WASHINGTON 25, D.C., 19 June 1961

TOPOGRAPHIC SYMBOLS

_			graph	Page		Paragraph	Pag
CHAPTER	1.	INTRODUCTION				Buildings and populated	
		Purpose	_	2		places on large-scale	
		Scope		2		maps 19	56
		References	3	2		Buildings and populated	
		Symbols and abbreviations		2		places on medium- and	
		Use of special symbols	5	2		small-scale maps 20 6 Industrial and public	64
		Scales of topographic maps	6	3			-
		Topographic maps	7	3			68
	2.	TOPOGRAPHIC SYMBOLS					00
		Scope	8	5		Control points and	
		Drainage features	9	5		elevations	79
		Relief features	10	16		Boundaries 23	83
		Vegetation features	11	26	3.	TOPOGRAPHIC ABBREVIATIONS	
		Coastal hydrography	12	29		List of abbreviations 24	87
		Roads in the United				Application 25	87
		States on large- and	13	35	4.	MARGINAL INFORMATION	
		medium-scale maps				Scope 26	88
		Roads in foreign areas			Map identifications 27	88	
		on large- and medium- scale maps	1.4	38		Other marginal data 28	89
		Roads on small-scale	14	00	A PPENNIY I	REFERENCES	91
		maps	15	41			91
		Related road features		43	II.	TOPOGRAPHIC	
		Railroads		46		ABBREVIATIONS	94
		Features related to	- 1	40	III.	CHARTS	96
		- • • • • • • • • • • • • • • • • • • •	18	50	INDEV		90

^{*}This manual supersedes FM 21-31, 4 January 1952.

CHAPTER 1

INTRODUCTION

1. Purpose

This manual describes the topographic symbols and abbreviations authorized for use by all echelons in the interpretation of military maps, overlays, and related features and activities.

2. Scope

This manual is divided into four chapters.

a. Chapter 1 contains general information on the use of topographic symbols, gives the basic scales for topographic maps, defines topographic maps, and discusses map detail, map accuracy, and map colors.

b. Chapter 2 gives examples and illustrations of topographic symbols arranged by categories, such as drainage features, relief

features, and roads.

c. Chapter 3 gives topographic abbreviations, their scope and application.

d. Chapter 4 discusses marginal information.

3. References

Appendix I is a list of publications which give detailed information on maps and mapping, foreign conventional signs and symbols, reference data for the various services, transportation and signal facilities, and abbreviations for administrative and electrically transmitted messages.

4. Symbols and Abbreviations

a. Some of the symbols appearing on published maps may not agree entirely with those shown in this manual, since it is necessary to devise or modify symbols to portray conditions or features which are unique to the area being mapped. Consequently, before any map is used, the symbol legend appearing in the margin should be carefully studied.

b. The symbols and abbreviations given in this manual are the result of standardization proceedings and are in general agreement with those employed by the British Army, the Canadian Army, the Aeronautical Chart and Information Service of the U.S. Air Force, the Hydrographic Office of the U.S. Navy, the U.S. Coast and Geodetic Survey, the U.S. Forest Service, the U.S. Geological Survey, and the Tennessee Valley Authority.

c. Department of the Army units engaged in map making will be guided by AR 117-5, by TM 5-230 so far as the symbols given as examples do not conflict with those given here, and by the specifications contained in technical publications prepared under the direction of

the Chief of Engineers.

d. Abbreviations given in this manual are for topographic use only and in some instances conflict with those given in AR 320-50, which are authorized for use in military records, publications, correspondence, messages, and in field work. In accordance with AR 320-50, abbreviations will not be used if uncertainty may result.

e. The information contained herein is applicable without modification to both nuclear

and nonnuclear warfare.

5. Use of Special Symbols

Where no symbol is prescribed for a specialized local feature, the map maker is authorized to use a special symbol, providing —

a. There is no conflict with symbols shown

in this manual.

b. Any special symbol used is explained either in the legend of the map or by appropriate labeling within the body of the map, so that no uncertainty may result.

6. Scales of Topographic Maps

a. Maps fall into the following general scale categories:

Small scale 1:600,000 and smaller. Medium scale Larger than 1:600,000 but smaller than 1:75,000.

Large scale 1:75,000 and larger.

b. Standard scales for Department of the Army topographic maps are 1:1,000,000, 1:250,000, 1:100,000, 1:50,000, and 1:25,000. Military city maps normally are published at the scale of 1:12,500. Photomaps normally are published at 1:25,000. General maps at scales smaller than 1:1,000,000 are issued for special purposes.

c. Depending upon the availability of mapping information and the importance of the area, the scale of 1:500,000 is sometimes sub-

stituted for 1:250,000.

d. All of the above types and scales of maps will not necessarily be available for a particular area. Their issue will be governed by military

and logistic considerations.

e. Maps with scales different from those given above occasionally will be encountered. Usually, they are foreign military maps. The most common examples are 1:62,500 or 1:63,360 in place of 1:50,000; 1:125,000 in place of 1:100,000; and 1:253,440 in place of 1:250,000, In the United States, nonmilitary governmental mapping agencies may use other scales such as 1:24,000 or 1:31,680 in place of 1:25,000; and 1:48,000 or 1:62,500 in place of 1:50,000.

7. Topographic Maps

a. Introduction. A topographic map is a graphic representation to scale, horizontal and vertical, of some portion of the earth's surface, systematically plotted on a plane surface. The ideal situation would be realized if every feature on the portion of the earth being mapped could be shown in its true shape, orientation, and proportion. Unfortunately, such a representation is impossible. This is evident when one considers that on a map at the scale of 1:50,000, a square mile must be condensed into a small square approximately 1.27 by 1.27 inches. If every feature were plotted true to scale, the resulting map would be impossible to read, for many items would be drawn so

minutely as to be unrecognizable even with a magnifying glass. For a map to be intelligible, features must be indicated by symbols. Many of these must necessarily be exaggerated in size for legibility. For example, on a map at the scale of 1:50,000 the prescribed symbol for a small house covers an area corresponding to about 85 feet square, the scaled width of a road measures about 95 feet; the symbol for a singletrack railroad occupies a width equivalent to about 165 feet on the ground. Consequently, only the landmarks and important features of an area can be shown. Those shown on a map represent the characteristic pattern of the area and are usually those most readily recognized in the field.

- b. Map Detail. Map detail represents ground features as they existed at the date of map compilation or latest revision. Since man is continually building, demolishing, and changing ground features, the detail appearing on a map may not exactly match that appearing on the ground. This is especially true in developed areas. The amount of detail shown on a map increases with its scale. A map attempts to show the maximum of detail without impairing legibility. In areas of heavy cultural density, many of the less important items must be omitted. In areas of sparse density, fewer items are omitted. When deletions are necessary because of the density of detail, care is taken to retain the general pattern of the features in the area. For example, where all buildings of a group cannot be shown, those retained portray the general pattern of the group without exaggerating the area covered. Similarly, where numerous ditches, streams, levees, and the like exist, the less important are omitted and the more important are retained to show the characteristic pattern of the features in the area.
- c. Symbols. So far as is practicable, a mapped feature is shown by the same symbol on maps of different scales, but certain modifications and departures are necessary because of varying map uses and scales. Normally, symbols resemble the features they represent. The center and the orientation of a symbol usually correspond to the true center and orientation of the feature represented. All line features such as roads, railroads, streams, power lines, and similar features retain, within

the limitations of scale, the variations of alinement which actually exist. Along such features as roads, the locations of buildings and other features are necessarily displaced because of the exaggerated size of the symbols. Reference to the positions of such features must be made with caution.

d. Accuracy of Maps. On a map of 1:1,000,-000, a sixteenth of an inch represents approximately 1 mile; on a map of 1:250,000, a quarter of an inch represents approximately 1 mile. It is apparent, then, that on such maps it is impossible to obtain the precise accuracy in plotting possible on large-scale maps. Smalland medium-scale maps normally are compiled from the best available larger-scale maps. Since these sources vary in reliability, the map user should study the coverage diagram shown in the margin of the map to determine the general reliability of the map. On most large-scale maps of areas within the continental limits of the United States, 90 percent of all features shown are within 1/50 inch of their true geo-

graphic positions. The remaining 10 percent are within 1/20 inch. Ninety percent of the contours are accurate within one-half of the basic contour interval, and 90 percent of the spot heights (elevations of particular locations) are accurate within one-fourth of the contour interval. In compiling large-scale maps covering foreign areas, it is not always possible to achieve the high standards of accuracy obtainable on maps of the United States. The accuracy standards of such maps usually may be determined from the marginal coverage diagram.

e. Map Colors. Topographic symbols usually appear in characteristic colors: black for *cul*tural (man-made) features other than roads, blue for water features, brown or gray for relief features, green for vegetation, and red for road classifications. Modifications of these colors occasionally are used to portray unique circumstances. Consequently, the symbol legend and other marginal information should be care-

fully studied before using any map.

CHAPTER 2

TOPOGRAPHIC SYMBOLS

8. Scope

This chapter illustrates and explains the topographic symbols used on military maps of all scales. The symbols are in general the same for all categories, but because of differences in use and scales, certain symbols are modified or omitted on medium- and small-scale maps.

9. Drainage Features

a. A perennial feature contains water during most of the year.

- b. An intermittent feature contains water during only part of the year. The shoreline of an intermittent lake or pond is represented as indefinite and approximate.
- *c.* A dry or cyclical feature or a wash is usually dry. The limits of such features are represented as indefinite.
- *d. Symbols.* The following pages contain the approved symbols for drainage features:

Figure 1. Shoreline. The mean high or normal water line is the shoreline.

(a) Definite. (b) Indefinite or unsurveyed.




Figure 2. Perennial Lake or Pond.

(a) Definite shoreline. (b) Indefinite or unsurveyed shoreline.




Figure 3. Intermittent Lake or Pond.




Figure 4. Dry or Cyclical Lake or Pond.




Figure 5. Reservoir with Natural Shoreline. The shoreline is controlled by the height of the dam.




Figure 6. Narrow Perennial Stream.

(a) Surveyed. (b) Unsurveyed.




Figure 7. Wide Perennial Stream.

(a) Surveyed. (b) Unsurveyed.



Figure 8. Intermittent Stream.




Figure 9. Narrow Wash or Dry Stream.

(a) United States or foreign. (b) Foreign (in certain arid areas).




Figure 10. Wide Wash or Dry River Bed.

(a) United States or toreign. (b) Foreign (in certain arid areas).




Figure 11. Unclassified Stream. This symbol is used when a stream cannot be determined to be either perennial or intermittent.




Figure 12. Braided Stream.




Figure 13. Disappearing Stream.




Figure 14. Large Rapids.




Figure 15. Large Falls.




Figure 16. Small Rapids.




Figure 17. Small Falls.




Figure 18. Navigable Canal, in Operation.
(a) Narrow. (b) Medium-width. (c) Wide.




Figure 19. Abandoned Canal, Containing Water.
(a) Narrow. (b) Medium-width. (c) Wide.




Figure 20. Abandoned Canal, Generally Dry.
(a) Narrow. (b) Medium-width. (c) Wide.




Figure 21. Perennial Ditch.

(a) Narrow. (b) Medium-width. (c) Wide.




Figure 22. Intermittent Ditch.




Figure 23. Aqueduct. The symbol represents a conduit used for carrying water. It may be either an open or closed canal. Water pipelines are symbolized by the aqueduct symbol.




Figure 24. Underground Aqueduct, with Outlet.




Figure 25. Aqueduct Tunnel.




Figure 26. Elevated Conduit of Any Type.




Figure 27. Flume, Penstock, and Similar Features.




Figure 28. Salt Evaporator. Only major separations are shown; minor ditches and levees are omitted.




Figure 29. Marsh or Swamp. No distinction is made between fresh and salt marshes.




Figure 30. Coastal Marsh in Tidal Waters. The shoreline is drawn as the water side limits of the marsh.




Figure 31. Coastal Marsh in Nontidal Waters. The shoreline is drawn as the true shoreline.




Figure 32. Hummocks and Ridges in Swamps or Marshes.




Figure 33. Peat Bogs, Peat Cuttings. The symbol is representative and does not show the actual shape or the number of cuttings.

Small Scale




Figure 34. Cranberry Bog. Only major separations are shown. The inundation is controlled.




Figure 35. Fish Ponds. Features of this type are usually shown only on maps of foreign areas. Only major separations are shown.




Figure 36. Rice Paddy. Only fields subject to inundation, either controlled or natural, are shown. Minor ditches and levees are omitted.




Figure 37. Land Subject to Inundation. In the United States only those areas subject to controlled inundation are shown. In foreign areas the inundation may be either controlled or natural. Areas subject to temporary natural inundation are not symbolized.




Figure 38. Spring. Springs are shown only in arid areas or where they are important landmark features. When the feature is intermittent, mineral, alkaline, undrinkable, or hot, it will be so labeled.





Figure 39. Well. Wells are shown only in arid areas or when they are landmark features. Walledin springs, cisterns, and underground water tanks are shown as wells. Artesian or intermittent wells will be so labeled.



10. Relief Features

a. Methods of Showing Relief. Depending upon the accuracy of information, the shapes of the terrain are shown on a map by lines representing contours, approximate contours, and form lines. Any one or all of these methods may be used on a single map. On medium- and small-scale maps, significant relief features may be shown by hachures when available data are insufficient to warrant the use of contours. On large- and medium-scale maps, the lines usually are printed in brown. Also, on mediumscale maps, hill shading usually is added over the brown lines, to print gray. This creates a three-dimensional effect and permits a ready appreciation of the terrain, since the hills and ridges stand out much as they would on a relief map. On small-scale maps the contour lines usually are printed in gray. Normally, on small-scale maps, the contours are supplemented by layer tints. A key box on each map indicates the elevation bands and their corresponding tints.

b. Units of Measure. Except in the United States and a few other countries where the *foot* is the standard unit of measure, the elevations on military maps are in terms of the

meter (39.37 inches or 3.28 feet).

c. Contours. Relief normally is shown by contour lines. A contour line on a map represents an imaginary line on the earth's surface, all points of which, within permissible tolerances, are of the same elevation above a fixed datum, usually mean sea level. To aid the map user, every fifth contour is a heavier line. These are commonly referred to as index contours. The remaining contours are called intermediate contours. In certain areas on a map, the normal contour interval is sometimes too large to present significant topographic formations correctly and supplementary half-interval contours are added. On small-scale maps, index contours are shown by using layer tints.

d. Approximate Contours. Whenever there is any question as to the reliability of the source material or of the survey, approximate contours are substituted for normal contours. An approximate contour on a map represents an imaginary line on the earth's surface, all points of which are estimated to be of the same elevation. As with normal contours, a distinc-

tion is made between index, intermediate, and supplementary contours.

e. Contour Intervals. Contour lines are drawn on a map at definite elevation intervals. Using a given contour interval, the lines are far apart in flat areas and close together in hilly areas. Consequently, to present the best picture, the size of the contour interval used varies with the nature of the terrain, although normally a contour interval is constant in a series of map sheets. On sheets where the relief is generally flat or gently rolling, a smaller contour interval is used than on sheets where the relief is generally hilly. Scale also affects the contour interval; if the contour interval on a 1:25,000 scale map were 5 meters, for example, the interval used on a 1:50,000 map covering the same area would be 10 meters.

f. Form Lines. When available information is insufficient to warrant the use of either normal or approximate contours, form lines are used. Normally, form lines are used only in areas outside the United States. Form lines collectively portray the general shapes of topographic features, but with little or no reference to a datum plane. They do not present an accurate representation of the terrain, but merely illustrate the general topographic shapes of an area. Since the lines are based on little or no control, their intervals cannot be used to estimate differences in elevations.

g. Hachures. Hachures are used on mediumand small-scale maps to indicate promontories, where available data are insufficient to warrant the use of normal or approximate contours, but are sufficient to determine the location of the promontories. Hachures also are used in conjunction with normal or approximate, contours to indicate important promontories which would not be properly depicted otherwise, because of the contour interval and the nature of the terrain.

h. Marginal Notes. Before reading relief from the map, the user should determine the contour interval and the nature of any other methods used to show relief. This information is found in the margin of the map either in the contour interval note or the layer tint box. Other special notes pertaining to relief are sometimes found in the lower margin. The user should also study the coverage diagram or re-

Large Scale

Madina Scale

Small Scal

Illustration

Figure 40. Contours.

(a) Index. (b) Intermediate. (c) Supplementary.




Figure 41. Approximate Contours.

(a) Index. (b) Intermediate.




Figure 42. Form Lines.




Figure 43. Hachures. This symbol is used to indicate significant formations not revealed by contours.




Figure 44. High Cliff, with Height Equal to or Greater than Contour Interval.




Figure 45. Abrupt Slope or Scarp, With Height Less Than the Contour Interval.

Features of this type are usually shown only on maps of foreign areas.

The tick marks always point downgrade.




Figure 46. Depression, With Depth Less Than Contour Interval. The tick marks always point downgrade.




Figure 47. Depression, With Depth Greater Than Contour Interval. The tick marks always point downgrade.




Figure 48. Crevice. (See also fig. 70, crevasse.)

(a) Large. (b) Small





Figure 49. Cut. Cuts less in depth than the contour interval are usually omitted.











Figure 50. Fill. Fills less in height than the contour interval are usually omitted, except in extremely flat areas.











Figure 51. Small Levee. Large levees are shown by contours, except in extremely flat areas.










Figure 52. Small Levee Carrying Road.




Figure 53. Small Levee Carrying Railroad.




Figure 54. Sand.



Figure 55. Sand. Alternate of symbol 54; used in certain foreign areas.



Figure 56. Crescent Dunes.



Figure 57. Lateral Dunes.




Figure 58. Wet Sand.




Figure 59. Sand Beach.




Figure 60. Gravel Beach. Gravel is defined as aggregate predominantly .2-10 inches in diameter.




Figure 61. Boulder-Strewn Beach. Boulders are defined as aggregate predominantly over 10 inches in diameter.




Figure 62. Distorted Surface Area. The symbol represents such features as gas or oil blisters or bumps found in the midwest United States, rock- or boulder-covered areas, rock outcrops, lava- covered areas, and areas of a similar nature. Labeling indicates nature.




Figure 63. Isolated Boulder. Isolated boulder is shown only if of enough size or prominence to serve as a landmark




Figure 64. Strip Mine, Tailings Pile, Mine Dump.




Figure 65. Icefield or Snowfield. Depending on the available information, formations are shown as:
(a) Contoured. (b) Approximate contours. (c) Form lines.




Figure 66. Glacier. Depending upon available information, shapes within the glacial area are shown as:

(a) Approximate contours. (b) Form lines.




Figure 67. Glacial Moraine.




Figure 68. High Ice Cliff, With Height Equal to or Greater Than Contour Interval.




Figure 69. Low Ice Cliff, With Height Less Than Contour Interval. Only those of landmark nature are shown. The tick marks always point downgrade.




Figure 70. Crevasse. (See also fig. 48, crevice.) Crevasses are constantly forming and disappearing; the symbols indicate areas in which crevasses exist.


(a) Large. (b) Small.







Figure 71. Cave. Only important caves and those of a landmark nature are shown. The "V" marks the location of the entrance and the shaft marks the general direction of the cave.

(a) Land cave. (b) Ice cave.










Figure 72. Asphalt Lake.





Figure 73. Mountain Pass.



11. Vegetation Features

a. General. Although special care is taken in mapping woodland cover, vegetation in many areas is subject to rapid growth or to elimination by cutting or burning. Before using the map, the user should determine the last date of information of the map (found in the notes in the lower left margin) and gage the reliability of the woodland information accordingly. The symbols used indicate such features as cover suitable for the concealment of troops, obstacles to free passage, and landmarks in areas bearing little vegetation. On small-scale maps, particularly the 1:1,000,000 scale, the vegetation is usually omitted entirely.

b. Growths Shown. Only perennial types of growth are mapped. Isolated trees and low scattered growths usually are omitted. Small clumps of growths are usually omitted, except where they serve as landmarks in areas of little woodland cover. Small clearings usually are also omitted. In certain areas, the limits and types of growth are fairly constant. In such cases, a distinction may have been made on the map between deciduous, coniferous, and brushwood growths. In many other cases, lack of information and the changing nature of growths make it impractical to make such a distinction.

- c. Continuous Cover. The presence of a vegetation symbol does not necessarily mean that the area is completely covered. Depending upon the area, growth having as little as 20 to 35 percent canopy cover is symbolized as continuous.
- *d. Symbols.* The following pages contain the approved symbols for vegetation features.

Figure 74. Woods or Brushwood. Any perennial vegetation of enough stand or height to conceal troops, or which is thick enough to be a serious obstacle to free passage is classified as woods or brushwood. No distinction is made between woods and brushwood or between different types of vegetation.







Figure 75. Scrub. Scrub growth includes cactus, stunted shrubs, sagebrush, mesquite, and similar plants of low growth which present an obstacle to free passage or which serve as landmarks in desert areas.





Figure 76. Orchard or Plantation. An area of orchards or plantations usually consists of rows of evenly spaced trees, showing evidence of planned planting. The type of growth is indicated except when it is of the common fruit variety, such as apple, orange, pear, or the like.









Figure 77. Vineyard. Vine growths which are not perennial are omitted. No indication as to the type of growth is given.








Figure 78. Tropical Grass. The symbol represents a dense growth of tall grass found in tropical or semitropical regions.






Figure 79. Mangrove. Mangrove is an impenetrable growth existing in tidal waters of tropical and semitropical areas. The shoreline shown on the seaside indicates the outer limits of mangrove and does not represent the mean high water line. Channels through mangrove are shown.









Figure 80. Nipa. Nipa is a stemless palm growing in tidal or brackish waters in tropical climates adjacent to coast lines. The shoreline as shown is the outer limits and is not the mean high water line.










Figure 81. Marshy Areas in Northern Latitudes. This symbol represents features such as tundra in the USSR, muskeg in Canada, etc. The nature of the feature will be indicated in the legend.








12. Coastal Hydrography

- a. General. Coastal hydrographic features and notes pertinent to those features usually are shown on all sheets showing navigable waters. Sheets showing land areas bordering on inland bodies of water, such as lakes, contain only offshore data. Sheets showing land areas bordering on oceans, seas, bays, or similar bodies of water contain both offshore and foreshore data.
 - b. Definition of Coastal Terms (fig. 82).
 - (1) Coastal hydrographic features. All features within the foreshore and off-

- shore areas, including permanent cultural and natural features which affect the navigability of the area.
- (2) Foreshore area. That area which is bare or awash at the hydrographic datum (low water) but which is covered at mean high water.
- (3) *Offshore area.* That area which is covered at the hydrographic datum.
- (4) *Hydrographic datum.* That stage of low tide to which depths are referred. This varies somewhat in different parts of the world.



c. Symbols. The following pages contain the approved symbols for coastal hydrographic features.

Figure 83. Foreshore Flat. A foreshore flat occurs only in tidal waters. It is generally devoid of vegetation and is composed of sand, gravel, boulders, mud, clay, or any combination of such materials. Labeling indicates the type of composition. Labeling is omitted if the feature is small or its composition indefinable.





Figure 84. Reef or Ledge. Labeling indicates whether the reef is of rock or coral.






Figure 85. Sunken Rock. Rock covered at all stages of the tide. Only rocks which are actual dangers to navigation are shown on medium- and small-scale maps.

(a) Potential danger to navigation. (b) Actual danger to navigation.




Figure 86. Rock, Bare, or Awash. This symbol represents rocks exposed or awash at the hydrographic datum. Only rocks which are actual dangers to navigation are shown on medium and small-scale maps.

(a) Potential danger to navigation. (b) Actual danger to navigation.




Figure 87. Exposed Wreck. A wreck is exposed when any portion of its hull is above water at the hydrographic datum plane. The circle of the symbol marks the location of the wreck.




Figure 88. Sunken Wreck. The symbol represents wrecks which are less than 10 fathoms (60 feet) deep, with no part of the hull above water at the hydrographic datum. Masts may or may not be above water. The center of the symbol marks the location of the wreck.

Only actual dangers are shown on medium-scale maps.

(a) Potential danger to navigation. (b) Actual danger to navigation.






Figure 89. Sunken Danger or Obstruction. Labeling indicates the nature of the feature.

(a) Least depth indicated. (b) Depth determined by wire drag.







Figure 90. Limit of Danger Line. A danger line outlines any feature which is a danger to navigation, such as rocks, foul ground, shoals, small reefs and similar obstructions. Labeling usually is added to indicate the nature of the danger.









Figure 91. Sounding. The depth of the bottom at hydrographic datum is usually expressed in fathoms (6 feet). Depths are given in feet in the eastern United States and on the Gulf Coast. The map legend indicates the unit of measure.






Figure 92. No-Bottom Sounding. The symbol represents soundings for which true depths have not been determined. The value indicates the depth sounded without bottom being struck.







Figure 93. Swept Depth. The figure in the bracket indicates the depth of clearance. This is not necessarily the actual depth. Labeling describes the nature of any danger.






Figure 94. Depth Curves. A depth curve is a line drawn on a map to represent an imaginary line on the sea bottom, all points of which are at an equal depth below the hydrographic datum. Values labeling depth curves are in the same unit of measure as the soundings.




Figure 95. Bottom Characteristics. The character or composition of the bottom is indicated by labeling.






Figure 96. Breaker.

(a) Limits known. (b) Limits unknown.









Figure 97. Current. If the speed is known, it is indicated in knots.
(a) General. (b) Flood. (c) Ebb.





The symbol represents the limits of anchorages, fishing stakes, fishing Figure 98. Area Limits. weirs, cable areas, dredged channels, dredge dumps, pipeline areas, prohibited areas, spoil ground, swept areas, and similar areas.





Appropriate labeling indicates the type of obstruction. Figure 99. Dolphin, Piling, Stump, Snag.






Figure 100. Anchorage for Large Vessels. Shown only on maps of foreign areas.











Figure 101. Anchorage for Small Vessels. Shown only on maps of foreign areas.





13. Roads in the United States on Large- and Medium-Scale Maps

a. Road Classifications on Large-scale Maps. Roads within the limits of the United States are classified on large-scale maps as—

(1) Hard-surface, heavy-duty roads.

(a) Four or more lanes wide. (b) Two or three lanes wide.

- (2) Hard-surface, medium-duty roads.
- (a) Four or more lanes wide.(b) Two or three lanes wide.(3) Improved, light-duty roads.

(4) Unimproved dirt roads.

(5) Trails.

b. Road Classifications on Medium-Scale Maps. The classifications on medium-scale maps are the same, except for hard-surface roads, where a distinction is made between roads two lanes wide

and roads more than two lanes wide.

c. Hard-Surface, Heavy-Duty Roads. Roads of this classification carry heavy truck loads in all weather with a minimum of maintenance. The construction is usually of portland-cement concrete, bituminous concrete, or sheet asphalt, rock asphalt, bituminous penetration, or mixed bituminous on a heavy foundation. Brick or block roads are also included in this category.

d. Hard-Surface, Medium-Duty Roads. These roads carry medium-heavy truck loads in all weather. Occasional maintenance is required. Construction is usually a bituminous-penetration or mixed-bituminous surface, or bituminous-treated surface on a light foundation.

treated surface on a light foundation.

e. Improved, Light-Duty Roads. These roads carry light loads in all weather. Periodic mainte nance is usually necessary. Construction consists of stabilized or oiled-surface gravel or stone, graded and drained gravel or stone, or graded and drained soil surface. Included in this category are hard-surface roads less than two lanes wide and improved private roads which normally are not practical for use in rerouting of traffic in emergencies.

f. Unimproved Dirt Roads. These roads are suitable only for light loads in dry weather. They are without surface improvement and are seldom maintained. Included are abandoned roads, fire

roads, and lumber roads.

g. Trails. The map shows important foot paths, foot trails, and pack trails which can accommodate ¹/4-ton trucks in dry weather. Minor and short connecting trails usually are omitted.

h. Symbols. The following pages contain the approved symbols for roads in the United States.

Figure 102. Hard-Surface, Heavy-Duty Road.

LARGE-SCALE: Four or more lanes wide. MEDIUM-SCALE: Three or more lanes wide.

Labeling indicates the number of lanes.







Figure 103. Hard-Surface, Heavy-Duty Road.

LARGE-SCALE: Two or three lanes wide. Unless otherwise labeled, the road is two lanes wide.

MEDIUM-SCALE: Two lanes wide.








Figure 104. Hard-Surface, Medium-Duty Road.

LARGE-SCALE: Four or more lanes wide. MEDIUM-SCALE: Three or more lanes wide.

Labeling indicates the number of lanes.







Figure 105. Hard-Surface, Medium-Duty Road.

LARGE-SCALE: Two or three lanes wide. Unless otherwise labeled, the road is two lanes wide.

MEDIUM-SCALE: Two lanes wide.







Figure 106. Improved, Light-Duty Road.






Figure 107. Unimproved Dirt-Road.







Figure 108. Trail.





14. Roads in Foreign Areas on Large- and Medium-Scale Maps

a. Road Classifications. Roads outside the limits of the United States are classified on both large- and medium-scale maps as—

(1) Hard-surface, all-weather roads.

(a) Two or more lanes wide.

(b) One lane wide.

(2) Loose or light surface, all-weather roads. (a) Two or more lanes wide.

(b) One lane wide.

(3) Loose surface, fair- or dry-weather roads.

(4) Tracks.

(5) Trails.

b. Hard-Surface, All- Weather Road. These roads carry fairly heavy truck loads in all weather. Minimum maintenance requirements are periodic inspection and repair. The construction is usually concrete or asphaltic concrete, bituminous macadam, surface-treated oiled gravel, and light tar-bound macadam.

c. Loose or Light Surface, All-Weather Road. These carry light loads in all weather. The roads generally are drained and graded. Periodic maintenance is required. Construction is usually of gravel, stone, or some stable material, such as sand-clay, on a light foundation.

- d. Loose Surface, Fair- or Dry- Weather Road. These roads carry light loads in dry weather only. The road may or may not be graded or drained and requires continual maintenance. Any surfacing consists of gravel, or sand-clay with a poor foundation.
- e. Tracks. Tracks include winter roads, caravan routes, and natural roadways and can accommodate very light vehicles, such as ¹/4-ton trucks, in dry weather. Tracks are normally shown only in areas having poor road systems.
- f. Trails. Trails include important foot trails, foot paths, and pack trails. Minor trails and unimportant connecting trails are omitted. In areas with good road systems, tracks are included in this category.
- g. Symbols. The following pages contain the approved symbols for roads in foreign areas.

Figure 109. Hard-Surface, All-Weather Road, Two or More Lanes Wide.






Figure 110. Hard-Surface, All-Weather Road, One Lane Wide.






Figure 111. Loose or Light-Surface, All-Weather Road, Two or More Lanes Wide.






Figure 112. Loose or Light-Surface, All-Weather Road, One Lane Wide.






Figure 113. Loose-Surface. Fair or Dry-Weather Road.




Figure 114. Track





Figure 115. Trail



15. Roads on Small-Scale Maps

a. Road Classifications. Roads on small-scale maps are classified as—

(1) Dual or super highways.

- (2) Main roads.
- (3) Secondary roads.
- (4) Other roads.
- (5) Tracks or trails.
- b. Main Roads. Main roads are those which serve as the main thoroughfares between the important populated places of an area. Well alined roads of a substantial width and surface which connect a number of populated places, and cross-country roads which form a direct route connecting with roads and trails leading to important features are included in this category. Main roads are generally hard-surfaced except in areas with poor road systems.
- c. Secondary Roads. Secondary roads include those roads connecting the minor cities and towns of an area. A road connecting two main roads, at least one of which is higher in

- classification than the connecting road, is included in this category. In comparison with main roads, secondary roads have less reported use and less substantial construction, and are generally loose-surfaced roads.
- d. Other Roads. Included in this category are local community roads serving the villages and settlements of an area. Also included are those connecting roads important to the communications network but obviously of a lower classification than the secondary roads. Such roads may be loose-surfaced or dirt roads.
- e. Tracks or Trails. Tracks and trails are symbolized alike. Both normally are shown only in areas of sparse culture where they supply the only means of communication. Minor tracks and trails are omitted. Included in this category are winter roads and caravan routes. Normally, the roadway is natural with little or no improvements.
- f. Symbols. The following pages contain the approved symbols for roads on small-scale maps.

Figure 116. Dual or Super Highway.




Figure 117. Main Road.




Figure 118. Secondary Road.




Figure 119. Other Road.





Figure 120. Track or Trail.



16. Related Road Features

The following symbols indicate eatures related to roads.

Large Scale Medium Scale Small Scale Illustration

Figure 121. Dual Highway. A dual highway consists of two or more lanes on each side of a physical separation such as a parkway. Surface and construction are indicated by the proper road fill. The number of lanes is indicated by labeling. When scale permits, each side of the highway is symbolized separately.




Figure 122. Road Under Construction. Only roads on which construction is actually under way are shown. If information is available, the classification of the completed road is shown by the proper road fill. Proposed roads are omitted.




Figure 123. Point of Change in Number of Lanes of Extra-Width Road.




Figure 124. Route Marker.

(a) Federal or national. (b) State, province or equivalent.




Figure 125. Streets in Developed Areas. In areas having a developed street pattern, streets are shown to agree with the cultural density and the scale of the map. Normally, streets are symbolized alike regardless of construction. If width permits, a street is shown to scale. Alleys are not shown. Through routes are indicated by red fills.




Figure 126. Street Ending at Barrier or Embankment.



Figure 127. Traffic Circle. These are sometimes omitted on 1:50,000 scale maps, especially in congested areas.







Figure 128. Traffic Circle, Cloverleaf, and Interchange. A cloverleaf is shown to true shape whenever the scale permits. They are sometimes omitted on 1:50,000 scale maps, especially in congested areas. On medium-scale maps the access points on limitedaccess roads are the only cloverleafs shown.








Figure 129. Steep Gradients on Roads.







Figure 130. Road Distances. Distances are shown between towns and road junctions.





17. Railroads

a. Gage.

(1) Normal gage is the gage used on the majority of the mainline railroads of a country. Normal gage in the United States is standard (4' 8 1/2") gage.

(2) Broad gage is any gage greater than the normal gage used in a country.

(3) Narrow gage is any gage lesser than the normal gage used in a country.

(4) Either the symbol legend in the margin or labeling on the map identifies

the gage of the railroads.

b. Multiple-Track Railroad. A multiple-track railroad contains three or more mainline tracks paralleling each other. The number of tracks of a multiple-track railroad is indicated by labeling placed parallel to the symbol.

c. Nonoperating Railroad. A nonoperating railroad is one not in use. Included in this category are railroads under construction, abandoned railroads, and destroyed railroads. Labeling placed parallel to the symbol indicates whether the line is abandoned, destroyed, or under construction.

> (1) An abandoned railroad is one which is no longer in use, but the ballast, bridges, and tracks remain in major part and could be put into limited or full operation with a minimum of repair.

> (2) Only those railroads on which actual work is under way are symbolized as under construction. Proposed lines are not shown. An operating line some

times has additional tracks under construction. The symbol for the operating line is shown with appropriate labeling to indicate the construction.

d. Dismantled Railroad. A dismantled railroad is one which is no longer in use and which has the major part of its tracks and bridges removed. If the right-of-way is being used as a road only, the proper road symbol will be shown. If there is no road and the feature is of landmark importance, it is symbolized by a dashed line and labeled.

e. Electrified Railroad. Electrified railroads are shown by the proper symbol indicating the gage and number of tracks, with the word Electrified added parallel to the symbol.

f. Developed Areas.

(1) Minor line and sidings sometimes are omitted in congested areas. Through lines are always shown.

(2) Railroads which run underground for long distances in a city are not shown. The dashed lines indicating tunnels are omitted. Only the headwalls and wings of the tunnel entrances are

shown.

(3) Rapid transit lines, when located in subways, are not shown. They are shown by the appropriate railroad symbol when located in open cut, on the surface, or on above-surface struc-

g. Symbols. The following pages contain the approved symbols for railroads and related features.

Figure 131. Single-Track Railroad, in Operation.

(a) Normal or broad gage. (b) Narrow gage. Broad and narrow gage railroads are labeled as to gage.




Figure 132. Single-Track Railroad, Nonoperating. Labeling indicates whether railroad is abandoned, destroyed, or under construction.

(a) Normal or broad gage. (b) Narrow gage. Broad and narrow gage railroads are labeled as to gage.





Figure 133. Double- or Multiple-Track Railroad, in Operation. Railroad is double-track if not otherwise labeled.

(a) Normal or broad gage. (b) Narrow gage. (c) Standard gage (for use in United States only). Broad gage railroads are labeled as to gage.



Illustration

Figure 134. Double- or Multiple-Track Railroad, Nonoperating. Labeling indicates whether railroad is abandoned, destroyed, or under construction. (a) Normal or broad gage. (b) Narrow gage. (c) Standard gage (for use in United States only). Broad gage railroads are labeled as to gage.




Figure 135. Point of Change in the Gage or the Number of Tracks.




Figure 136. Railroad in Street or Wharf. Normal symbols are used if the width of the containing feature permits. On medium-scale maps appropriate labeling shall indicate where a railroad coincides with a road.






Figure 137. Railroad Siding. Included are tracks for passing, storage, and loading and unloadir of passengers or freight. In congested areas, sidings are sometimes omitted.




Figure 138. Railroad Yard. The limiting sidings indicate the correct shape of the yard. Lines inside the outline are symbolic and do not show the correct number of sidings.




Figure 139. Railroads in Juxtaposition. Railroads of different ownership closely parallel to each other





Figure 140. Turntable. A turntable is not drawn to scale. It is usually omitted in congested areas.








Figure 141. Railroal Station. Within built-up areas, stations are shown only when they are significant as landmarks. If the building is identifiable, it appears in correct location. Flagstops, halts and similar stops without permanent buildings are not shown on medium-scale maps. On large-scale maps they are shown by name only.

(a) Position known. (b) Position unknown.










Figure 142. Railroad Snowshed.








Figure 143. Carline. Carlines are shown only in open areas; they are omitted in built-up areas, streets, and roads. If the line is not in operation, labeling indicates whether it is abandoned, destroyed, or under construction. Single and double-track lines are shown by the same symbol on medium-scale maps. Carlines which are not in operation are symbolized the same as those in operation, except that appropriate labeling is added. Dismantled carlines are shown in the same manner as dismantled railroads.

(a) Single. (b) Double.






Figure 144. Aerial Cableway, Ski Lift, or Conveyor Belt. Included in this category are linear features, other than railroads or carlines, whose function is the transportation of people or material. Usually, these features are suspended above ground level. They are shown only when they are permanent installations and of sufficient size and importance.

Appropriate labeling indicates the type of feature.





Figure 145. Dismantled Railroad or Carline. Used when the major parts of the tracks and bridges have been removed.





18. Features Related to Communications

a. Overpasses and Underpasses. On largescale maps, overpasses and underpasses normally are shown wherever they exist. On medium- and small-scale maps they generally are shown only in open areas. An overpass is a short viaduct carrying a road or railroad above the grade of another road or railroad. An underpass is a short tunnel carrying a road or railroad below the grade of another road or railroad.

b. Bridges and Viaducts.

(1) The distinction between a bridge and a viaduct is that a bridge passes over what is predominantly water while a viaduct passes over what is predominantly land.

(2) Long bridges or viaducts are always shown. A shorter bridge or viaduct is shown if it serves as an identifiable landmark or is the only means of crossing within the general area.

- (3) On long bridges or viaducts, the ends of the symbol appear in their correct locations. On shorter ones, the symbol is merely representative and the ends are not necessarily in their correct locations.
- (4) Bridges and viaducts less than 20 feet long normally are not shown except when they are underpasses or overpasses.
- (5) When a bridge is used to carry both a road and a railroad on either the same or different levels, the feature is

- shown by the road-bridge symbol with the railroad shown to the bridge ends. The symbol is labeled "Road and railroad".
- (6) Footbridges are shown only in areas of sparse culture.

c. Drawbridges.

- (1) Drawbridges are structures of which either the whole or part can be raised, lowered, pivoted, or turned aside to allow or to interrupt traffic.
- (2) On large-scale maps, the small circle of the symbol is centered on the true location of the center of the movable part of the bridge.

d. Ferries.

- (1) Ferries capable of carrying vehicular or railroad traffic normally are shown wherever they exist.
- (2) Ferries for pedestrians are shown only in areas of sparse culture or where they provide the only means of water-crossing in the general area.
- (3) The dashed line connects the points between which the ferry operates, without regard for the actual navigating course of the ferry.
- (4) Steamship lines are not shown.
- *e. Fords.* Fords are shown only in areas of sparse culture or where they provide the only means of water-crossing in the general area.
- *f. Symbols.* The following pages contain the approved symbols for features related to communications.

Figure 146. Overpass or Underpass.




Figure 147. Grade Crossing.




Figure 148. Road Tunnel. Road classification fills are omitted within the tunnel.




Figure 149. Railroad Tunnel. The railroad symbol is omitted within the tunnel.




Figure 150. Railroad Bridge or Viaduct.




Figure 151. Railroad Drawbridge. Drawbridges are not indicated on medium and small-scale maps.




Figure 152. Highway Bridge or Viaduct.




Figure 153. Highway Drawbridge. Drawbridges are not indicated on medium and small-scale maps.




Figure 154. Footbridge.






Figure 155. Ferry.





Figure 156. Ford.



19. Buildings and Populated Places on Large-Scale Maps

a. Built-Up Areas.

(1) A built-up area is a large continuous area which is developed or is in the advanced stage of development for occupancy by concentrated populations. It usually is laid out in a definite street pattern and normally contains a business or industrial district. Since all buildings cannot be shown individually, the area is indicated by an overall screened red tint.

(2) Only landmark buildings are shown individually in built-up areas. These are buildings which are prominent because of size, location, or usage, such as government or public buildings, colleges, schools, churches, hospitals, railroad stations, markets, factories, and buildings of historical or cultural

interest

(3) Within the general outline of the built-up area, individual symbols are used and the built-up area tint is generally omitted for the following features:

(a) Parks and cemeteries equivalent to

or larger than one block.

(b) Institutions such as colleges, schools, and hospitals possessing o p e n ground areas equivalent to or larger than one block.

(c) Section with little construction or development if equivalent to or

larger than two blocks.

(4) All woodland cover is omitted in built-

up areas.

b. Native Settlements. These include native settlements in foreign areas in which the buildings are not usually of permanent construction. Kampongs in southwestern Asia and encampments in western Africa are examples. The symbol legend of the map defines the symbol properly.

c. Buildings in General.

(1) Conventional symbols are used to show a small building or a small structure similar to a building. The symbol is shown in correct orientation and its center usually coincides with the correct location of the center of the structure.

- (2) Buildings and similar structures whose plotted size exceeds the conventional symbols are shown in correct orientation and shape and usually in correct location.
- (3) Buildings and structures located along roads are shown in their correct location unless they would then fall within the road. In such cases, the symbol is moved back.
- (4) In many cases it is impossible to show all buildings because of congestion. The map retains the general shape and pattern of the area and omits the less important buildings.

d. Structures Similar to Buildings.

- (1) These are features of substantial construction not definable as buildings. In many instances they are roofed, although not necessarily enclosed on all sides. The term includes barns, grandstands, railroad sheds, large open sheds, fruit packing sheds, snow sheds, open-air refineries, and similar structures.
- (2) Structures which are smaller than the average dwelling in the locality are not shown.
- (3) In foreign areas, when information is unavailable, no distinction is made between buildings and structures similar to buildings.

e. Schools and Churches.

- (1) When a building is used both as a church and a school, it is symbolized as a school.
- (2) In the United States, the church symbol is used commonly for all denominations. On maps of foreign areas, this symbol usually denotes a Christian place of worship, with other symbols being used to denote places of worship of other sects. In such cases, the marginal symbol legend should be consulted for detailed information.
- (3) When a school has numerous buildings, the flag symbol is shown only on the administration building or the most prominent building in the group.

(4) When there are numerous religious buildings in a group, as in a convent or monastery, the cross symbol is shown only on the building used for religious services or the most prominent building in the group.

f. Ruins. Ruins are buildings or structures

in such a state of dilapidation or decay that they

can no longer be used for their original purpose. Ruins which are smaller than the average dwelling in the locality are not shown unless they possess unusual significance.

g. Symbols. The following pages contain the approved symbols for buildings and populated places on large-scale maps.

Figure 157. Built-Up Area.





Figure 158. Native Settlement. Native settlements occur only in foreign areas. The map legend fully defines the symbol.






Figure 159. Buildings in General.







Figure 160. School.





Large Scale Illustration

Figure 161. Church.






Figure 162. Christian Shrine. A Christian shrine is shown only in foreign areas. (a) and (b) are alternate symbols, or are sometimes used on the same map to denote different features. Consult the map legend for distinctions.






Figure 163. Non-Christian House of Worship. A non-Christian house of worship is shown only in foreign areas. The map legend fully defines the symbol. (a) and (b) are alternate symbols, or are sometimes used on the same map to denote different features. Consult the map legend for distinctions.






Figure 164. Non-Christian Shrine. A non-Christian shrine is shown only in foreign areas. The map legend fully defines the symbol. (a), (b), (c), and (d) are alternate symbols, or are sometimes used on the same map to denote different features. Consult the map legend for distinctions.






Figure 165. Mosque. A mosque is shown only in foreign areas.






Figure 166. Moslem Shrine. A Moslem shrine is shown only in foreign areas. (a) and (b) are alternate symbols, or are sometimes used on the same map to denote different features. Consult the map legend for distinctions.






Figure 167. Pagoda. A pagoda is shown only in foreign areas.






Figure 168. Structures Similar to Buildings.





Figure 169. Ruins. (a) Large. (b) Small.






Figure 170. Greenhouse.






Figure 171. Ruined or Destroyed Areas.






Figure 172. Lighthouse or Light.






Figure 173. Windmill or Windpump.






Figure 174. Watermill.







Figure 175. Cliff Dwelling. Cliff dwellings occur in the southwestern United States. Where numerous cliff dwellings occur, one symbol is usually used to represent several.





Large Scale Illustration

Figure 176. Historical Site. Historical sites are shown only in foreign areas.






Figure 177. Historical Battlefield. Historical battlefields are shown only in foreign areas. If they cover a large area, historical battlefields are shown with outlines.






Figure 178. Cemetery. In cemeteries in the United States no distinction is made between denomination or race. In cemeteries in foreign areas, religious denominations are indicated if the information is available. Small private cemeteries and isolated graves are usually omitted.





20. Buildings and Populated Places on Medium- and Small-Scale Maps

- a. Reduced Scale. Because of the reduced scale, it is impossible to show the buildings and populated places on medium- and small-scale maps in great detail. Consequently, the symbols are truly symbolic or representative. The only buildings shown are those which serve as outstanding landmarks in isolated areas.
- b. Populated Places. A small populated place is shown by a small circle. A larger populated place is shown, generally true to shape, by an outlined and tinted area. Within the outline, the only features usually shown are the mainline railroads and through-route roads. On 1:250,000 scale maps, the tint is usually shown in yellow; on small-scale maps, it is shown in red.
- c. Use of Tinted Squares. In many areas, there is insufficient information available to plot the correct outlines of populated places. In such cases, tinted squares of varying sizes are used as symbols, with the size depending upon the population or importance. Explanation of these squares is contained in the marginal legend of the map.
- d. Names of Populated Places. The names of populated places are shown in type of varying size, with the size depending upon population or importance. When information is available, the marginal legend shows the different sizes keyed to a population breakdown. When information is not available, the sizes are keyed to an important breakdown.
- *e. Symbols.* The following pages contain the approved symbols for buildings and populated places on medium- and small-scale maps.

Figure 179. Populated Place, Limits Known. Size of type used for name indicates population or relative importance.




Figure 180. Populated Place, Limits Unknown, First Importance. Usually a large city or metropolitan area.





Figure 181. Populated Place, Limits Unknown, Second Importance. Usually a medium sized city.



Populated Place, Limits Unknown, Third Importance. Usually a small city. Figure 182.




Figure 183. Populated Place, Limits Unknown, Fourth Importance. Usually a small city or large town.




Figure 184. Populated Place, Limits Unknown, Fifth Importance. Usually a town of fair size.




Figure 185. Town, Village or Settlement.




Figure 186. Landmark Building. Labeling indicates nature or identity of structure.





Figure 187. Fort.




Laura Strake

Medium Stel

Small Seal

Diversalies

Figure 188. Small Dam. Includes those dams, either earthen or masonry, too narrow to plot to scale. On certain maps, the symbol in black indicates a masonry dam, and in brown, an earthen dam.








Figure 189. Dam Carrying Road.







Figure 190. Large Masonry Dam. The correct shape of the feature is shown and spillways or other details are included wherever possible. Buildings located on the dam are shown in their correct position. Only the important dams are shown on small-scale maps.










Figure 191. Passable Lock. The angle of the symbol always points upstream.






Figure 192. Sluice Gate or Small Canal Lock. The angle of the symbol always points upstream.




Figure 193. Small Breakwater, Jetty or Diversion Dam. Unimportant features are usually omitted.







Figure 194. Large Breakwater.







Figure 195. Submerged Breakwater. Breakwaters which are submerged at mean high tide even though exposed at low tide are included.






Figure 196. Narrow Seawall or Revetment.





Figure 197. Large Seawall.






Figure 198. Large Revetment.





Figure 199. Small Pier, Dock or Wharf.






Figure 200. Large Pier, Dock or Wharf.







Figure 201. Ferry Slip.






Figure 202. Ramp. The part submerged at mean high tide is shown by a dashed line.






Figure 203. Drydock.







Figure 204. Marine Railroad.







Figure 205. Tank. Tanks which are used for storage of oil, gas, water, vinegar, or other liquids. Labeling usually describes the contents. Large tanks are plotted to scale on large-scale maps.










Figure 206. Well. This symbol includes wells drilled for gas, oil, or other minerals, which are in operation. Wells for water are not included. Labeling usually indicates the kind of well.











Figure 207. Reservoir, Other Than Water. Open reservoirs used for the storage of asphalt, oil, or other liquids except water are indicated if they can be plotted to scale. Those too small to show to scale are omitted. Labeling identifies the feature.






Figure 208. Sewage Disposal or Filtration Bed. These are shown only when they can be plotted to scale. Wherever possible, major separations within the feature are shown. Labeling identifies the feature.






Figure 209. Swimming Pool.





Figure 210. Pipeline. This includes only those pipelines not used for water which are landmark features in areas of sparse culture. They are omitted in developed areas. No effort is made to show pipelines as a continuous feature and only landmark parts are shown.




Figure 211. Underground Pipeline. The symbol represents underground pipelines which are obvious from cleared rights-of-way, ground scars, or levee-like mounds.




Figure 212. Landmark or Located Object. A feature is a landmark when it is visible from a distance.

Landmarks include towers, chimneys, air beacons, monuments, and similar features.

Labeling indicates the nature of the object.




Figure 213. Open-Pit Mine or Quarry. This feature is usually omitted in areas of dense culture. In foreign areas all types of mines are shown by this symbol. Whenever possible, the appropriate labeling supplements the symbol indicating the material mined.




Figure 214. Mine Shaft. A mine shaft is vertical or nearly vertical in direction. (a) United States. (b) Foreign.




Figure 215. Mine Tunnel. A mine tunnel is horizontal or nearly horizontal in direction. (a) United States. (b) Foreign.




Figure 216. Prospect. Prospects are shown only on large-scale maps of the United States. A prospect is shown only where there is evidence of current or recent digging.



Figure 217. Telephone and Telegraph Lines. These are shown only when they are landmark features in areas of sparse cultural development. They are usually omitted along roads or railroads.




Figure 218. Power-Transmission Line. These are shown only when they are landmark features in areas of sparse cultural development. They are seldom shown along roads and railroads. Voltage is not indicated.




Figure 219. Fence, Hedgerow, Field Line. This symbol applies to maps of certain foreign areas only.



Figure 220. Prominent Fence. Only fences which provide definite landmarks in areas of sparse culture are shown.




Figure 221. Prominent Wall. Such walls as the Great Wall of China and walls surrounding forts or cities, and the like are included. Minor walls are usually not shown.




Figure 222. Race Track.




Figure 223. Airport or Airfield. Airports and airfields are shown to true shape on large-scale maps.




Figure 224. Landing Ground. Landing grounds are shown to true shape on large-scale maps.




Figure 225. Seaplane Base. Seaplane bases are shown to true shape on large-scale maps.





Figure 226. Seaplane Anchorage. Seaplane anchorages are shown to true shape on large-scale maps.



22. Control Points and Elevations

- a. Application of Definitions. The definitions of horizontal and vertical control stations which follow are generally applicable only to the United States.
- b. Exceptions. In foreign areas, horizontal control stations may not be monmented and

in some cases, may be less than third order accuracy. Whenever information is available. exceptions are noted in the marginal legend of the map.

c. Symbols. The following pages contain the approved symbols for control points and elevations.

Large Scale



Small Scale

Figure 227. Horizontal Control Point. The symbol represents a described horizontal control point which is marked on the ground and which was established by triangulation or traverse of third or higher order accuracy.




Figure 228. Monumented Bench Mark. The symbol represents a described vertical control point which is marked by a tablet on the ground and which was established by survey methods of third or higher order accuracy. On medium and small-scale maps Bench Marks are not specially symbolized. Their elevations are shown as spot elevations. (a) and (b) are alternate symbols.




Figure 229. Monumented Bench Mark At Horizontal Control Point. The symbol represents a described control point which is marked on the ground and whose horizontal and vertical positions were established by survey methods of third or higher order accuracy.




Figure 230. Non-monumented Bench Mark. (sometimes called temporary, supplementary, or intermediate). The symbol represents a described vertical control point which was established by survey methods of third or higher order accuracy. The point is usually recoverable. The mark does not bear a tablet.




Figure 231. Astronomic Position. The symbol represents a described horizontal control point whose geographic position was determined through local astronomic observations.






Figure 232. Checked Spot Elevation. The symbol represents an elevation established by closed lines, including spirit level, stadia, and vertical angle methods.

(a) Identifiable point (b) Unidentifiable point (c) Unidentifiable point alternate

(a) Identifiable point. (b) Unidentifiable point. (c) Unidentifiable point, alternate symbol on large-scale maps.



- Figure 233. Unchecked Spot Elevation. The symbol represents an elevation determined by unchecked field surveys such as side shots on stadia lines, unchecked vertical angle or precision altimetry, or by repeated photogrammetric readings. An un-checked spot elevation is not as reliable as checked spot elevations. (a) Identifiable point. (b) Unidentifiable point. (c) Unidentifiable point.
 - alternate symbol on large-scale maps.



23. Boundaries

- a. Where two or more boundaries coincide, only the symbol representing the higher-ranking boundary is shown.
- b. Boundaries which are approximate or indefinite are appropriately labeled.
- c. In cases where a boundary follows a road, stream, or river, usually only every third unit

of the symbol is shown. The intervening symbol units are omitted, except where the omission would create uncertainty as to the alinement of the boundary.

d. Terminology of boundaries in foreign areas varies; see the map legend for the correct terms.

e. The following pages contain the approved symbols for boundaries.

Figure 234. International.




Figure 235. Major Administrative. (As Intercolonial in French West Africa.)




Figure 236. First Class Administrative. (As State in United States; Province or equivalent in foreign areas.)





Figure 237. Second Class Administrative. (As County or Parish in the United States.)






Figure 239. Fourth Class Administrative. (As Corporate Limits in the United States.)




Figure 240. Fifth Class Administrative. (As Ward in the United States.) Shown only on very-large-scale maps.




Figure 241. Special. (As Reservation in the United States). On large-scale maps of the United States, a red overprint is shown for Military Reservations.





Figure 242. International Boundary Marker.



CHAPTER 3

TOPOGRAPHIC ABBREVIATIONS

24. List of Abbreviations

Appendix II contains the list of topographic abbreviations. with their meanings, authorized for use on the standard topographic maps discussed in this manual.

25. Application

a. Abbreviations on the face of the map are held to an absolute minimum. They are employed only where space prohibits the use of a full term or where use of the full term would require unreasonable repetition.

- b. Periods are omitted from abbreviations on the face of the map. In the margin, periods normally are retained. They are, however, omitted from coded abbreviations of governmental agency names. In such cases, no spacing is shown between the coded letters.
- *c.* In addition to the abbreviations listed herein, commonly accepted abbreviations of time, measures, and countries are authorized.

CHAPTER 4

MARGINAL INFORMATION

26. Scope

a. This chapter explains the map identifications and other marginal data appearing on topographic maps prepared for use by the Department of the Army.

b. These marginal items are illustrated in the charts which appear in appendix III. They

are—

Chart 1 — large-scale and 1:100,000 scale maps.

Chart 2 — medium-scale (except 1:100,-000) maps.

Chart 3 - 1.1,000,000 scale maps.

c. The arrangement of marginal items will vary. For example, on sheets having a narrow east-west neatline dimension, certain items will appear in the right-hand margin rather than in the lower margin. The composition is generally the same for maps of like scales.

d. Detailed information on marginal data will be found in AMS technical manuals and style sheets published under the direction of

the Chief of Engineers.

27. Map Identifications

a. Purpose. Map identifications are those items appearing in the margins of maps which serve to identify any individual map completely. On maps prepared for the Department of the Army, these identifications are the series name and scale, the series number, the edition number, the sheet name, the sheet number, the unit imprint, and the geographic location name.

b. Series Name and Scale. A map series, which normally consists of a common scale of maps which collectively cover a specific area, is generally assigned the geographic or political name of the area covered. The map scale is written as a ratio of map distance to ground distance. Example: GERMANY 1:25,000.

- c. Series Number. The series number is a comprehensive reference composed of four and sometimes five elements, usually four numerals or a letter and three numerals. The number is unique for the series. It identifies the area and scale of the series. Example: M841.
- d. Edition Number. The edition number is a specific identification based on the publication sequence of a particular map. Edition numbers run consecutively; thus, it can be assumed that a map labeled with a higher edition number contains more recent information than another printing with a lower edition number. The edition number also identifies the agency which produced the map. Example: Edition 4-AMS.
- e. Sheet Name. Generally, a map is named after its outstanding cultural or geographic feature. The name of a cultural feature is customarily chosen, but if a geographic feature is better known than any cultural feature appearing on the map, the geographic name is chosen. Example: FORT KNOX.
- f. Sheet Number. Sheet numbers for large-scale maps are based on an arbitrary geographic coordinate system covering the area to be mapped. The sheet number of a 1:25,000 scale sheet is directly related to the number of a 1:50,000 scale sheet covering the same area, which in turn is directly related to the sheet number of a 1:100,000 scale sheet covering the same area. Sheet numbers for 1:250,000 and 1:1,000,000 scale maps are based on the International Map of the World (IMW) numbering system. Examples: 1:25,000 6123 III NW; 1:50,000 6123 III; 1:100,000 6123; 1:250,000 NJ 16-4; 1:1,000,000 NJ 16.
- g. Unit Imprint. The unit imprint is the signature of the agency responsible for printing the map. This is followed by the date identify-

ing the particular printing. *Example:* Printed by Army Map Service, Corps of Engineers, 7-60.

h. Geographic Location Name. The geographic location name indicates the country, state, or general geographic area within which the map lies. The geographic location name includes the sheet name, which is repeated in the lower margin. Large-scale maps of the United States which cover an area entirely within one county or parish, carry the county or parish name below the sheet name and geographic location name. Example: FUJI — SAN, JAPAN.

i. Refer to Note. In the upper right corner of the map margin, the sheet number and series number are grouped under a note, REFER TO THIS MAP AS. This group provides the primary identification for ordering copies of a map. *Example:* REFER TO THIS MAP AS:

SHEET NJ 16-4 SERIES V501

j. Identification Panels. For quick identification of maps when filed or stacked, identification panels in opposite corners of the map sheet, outside the printed limits of other marginal information, are provided. These panels contain the *series number, sheet number,* and *edition number.*

Example: SERIES 1301 SHEET NK52 EDITION 2-AMS

28. Other Marginal Data

In addition to the identifications described above, the margin of a map contains other information important to the user in evaluating and interpreting the map (table I).

a. Credit Note. The credit note aids in evaluating the map and contains interpretive information. The note describes the method of preparation, identifies the source material used in compilation, gives the dates of aerial photography, and lists the source of horizontal and vertical control. It notes whether the map conforms with national map accuracy requirements and whether the map has been field checked. It includes any special information pertinent to the particular sheet.

b. Symbol Legend. The symbol legend defines and illustrates the symbols most commonly used such as populated places, roads, and rail-

roads. It also contains symbols for items peculiar to the area being mapped.

Table 1. Other Marginal Data

Marginal data	Large scale	Medium scale	Small scale
Bar scales and scale note	Yes	Yes	Yes.
Contour interval note, or altitude tint legend.	Yes	Yes	Yes.
Copyright note (on CE maps utilizing materials for which another agency has a copy-			
right).	Yes		Yes.
Coverage diagram	Yes	No *	No.
Credit or sources note	Yes	Yes	Yes.
Glossary (in foreign areas			
where native language is other than English).	Yes	Yes	Vac
Grid notes and information	Yes	Yes	Yes.
Horizontal datum-plane note	Yes	No *	No.
Hydrographic datum notes	Yes	No *	No.
Index to adjoining sheets, or	1 63	140	140.
location diagram.	Yes	Yes	Yes
Index to boundaries, or loca-	• • • • • • • • • • • • • • • • • • • •		
tion diagram.	Yes	Yes	Yes.
Magnetic declination note	Yes	Yes	No.
Projection note	Yes	Yes	Yes.
Reliability diagram	No	Yes	Yes.
Security classification when re-			
quired.	Yes	Yes	Yes.
Symbol legend	Yes	Yes	Yes.
Unit insignia	Yes	Yes	Yes.
Users' note (concerning correc-			
tions).	Yes	Yes	Yes.
Vertical datum note	Yes	No *	Yes.

NOTES:

- (1) When required, special notes referring to items within the map are placed in the lower margin.
- (2) *These data are shown on 1:100,000 scale maps for tactical use.
- c. Index to Adjoining Sheets. The index to adjoining sheets, or on 1:250,000 scale maps the location diagram, identifies the surrounding sheets.
- d. Index to Boundaries. The index to boundaries identifies the political areas appearing in the body of the map. The boundaries in the diagram are schematic but serve as aids in locating the boundaries on the map. On the 1:250,000 scale maps this information is shown in the location diagram.

e. Coverage Diagram. The coverage diagram, shown on large-scale maps, portrays in graphic form the methods of compilation, notes the dates of any photography used, and identifies and evaluates any maps used as bases.

f. Reliability Diagram. The reliability diagram, shown on medium- and small-scale maps, contains graphic references to the reliability of the sources used and identifies the scale, method of survey, and date of the basic sources.

g. Datum Notes. The horizontal, vertical, and hydrographic datum notes identify the controls used for these items on the map. Generally, horizontal and hydrographic datum notes are not shown on medium- and small-scale maps.

h. Grid Notes and Data. Maps of 1:1,000,-000 and larger scale contain grid notes and a grid reference box with sample reference, to explain the grid data on the map. Maps carrying 1,000-unit-interval grid lines also show a declination diagram and a protractor scale in the margin. The declination diagram shows the relationship bet ween true north, magnetic north, and grid north for the major grid at the center of the sheet. Maps carrying 10,000-unit-interval grid lines show a magnetic declination note. This note indicates the variation in the east and west map edges. It also shows the mean annual change.

APPENDIX I

REFERENCES

1. Army Regulat AR 117-5 AR 320-5 AR 320-50	Military Mapping and Surveying. Dictionary of United States Army Terms. Authorized Abbreviations and Brevity Codes.	FM 21-5 FM 21-6 FM 21-26 FM 21-30 FM 30-5 FM 30-10 FM 101-10, Part 1	Military Training. Techniques of Military Instruction. Map Reading. Military Symbols. Combat Intelligence. Terrain Intelligence. Staff Officer's Field Manual: Organization, Technical and
2. Department of	the Army Pamphlets (DA Pam)		Logistical Data.
DA PAM 310-1 DA PAM 310-3	Index of Army Motion Pictures, Film Strips, Slides and Phono-Recordings. Military Publications: Index of Administrative Publications. Military Publications: Index of Training Publications. Index of Technical Manuals, Technical Bulletins, Supply Bulletins, Lubrication Orders, and Modification Work	4. Technical Ma TM 5-230 TM 5-240 TM 5-244 TM 5-245 TM 5-248 TM 5-9990 TM 30-246	General Drafting. A Guide to the Compilation and Revision of Maps. Multiplex Mapping. Map Reproduction. Foreign Maps. Kit Instruction Map Reading. Tactical Interpretation of Air Photos.
DA PAM 310-5	Orders. Military Publications: Index of	5. Tables of Org	anization and Equipment
	Graphic Training Aids and Devices. Military Publications: Index of Tables of Organization and Equipment, Type Tables of Distribution and Tables of Allowances. Military Publications: Index of	TOE 5-55D TOE 5-56D TOE 5-57D	Engineer Topographic Battalion, Army. Headquarters and Headquarters Company, Engineer Topographic Battalion, Army. Engineer Map Reproduction
DITTINI OIO 20	Supply Manuals, Corps of Engineers.	TOE 5-59D	and Distribution Company, Army.
3. Field Manuals	(FM)		Engineer Photomapping Company, Army.
FM 5-1	Engineer Troop Organizations	TOE 5-167C	Engineer Topographic Company, Corps.
FM 5-30	and Operations. Engineer Intelligence.	TOE 5-344R	Engineer Base Map Depot Company.

TOE 5-446D	Headquarters and Headquarters Detachment, Engineer	TF 5-2412 TF 5-2413	Intersection. Location.
TOE 5-347D	Base Topographic Battalion. Engineer Base Reproduction	TF 5-2415 TF 5-2416 TF 5-2417	Resection. Scale and Distance. Using the Protractor.
TOE FOLOD	Company.	TF 5-2407	Azimuth Conversion.
TOE 5-348D	Engineer Base Survey Com-	TF 5-2414	Percent of Slope.
TOE 5-349D	pany. Engineer Base Photomapping Company.	TF 5-2408	Characteristic of Contour Lines.
TOE 5-500C	Engineer Service Organiza-	TF 55-2365	Sextant Adjustment.
1020000	tion:	TF 5-1546	Multiplex Mapping, Part II.
	1A Engineer Topographic	TF 5-1549	Multiplex Mapping, Part I.
	Staff Team.	MF 5-8275	Maps for the Army.
	lB Engineer Survey Team. lC Engineer Survey Pla-	8 Army Man	Service Technical Manuals
	toon.	AMS TM 22	Map Identification and Other
	lD Engineer Photomap-	AND IN LL	Marginal Information.
	ping Platoon. 1E Engineer Reproduction Platoon.	AMS TM 23A	Symbols for Large-Scale Maps, No Reduction.
	lF Engineer Map Distri- bution Platoon.	AMS TM 33A	Symbols for Medium-Scale Maps, No Reduction.
	lG Engineer Relief Map Making Team.	AMS TM 43A	Symbols for Small-Scale Maps, No Reduction.
	IH Engineer Relief Map	0 Supply Ma	nuals (Sats of Fauinment)
	Making Platoon.	SM 5-4 Series	nuals (Sets of Equipment)
	lN Engineer Hydrology	3610-S01	Reproduction Set, Ammonia
	Team. 1P Engineer Geodetic Survey Team.	3010-301	Process: Reproduction of Line Tracings.
	_	3610-S02	Reproduction Set, Black and
6. Graphic Tra			White Process: Drawing
GTA 5-2	Elementary Map Reading.	0010 007	Tracings.
GTA 5-12	Coordinate Scales and Protractor.	3610-S07	Reproduction Set, Topogra- phic, Photolithographic: Reproduction Company.
	ures, Film Strips, Slides, and	3610-S13	Reproduction Set, Silk Screen
	ecordings	0010 510	Process: Sign Reproduction.
TF 5-1788	Topographic Symbols.	6675-S02	Computing and Drafting
TF 5-1789 TF 5-1791	Elevation, Distance, and Grid. Direction, Orientation, and		Equipment Set: Field Sur-
11 3-1/31	Location With Compass.		vey Data.
TF 5-1790	Direction, Orientation, and Location Without Compass.	6675-S03	Drafting Equipment Set, Battalion: For Charts, Sketches,
TF 5-1792	Photos and Photomaps.	007E C19	and Overlays.
TF 5-1270	British Conventional Signs and Symbols.	6675-S12	Drafting Equipment Set, Topographic Battalion, Head-
TF 5-2406	Azimuth.		quarters and Service Company: For Operational
TF 5-2409	Contour Lines and Intervals. Direction.		Plans, Maps, Drawings, and
TF 5-2410 TF 5-2411	Elevation.		Charts.
II U WIII	LICTUUII.		

6675-S13	Drafting Equipment Set, Topographic Battalion, Photomapping Company: For Map Revision, Compilation	6675-S49 7520-S01 7610-S07	Map Distribution Set: Depot. Sign Painting Set. Book Set: Topographic, General Purpose.
6675-S15	and Color Separation. Drafting and Duplication Equipment Set: For Small Sketches, Notes and Orders.	7610-S09 7610-S10	Book Set: Topographic Bat- talion, Photomapping Com- pany. Book Set: Topographic 'Bat-
6675-S16	Drafting Instrument Set: Field.		talion, Reproduction Company.
6675-S17	Drafting Instrument Set: Office.	10. Departmen	t of Commerce Publications
6675-S18	Drafting Instrument Set: Pocket.	a. U.S. Coast Publications.	and Geodetic Survey Special
6675-S19	Plotting Instrument Set, Stereoplotter Multiplex Con- trol Booth.	No. 8 Tables and	Formulas for the Computation etic Positions.
6675-S20	Plotting Instrument Set, Stereoplotter, Multiplex	28 Applicat	ion of the Theory of Least to the Adjustment of Triangu-
6675-S21	Drafting Unit. Plotting Instrument Set, Stereoplotter, Multiplex Laboratory.	68 Elements of 193 Manual of	of Map Projection. Plane Coordinate Computation. Im-l Tables for the Computation
6675-S22	Plotting Instrument Set, Stereoplotter, Multiplex Plotting Booth.	of Geod tional El	etic Positions on the Interna-
6675-S23	Plotting Instrument Repair Set, Stereoplotter, Projec- tion: For Minor Mechanical Repairs.	Surveyo 241 Natural T Geodetic	rs). ables for the Computation of Positions. of Terms Used in Geodetic and
6675-S24	Plotting Instrument Repair Set, Stereoplotter, Projec- tion: Supplementary.	Other b. U.S. Coast	Surveys. t and Geodetic Survey Serial. urveys and Their Uses.
6675-S30	Sketching Set, Surveying: Military Field Sketching.		t of Interior Publications
6675-S31	Stereometer Set, Stereocom- paragraph, Photogram- metric.	Topographic I	al Survey Bulletin nstructions: Symbols for stand- maps published at the scale of
6675-S48	Map Distribution Set: Portable.	1:63,360 and lar and 1:48,000, da	ger, to be scribed at 1:24,000"


APPENDIX II


TOPOGRAPHIC ABBREVIATIONS

A	Army	DC	District of Columbia
Aband	abandoned	Dec	December
AF	Air Force	Deg	degrees
AFB	Air Force Base	Del	
Ala	Alabama	Dept	department
Alin	alinement	Div	division
Alt	alternate	DSvy	Directorate of Military Surveys
AMS	Army Map Service	•	(Great Britian)
Anc		E	east
Anch		Elec	electric, electrified
Approx	approximate	Elev	elevated
Apr		Fd	ford
Arch		Feb	February
Ariz		Fl	flood
Ark	Arkansas	Fla	Florida
ASE	Army Survey Establishment	Fld	field
	(Canada)	Fm	fathom
Aug	· · · · · · · · · · · · · · · · · · ·	For	forest
Ave		Ft	fort
В		Fy	
Bdry		G	
Bk		Ga	-
Bldg		Gas	
Blvd		GN	
BM		Govt	
Br		Grd	
Brg			Geographic General Staff
Вур			(Great Britain)
C		Hbr	harbor
Calif	<u> </u>	Hosp	hospital
Cath		HS	
CE		Ну	
Cem		I	island
CG	•	Ill	
CH		In	
Ch		Ind	
Chan		Jan	
Chy		Jul	
Co		Jun	•
Col		Junc	
Colo		Kans	
Comm		Km	
Conn		Kn	
Const		Ку	
CR		L	
Cr		La	
Cus Ho		Lat	
Cub IIU	cusvoiii iivuse	LRAD	

Ldg	landing	RI
LH	lighthouse	RR
Long	longitude	RS
-	meter (s)	Ry
Mag	magnetic	S
Mar	<u> </u>	SC
	Massachusetts	Sch
	Maryland	S Dak
	mile (s)	sec
	Michigan	Sept
	military	St
	minute (s)	St
	Minnesota	Sta
Miss	Mississippi	Ste
	Missouri	Str
	monument	
	Montana	Subm
		T
	mount, mountain	Tel
	mountains	<u>Temp</u>
N		Tenn
	national	Tex
	navigable	Tnpk
	North Carolina	Tr
	North Dakota	Univ
	Nebraska	US
	Nevada	USC&GS
	New Hampshire	
NJ	New Jersey	USDA
NMex	New Mexico	
No	number	USFS
Nov	November	USGS
NY	New York	
	obstacle	USNHO
	obstruction	
	October	USLS
	Oklahoma	Va
	Oregon	VABM
	protractor point (pivot point)	Vil
Pa	Pennsylvania	Vt
	peninsula	W
Pk		Wash
	parkway	
	parkway	Wdm
Pt		Wis
		WM
	post and telegraph office	WT
	quarantine	W Va
Rd		Wyo
	reservation	Yd

RI	Rhode Island
RR	
RS	
Ry	rauway
3	south
3C	South Carolina
3ch	school
3 Dak	South Dakota
ec	
Sept	
8t	
3t	
Sta	
Ste	Sainte
Str	.stream
Subm	submerged
Pa1	telephone or telegraph line
N	.telephone or telegraph line
Cemp	
Cenn	
Cex	Texas
inpk	.turnpike
<u> የ</u>	tower
Jniv	
JS	
1002.00	.United States Coast and
75CetG5	
	Geodetic Survey.
JSDA	.United State Department of
	Agriculture.
JS FS	.United States Forest Service
JSGS	.United States Geological
	Survey.
JSNHO	United States Navy
,514110	Hydrographic Office.
TOT 0	
	.United States Lake Survey
⁷ a	
'ABM	vertical angle benchmark
7il	.village
⁷ t	.Vermont
V	
Vash	
Vdm	
Vis	
VM	
VT	water tank, water tower.
V Va	
Vyo	Wyoming
'd	vard
u	.yaiu





SE NIVE FOR									- i		ЩЩ	See and a second	
COMPT	bB Bd		A _A		À à	-	P.G.	-	PT			CEOCRAPHE LOCA	
ACTER NO. 12 THE STATE	E Z	~	4 Z	0	> Z		n Z		LZ LZ				<u> </u>
COTION MANNETS - SERVICE +-	MB MB		٧,		> ¥		MU		T.		112 molt		
ndictors.	9	0	7		ΓΛ		TO TO THE TOTAL COM		<u> </u>		TO O O LIVE DO NOT THE TOTAL TO DO NOT THE TOTAL THE TOT		
ot •) H		× 5		Ĝ.		ξ		Ž		VERTICAL DATA NOTE: THE VERTIC		
ENCONEE OF THE								:		+	WEFFER, DATE NO		i I
	ES	-	Ę		EQ		CONTROPTAL CAND		EZ			F 1001	
NO BCALE	SC	-)R	·	O _G		DP		NG.		[HOW VALCHALOR	, , , , , , , , , , , , , , , , , , ,
MENS OF BUILD SEALS	S	0	8		3		đ		Z.		CREST HOTE		
							1		823370		Case 1 America		

INDEX

	Paragraphs	Page		Paragraphs	Page
Abbreviations		87	Conveyor belt	17	46
Accuracy of maps		3	Coverage diagram	28 <i>e</i>	90
Administrative boundaries	23	83	Cranberry bog	9	5
Aerial cableway		46	Credit note		89
Airfield		68	Crevasse		16
Airport		68	Crevice		16
Anchorage	12	29	Crossing, grade		52
Aqueducts		5	Current		
Area limits		29	Cut		29
Asphalt lake		16	Out	10	16
Astronomic position	. 22	79	Dams	21	68
Beach	10	1.0	Danger line navigation	12	29
Bench mark		16	Datum notes		90
Bottom characteristics		79	Definition of coastal terms		29
Boulders	12	29	Depression		16
Boundaries:	. 10	16	Depth curves		
					29
Administrative		83	Distances, roads	16	43
International		83	Distorted surface area		16
Special		83	Ditch	·· -	2
Braided stream	. 9	5	Docks		68
Breakers		29	Dolphin		29
Breakwater		68	Drawbridge, highway	. 18	52
Bridge highway		52	Drawbridge, railroad	18	52
Bridges		52	Dry dock	. 21	68
Brush woods	11	26	Dry lake	9	5
Buildings and populated places on			Dry pond	9	5
large scale maps	19	56	Dunes		16
Buildings and populated places on					
medium and small scale maps	20	64	Edition number	28	89
Buildings, general	19	56	Elevation, unit of measure		16
Buildings, miscellaneous		56	Evaporator, salt	. 9	5
Built up area	. 19	56			_
Canals	9	5	Falls, large		5
Cave	•		Falls, small		5
Cemetery		16 56	Features, drainage		5
Church	19	56	Features related to communication		52
Circle, traffic		43	Features relief		16
Cities, medium and small scales		64	Features vegetation		26
Cliff	10		Fence	. 21	68
Cliff dwelling		16	Ferry	. 18	52
Cloverleaf	19 16	56	Ferry slip	21	68
		43	Field line		68
Color	17	46	Fill		16
Conduit elevated, any type		52	Filtration bed		68
		5	Fish ponds		
Contours approximate	10	16			5
Contours approximate	10	16	Flume		5
Contour interval		16	Footbridge		52
Control points and elevations		79	Ford		52
Control point, horizontal	22	79	Foreshore flat	12	29

	Paragraphs	Page		Paragraphs	Page
Form lines:			Mine, strip	10	16
General	10	16	Mine tunnel		68
Specific		16	Monastery		64
Fort		64	Moraine, glacial		16
		•	Moslem shrine		56
Geographic location name		89	Mosque		56
Glacial moraine		16	Mountain pass		16
Glacier	10	16	Mountain pass	10	10
Grade crossing	. 18	52	Native settlement	19	56
Gradient roads steep	. 16	43	Nipa		56
Grass tropical		26			
Greenhouse		56	Obstructions	12	29
Grid notes in datum		90	Offshore area	. 12	29
		•	Orchard plantation	. 11	26
Hachures:			Overpass or underpass	18	52
General		16	•		
Specific	. 10	16	Pagoda	19	56
Hedgerow	21	68	Pass, mountain	. 10	16
Highway, dual	16	43	Peat cutting	. 9	5
Highway bridge or viaduct	18	52	Penstock		5
Highways		35	Perennial lake	. 9	5
Historical site		56	Perennial pond		5
			Pier	· ·	68
Ice cliff		16	Piling		29
Ice field or snow field	10	16	Pipeline		68
Index to adjoining sheets	28c	89	Plantation orchard		26
Index to boundaries	28d	89			64
Industrial and public works	21	68	Populated place		
Intermittent lake		5	Power transmission line		68
Intermittent pond	9	5	Prospect	21	68
International boundaries		83	Over mmv	01	co
Inundation, land subject to		5	Quarry	. 21	68
Key number	28	89	Race track		68
•			Railroads, Introduction		46
Lake or Pond:			Railroad bridge or viaduct	. 18	52
Dry	9	5	Railroads:		
Intermittent	9	5	Carline		46
Perennial	9	5	Dismantled railroad		46
Landing ground	21	68	Electrified	. 17	46
Landmark building	20	64	Gage	. 17	46
Landmark or located object		68	In street or on wharf	. 17	46
Land subject to inundation		5	Multiple track	. 17	46
Lava covered area		16	Nonoperating	. 17	46
Ledge or reef		29	Point of change in gage or		
Levee		16	number of tracks	. 17	46
Levee carrying railroad		16	Railroad on levee	. 10	16
Levee, carrying road		16	Railroads in juxtaposition		46
Lighthouse or light		56	Siding		46
Locks		68	Single track	: <u>: _</u>	46
Locks	21	VO	Snow shed		46
Mangrove	11	26	Station		46
Map accuracy	7	3	Turntables	_	46
Map detail	7	3	Yards	2.2	46
Map identification		89			
		89	Ramp		68 5
Marginal data (Table I)		-	Rapids, large		
Marginal notes	10	16	Rapids, small		5
Marine railroad	21	68	Reef or ledge		29
Marsh or swamp	9	5	Reliability diagram		90
Marshy areas in northern latitudes	11	26	Relief features, general		16
Mine dump	10	16	Relief features, unit of measure		16
Mine, open pit	21	68	Reservoir		5
Mine shaft	21	68	Reservoir, other than water	21	68

	Paragraphs	Page		Paragraphs	Page
Revetments	. 21	68	Streets		43
Rice paddy	9	5	Stump		29
Road on levee	10	16	Sunken obstructions		29
Roads	16	43	Sunken rock		29
Rocks	. 10	16	Swamp or marsh		5
Rocks, bare and awash		29	Swept depth		29
Route marker	. 16	43	Swimming pool		68
Ruined areas	19	56	Symbol legend		89
Ruins	17	46	Symbols	. 7	3
Salt evaporator	9	5	Tailing piles	10	16
Sand	10	16	Tank		68
Scarp or slope	10	16	Telephone and telegraph		68
School	19	56	Town, medium and small scale		64
Seaplane anchorage		68			
Seaplane base	21	68	Traffic circle		43
Seawalls	21	68	Trails	13, 14,	35, 38,
Series names	28	89		15	41
Series number		89	Tunnel, railroad	. 18	52
Series scale	28	89	Tunnel, road	18	52
Sewage disposal bed	21	68	,		
Sheet name	28	89	Unit imprint	. 27 <i>g</i>	88
Sheet number	28	89	Unit of measure, elevation	. 10	16
Ship wrecks	12	29	,		
Shore-line	9	5	Viaduct	18	52
Shrines	19	56	Vegetation, general	. 11	26
Ski lift	17	46	Village, medium and small scale	. 20	64
Slope or scarp	10	16	Vineyard		26
Sluice gate	21	68	vineyard	. 11	20
Snag	12	29	Wall	21	68
Snowfield or ice field	10	16	Wash		5
Sounding	12	29			
Special boundaries	23	83	Watermill		56
Spot elevation	22	79	Well, oil	. 21	68
Spring	9	5	Well, water	9	5
Streams:			Wharfs	. 21	68
Braided	9	5	Windmill		56
Disappearing	9	5	Woods or brush woods		26
Intermittent	9	5			
Narrow, perennial	9	5	Woods scrub		26
Unclassified	9	5	Wrecks exposed		29
Wide, perennial	9	5	Wrecks sunken	. 12	29

AG 353 (2 Feb 61)

BY ORDER OF THE SECRETARY OF THE ARMY:

G. H. DECKER General, United States Army, Chief of Staff.

Official:

R. V. LEE,
Major General, United States Army,
The Adjutant General.

Distribution:

In accordance with survey conducted by AG Publication Centers.

PIN: 007195-001