


*S. Parker,* 2. Sheets, Sheet 1,  
*Hook Shaver,*  
*No. 107,622,* *Patented Sept. 20, 1870.*

*Fig. 1*



Witnesses,

*H. A. Daniels,*  
*J. H. Mester.*

*Stillman Parker, Inventor,*  
*Charles S. Whitman, Attorney*

*S. Parker.*


*2 Sheets, Sheet 2.*

*Hoop Shaver.*


*No. 107,622.*

*Patented Sept 20 1870.*

*Fig. 2.*



*Fig. 3.*



*Witnesses,*

*H. A. Daniels,*  
*J. H. Nestor.*

*Stillman Parker, Inventor, by*  
*Chas. S. Whitman, Attorney,*

# United States Patent Office.

STILLMAN PARKER, OF ALTOONA, PENNSYLVANIA.

Letters Patent No. 107,622, dated September 20, 1870.

## IMPROVEMENT IN HOOP-SHAVING MACHINES.

The Schedule referred to in these Letters Patent and making part of the same.

To all whom it may concern:

Be it known that I, STILLMAN PARKER, of Altoona, in the county of Blair and in the State of Pennsylvania, have invented a new and useful Improvement in Hoop-Shaving Machines; and do hereby declare that the following description, taken in connection with the accompanying drawing, hereinafter referred to, forms a full and exact specification of the same, wherein I have set forth the nature and principles of my said improvement, by which my invention may be distinguished from others of a similar class, together with such parts as I claim and desire secure by Letters Patent.

My invention relates to that class of machines used for the purpose of shaving hoops for barrels, casks, &c., and the nature thereof consists in certain modifications in the details and improvements in the construction of the same, whereby both the sides, and edges of the hoop may be shaved simultaneously and work of any size required performed, hereinafter fully specified.

In the accompanying drawing, which illustrates my invention and forms a part of the specification thereof—

Figure 1 is a perspective view of my invention, with one of the legs or uprights of the frame removed;

Figure 2, a plan view of the same; and

Figure 3, an under-side view of the plate or top of the machine.

The construction, operation, and relative arrangement of the component parts of my invention are as follows:

A A represent four uprights or legs, firmly braced together at their lower ends by means of the transverse supports *a a'*, and supporting at their upper ends the metallic plate or table B, which is screwed down thereon.

Screwed or formed on the said table is a triangular-shaped metallic block, C, having a slot of suitable width and depth, extending through its entire length, or from its apex to its base, to allow the hoop being shaved to pass through it.

A knife, *c*, constructed similarly to the ordinary plane-bit, and provided with an elongated slot, is located upon the upper side of the block C, near one edge of its inclined portion, with its cutting surface resting directly over the slot cut in the said block C, in such a manner as to come in contact with the upper edge of the hoop on its first entering said slot.

By means of the screw *c'* passing through the elongated slot of knife *c*, and entering the block C, the said knife may be adjusted at any desired point, or removed for sharpening or renewal, when required.

D D represent two other knives, made similarly to knife *c*, but larger in dimensions, with elongated slots, through which pass set-screws, *d d'*, and resting against the conically-shaped portion, or inclined sides of the block C, the sides of said knives being at right angles with the upper surface of the table or plate B.

These knives are for the purpose of shaving the sides of the hoop.

Situated directly in front of the knives D D, and in close proximity therewith, are the fluted or corrugated rollers E E, secured upon the vertical shafts F F, passing through elongated slots, *f f*, cut in the plate B, (see fig. 2,) and having attached to their lower ends pinions or cogs, *e*, gearing into each other.

By means of the elongated slots *f f*, it will be seen that the upper ends of the shafts F, carrying the fluted rollers E, may be laterally adjusted, in the manner hereinafter described, for the purpose of placing the said rollers nearer or further apart, in order to receive hoops of any desired thickness, which are to be shaved.

The rollers E are designed for the purpose of feeding the work to be performed to the knives aforesaid, their teeth or corrugations, while being revolved, grasping the work and carrying it forward to its proper destination.

G G designate two levers, having their fulcrums at the points *g g*, the pivots of which are made to enter the under side of the table or plate B at one end, and recesses cut in the upper side of a pendant or support, *a*, secured to the said plate or table, at the opposite end.

The right-angular ends of the said pendant are provided on their upper surfaces with female screws for the reception of the male screws *h' h'*, which pass through apertures cut in the plate B.

The outer ends of the levers G G are supplied with set-screws, *i i*, whose inner ends enter the uprights A, the outer ends of which being supplied with square heads, by means of which the said screws may be operated or rotated, causing the levers G to be pressed against the shafts F, or released therefrom, according to the direction given to the said screws in revolving the same.

The inner ends of the said levers are recessed or made concave, in order to suit the curvilinear surface of the vertical shafts F, against which they bear, and also formed thereat with semicircular shoulders, *g' g'*, against which presses one end of the horizontal cylindrical rubber pieces or springs *g' g'*, the opposite ends of said springs being retained in position by means of metallic circular plates, *g' g'*.

The screws *g' g'* are for the purpose of giving the required tension to the springs *g' g'*, and pass through

lugs or projections, *k k*, secured to the lower side of the table B.

The object of the springs *g<sup>2</sup> g<sup>2</sup>* is to allow the shafts F to yield laterally, causing their fluted rollers to automatically adjust themselves to the size of the work to be performed.

*I* designates a slot, of a suitable length, cut in the table B, into which is inserted in an inclined position, the lower knife *c<sup>2</sup>*, for shaving the lower edge of the hoop.

The upper end of said knife is made to extend upward through its slot, and project a short distance beyond the same, so as to come in contact with the edge of the hoop to be shaved, and the lower end thereof is supplied with an elongated slot, through which passes a set-screw, *c<sup>3</sup>*, entering a beveled slot cut in a removable block, *c<sup>4</sup>*, screwed to the under side of table B.

*L* designates a metallic transverse plate or support screwed down to the cross-pieces *a' a'* of frame or uprights, A, and constructed with two small semi-circular projections, (only partially, one of which is shown in the drawing,) for the purpose of receiving and forming bearings for the lower ends of the vertical shafts F, one of said shafts being made to extend below the support L, in order to receive a beveled horizontal gear-wheel, *m*.

The beveled gear-wheel *m* engages with a correspondingly beveled pinion, *n*, located upon the transverse horizontal shaft I, having its bearings in journal-boxes *j j*, screwed down to the cross-pieces *a a* of uprights A.

Situated upon the projecting end of shaft I is a pulley, around which is designed to be passed a driving-belt, connected with the machinery for operating the same, imparting motion to the said pulley, and the various parts of the machine to be operated.

Having thus described my invention, I will indicate what I claim and desire to secure by Letters Patent in the following clause:

I claim—

The arrangement of the plate B, provided with the adjustable knives D D *c c<sup>2</sup>*, and the elongated apertures *f f*, feed-rollers E E, shafts F F, levers G G, springs *g<sup>2</sup> g<sup>2</sup>*, pinions *e e*, and wheels *m* and *n*, when constructed and operating together as described.

In testimony that I claim the foregoing, I have hereunto set my hand this 26th day of March, 1870.

STILLMAN PARKER.

Witnesses:

JOHN SHOEMAKER,  
WILLIAM MCLELLAND.