

DAVID CROWELL, Jr.

Knife Scourers and Sharpeners.

No. 116,029.

Patented June 20, 1871.





Minesses form down Inventor David Cowell go

UNITED STATES PATENT OFFICE.

DAVID CROWELL, JR., OF YARMOUTH PORT, MASSACHUSETTS.

IMPROVEMENT IN KNIFE-SCOURERS AND SHARPENERS.

Specification forming part of Letters Patent No. 116,029, dated June 20, 1871.

To all whom it may concern:

Be it known that I, DAVID CROWELL, Jr., of Yarmouth Port, in the county of Barnstable, in the State of Massachusetts, respectfully show that I have invented a new and useful Device for Scouring and Sharpening Knives, Forks, Spoons, and other articles; and that the following is a specification of the same.

My invention consists of the combination of two cork-wood rollers, placed in wood, or iron, or brass frame, as represented in Figure 1, which shows a front view of the machine.

A represents a whet stone, which is placed in a notch or rack fastened either on the front or back part of the machine, and is of a sharp fine texture of stone, the notch or rack holding the stone firmly, as represented in the drawing hereunto annexed. B, in Fig. 1, represents a piece of cork-wood placed on the end of the rollers C C. The convex, as represented by letter B, has a concave for the purpose of scouring the concave of the spoon. C C are the rollers, and are cork-wood, and are pressed close together with two spiral springs placed in the end of the frame, as represented by letter D in Fig. 2. The springs are placed in tubes and are secured by a bar across the top end of the

machine, as represented by letter H in Fig. 1 and letter H in Fig. 2. The rollers C C, represented in Fig. 1, are pressed together by the spring, and the knife is run through between the rollers and immediately receives a fine polish from the brick-dust or emery, which is placed in a hopper or tunnel immediately above the rollers C C in Fig. 1. The rollers receive the brick-dust or emery from the hopper or tunnel, represented by letter F in Fig. 1. Letter G, in Fig. 1, represents a screw and arm by which the machine may be fastened to a table or shelf, so that it can be put in working order.

Claim.

What I claim is—

The combination and arrangement of the rollers C C, the extended roller B, scouring and sharpening devices A and F, journal-boxes with springs D, connecting device G with its gearing and crank to give motion, all as shown, for the purpose described.

DAVID CROWELL, JR.

Witnesses:
JEROME AMOS,

F. W. HOWARD.