

(No Model.)

J. COSTELLO.
BUTTON.

No. 266,611.

Patented Oct. 31, 1882.




FIG. 1.




FIG. 2.




FIG. 3.

WITNESSES.

Geo. W. Carey.
Henry J. Stapleton.

INVENTOR,

John Costello.
by *Edson Salistany Jones.*
Attorney.

UNITED STATES PATENT OFFICE.

JOHN COSTELLO, OF ATTLEBOROUGH, MASSACHUSETTS, ASSIGNOR TO
WATSON & NEWELL, OF SAME PLACE.

BUTTON.

SPECIFICATION forming part of Letters Patent No. 266,611, dated October 31, 1882.

Application filed September 14, 1882. (No model.)

To all whom it may concern:

Be it known that I, JOHN COSTELLO, of Attleborough, in the county of Bristol and State of Massachusetts, have invented a new and
5 useful Improvement in Buttons; and I do hereby declare that the following specification, taken in connection with the accompanying drawings, forming a part of the same, is a full, clear, and exact description thereof.

10 My invention relates to means for attaching the backs of buttons to heads or face members composed of pearl, ivory, hard rubber, &c.; and my improvement consists in a fastening-plate which is adapted to be secured to the
15 post or shank of a button-back, and has a ribbed edge adapted to be swaged outwardly to engage the beveled wall of a cavity in the button-head, and thereby hold the parts in combination, as will hereinafter appear.

20 Referring to the drawings, Figure 1 represents in partial section a button embodying my improvement. Fig. 2 shows the fastening-plate in perspective, a portion being cut away the better to show the ribbed edge. Fig. 3
25 shows said plate attached to a two-arm post.

A is the button-head, which is provided with a cavity, *a*, having a beveled wall, *a'*. B is the fastening-plate, having a ribbed edge, *b*. C is the post, secured to the plate B; and D is
30 the shoe, which is attached to the post in any preferred manner. Normally the diameter of the plate B is slightly less than that of the top of the cavity *a*, so that the plate can enter the cavity. The plate B is secured to the button-
35 head by placing the plate in the cavity in the head and flattening the rib with a proper tool or tools in a well-known manner, so that the edge of the rib will engage the wall of the cavity, as shown in Fig. 1.

Fastening-plates which are curved over their
entire area have heretofore been employed; but since the diameter of the cavities in a definite size of button-heads varies more or less, comparatively considerable curvature has to
40 be given to such plates in order that sufficient expansion or spread may be obtained to cause them to fit cavities of a maximum diameter within the usual limits of variation. When
45 such a plate is combined with a head having a cavity of a minimum diameter the plate often becomes crimped, thereby rendering it un-
50 sightly, and the post soldered to said plate is liable to become detached or its attachment to the plate be rendered insecure during the fast-
55 ening operation.

My improved plate possesses advantages
over one curved over its entire area, in that thinner, and therefore less expensive, stock may be used, owing to the rigidity imparted to the
plate by the rib. The ribbed plate will not be
60 crimped or the attachment of the post soldered thereto be disturbed by the fastening operation, and the ribbed plate will expand to fill
cavities of greater variation in diameter.

What I claim, and desire to secure by Letters
Patent, is—

The combination, with the head of a button or other article having a cavity with a beveled wall, as described, of a back member provided
with a fastening-plate, B, having a rib, *b*, sub-
70 stantially as and for the purposes specified.

JOHN COSTELLO.

Witnesses:

EDSON SALISBURY JONES,
ELIZA J. PRATT.