
C. C. HINKLE.

FENCE.

No. 304,932.

Patented Sept. 9, 1884.



UNITED STATES PATENT OFFICE.

CHARLES C. HINKLE, OF HAZLETON, INDIANA.

FENCE.

SPECIFICATION forming part of Letters Patent No. 304,932, dated September 9, 1884.

Application filed February 29, 1884. (No model.)

To all whom it may concern:

Be it known that T, CHARLES CULBERSON HINKLE, of Hazleton, in the county of Gibson and State of Indiana, have invented a new and 5 useful Improvement in Fences, of which the following is a full, clear, and exact description, reference being had to the annexed drawings, forming part of this specification.

This invention relates to portable board 10 fences; and the invention consists of the construction hereinafter described and claimed.

In the drawings, Figure 1 is a side elevation of my fence, partly broken away; and Fig. 2 is

a plan view of the same.

A A indicate two panels of fence, each consisting of five boards, a b c d e, to one end of which, and on each side of said end, are nailed two four-inch strips, f g, while a single strip, h, is nailed to their center, and another single strip, i, is nailed to their other end. The strips f g h are nailed flat against the boards; but the strip i is nailed with its edge against the boards. The boards a d are made to project slightly beyond the others at one end of the panel, to form tongues j, while at the other end of the panel they are cut away to form seats k be-

tween the strips f g, in order that the tongues j of one panel may be set in the seats k of another,

and the strips i are made shorter than the strips f g h at the lower end, so that they shall 30 not touch the ground, as the others do, but shall allow the panel to be supported at that end by the tongues j resting on the next panel. The object of this is to make a frictional joint between the two panels. The fence thus rests on the ends of the strips f g h, and is to be held upright by braces l, one to a panel, each consisting of a strip, which is bolted to the flat side of the strip i by a horizontal bolt, m, and has its foot secured to the ground by a stake, 40 n, passing through the same. If desired, two or more braces may be used to a panel, and these may be arranged on both sides thereof.

What I claim is—

The fence-panel having at one end opposed 45 side strips, fg, and between said strips sockets or seats k, and at the other end an edgewise-disposed side strip, i, and tongues j, together with a brace, l, bolted to said strip i and staked to the ground, substantially as and for the 50 purpose set forth.

CHARLES C. HINKLE.

Witnesses:

AARON TRIPPET, G. H. KNAUB.