
(No Model.)

H. HEINE.

CLOTHES DRIER.

No. 382,422.

Patented May 8, 1888.



Witnesses: Elfonne. P. Plats

Herman Heine

By Stout Vollnderwood

Altororys.

UNITED STATES PATENT OFFICE.

HERMAN HEINE, OF MILWAUKEE, WISCONSIN, ASSIGNOR TO HAROLD G. UNDERWOOD, OF SAME PLACE.

CLOTHES-DRIER.

SPECIFICATION forming part of Letters Fatent No. 382,422, dated May 8, 1888.

Application filed March 17, 1885. Renewed September 7, 1887. Serial No. 249,040. (No model.)

To all whom it may concern:

Be it known that I, HERMAN HEINE, of Milwaukee, in the county of Milwaukee, and in the State of Wisconsin, have invented certain new and useful Improvements in Clothes-Driers; and I do hereby declare that the following is a full, clear, and exact description thereof.

My invention relates to clothes driers, and

10 will be fully described hereinafter.

In the drawings, Figure 1 is a perspective view of my device in position on a stove pipe. Fig. 2 is a plan view of the same. Fig. 3 is an edge view, and Fig. 4 is a section on line x

 $\mathbf{r} = x$ of Fig. 2.

The body of my device consists of two sections, A A', hinged together at a at one end. The section A' has a flange, b', on its end opposite the hinge, which flange is perforated to 20 receive a screw-bolt, c, that projects from a flange, b, of section A, and the parts are held together at this point by a thumb nut, c', that fits on the screw bolt. The form of the sections is shown in cross section in Fig. 4 of the drawings, each having a vertical portion adapted to fit about the stove pipe and a horizontal portion which is slotted at f. The arms that support the clothes consist each of a rod, F, preferably of wood, and a ferrule, F', the 30 end of which projects at right angles to its body and terminates in a flat or nearly flat head, F2, which latter is introduced into the enlargement f' of slot f, as shown at the right in Fig. 2, and then turned into the position 35 shown to the left on same figure, or more

clearly in Fig. 4, after which it may be carried toward the opposite end of the slot to give place to another, and thus several arms may be strung on each section.

It will be observed that the bent ends of the 40 ferrules fit loosely in the slots f, and therefore the rods F may be turned to either side, so as to lie either parallel or at angles to each other.

My device may be clamped to any stove-

pipe and as easily removed therefrom.

Having thus fully described my invention, what I claim as new, and desire to secure by Letters Patent, is-

1. In a clothes rack, the circumferentiallyslotted hinged sections in combination with 50 arms having bent and headed ferrules, as set forth.

2. In a clothes drier, the combination of the hinged sections, each section having a horizontal and a vertical flange, the latter to em- 55 brace the support of the drier, and the former provided with a circumferential slot extending continuously from end to end, with removable arms having ferrules bent at about a right angle, and provided with headed ends for engage- 60 ment with the described slots, substantially as set forth.

In testimony that I claim the foregoing I have hereunto set my hand, at Milwaukee, in the county of Milwaukee and State of Wiscon 65 sin, in the presence of two witnesses.

HERMAN HEINE.

Witnesses:

S. S. STOUT.

H. G. UNDERWOOD.