

(No Model.)


W. P. SINNOCK.

FINGER RING.


No. 385,073.

Patented June 26, 1888.

*Fig. 1.*




*Fig. 2.*



*Fig. 3.*



*Fig. 4.*



WITNESSES:  
*Gustave Dietrich*  
*Bert H. Van Houten*

INVENTOR,  
*W. P. Sinnock*  
BY *Wm. H. Bates*  
ATTORNEY.

# UNITED STATES PATENT OFFICE.

WILLIAM P. SINNOCK, OF NEWARK, NEW JERSEY.

## FINGER-RING.

SPECIFICATION forming part of Letters Patent No. 385,073, dated June 26, 1888.

Application filed September 28, 1887. Serial No. 250,881. (No model.)

*To all whom it may concern:*

Be it known that I, WILLIAM P. SINNOCK, a citizen of the United States, residing at Newark, in the State of New Jersey, have invented  
5 a new and useful Improvement in Finger-Rings, of which the following specification is a full, clear, and exact description.

This invention relates to an improved manner of fastening a raised initial, monogram, or  
10 other ornament upon the stone or head of a finger-ring.

The object of this invention is to construct the heads of the rings and the initials, monograms, or other ornaments so that the dealer  
15 to whom they are sold by the manufacturer can attach any one of the initials, monograms, or ornaments to any one of the rings he may buy, no matter what the pattern or finger size of the ring may be.

20 The invention consists of the various features of improvement hereinafter more specifically pointed out.

In the accompanying diagram, Figure 1 is a view of the ring after the initial, monogram, or ornament is attached. Fig. 2 is a front  
25 view of the ring before the initial, monogram, or ornament is attached. Fig. 3 is a view of the initial, monogram, or ornament before it is attached to the ring. Fig. 4 is a vertical cross-section of the ring complete on the plane  
30 of the line *x x*, Fig. 2.

The head and stone, if the ring has a stone-setting, are perforated with two holes, as shown  
35 on Figs. 2 and 4. The holes are countersunk at the inside of the ring, as shown on Fig. 4.

The initial, monogram, or ornament has soldered upon its back in a vertical position two  
40 hollow round wire rivets of a length equal to the length of the holes through the head of the ring, of a size equal to the size of the holes through the head of the ring, and just as far apart as are the holes through the head of the ring, as shown in Fig. 3 by letters *d d*, so that when the initial, monogram, or ornament is

placed upon the head or stone of the ring the  
45 rivets will enter into the holes of the head of the ring and extend just to the inside of the ring.

After the dealer has selected an initial, monogram, or ornament for a ring of the  
50 proper finger size and pattern, the ring is made complete in the following manner: The same is placed upon the head or stone of the ring, so that the rivets enter the holes in the ring, and is fastened upon the ring by insert-  
55 ing the point of a riveting-tool in the hollow ends of the rivets, which are then flush with the inside of the ring, and pressing the same into said hollow ends and turning the same  
60 about until the ends of said rivets are so expanded as to fill the countersunk portions of said holes, thus securely attaching the initial, monogram, or ornament to the ring without the use of solder.

My improved method of attaching the mono-  
65 gram or other device to the ring-band by having the rivets pass through the stone and the band will obviate the necessity of additional fastening for the stone, as has heretofore been the case.

70 Having thus described my invention, I claim as new and desire to secure by Letters Patent—

In a ring of the character described, the finger-band having a perforated seal-head thereon  
75 with two or more perforations therethrough for the reception of the hollow tubular rivets, in combination with a stone, similarly perforated through its face or lesser diameter, to be mounted thereon, and the monogram or other  
80 device provided with tubular rivets, as described, said rivets passing through the stone and finger-band, upset within the latter, whereby all the parts are rigidly secured together, as set forth.

WILLIAM P. SINNOCK.

Witnesses:

H. D. SHERRILL,  
J. E. ANDERSON.