

(No Model.)

S. JENKINSON.
SASH CORD FASTENER.

No. 491,966.

Patented Feb. 14, 1893.

Fig. 1.





Fig. 2.



WITNESSES:

Thomas Durant,
Durant & Church.

INVENTOR

Samuel Jenkinson
BY
Church & Church
his ATTORNEYS

UNITED STATES PATENT OFFICE.

SAMUEL JENKINSON, OF ROCHESTER, ASSIGNOR TO THE VANDERBILT SASH
BALANCE COMPANY, OF CANANDAIGUA, NEW YORK.

SASH-CORD FASTENER.

SPECIFICATION forming part of Letters Patent No. 491,966, dated February 14, 1893.

Original application filed November 2, 1891, Serial No. 410,574. Divided and this application filed August 11, 1892. Serial No. 442,752. (No model.)

To all whom it may concern:

Be it known that I, SAMUEL JENKINSON, of Rochester, in the county of Monroe and State of New York, have invented certain new and
5 useful Improvements in Window-Sash Tape or Cord Fasteners; and I do hereby declare the following to be a full, clear, and exact description of the same, reference being had to the accompanying drawings, forming a part
10 of this specification, and to the reference-numerals marked thereon.

My present invention has for its object, to provide a simple and cheap device for securing the sustaining tape or cord to window
15 sashes, and it consists in an improved construction hereinafter described; the novel features being pointed out in the claims at the end of this specification.

In the drawings, Figure 1 is a perspective
20 view of my tape fastener; and Fig. 2 a sectional view of the same, showing its application to a window sash.

Similar reference numerals indicate similar parts.

25 My fastener is composed of a single piece preferably of cast metal having a body portion 1 in the form of a plate provided at its inner end with a downwardly projecting semi-circular web or flange 2, and near its outer
30 end with a corresponding upwardly projecting web or flange 3; and beyond this with a loop 4 for the application of the sustaining tape or cord 5. In the present instance this loop 4 is adapted for the attachment of a tape
35 and projects a very short distance beyond the edge of the sash; but it is obvious that it could be made larger so that a sash cord could be readily applied, which cord would as is usual lie in a groove in the edge of the sash.

The flanges 2 and 3 are as stated, rounded so
40 that they will fit into the usual auger holes 6 in the sash, and the edges are preferably somewhat sharpened so that they will bite into the top and bottom thereof when the weight of the sash is upon the tape and prevent the ac-
45 cidental outward movement of the fastener. Unless this outward movement is prevented, the fastener might work out and mar the window casing, and interfere with the proper operation of the sash.

In applying the device to a sash, it is only
50 necessary to place it in the aperture in the sash and attach the tape; or a cord could as well be attached by varying the shape of the loop on the end of the device as will be un-
55 derstood by those skilled in the art.

This application is a division of an application filed by me November 2, 1891, Serial No. 410,574.

I claim as my invention—

60 1. The fastener or attaching device for window tapes adapted to be inserted in an aperture in a sash, composed of the body portion having the upwardly extending flange or web near its outer end, and the downwardly ex-
65 tending flange or web near its inner end, substantially as described.

2. The fastener or attaching device for window tapes adapted to be inserted in an aperture in a sash, composed of a body portion
70 having the loop at its outer end, the upwardly extending web or flange also near said end and the downwardly extending flange or web near its inner end, substantially as described.

SAMUEL JENKINSON.

Witnesses:

FRED F. CHURCH,
GRACE A. RODA.