
H. M. WINTER. BOX FASTENER.

(Application filed Aug., 1, 1899.)

(No Model.)



WITNESSES: Ella L. Giles Oldrinner Hermann May Hinter

BY

Charles

ATTORNEYS

UNITED STATES PATENT OFFICE.

HERMANN MAX WINTER, OF BLASEWITZ, GERMANY.

BOX-FASTENER.

SPECIFICATION forming part of Letters Patent No. 647,126, dated April 10, 1900.

Application filed August 1, 1899. Serial No. 725,787. (No.model.)

To all whom it may concern:

Be it known that I, HERMANN MAX WINTER, a subject of the Emperor of Germany, and a resident of Blasewitz, near Dresden, in the Kingdom of Saxony, German Empire, have invented certain new and useful Improvements in Locking Devices for Chests or Boxes, of which the following is a specification.

for the chests or boxes which are set outside the door of a house and in which bakers leave their goods, the object being to prevent tampering with the goods by other than a property-authorized person.

The invention is illustrated in the accom-

panying drawings, in which-

Figure 1 is a front view with part of the wall broken away, showing the box locked.

Fig. 2 is a transverse sectional view of the same. Fig. 3 is a view similar to Fig. 1, showing the box unlocked; and Fig. 4 is a view similar to Fig. 2, also showing the box unlocked.

25 In the drawings the box or chest is indicated by the letter a and is provided with a suitable hinged cover g, having a locking tongue or bolt h. The front of the box is provided with a compartment or recess in which 30 is pivotally mounted a locking-lever having a hooked upper end which is normally pressed into engagement with the bolt h by a spring e. A small section of the bottom of the box f is hinged at one edge as shown and is provided.

hinged at one edge, as shown, and is provided with a lock f', of the ordinary or any desired construction, which may be unlocked by a key, as f^2 , and opened, as shown in Figs. 3 and 4.

A lever d is also pivoted in the compartment or recess with its free end in proximity to the lower end of the lever c and has its opposite 40 end linked by a link d' with the hinged portion f, so that when said hinged portion is opened the lever d will contact with the lever c and move the latter out of locking engagement with bolt h and against the tension of 45 spring e, and when so disengaged the cover g will be raised at once by the spring i.

In use the box is left open until the baker comes, who inserts his goods and presses down upon the cover, which simultaneously forces 50 the bottom upward and allows the lever c to spring into locking engagement with the bolt h. It will be observed that the box as thus locked cannot be opened except by a person who not only has the proper key, but knows 55 where the keyhole is and understands swinging out the sectional bottom.

Having thus described my invention, what

In combination, the box having a hinged 60 cover and a hinged bottom section, a spring-pressed lever mounted in said box and having a hooked end adapted to engage with said cover, a second lever adapted to move said locking-lever to disengage the same, a link 65 connecting the bottom section and said second lever and locking means for said bottom section, substantially as described.

In witness whereof I have hereunto set my hand in presence of two witnesses.

HERMANN MAX WINTER.

Witnesses:

PAUL ARRAS, HERNANDO DE SOTO.