



- AMMETER
- CURRENT LIMITING FUSE
- CONTROL POWER INTERLOCK, CONTACT HELD CLOSED (AS SHOWN)
- WHEN RACKING HANDLE IS IN "ON" POSITION.
- CONTROL POWER TRANSFORMER
- CURRENT TRANSFORMER
- DRIVE UNIT
- FUSE
- ISOLATION SWITCH
- MAIN CONTACTOR
- MECHANICAL INTERLOCK
- MAIN CONTACTOR INTERPOSING RELAY
- PUSHBUTTON
- PILOT LIGHT
- CUBICLE SPACE HEATERS, 150W, 240V EA.
- SURGE SUPPRESSOR
- TERMINAL BLOCK
- "2E" MOTOR PROTECTION RELAY; OVERLOAD AND SINGLE PHASE PROTECTION.
- * — REMOVE JUMPER AFTER INSTALLING REMOTE DEVICE.

TOSHIBA TOSHIBA INTERNATIONAL CORPORATION MADE IN HONG KONG, U.S.A. THIS MATERIAL IS THE EXCLUSIVE PROPERTY OF TOSHIBA INTERNATIONAL CORPORATION AND MUST NOT BE REPRODUCED, USED, OR DISCLOSED TO OTHERS WITHOUT PRIOR WRITTEN AUTHORIZATION.		TITLE: SCHEMATIC DIAGRAM CUBICLE# 4A, 4B, 5B MEDIUM VOLTAGE FVNR STARTER		REVISION: 0		SCALE: 1.0=1.0	
REV	DATE	DESCRIPTION	BY	CHK	APPR	DRAWING NUMBER: 1437741V8002	
0	9/21/09	FIRST ISSUE	PD	AL	AL	J/K SERIES CONTROLLER	
3							
4							