

NAG C Library Function Document

nag_zgbcon (f07buc)

1 Purpose

nag_zgbcon (f07buc) estimates the condition number of a complex band matrix A , where A has been factorized by nag_zgbtrf (f07brc).

2 Specification

```
void nag_zgbcon (Nag_OrderType order, Nag_NormType norm, Integer n, Integer kl,
                Integer ku, const Complex ab[], Integer pdab, const Integer ipiv[],
                double anorm, double *rcond, NagError *fail)
```

3 Description

nag_zgbcon (f07buc) estimates the condition number of a complex band matrix A , in either the 1-norm or the infinity-norm:

$$\kappa_1(A) = \|A\|_1 \|A^{-1}\|_1 \quad \text{or} \quad \kappa_\infty(A) = \|A\|_\infty \|A^{-1}\|_\infty.$$

Note that $\kappa_\infty(A) = \kappa_1(A^H)$.

Because the condition number is infinite if A is singular, the function actually returns an estimate of the **reciprocal** of the condition number.

The function should be preceded by a call to nag_zgb_norm (f16ubc) to compute $\|A\|_1$ or $\|A\|_\infty$, and a call to nag_zgbtrf (f07brc) to compute the LU factorization of A . The function then uses Higham's implementation of Hager's method (see Higham (1988)) to estimate $\|A^{-1}\|_1$ or $\|A^{-1}\|_\infty$.

4 References

Higham N J (1988) FORTRAN codes for estimating the one-norm of a real or complex matrix, with applications to condition estimation *ACM Trans. Math. Software* **14** 381–396

5 Parameters

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** parameter specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order = Nag_RowMajor**. See Section 2.2.1.4 of the Essential Introduction for a more detailed explanation of the use of this parameter.
Constraint: **order = Nag_RowMajor** or **Nag_ColMajor**.
- 2: **norm** – Nag_NormType *Input*
On entry: indicates whether $\kappa_1(A)$ or $\kappa_\infty(A)$ is estimated as follows:
 if **norm = Nag_OneNorm**, $\kappa_1(A)$ is estimated;
 if **norm = Nag_InfNorm**, $\kappa_\infty(A)$ is estimated.
Constraint: **norm = Nag_OneNorm** or **Nag_InfNorm**.
- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.

- 4: **kl** – Integer *Input*
On entry: k_l , the number of sub-diagonals within the band of A .
Constraint: $\mathbf{kl} \geq 0$.
- 5: **ku** – Integer *Input*
On entry: k_u , the number of super-diagonals within the band of A .
Constraint: $\mathbf{ku} \geq 0$.
- 6: **ab**[*dim*] – const Complex *Input*
Note: the dimension, *dim*, of the array **ab** must be at least $\max(1, \mathbf{pdab} \times \mathbf{n})$.
On entry: the LU factorization of A , as returned by nag_zgbtrf (f07brc).
- 7: **pdab** – Integer *Input*
On entry: the stride separating row or column elements (depending on the value of **order**) of the matrix in the array **ab**.
Constraint: $\mathbf{pdab} \geq 2 \times \mathbf{kl} + \mathbf{ku} + 1$.
- 8: **ipiv**[*dim*] – const Integer *Input*
Note: the dimension, *dim*, of the array **ipiv** must be at least $\max(1, \mathbf{n})$.
On entry: the pivot indices, as returned by nag_zgbtrf (f07brc).
- 9: **anorm** – double *Input*
On entry: if **norm** = **Nag_OneNorm**, the 1-norm of the **original** matrix A ; if **norm** = **Nag_InfNorm**, the infinity-norm of the **original** matrix A . **anorm** may be computed by calling nag_zgb_norm (f16ubc) with the same value for the parameter **norm**. **anorm** must be computed either **before** calling nag_zgbtrf (f07brc) or else from a **copy** of the original matrix A .
Constraint: $\mathbf{anorm} \geq 0.0$.
- 10: **rcond** – double * *Output*
On exit: an estimate of the reciprocal of the condition number of A . **rcond** is set to zero if exact singularity is detected or the estimate underflows. If **rcond** is less than *machine precision*, A is singular to working precision.
- 11: **fail** – NagError * *Output*
The NAG error parameter (see the Essential Introduction).

6 Error Indicators and Warnings

NE_INT

On entry, **n** = $\langle value \rangle$.
Constraint: $\mathbf{n} \geq 0$.

On entry, **kl** = $\langle value \rangle$.
Constraint: $\mathbf{kl} \geq 0$.

On entry, **ku** = $\langle value \rangle$.
Constraint: $\mathbf{ku} \geq 0$.

On entry, **pdab** = $\langle value \rangle$.
Constraint: $\mathbf{pdab} > 0$.

NE_INT_3

On entry, **pdab** = $\langle value \rangle$, **kl** = $\langle value \rangle$, **ku** = $\langle value \rangle$.
 Constraint: **pdab** $\geq 2 \times \mathbf{kl} + \mathbf{ku} + 1$.

NE_REAL

On entry, **anorm** = $\langle value \rangle$.
 Constraint: **anorm** ≥ 0.0 .

NE_ALLOC_FAIL

Memory allocation failed.

NE_BAD_PARAM

On entry, parameter $\langle value \rangle$ had an illegal value.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please consult NAG for assistance.

7 Accuracy

The computed estimate **rcond** is never less than the true value ρ , and in practice is nearly always less than 10ρ , although examples can be constructed where **rcond** is much larger.

8 Further Comments

A call to nag_zgbcon (f07buc) involves solving a number of systems of linear equations of the form $Ax = b$ or $A^H x = b$; the number is usually 5 and never more than 11. Each solution involves approximately $8n(2k_l + k_u)$ real floating-point operations (assuming $n \gg k_l$ and $n \gg k_u$) but takes considerably longer than a call to nag_zgbtrs (f07bsc) with 1 right-hand side, because extra care is taken to avoid overflow when A is approximately singular.

The real analogue of this function is nag_dgbcon (f07bgc).

9 Example

To estimate the condition number in the 1-norm of the matrix A , where

$$A = \begin{pmatrix} -1.65 + 2.26i & -2.05 - 0.85i & 0.97 - 2.84i & 0.00 + 0.00i \\ 0.00 + 6.30i & -1.48 - 1.75i & -3.99 + 4.01i & 0.59 - 0.48i \\ 0.00 + 0.00i & -0.77 + 2.83i & -1.06 + 1.94i & 3.33 - 1.04i \\ 0.00 + 0.00i & 0.00 + 0.00i & 4.48 - 1.09i & -0.46 - 1.72i \end{pmatrix}.$$

9.1 Program Text

```
/* nag_zgbcon (f07buc) Example Program.
*
* Copyright 2001 Numerical Algorithms Group.
*
* Mark 7, 2001.
*/

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <naga02.h>
#include <nagf07.h>
#include <nagx02.h>

int main(void)
```

```

{
/* Scalars */
Integer i, ipiv_len, j, kl, ku, n, pdab;
Integer exit_status=0;
double anorm, rcond, sum;
NagError fail;
Nag_OrderType order;

/* Arrays */
Complex *ab=0;
Integer *ipiv=0;

#ifdef NAG_COLUMN_MAJOR
#define AB(I,J) ab[(J-1)*pdab + kl + ku + I - J]
order = Nag_ColMajor;
#else
#define AB(I,J) ab[(I-1)*pdab + kl + J - I]
order = Nag_RowMajor;
#endif

INIT_FAIL(fail);
Vprintf("f07buc Example Program Results\n\n");

/* Skip heading in data file */
Vscanf("%*[\n] ");
Vscanf("%ld%ld%ld%*[\n] ", &n, &kl, &ku);
ipiv_len = n;
pdab = 2*kl + ku + 1;

/* Allocate memory */
if ( !(ab = NAG_ALLOC((2*kl+ku+1) * n, Complex)) ||
    !(ipiv = NAG_ALLOC(ipiv_len, Integer)) )
{
    Vprintf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Read A from data file */
for (i = 1; i <= n; ++i)
{
    for (j = MAX(i-kl,1); j <= MIN(i+ku,n); ++j)
        Vscanf(" ( %lf , %lf )", &AB(i,j).re, &AB(i,j).im);
}
Vscanf("%*[\n] ");
/* Compute norm of A */
anorm = 0.0;
for (j = 1; j <= n; ++j)
{
    sum = 0.0;
    for (i = MAX(j-ku,1); i <= MIN(j+kl,n); ++i)
        sum = sum + a02dbc(AB(i,j));
    anorm = MAX(anorm,sum);
}
/* Factorize A */
f07brc(order, n, n, kl, ku, ab, pdab, ipiv, &fail);
if (fail.code != NE_NOERROR)
{
    Vprintf("Error from f07brc.\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
/* Estimate condition number */
f07buc(order, Nag_OneNorm, n, kl, ku, ab, pdab, ipiv,
        anorm, &rcond, &fail);
if (fail.code != NE_NOERROR)
{
    Vprintf("Error from f07buc.\n%s\n", fail.message);
    exit_status = 1;
    goto END;
}
}

```

```

/* Print condition number */
if (rcond > X02AJC)
    Vprintf("Estimate of condition number = %10.2e\n",1.0/rcond);
else
    Vprintf("A is singular to working precision\n");
END:
if (ab) NAG_FREE(ab);
if (ipiv) NAG_FREE(ipiv);
return exit_status;
}

```

9.2 Program Data

f07buc Example Program Data

```

4 1 2                                     :Values of N, KL and KU
(-1.65, 2.26) (-2.05,-0.85) ( 0.97,-2.84)
( 0.00, 6.30) (-1.48,-1.75) (-3.99, 4.01) ( 0.59,-0.48)
              (-0.77, 2.83) (-1.06, 1.94) ( 3.33,-1.04)
              ( 4.48,-1.09) (-0.46,-1.72) :End of matrix A

```

9.3 Program Results

f07buc Example Program Results

Estimate of condition number = 1.04e+02
