

NAG C Library Function Document

nag_zspttrs (f07qsc)

1 Purpose

nag_zspttrs (f07qsc) solves a complex symmetric system of linear equations with multiple right-hand sides, $AX = B$, where A has been factorized by nag_zsptf (f07qrc), using packed storage.

2 Specification

```
void nag_zspttrs (Nag_OrderType order, Nag_UploType uplo, Integer n, Integer nrhs,
                 const Complex ap[], const Integer ipiv[], Complex b[], Integer pdb,
                 NagError *fail)
```

3 Description

To solve a complex symmetric system of linear equations $AX = B$, this function must be preceded by a call to nag_zsptf (f07qrc) which computes the Bunch–Kaufman factorization of A using packed storage.

If **uplo** = **Nag_Upper**, $A = PUDU^T P^T$, where P is a permutation matrix, U is an upper triangular matrix and D is a symmetric block diagonal matrix with 1 by 1 and 2 by 2 blocks; the solution X is computed by solving $PUDY = B$ and then $U^T P^T X = Y$.

If **uplo** = **Nag_Lower**, $A = PLDL^T P^T$, where L is a lower triangular matrix; the solution X is computed by solving $PLDY = B$ and then $L^T P^T X = Y$.

4 References

Golub G H and Van Loan C F (1996) *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

- 1: **order** – Nag_OrderType *Input*
On entry: the **order** parameter specifies the two-dimensional storage scheme being used, i.e., row-major ordering or column-major ordering. C language defined storage is specified by **order** = **Nag_RowMajor**. See Section 2.2.1.4 of the Essential Introduction for a more detailed explanation of the use of this parameter.
Constraint: **order** = **Nag_RowMajor** or **Nag_ColMajor**.
- 2: **uplo** – Nag_UploType *Input*
On entry: indicates how A has been factorized as follows:
 if **uplo** = **Nag_Upper**, $A = PUDU^T P^T$, where U is upper triangular;
 if **uplo** = **Nag_Lower**, $A = PLDL^T P^T$, where L is lower triangular.
Constraint: **uplo** = **Nag_Upper** or **Nag_Lower**.
- 3: **n** – Integer *Input*
On entry: n , the order of the matrix A .
Constraint: $n \geq 0$.

- 4: **nrhs** – Integer *Input*
On entry: r , the number of right-hand sides.
Constraint: $\mathbf{nrhs} \geq 0$.
- 5: **ap**[dim] – const Complex *Input*
Note: the dimension, dim , of the array **ap** must be at least $\max(1, \mathbf{n} \times (\mathbf{n} + 1)/2)$.
On entry: details of the factorization of A stored in packed form, as returned by nag_zsptrf (f07qrc).
- 6: **ipiv**[dim] – const Integer *Input*
Note: the dimension, dim , of the array **ipiv** must be at least $\max(1, \mathbf{n})$.
On entry: details of the interchanges and the block structure of D , as returned by nag_zsptrf (f07qrc).
- 7: **b**[dim] – Complex *Input/Output*
Note: the dimension, dim , of the array **b** must be at least $\max(1, \mathbf{pdb} \times \mathbf{nrhs})$ when **order** = **Nag_ColMajor** and at least $\max(1, \mathbf{pdb} \times \mathbf{n})$ when **order** = **Nag_RowMajor**.
If **order** = **Nag_ColMajor**, the (i, j) th element of the matrix B is stored in $\mathbf{b}[(j - 1) \times \mathbf{pdb} + i - 1]$ and if **order** = **Nag_RowMajor**, the (i, j) th element of the matrix B is stored in $\mathbf{b}[(i - 1) \times \mathbf{pdb} + j - 1]$.
On entry: the n by r right-hand side matrix B .
On exit: the n by r solution matrix X .
- 8: **pdb** – Integer *Input*
On entry: the stride separating matrix row or column elements (depending on the value of **order**) in the array **b**.
Constraints:
if **order** = **Nag_ColMajor**, $\mathbf{pdb} \geq \max(1, \mathbf{n})$;
if **order** = **Nag_RowMajor**, $\mathbf{pdb} \geq \max(1, \mathbf{nrhs})$.
- 9: **fail** – NagError * *Output*
The NAG error parameter (see the Essential Introduction).

6 Error Indicators and Warnings

NE_INT

On entry, $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{n} \geq 0$.

On entry, $\mathbf{nrhs} = \langle value \rangle$.

Constraint: $\mathbf{nrhs} \geq 0$.

On entry, $\mathbf{pdb} = \langle value \rangle$.

Constraint: $\mathbf{pdb} > 0$.

NE_INT_2

On entry, $\mathbf{pdb} = \langle value \rangle$, $\mathbf{n} = \langle value \rangle$.

Constraint: $\mathbf{pdb} \geq \max(1, \mathbf{n})$.

On entry, $\mathbf{pdb} = \langle value \rangle$, $\mathbf{nrhs} = \langle value \rangle$.

Constraint: $\mathbf{pdb} \geq \max(1, \mathbf{nrhs})$.

NE_ALLOC_FAIL

Memory allocation failed.

NE_BAD_PARAM

On entry, parameter $\langle value \rangle$ had an illegal value.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please consult NAG for assistance.

7 Accuracy

For each right-hand side vector b , the computed solution x is the exact solution of a perturbed system of equations $(A + E)x = b$, where

if **uplo** = **Nag_Upper**, $|E| \leq c(n)\epsilon P|U||D||U^T|P^T$;

if **uplo** = **Nag_Lower**, $|E| \leq c(n)\epsilon P|L||D||L^T|P^T$,

$c(n)$ is a modest linear function of n , and ϵ is the *machine precision*.

If $\hat{x}$ is the true solution, then the computed solution x satisfies a forward error bound of the form

$$\frac{\|x - \hat{x}\|_\infty}{\|x\|_\infty} \leq c(n) \text{cond}(A, x)\epsilon$$

where $\text{cond}(A, x) = \| |A^{-1}| |A| |x| \|_\infty / \|x\|_\infty \leq \text{cond}(A) = \| |A^{-1}| |A| \|_\infty \leq \kappa_\infty(A)$. Note that $\text{cond}(A, x)$ can be much smaller than $\text{cond}(A)$.

Forward and backward error bounds can be computed by calling `nag_zsprfs` (f07qvc), and an estimate for $\kappa_\infty(A)$ ($= \kappa_1(A)$) can be obtained by calling `nag_zspcon` (f07quc).

8 Further Comments

The total number of real floating-point operations is approximately $8n^2r$.

This function may be followed by a call to `nag_zsprfs` (f07qvc) to refine the solution and return an error estimate.

The real analogue of this function is `nag_dspttrs` (f07pec).

9 Example

To solve the system of equations $AX = B$, where

$$A = \begin{pmatrix} -0.39 - 0.71i & 5.14 - 0.64i & -7.86 - 2.96i & 3.80 + 0.92i \\ 5.14 - 0.64i & 8.86 + 1.81i & -3.52 + 0.58i & 5.32 - 1.59i \\ -7.86 - 2.96i & -3.52 + 0.58i & -2.83 - 0.03i & -1.54 - 2.86i \\ 3.80 + 0.92i & 5.32 - 1.59i & -1.54 - 2.86i & -0.56 + 0.12i \end{pmatrix}$$

and

$$B = \begin{pmatrix} -55.64 + 41.22i & -19.09 - 35.97i \\ -48.18 + 66.00i & -12.08 - 27.02i \\ -0.49 - 1.47i & 6.95 + 20.49i \\ -6.43 + 19.24i & -4.59 - 35.53i \end{pmatrix}.$$

Here A is symmetric, stored in packed form, and must first be factorized by `nag_zsptf` (f07qrc).

9.1 Program Text

```

/* nag_zspttrs (f07qsc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagf07.h>
#include <nagx04.h>

int main(void)
{
    /* Scalars */
    Integer ap_len, i, j, n, nrhs, pdb;
    Integer exit_status=0;
    NagError fail;
    Nag_UploType uplo_enum;
    Nag_OrderType order;
    /* Arrays */
    Integer *ipiv=0;
    char uplo[2];
    Complex *ap=0, *b=0;

#ifdef NAG_COLUMN_MAJOR
#define A_UPPER(I,J) ap[J*(J-1)/2 + I - 1]
#define A_LOWER(I,J) ap[(2*n-J)*(J-1)/2 + I - 1]
#define B(I,J) b[(J-1)*pdb + I - 1]
    order = Nag_ColMajor;
#else
#define A_LOWER(I,J) ap[I*(I-1)/2 + J - 1]
#define A_UPPER(I,J) ap[(2*n-I)*(I-1)/2 + J - 1]
#define B(I,J) b[(I-1)*pdb + J - 1]
    order = Nag_RowMajor;
#endif

    INIT_FAIL(fail);
    Vprintf("f07qsc Example Program Results\n\n");

    /* Skip heading in data file */
    Vscanf("%*[\n] ");
    Vscanf("%ld%ld%*[\n] ", &n, &nrhs);
    ap_len = n * (n + 1)/2;
#ifdef NAG_COLUMN_MAJOR
    pdb = n;
#else
    pdb = nrhs;
#endif

    /* Allocate memory */
    if ( !(ipiv = NAG_ALLOC(n, Integer)) ||
        !(ap = NAG_ALLOC(n * (n + 1)/2, Complex)) ||
        !(b = NAG_ALLOC(n * nrhs, Complex)) )
    {
        Vprintf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Read A and B from data file */
    Vscanf(" ' %1s '%*[\n] ", uplo);
    if (*(unsigned char *)uplo == 'L')
        uplo_enum = Nag_Lower;
    else if (*(unsigned char *)uplo == 'U')
        uplo_enum = Nag_Upper;
    else

```

```

    {
        Vprintf("Unrecognised character for Nag_UploType type\n");
        exit_status = -1;
        goto END;
    }
    if (uplo_enum == Nag_Upper)
    {
        for (i = 1; i <= n; ++i)
        {
            for (j = i; j <= n; ++j)
                Vscanf(" ( %lf , %lf )", &A_UPPER(i,j).re, &A_UPPER(i,j).im);
        }
        Vscanf("%*[^\\n] ");
    }
    else
    {
        for (i = 1; i <= n; ++i)
        {
            for (j = 1; j <= i; ++j)
                Vscanf(" ( %lf , %lf )", &A_LOWER(i,j).re, &A_LOWER(i,j).im);
        }
        Vscanf("%*[^\\n] ");
    }
    for (i = 1; i <= n; ++i)
    {
        for (j = 1; j <= nrhs; ++j)
            Vscanf(" ( %lf , %lf )", &B(i,j).re, &B(i,j).im);
    }
    Vscanf("%*[^\\n] ");

    /* Factorize A */
    f07qrc(order, uplo_enum, n, ap, ipiv, &fail);
    if (fail.code != NE_NOERROR)
    {
        Vprintf("Error from f07qrc.\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Compute solution */
    f07qsc(order, uplo_enum, n, nrhs, ap, ipiv, b, pdb, &fail);
    if (fail.code != NE_NOERROR)
    {
        Vprintf("Error from f07qsc.\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    /* Print solution */
    x04dbc(order, Nag_GeneralMatrix, Nag_NonUnitDiag, n, nrhs, b, pdb,
           Nag_BracketForm, "%7.4f", "Solution(s)", Nag_IntegerLabels,
           0, Nag_IntegerLabels, 0, 80, 0, 0, &fail);
    if (fail.code != NE_NOERROR)
    {
        Vprintf("Error from x04dbc.\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    END:
    if (ipiv) NAG_FREE(ipiv);
    if (ap) NAG_FREE(ap);
    if (b) NAG_FREE(b);
    return exit_status;
}

```

9.2 Program Data

f07qsc Example Program Data

```

4 2
'L'
(-0.39,-0.71)
( 5.14,-0.64) ( 8.86, 1.81)

```

:Values of N and NRHS
:Value of UPLO

```
(-7.86,-2.96) (-3.52, 0.58) (-2.83,-0.03)
( 3.80, 0.92) ( 5.32,-1.59) (-1.54,-2.86) (-0.56, 0.12) :End of matrix A
(-55.64, 41.22) (-19.09,-35.97)
(-48.18, 66.00) (-12.08,-27.02)
( -0.49, -1.47) ( 6.95, 20.49)
( -6.43, 19.24) ( -4.59,-35.53) :End of matrix B
```

9.3 Program Results

f07qsc Example Program Results

```
Solution(s)
              1              2
1  ( 1.0000,-1.0000) (-2.0000,-1.0000)
2  (-2.0000, 5.0000) ( 1.0000,-3.0000)
3  ( 3.0000,-2.0000) ( 3.0000, 2.0000)
4  (-4.0000, 3.0000) (-1.0000, 1.0000)
```
