

nag_mv_prin_coord_analysis (g03fac)

1. Purpose

nag_mv_prin_coord_analysis (g03fac) performs a principal coordinate analysis also known as classical metric scaling.

2. Specification

```
#include <nag.h>
#include <nagg03.h>

void nag_mv_prin_coord_analysis(Nag_Eigenvalues roots, Integer n,
                               double d[], Integer ndim, double x[], Integer tdx,
                               double eval[], NagError *fail)
```

3. Description

For a set of n objects, a distance matrix D can be calculated such that d_{ij} is a measure of how ‘far apart’ objects i and j are (see **nag_mv_distance_mat (g03eac)** for example). Principal coordinate analysis or metric scaling starts with a distance matrix and finds points X in Euclidean space such that those points have the same distance matrix. The aim is to find a small number of dimensions, $k \ll (n - 1)$, that provide an adequate representation of the distances.

The principal co-ordinates of the points are computed from the eigenvectors of the matrix E where $e_{ij} = -\frac{1}{2}(d_{ij}^2 - d_{i.}^2 - d_{.j}^2 + d_{..}^2)$ with $d_{i.}^2$ denoting the average of d_{ij}^2 over the suffix j etc.. The eigenvectors are then scaled by multiplying by the square root of the value of the corresponding eigenvalue.

Provided that the ordered eigenvalues, λ_i , of the matrix E are all positive, $\sum_{i=1}^k \lambda_i / \sum_{i=1}^{n-1} \lambda_i$ shows how well the data is represented in k dimensions. The eigenvalues will be non-negative if E is positive semi-definite. This will be true provided d_{ij} satisfies the inequality: $d_{ij} \leq d_{ik} + d_{jk}$ for all i, j, k . If this is not the case the size of the negative eigenvalue reflects the amount of deviation from this condition and the results should be treated cautiously in the presence of large negative eigenvalues. See Krzanowski (1990) for further discussion. **nag_mv_prin_coord_analysis** provides the option for all eigenvalues to be computed so that the smallest eigenvalues can be checked.

4. Parameters

roots

Input: indicates if all the eigenvalues are to be computed or just the **ndim** largest.

If **roots** = **Nag_AllEigVals**, all the eigenvalues are computed.

If **roots** = **Nag_LargeEigVals**, only the largest **ndim** eigenvalues are computed.

Constraint: **roots** = **Nag_AllEigVals** or **Nag_LargeEigVals**.

n

Input: the number of objects in the distance matrix, n .

Constraint: **n** > **ndim**.

d[n*(n-1)/2]

Input: the lower triangle of the distance matrix D stored packed by rows. That is, **d**[($i - 1$) * ($i - 2$)/2 + $j - 1$] must contain d_{ij} for $i = 2, 3, \dots, n$; $j = 1, 2, \dots, i - 1$.

Constraint: **d**[$i - 1$] ≥ 0.0 , $i = 1, 2, \dots, n(n - 1)/2$.

ndim

Input: the number of dimensions used to represent the data, k .

Constraint: **ndim** ≥ 1 .

x[n][tdx]

Output: the i th row contains k coordinates for the i th point, $i = 1, 2, \dots, n$.

tdx

Input: the last dimension of the array **x** as declared in the calling program.

Constraint: **tdx** \geq **ndim**.

eval[n]

Output: if **roots** = **Nag_AllEigVals**, **eval** contains the n scaled eigenvalues of the matrix E .

If **roots** = **Nag_LargeEigVals**, **eval** contains the largest k scaled eigenvalues of the matrix E .

In both cases the eigenvalues are divided by the sum of the eigenvalues (that is, the trace of E).

fail

The NAG error parameter, see the Essential Introduction to the NAG C Library.

5. Error Indications and Warnings**NE_BAD_PARAM**

On entry, parameter **roots** had an illegal value.

NE_INT_ARG_LT

On entry, **ndim** must not be less than 1: **ndim** = $\langle value \rangle$.

NE_2_INT_ARG_LE

On entry, **n** = $\langle value \rangle$ while **ndim** = $\langle value \rangle$.

These parameters must satisfy **n** $>$ **ndim**.

NE_2_INT_ARG_LT

On entry, **tdx** = $\langle value \rangle$ while **ndim** = $\langle value \rangle$.

These parameters must satisfy **tdx** \geq **ndim**.

NE_REALARR

On entry, **d**[$\langle value \rangle$] = $\langle value \rangle$.

Constraint: **d**[$i - 1$] \geq 0.0, $i = 1, 2, \dots, n * (n - 1) / 2$.

NE_NONZERO_EIGVALS

There are fewer than **ndim** eigenvalues greater than zero.

Try a smaller number of dimensions (**ndim**) or use non-metric scaling (nag_mv_ordinal_multidimscale (g03fcc)).

NE_EIGVAL

The computation of eigenvalues or eigenvectors has failed.

NE_ALLOC_FAIL

Memory allocation failed.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes.

If the call is correct then please consult NAG for assistance.

6. Further Comments**6.1. Accuracy**

Alternative, non-metric, methods of scaling are provided by nag_mv_ordinal_multidimscale (g03fcc).

The relationship between principal coordinates and principal components

(see nag_mv_ordinal_multidimscale (g03fcc)), is discussed in Krzanowski (1990) and Gower (1966).

6.2. References

Gower J C (1966) Some distance properties of latent root and vector methods used in multivariate analysis *Biometrika* **53** 325–338.

Chatfield C and Collins A J (1980) *Introduction to Multivariate Analysis* Chapman and Hall.

Krzanowski W J (1990) *Principles of Multivariate Analysis* Oxford University Press.

7. See Also

nag_mv_ordinal_multidimscale (g03fcc)

nag_mv_distance_mat (g03eac)

8. Example

The data, given by Krzanowski (1990), are dissimilarities between water vole populations in Europe. The first two principal co-ordinates are computed by nag_mv_prin_coord_analysis.

8.1. Program Text

```

/* nag_mv_prin_coord_analysis (g03fac) Example Program.
 *
 * Copyright 1998 Numerical Algorithms Group.
 *
 * Mark 5, 1998.
 *
 */

#include <nag.h>
#include <stdio.h>
#include <nag_stdlib.h>
#include <nagg01.h>
#include <nagg03.h>

#define NMAX 14
#define NNMAX NMAX*(NMAX-1)/2

#define XTMP(I) xtmp[(I)-1]
#define YTMP(I) ytmp[(I)-1]

main()
{
    double d[NNMAX], e[NMAX], x[NMAX][NMAX];

    Integer ndim;
    Integer tdx=NMAX;
    Integer i, j, n;
    Integer nn;

    char char_roots[2];

    Nag_Eigenvalues roots;

    Vprintf("g03fac Example Program Results\n\n");

    /* Skip heading in data file */
    Vscanf("%*[^\\n]");

    Vscanf("%ld",&n);
    Vscanf("%ld",&ndim);
    Vscanf("%s",char_roots);

    if (n <= NMAX)
    {
        nn = n * (n - 1) / 2;
        for (i = 0; i < nn; ++i)
            Vscanf("%lf",&d[i]);

        if (*char_roots == 'L')
            roots = Nag_LargeEigVals;
        else
            roots = Nag_AllEigVals;

        g03fac(roots, n, d, ndim, (double *)x, tdx, e, NAGERR_DEFAULT);
        Vprintf("\nScaled Eigenvalues\n\n");

        if (*char_roots == 'L')
        {
            for (i = 0; i < ndim; ++i)
                Vprintf("%10.4f",e[i]);
        }
        else
    }
}

```

```

    {
        for (i = 0; i < n; ++i)
            Vprintf("%10.4f",e[i]);
        Vprintf("\n");
    }
    Vprintf("\nCo-ordinates\n\n");
    for (i = 0; i < n; ++i)
    {
        for (j = 0; j < ndim; ++j)
            Vprintf("%10.4f",x[i][j]);
        Vprintf("\n");
    }
    exit(EXIT_SUCCESS);
}
else
{
    Vprintf("Incorrect input value of n or m.\n");
    exit(EXIT_FAILURE);
}
}

```

8.2. Program Data

g03fac Example Program Data

14 2 L

```

0.099
0.033 0.022
0.183 0.114 0.042
0.148 0.224 0.059 0.068
0.198 0.039 0.053 0.085 0.051
0.462 0.266 0.322 0.435 0.268 0.025
0.628 0.442 0.444 0.406 0.240 0.129 0.014
0.113 0.070 0.046 0.047 0.034 0.002 0.106 0.129
0.173 0.119 0.162 0.331 0.177 0.039 0.089 0.237 0.071
0.434 0.419 0.339 0.505 0.469 0.390 0.315 0.349 0.151 0.430
0.762 0.633 0.781 0.700 0.758 0.625 0.469 0.618 0.440 0.538 0.607
0.530 0.389 0.482 0.579 0.597 0.498 0.374 0.562 0.247 0.383 0.387 0.084
0.586 0.435 0.550 0.530 0.552 0.509 0.369 0.471 0.234 0.346 0.456 0.090 0.038

```

8.3. Program Results

g03fac Example Program Results

Scaled Eigenvalues

```

    0.7871    0.2808
Co-ordinates

```

```

    0.2408    0.2337
    0.1137    0.1168
    0.2394    0.0760
    0.2129    0.0605
    0.2495   -0.0693
    0.1487   -0.0778
   -0.0514   -0.1623
    0.0115   -0.3446
   -0.0039    0.0059
    0.0386   -0.0089
   -0.0421   -0.0566
   -0.5158    0.0291
   -0.3180    0.1501
   -0.3238    0.0475

```