

# NAG C Library Function Document

## nag\_rngs\_von\_mises (g05lpc)

### 1 Purpose

nag\_rngs\_von\_mises (g05lpc) generates a vector of pseudo-random numbers from a von Mises distribution with concentration parameter  $\kappa$ .

### 2 Specification

```
void nag_rngs_von_mises (double vk, Integer n, double x[], Integer igen,
    Integer iseed[], NagError *fail)
```

### 3 Description

The von Mises distribution is a symmetric distribution used in the analysis of circular data. The probability density function of this distribution on the circle with mean direction  $\mu_0 = 0$  and concentration parameter kappa,  $\kappa$ , can be written as:

$$f(\theta) = \frac{e^{\kappa \cos \theta}}{2\pi I_0(\kappa)},$$

where  $\theta$  is reduced modulo  $2\pi$  so that  $-\pi \leq \theta < \pi$  and  $\kappa \geq 0$ . For very small  $\kappa$  the distribution is almost the uniform distribution, whereas for  $\kappa \rightarrow \infty$  all the probability is concentrated at one point.

The  $n$  variates,  $\theta_1, \theta_2, \dots, \theta_n$ , are generated using an envelope rejection method with a wrapped Cauchy target distribution as proposed by Best and Fisher (1979) and described by Dagpunar (1988).

One of the initialisation functions nag\_rngs\_init\_repeatable (g05kbc) (for a repeatable sequence if computed sequentially) or nag\_rngs\_init\_nonrepeatable (g05kcc) (for a non-repeatable sequence) must be called prior to the first call to nag\_rngs\_von\_mises (g05lpc).

### 4 References

Best D J and Fisher N I (1979) Efficient simulation of the von Mises distribution *Appl. Statist.* **28** 152–157

Dagpunar J (1988) *Principles of Random Variate Generation* Oxford University Press

Mardia K V (1972) *Statistics of Directional Data* Academic Press

### 5 Parameters

- |    |  |               |
|----|--|---------------|
| 1: | <b>vk</b> – double   | <i>Input</i>  |
|    | <i>On entry:</i> the concentration parameter, $\kappa$ , of the required von Mises distribution.<br><i>Constraint:</i> <b>vk</b> > 0.0.  |               |
| 2: | <b>n</b> – Integer   | <i>Input</i>  |
|    | <i>On entry:</i> the number, $n$ , of pseudo-random numbers to be generated.<br><i>Constraint:</i> <b>n</b> ≥ 0.   |               |
| 3: | <b>x[dim]</b> – double   | <i>Output</i> |
|    | <b>Note:</b> the dimension, $dim$ , of the array <b>x</b> must be at least $\max(1, \mathbf{n})$ .<br><i>On exit:</i> the $n$ pseudo-random numbers from the specified von Mises distribution. |               |

- 4: **igen** – Integer *Input*  
*On entry:* must contain the identification number for the generator to be used to return a pseudo-random number and should remain unchanged following initialisation by a prior call to one of the functions `nag_rngs_init_repeatable` (g05kbc) or `nag_rngs_init_nonrepeatable` (g05kcc).
- 5: **iseed**[4] – Integer *Input/Output*  
*On entry:* contains values which define the current state of the selected generator.  
*On exit:* contains updated values defining the new state of the selected generator.
- 6: **fail** – NagError \* *Input/Output*  
The NAG error parameter (see the Essential Introduction).

## 6 Error Indicators and Warnings

### NE\_INT

On entry, **n** =  $\langle value \rangle$ .  
Constraint: **n**  $\geq 0$ .

### NE\_REAL

On entry, **vk** =  $\langle value \rangle$ .  
Constraint: **vk**  $> 0.0$ .

### NE\_BAD\_PARAM

On entry, parameter  $\langle value \rangle$  had an illegal value.

### NE\_INTERNAL\_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please consult NAG for assistance.

## 7 Accuracy

Not applicable.

## 8 Further Comments

For a given number of random variates the generation time increases slightly with increasing  $\kappa$ .

If **vk** is supplied too large (i.e., **vk**  $> \sqrt{\text{nag\_real\_largest\_number}(X02ALC())}$ ) then floating point overflow will occur in internal calculation.

## 9 Example

The example program prints the first five pseudo-random real numbers from a von Mises distribution with  $\kappa = 1.0$ , generated by a single call to `nag_rngs_von_mises` (g05lpc), after initialisation by `nag_rngs_init_repeatable` (g05kbc).

### 9.1 Program Text

```
/* nag_rngs_von_mises(g05lpc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */
```

```

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
    /* Scalars */
    Integer  igen, j, m;
    Integer  exit_status=0;
    NagError fail;

    /* Arrays */
    double  *x=0;
    Integer  iseed[4];

    INIT_FAIL(fail);
    Vprintf("g05lpc Example Program Results\n\n");

    m = 5;
    /* Allocate memory */
    if ( !(x = NAG_ALLOC(m, double)) )
    {
        Vprintf("Allocation failure\n");
        exit_status = -1;
        goto END;
    }

    /* Initialise the seed to a repeatable sequence */
    iseed[0] = 1762543;
    iseed[1] = 9324783;
    iseed[2] = 42344;
    iseed[3] = 742355;
    /* igen identifies the stream. */
    igen = 1;
    g05kbc(&igen, iseed);

    g05lpc(1.0, m, x, igen, iseed, &fail);
    if (fail.code != NE_NOERROR)
    {
        Vprintf("Error from g05lpc.\n%s\n", fail.message);
        exit_status = 1;
        goto END;
    }
    for (j = 0; j < m; ++j)
    {
        Vprintf("%10.4f\n", x[j]);
    }
    END:
    if (x) NAG_FREE(x);
    return exit_status;
}

```

## 9.2 Program Data

None.

## 9.3 Program Results

g05lpc Example Program Results

```

-1.1339
-2.5880
-0.6178
 0.0519
-0.9584

```