

NAG C Library Function Document

nag_rngs_hypergeometric (g05mlc)

1 Purpose

nag_rngs_hypergeometric (g05mlc) generates a vector of pseudo-random integers from the discrete hypergeometric distribution of the number of specified items in a sample of size l , taken from a population of size n with m specified items in it.

2 Specification

```
#include <nag.h>
#include <nagg05.h>
```

```
void nag_rngs_hypergeometric (Integer mode, Integer ns, Integer np, Integer m,
    Integer n, Integer x[], Integer igen, Integer iseed[], double r[],
    NagError *fail)
```

3 Description

nag_rngs_hypergeometric (g05mlc) generates n integers x_i from a discrete hypergeometric distribution, where the probability of $x_i = I$ is

$$P(i = I) = \frac{l!m!(n-l)!(n-m)!}{l!(l-I)!(m-I)!(n-m-l+I)!n!} \quad \text{if } I = \max(0, m+l-n), \dots, \min(l, m),$$

$$P(i = I) = 0 \quad \text{otherwise.}$$

The variates can be generated with or without using a search table and index. If a search table is used then it is stored with the index in a reference vector and subsequent calls to nag_rngs_hypergeometric (g05mlc) with the same argument values can then use this reference vector to generate further variates. The reference array is generated by a recurrence relation if $lm(n-l)(n-m) < 50n^3$, otherwise Stirling's approximation is used.

One of the initialization functions nag_rngs_init_repeatable (g05kbc) (for a repeatable sequence if computed sequentially) or nag_rngs_init_nonrepeatable (g05kcc) (for a non-repeatable sequence) must be called prior to the first call to nag_rngs_hypergeometric (g05mlc).

4 References

Knuth D E (1981) *The Art of Computer Programming (Volume 2)* (2nd Edition) Addison–Wesley

5 Arguments

1: **mode** – Integer

Input

On entry: a code for selecting the operation to be performed by the function:

mode = 0

Set up reference vector only.

mode = 1

Generate variates using reference vector set up in a prior call to nag_rngs_hypergeometric (g05mlc).

mode = 2

Set up reference vector and generate variates.

- mode** = 3
Generate variates without using the reference vector.
Constraint: $0 \leq \mathbf{mode} \leq 3$.
- 2: **ns** – Integer *Input*
On entry: l , the sample size of the hypergeometric distribution.
Constraint: $0 \leq \mathbf{ns} \leq \mathbf{np}$.
- 3: **np** – Integer *Input*
On entry: n , the population size of the hypergeometric distribution.
Constraint: $\mathbf{np} \geq 0$.
- 4: **m** – Integer *Input*
On entry: m , the number of specified items of the hypergeometric distribution.
Constraint: $0 \leq \mathbf{m} \leq \mathbf{np}$.
- 5: **n** – Integer *Input*
On entry: the number of pseudo-random numbers to be generated.
Constraint: $\mathbf{n} \geq 1$.
- 6: **x[n]** – Integer *Output*
On exit: the n pseudo-random numbers from the specified hypergeometric distribution.
- 7: **igen** – Integer *Input*
On entry: must contain the identification number for the generator to be used to return a pseudo-random number and should remain unchanged following initialization by a prior call to one of the functions nag_rngs_init_repeatable (g05kbc) or nag_rngs_init_nonrepeatable (g05kcc).
- 8: **iseed[4]** – Integer *Input/Output*
On entry: contains values which define the current state of the selected generator.
On exit: contains updated values defining the new state of the selected generator.
- 9: **r[dim]** – double *Output*
Note: the dimension, dim , of the array **r** must be at least $20 + 20 \times \sqrt{(\mathbf{ns} \times \mathbf{m} \times (\mathbf{np} - \mathbf{m}) \times (\mathbf{np} - \mathbf{ns}))/\mathbf{np}^3}$.
On exit: the reference vector.
- 10: **fail** – NagError * *Input/Output*
The NAG error argument (see Section 2.6 of the Essential Introduction).

6 Error Indicators and Warnings

NE_BAD_PARAM

On entry, argument $\langle value \rangle$ had an illegal value.

NE_INT

On entry, **mode** = $\langle value \rangle$.
Constraint: $0 \leq \mathbf{mode} \leq 3$.

On entry, **n** = $\langle value \rangle$.

Constraint: **n** ≥ 1 .

On entry, **np** = $\langle value \rangle$.

Constraint: **np** ≥ 0 .

NE_INT_2

On entry, **m** $> np$ or **m** < 0 : **m** = $\langle value \rangle$, **np** = $\langle value \rangle$.

On entry, **ns** $> np$ or **ns** < 0 : **ns** = $\langle value \rangle$, **np** = $\langle value \rangle$.

NE_INTERNAL_ERROR

An internal error has occurred in this function. Check the function call and any array sizes. If the call is correct then please consult NAG for assistance.

NE_PREV_CALL

ns or **np** or **m** is not the same as when **r** was set up in a previous call or the data in **r** has been corrupted.

7 Accuracy

Not applicable.

8 Further Comments

None.

9 Example

The example program prints 20 pseudo-random integers from a hypergeometric distribution with $l = 500$, $m = 900$ and $n = 1000$, generated by a single call to `nag_rngs_hypergeometric (g05mlc)`, after initialization by `nag_rngs_init_repeatable (g05kbc)`.

9.1 Program Text

```

/* nag_rngs_hypergeometric (g05mlc) Example Program.
 *
 * Copyright 2001 Numerical Algorithms Group.
 *
 * Mark 7, 2001.
 */

#include <stdio.h>
#include <nag.h>
#include <nag_stdlib.h>
#include <nagg05.h>

int main(void)
{
    /* Scalars */
    Integer i, igen, m, np, ns, n, nr;
    Integer exit_status=0;
    NagError fail;

    /* Arrays */
    double *r=0;
    Integer *x=0;
    Integer iseed[4];

    INIT_FAIL(fail);
    Vprintf("nag_rngs_hypergeometric (g05mlc) Example Program Results\n\n");
    n = 20;

```

```

nr = 2200;

/* Allocate memory */
if ( !(r = NAG_ALLOC(nr, double)) ||
     !(x = NAG_ALLOC(n, Integer)) )
{
    Vprintf("Allocation failure\n");
    exit_status = -1;
    goto END;
}

/* Set the distribution parameters NS, NP, M */
ns = 500;
m = 900;
np = 1000;
/* Initialise the seed to a repeatable sequence */
iseed[0] = 1762543;
iseed[1] = 9324783;
iseed[2] = 42344;
iseed[3] = 742355;
/* igen identifies the stream. */
igen = 1;
/* nag_rngs_init_repeatable (g05kbc).
 * Initialize seeds of a given generator for random number
 * generating functions (that pass seeds explicitly) to give
 * a repeatable sequence
 */
nag_rngs_init_repeatable(&igen, iseed);

/* Choose MODE = 2 */
/* nag_rngs_hypergeometric (g05mlc).
 * Generates a vector of random integers from a
 * hypergeometric distribution, seeds and generator number
 * passed explicitly
 */
nag_rngs_hypergeometric(2, ns, np, m, n, x, igen, iseed, r, &fail);
if (fail.code != NE_NOERROR)
{
    Vprintf("Error from nag_rngs_hypergeometric (g05mlc).\n%s\n",
           fail.message);
    exit_status = 1;
    goto END;
}
for (i = 0; i < n; ++i)
{
    Vprintf("%12ld\n", x[i]);
}
END:
if (r) NAG_FREE(r);
if (x) NAG_FREE(x);
return exit_status;
}

```

9.2 Program Data

None.

9.3 Program Results

nag_rngs_hypergeometric (g05mlc) Example Program Results

```

444
458
449
453
458
449
451
449
448

```

456
450
449
451
462
442
448
455
448
441
452
