

NAG C Library

Advice on Replacement Calls for Withdrawn/Superseded Functions

The following list gives the names of replacement functions for those functions that have been withdrawn or superseded. The list indicates the minimum change necessary, but many of the replacement functions for those functions have additional flexibility and users may wish to take advantage of new features. It is strongly recommended that users consult the function documents.

Files containing the replacement call information are provided as part of the distribution materials and can be found in the directory `examples/replaced`.

a02 – Complex Arithmetic

nag_complex_sqrt (a02aac)

Withdrawn at Mark 2.

No replacement document required.

nag_complex_sqrt (a02abc)

Withdrawn at Mark 2.

No replacement document required.

nag_complex_divide (a02acc)

Withdrawn at Mark 2.

No replacement document required.

e01 – Interpolation

nag_2d_scatter_interpolant (e01sac)

Scheduled for withdrawal at Mark 10.

Replaced by `nag_2d_shep_interp (e01sgc)` or `nag_2d_triang_interp (e01sjc)`.

`nag_2d_scatter_interpolant (e01sac)` generates a two-dimensional surface interpolating a set of scattered data points, using either the method of Renka and Cline or a modification of Shepard's method. The replacement functions separate these two methods. `e01sac_rk.c` provides replacement call information for the Renka and Cline method (`nag_2d_shep_interp (e01sgc)`) and `e01sac_shep.c` provides replacement call information for the Shepard's method (`nag_2d_triang_interp (e01sjc)`).

nag_2d_scatter_eval (e01sbc)

Scheduled for withdrawal at Mark 10.

Replaced by `nag_2d_shep_eval (e01shc)` or `nag_2d_triang_eval (e01skc)`.

See the example program `e01sac_rk.c` and `e01sac_shep.c` for full details.

nag_2d_scatter_free (e01szc)

Scheduled for withdrawal at Mark 10.

No replacement document required.

e04 – Minimizing or Maximizing a Function

nag_opt_bounds_no_deriv (e04jbc)

Scheduled for withdrawal at Mark 10.

Replaced by `nag_opt_nlp_solve (e04wdc)`.

See the example program `e04jbce.c` for full details.

nag_opt_bounds_deriv (e04kbc)

Scheduled for withdrawal at Mark 10.

Replaced by nag_opt_nlp_solve (e04wdc).

See the example program e04kbce.c for full details.

nag_opt_sparse_convex_qp (e04nkc)

Scheduled for withdrawal at Mark 10.

Replaced by nag_opt_sparse_convex_qp_solve (e04nqc).

See the example program e04nkce.c for full details.

nag_opt_nlp (e04ucc)

Scheduled for withdrawal at Mark 10.

Replaced by nag_opt_nlp_solve (e04wdc).

See the example program e04ucce.c for full details.

x02 – Machine Constants**nag_active_set_size (X02CAC)**

Withdrawn at Mark 2.

No replacement document required.
