NAG Fortran Library Routine Document G10ACF

Note: before using this routine, please read the Users' Note for your implementation to check the interpretation of **bold italicised** terms and other implementation-dependent details.

1 Purpose

G10ACF estimates the values of the smoothing parameter and fits a cubic smoothing spline to a set of data.

2 Specification

```
SUBROUTINE G10ACF(METHOD, WEIGHT, N, X, Y, WT, YHAT, C, LDC, RSS, DF, RES, H, CRIT, RHO, U, TOL, MAXCAL, WK, IFAIL)

INTEGER

real

X(N), Y(N), WT(*), YHAT(N), C(LDC,3), RSS, DF, RES(N), H(N), CRIT, RHO, U, TOL, WK(7*(N+2))

CHARACTER*1

METHOD, WEIGHT
```

3 Description

For a set of n observations (x_i, y_i) , i = 1, 2, ..., n, the spline provides a flexible smooth function for situations in which a simple polynomial or non-linear regression model is not suitable.

Cubic smoothing splines arise as the unique real-valued solution function f, with absolutely continuous first derivative and squared-integrable second derivative, which minimises

$$\sum_{i=1}^{n} w_i (y_i - f(x_i))^2 + \rho \int_{-\infty}^{\infty} (f''(x))^2 dx,$$

where w_i is the (optional) weight for the *i*th observation and ρ is the smoothing parameter. This criterion consists of two parts: the first measures the fit of the curve and the second the smoothness of the curve. The value of the smoothing parameter ρ weights these two aspects; larger values of ρ give a smoother fitted curve but, in general, a poorer fit. For details of how the cubic spline can be fitted see Hutchinson and de Hoog (1985) and Reinsch (1967).

The fitted values, $\hat{y} = (\hat{y}_1, \hat{y}_2, \dots, \hat{y}_n)^T$, and weighted residuals, r_i , can be written as:

$$\hat{y} = Hy$$
 and $r_i = \sqrt{w_i}(y_i - \hat{y}_i)$

for a matrix H. The residual degrees of freedom for the spline is trace(I - H) and the diagonal elements of H are the leverages.

The parameter ρ can be estimated in a number of ways.

- (i) The degrees of freedom for the spline can be specified, i.e., find ρ such that trace $(H) = \nu_0$ for given ν_0 .
- (ii) Minimise the cross-validation (CV), i.e., find ρ such that the CV is minimised, where

$$CV = \frac{1}{\sum_{i=1}^{n} w_i} \sum_{i=1}^{n} \left[\frac{r_i}{1 - h_{ii}} \right]^2.$$

[NP3546/20A] G10ACF.1

(iii) Minimise the generalised cross-validation (GCV), i.e., find ρ such that the GCV is minimised, where

$$GCV = \frac{n^2}{\sum_{i=1}^{n} w_i} \left[\frac{\sum_{i=1}^{n} r_i^2}{\left(\sum_{i=1}^{n} (1 - h_{ii})\right)^2} \right].$$

G10ACF requires the x_i to be strictly increasing. If two or more observations have the same x_i value then they should be replaced by a single observation with y_i equal to the (weighted) mean of the y values and weight, w_i , equal to the sum of the weights. This operation can be performed by G10ZAF.

The algorithm is based on Hutchinson (1986). C05AZF is used to solve for ρ given ν_0 and the method of E04ABF is used to minimise the GCV or CV.

4 References

Hastie T J and Tibshirani R J (1990) Generalized Additive Models Chapman and Hall

Hutchinson M F (1986) Algorithm 642: A fast procedure for calculating minimum cross-validation cubic smoothing splines *ACM Trans. Math. Software* **12** 150–153

Hutchinson M F and de Hoog F R (1985) Smoothing noisy data with spline functions *Numer. Math.* 47 99–106

Reinsch C H (1967) Smoothing by spline functions Numer. Math. 10 177-183

5 Parameters

1: METHOD – CHARACTER*1

Input

On entry: indicates whether the smoothing parameter is to be found by minimization of the CV or GCV functions, or by finding the smoothing parameter corresponding to a specified degrees of freedom value.

If METHOD = 'C', cross-validation is used.

If METHOD = 'D', the degrees of freedom are specified.

If METHOD = 'G', generalized cross-validation is used.

Constraint: METHOD = 'C', 'D' or 'G'.

2: WEIGHT – CHARACTER*1

Input

On entry: indicates whether user-defined weights are to be used.

If WEIGHT = 'W', user-defined weights should be supplied in WT.

If WEIGHT = 'U', the data is treated as unweighted.

Constraint: WEIGHT = 'W' or 'U'.

3: N – INTEGER

Input

On entry: the number of observations, n.

Constraint: $N \geq 3$.

4: X(N) - real array

Input

On entry: the distinct and ordered values x_i , for i = 1, 2, ..., n.

Constraint: X(i) < X(i + 1), for i = 1, 2, ..., n - 1.

G10ACF.2 [NP3546/20A]

G10ACF

5: Y(N) - real array

Input

On entry: the values y_i , for i = 1, 2, ..., n.

6: WT(*) - real array

Input

Note: the dimension of the array WT must be at least 1 if WEIGHT = 'U' and N if WEIGHT = 'W'.

On entry: if WEIGHT = 'W' then WT must contain the n weights. If WEIGHT = 'U' then WT is not referenced and unit weights are assumed.

Constraint: if WEIGHT = 'W' then WT(i) > 0.0 for i = 1, 2, ..., n.

7: YHAT(N) - real array

Output

On exit: the fitted values, \hat{y}_i , for i = 1, 2, ..., n.

8: C(LDC,3) - real array

Output

On exit: the spline coefficients. More precisely, the value of the spline approximation at t is given by $((C(i,3) \times d + C(i,2)) \times d + C(i,1)) \times d + \hat{y}_i$, where $x_i \le t < x_{i+1}$ and $d = t - x_i$.

9: LDC – INTEGER

Input

On entry: the first dimension of the array C as declared in the (sub)program from which G10ACF is called.

Constraint: LDC $\geq N - 1$.

10: RSS - *real*

Output

On exit: the (weighted) residual sum of squares.

11: DF – *real*

Output

On exit: the residual degrees of freedom. If METHOD = 'D' this will be n - CRIT to the required accuracy.

12: RES(N) - real array

Output

On exit: the (weighted) residuals, r_i , for i = 1, 2, ..., n.

13: H(N) - real array

Output

On exit: the leverages, h_{ii} , for i = 1, 2, ..., n.

14: CRIT – *real*

Input/Output

On entry: if METHOD = 'D', the required degrees of freedom for the spline. If METHOD = 'C' or 'G', CRIT need not be set.

Constraint: $2.0 < CRIT \le N$.

On exit: if METHOD = 'C', the value of the cross-validation, or if METHOD = 'G', the value of the generalized cross-validation function, evaluated at the value of ρ returned in RHO.

15: RHO – *real*

Output

On exit: the smoothing parameter, ρ .

16: U – *real*

Input

On entry: the upper bound on the smoothing parameter. See Section 8 for details on how this parameter is used.

Constraint: U > TOL.

[NP3546/20A]

G10ACF.3

Suggested value: U = 1000.0.

17: TOL – real Input

On entry: the accuracy to which the smoothing parameter RHO is required. TOL should be preferably not much less than $\sqrt{\epsilon}$, where ϵ is the **machine precision**.

Constraint: $TOL \ge machine precision$.

18: MAXCAL – INTEGER

Input

On entry: the maximum number of spline evaluations to be used in finding the value of ρ .

Constraint: $MAXCAL \geq 3$.

Suggested value: MAXCAL = 30.

19: WK(7*(N+2)) - real array

Workspace

20: IFAIL - INTEGER

Input/Output

On entry: IFAIL must be set to 0, -1 or 1. Users who are unfamiliar with this parameter should refer to Chapter P01 for details.

On exit: IFAIL = 0 unless the routine detects an error (see Section 6).

For environments where it might be inappropriate to halt program execution when an error is detected, the value -1 or 1 is recommended. If the output of error messages is undesirable, then the value 1 is recommended. Otherwise, for users not familiar with this parameter the recommended value is 0. When the value -1 or 1 is used it is essential to test the value of IFAIL on exit.

6 Error Indicators and Warnings

If on entry IFAIL = 0 or -1, explanatory error messages are output on the current error message unit (as defined by X04AAF).

Errors or warnings detected by the routine:

```
IFAIL = 1
```

```
On entry, N < 3,
         LDC < N - 1,
or
         METHOD is not 'C', 'G' or 'D',
or
         WEIGHT is not 'W' or 'U',
or
         METHOD = 'D' and CRIT < 2.0,
or
         METHOD = 'D' and CRIT > N,
or
         TOL < machine precision,
or
         U < TOL
or
         MAXCAL < 3.
or
```

IFAIL = 2

On entry, WEIGHT = 'W' and at least one element of WT $\leq 0.0.$

IFAIL = 3

On entry, $X(i) \ge X(i+1)$, for some i, i = 1, 2, ..., n-1.

IFAIL = 4

METHOD = 'D' and the required value of ρ for specified degrees of freedom > U. Try a larger value of U; see Section 8.

G10ACF.4 [NP3546/20A]

IFAIL = 5

METHOD = 'D' and the accuracy given by TOL cannot be achieved. Try increasing the value of TOL

IFAIL = 6

A solution to the accuracy given by TOL has not been achieved in MAXCAL iterations. Try increasing the value of TOL and/or MAXCAL.

IFAIL = 7

METHOD = 'C' or 'G' and the optimal value of $\rho > U$. Try a larger value of U, see Section 8.

7 Accuracy

When minimising the cross-validation or generalised cross-validation, the error in the estimate of ρ should be within $\pm 3(\text{TOL} \times \text{RHO} + \text{TOL})$. When finding ρ for a fixed number of degrees of freedom the error in the estimate of ρ should be within $\pm 2 \times \text{TOL} \times \text{max}(1, \text{RHO})$.

Given the value of ρ , the accuracy of the fitted spline depends on the value of ρ and the position of the x-values. The values of $x_i - x_{i-1}$ and w_i are scaled and ρ is transformed to avoid underflow and overflow problems.

8 Further Comments

The time to fit the spline for a given value of ρ is of order n.

When finding the value of ρ that gives the required degrees of freedom, the algorithm examines the interval 0.0 to U. For small degrees of freedom the value of ρ can be large, as in the theoretical case of two degrees of freedom when the spline reduces to a straight line and ρ is infinite. If the CV or GCV is to be minimised then the algorithm searches for the minimum value in the interval 0.0 to U. If the function is decreasing in that range then the boundary value of U will be returned. In either case, the larger the value of U the more likely is the interval to contain the required solution, but the process will be less efficient.

Regression splines with a small (< n) number of knots can be fitted by E02BAF and E02BEF.

9 Example

The data, given by Hastie and Tibshirani (1990), is the age, x_i , and C-peptide concentration (pmol/ml), y_i , from a study of the factors affecting insulin-dependent diabetes mellitus in children. The data is input, reduced to a strictly ordered set by G10ZAF and a spline with 5 degrees of freedom is fitted by G10ACF. The fitted values and residuals are printed.

9.1 Program Text

Note: the listing of the example program presented below uses **bold italicised** terms to denote precision-dependent details. Please read the Users' Note for your implementation to check the interpretation of these terms. As explained in the Essential Introduction to this manual, the results produced may not be identical for all implementations.

```
G10ACF Example Program Text
Mark 20 Revised. NAG Copyright 2001.
.. Parameters ..
INTEGER
                   NIN, NOUT
PARAMETER
                   (NIN=5, NOUT=6)
INTEGER
                   NMAX, LDC
PARAMETER
                   (NMAX=50,LDC=49)
.. Local Scalars ..
real
                  CRIT, DF, RHO, RSS, TOL, U
INTEGER
                   I, IFAIL, MAXCAL, N, NORD
CHARACTER
                  METHOD, WEIGHT
.. Local Arrays ..
real
                   C(LDC,3), H(NMAX), RES(NMAX), WK(7*(NMAX+2)),
                   WT(NMAX), WWT(NMAX), X(NMAX), XORD(NMAX), Y(NMAX), YHAT(NMAX), YORD(NMAX)
```

[NP3546/20A] G10ACF.5

```
INTEGER
                       IWRK(NMAX)
      .. External Subroutines ..
      EXTERNAL
                  G10ACF, G10ZAF
      .. Executable Statements ..
      WRITE (NOUT,*) 'G10ACF Example Program Results'
      Skip heading in data file
      READ (NIN,*)
      READ (NIN,*) N
      IF (N.LE.NMAX) THEN
         READ (NIN, *) METHOD, WEIGHT
         IF (WEIGHT.EQ.'U' .OR. WEIGHT.EQ.'u') THEN
            READ (NIN, *) (X(I), Y(I), I=1, N)
         ELSE
           READ (NIN,*) (X(I),Y(I),WT(I),I=1,N)
         END IF
         READ (NIN,*) U, TOL, MAXCAL, CRIT
         IFAIL = 0
         Sort data, removing ties and weighting accordingly
         CALL G10ZAF(WEIGHT, N, X, Y, WT, NORD, XORD, YORD, WWT, RSS, IWRK, IFAIL)
         Fit cubic spline
         TFATL = 0
         CALL G10ACF(METHOD, 'W', NORD, XORD, YORD, WWT, YHAT, C, LDC, RSS, DF,
                     RES, H, CRIT, RHO, U, TOL, MAXCAL, WK, IFAIL)
         Print results
         WRITE (NOUT, *)
         WRITE (NOUT, 99999) RSS
         WRITE (NOUT, 99998) DF
         WRITE (NOUT, 99997) RHO
         WRITE (NOUT, 99996)
         DO 20 I = 1, NORD
            WRITE (NOUT, 99995) I, XORD(I), YORD(I), YHAT(I), H(I)
   20
        CONTINUE
      END IF
      STOP
99999 FORMAT (' Residual sum of squares = ',F10.2)
99998 FORMAT (' Degrees of freedom = ',F10.2)
99997 FORMAT (' RHO = ',F10.2)
Input data',16X,'Output results',/' I X
99995 FORMAT (I4,2F8.3,6X,2F8.3)
      END
```

9.2 Program Data

```
G10ACF Example Program Data
43
'D', 'U'
5.2 4.8
           8.8 4.1 10.5 5.2 10.6 5.5 10.4 5.0
                                       1.9 3.7
0.9 3.0
1.8 3.4
          12.7 3.4
                    15.6 4.9
                              5.8 5.6
2.2 3.9
                    7.9 4.8
           4.8 4.5
                              5.2 4.9
11.8 4.6
          7.9 4.8 11.5 5.5 10.6 4.5
          12.8 6.6 11.3 5.1
                              1.0 3.9 14.5 5.7
11.1 4.7
                            15.5 4.9
11.9 5.1
           8.1 5.2
                    13.8 3.7
                                        9.8 4.8
11.0 4.4
          12.4 5.2
                    11.1 5.1
                              5.1 4.6
                                        4.8 3.9
4.2 5.1
          6.9 5.1 13.2 6.0
                             9.9 4.9 12.5 4.1
13.2 4.6
          8.9 4.9 10.8 5.1
10000 0.001 40 12.0
```

G10ACF.6 [NP3546/20A]

9.3 Program Results

G10ACF Example Program Results

Residual sum of squares = 10.35 Degrees of freedom = 25.00 RHO = 2.68

	Input dat		Output	
Ι	X	Y	YHAT	Н
1	0.900	3.000	3.373	0.534
2	1.000	3.900	3.406	0.427
3	1.800	3.400	3.642	0.313
4	1.900	3.700	3.686	0.313
5	2.200	3.900	3.839	0.448
6	4.200	5.100	4.614	0.564
7	4.800	4.200	4.576	0.442
8	5.100	4.600	4.715	0.189
9	5.200	4.850	4.783	0.407
10	5.800	5.600	5.193	0.455
11	6.900	5.100	5.184	0.592
12	7.900	4.800	4.958	0.530
13	8.100	5.200	4.931	0.235
14	8.500	5.300	4.845	0.245
15	8.800	4.100	4.763	0.271
16	8.900	4.900	4.748	0.292
17	9.800	4.800	4.850	0.301
18	9.900	4.900	4.875	0.277
19	10.400	5.000	4.970	0.173
20	10.500	5.200	4.977	0.154
21	10.600	5.000	4.979	0.285
22	10.800	5.100	4.970	0.136
23	11.000	4.400	4.961	0.137
24	11.100	4.900	4.964	0.284
25	11.300	5.100	4.975	0.162
26	11.500	5.500	4.975	0.186
27	11.800	4.600	4.930	0.213
28	11.900	5.100	4.911	0.220
29	12.400	5.200	4.852	0.206
30	12.500	4.100	4.857	0.196
31	12.700	3.400	4.900	0.189
32	12.800	6.600	4.932	0.193
33	13.200	5.300	4.955	0.488
34	13.800	3.700	4.797	0.408
35	14.500	5.700	5.076	0.559
36	15.500	4.900	4.979	0.445
37	15.600	4.900	4.946	0.535

[NP3546/20A] G10ACF.7 (last)