

NAG Toolbox for MATLAB

c06hb

1 Purpose

c06hb computes the discrete Fourier cosine transforms of m sequences of real data values. This function is designed to be particularly efficient on vector processors.

2 Syntax

```
[x, trig, ifail] = c06hb(m, n, x, init, trig)
```

3 Description

Given m sequences of $n + 1$ real data values x_j^p , for $j = 0, 1, \dots, n$; $p = 1, 2, \dots, m$, c06hb simultaneously calculates the Fourier cosine transforms of all the sequences defined by

$$\hat{x}_k^p = \sqrt{\frac{2}{n}} \left\{ \frac{1}{2} x_0^p + \sum_{j=1}^{n-1} x_j^p \times \cos\left(jk\frac{\pi}{n}\right) + \frac{1}{2} x_n^p \right\}, \quad k = 0, 1, \dots, n; \quad p = 1, 2, \dots, m.$$

(Note the scale factor $\sqrt{\frac{2}{n}}$ in this definition.)

The Fourier cosine transform is its own inverse and two calls of this function with the same data will restore the original data.

The transform calculated by this function can be used to solve Poisson's equation when the derivative of the solution is specified at both left and right boundaries (see Swarztrauber 1977). (See the C06 Chapter Introduction.)

The function uses a variant of the fast Fourier transform (FFT) algorithm (see Brigham 1974) known as the Stockham self-sorting algorithm, described in Temperton 1983a, together with pre- and post-processing stages described in Swarztrauber 1982. Special coding is provided for the factors 2, 3, 4, 5 and 6. This function is designed to be particularly efficient on vector processors, and it becomes especially fast as m , the number of transforms to be computed in parallel, increases.

4 References

Brigham E O 1974 *The Fast Fourier Transform* Prentice-Hall

Swarztrauber P N 1977 The methods of cyclic reduction, Fourier analysis and the FACR algorithm for the discrete solution of Poisson's equation on a rectangle *SIAM Rev.* **19** (3) 490–501

Swarztrauber P N 1982 Vectorizing the FFT's *Parallel Computation* (ed G Rodrigue) 51–83 Academic Press

Temperton C 1983a Fast mixed-radix real Fourier transforms *J. Comput. Phys.* **52** 340–350

5 Parameters

5.1 Compulsory Input Parameters

1: **m** – int32 scalar

m , the number of sequences to be transformed.

Constraint: $m \geq 1$.

2: **n – int32 scalar**

One less than the number of real values in each sequence, i.e., the number of values in each sequence is $n + 1$.

Constraint: $n \geq 1$.

3: **x(m × (n + 1)) – double array**

The data must be stored in **x** as if in a two-dimensional array of dimension $(1 : m, 0 : n)$; each of the m sequences is stored in a **row** of the array. In other words, if the $(n + 1)$ data values of the p th sequence to be transformed are denoted by x_j^p , for $j = 0, 1, \dots, n$ and $p = 1, 2, \dots, m$, then the $m(n + 1)$ elements of the array **x** must contain the values

$$x_0^1, x_0^2, \dots, x_0^m, x_1^1, x_1^2, \dots, x_1^m, \dots, x_n^1, x_n^2, \dots, x_n^m.$$

4: **init – string**

If the trigonometric coefficients required to compute the transforms are to be calculated by the function and stored in the array **trig**, then **init** must be set equal to 'I' (Initial call).

If **init** = 'S' (Subsequent call), then the function assumes that trigonometric coefficients for the specified value of n are supplied in the array **trig**, having been calculated in a previous call to one of c06ha, c06hb, c06hc or c06hd.

If **init** = 'R' (Restart), the function assumes that trigonometric coefficients for the specified value of n are supplied in the array **trig**, but does not check that c06ha, c06hb, c06hc or c06hd have previously been called. This option allows the **trig** array to be stored in an external file, read in and re-used without the need for a call with **init** equal to 'I'. The function carries out a simple test to check that the current value of n is consistent with the value used to generate the array **trig**.

Constraint: **init** = 'I', 'S' or 'R'.

5: **trig(2 × n) – double array**

If **init** = 'S' or 'R', **trig** must contain the required coefficients calculated in a previous call of the function. Otherwise **trig** need not be set.

5.2 Optional Input Parameters

None.

5.3 Input Parameters Omitted from the MATLAB Interface

work

5.4 Output Parameters1: **x(m × (n + 1)) – double array**

The m Fourier cosine transforms stored as if in a two-dimensional array of dimension $(1 : m, 0 : n)$. Each of the m transforms is stored in a **row** of the array, overwriting the corresponding original data. If the $(n + 1)$ components of the p th Fourier cosine transform are denoted by $\hat{x}_k^p$, for $k = 0, 1, \dots, n$ and $p = 1, 2, \dots, m$, then the $m(n + 1)$ elements of the array **x** contain the values

$$\hat{x}_0^1, \hat{x}_0^2, \dots, \hat{x}_0^m, \hat{x}_1^1, \hat{x}_1^2, \dots, \hat{x}_1^m, \dots, \hat{x}_n^1, \hat{x}_n^2, \dots, \hat{x}_n^m.$$

2: **trig(2 × n) – double array**

Contains the required coefficients (computed by the function if **init** = 'I').

3: **ifail – int32 scalar**

0 unless the function detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the function:

ifail = 1

On entry, **m** < 1.

ifail = 2

On entry, **n** < 1.

ifail = 3

On entry, **init** $\neq$ 'T', 'S' or 'R'.

ifail = 4

Not used at this Mark.

ifail = 5

On entry, **init** = 'S' or 'R', but the array **trig** and the current value of **n** are inconsistent.

ifail = 6

An unexpected error has occurred in an internal call. Check all (sub)program calls and array dimensions. Seek expert help.

7 Accuracy

Some indication of accuracy can be obtained by performing a subsequent inverse transform and comparing the results with the original sequence (in exact arithmetic they would be identical).

8 Further Comments

The time taken by c06hb is approximately proportional to $nm \log n$, but also depends on the factors of n . c06hb is fastest if the only prime factors of n are 2, 3 and 5, and is particularly slow if n is a large prime, or has large prime factors.

9 Example

```
m = int32(3);
n = int32(6);
x = [0.3854;
     0.5417;
     0.9172;
     0.6772;
     0.2983;
     0.0644;
     0.1138;
     0.1181;
     0.6037;
     0.6751;
     0.7255;
     0.643;
     0.6362;
     0.8638;
     0.0428;
     0.1424;
     0.8723;
     0.4815;
     0.9562;
```

```
        0.4936;  
        0.2057];  
init = 'Initial';  
trig = zeros(12,1);  
[xOut, trigOut, ifail] = c06hb(m, n, x, init, trig)
```

```
xOut =  
    1.6833  
    1.9605  
    1.3838  
   -0.0482  
   -0.4884  
    0.1588  
    0.0176  
   -0.0655  
   -0.0761  
    0.1368  
    0.4444  
   -0.1184  
    0.3240  
    0.0964  
    0.3512  
   -0.5830  
    0.0856  
    0.5759  
   -0.0427  
   -0.2289  
    0.0110
```

```
trigOut =  
    1  
    1  
    1  
    1  
    1  
    6  
    0  
    0  
    0  
    0  
    0  
    6
```

```
ifail =  
      0
```