

NAG Toolbox for MATLAB

f08gb

1 Purpose

f08gb computes selected eigenvalues and, optionally, eigenvectors of a real n by n symmetric matrix A in packed storage. Eigenvalues and eigenvectors can be selected by specifying either a range of values or a range of indices for the desired eigenvalues.

2 Syntax

```
[ap, m, w, z, jfail, info] = f08gb(jobz, range, uplo, n, ap, vl, vu, il,
iu, abstol)
```

3 Description

The symmetric matrix A is first reduced to tridiagonal form, using orthogonal similarity transformations. The required eigenvalues and eigenvectors are then computed from the tridiagonal matrix; the method used depends upon whether all, or selected, eigenvalues and eigenvectors are required.

4 References

Anderson E, Bai Z, Bischof C, Blackford S, Demmel J, Dongarra J J, Du Croz J J, Greenbaum A, Hammarling S, McKenney A and Sorensen D 1999 *LAPACK Users' Guide* (3rd Edition) SIAM, Philadelphia URL: <http://www.netlib.org/lapack/lug>

Demmel J W and Kahan W 1990 Accurate singular values of bidiagonal matrices *SIAM J. Sci. Statist. Comput.* **11** 873–912

Golub G H and Van Loan C F 1996 *Matrix Computations* (3rd Edition) Johns Hopkins University Press, Baltimore

5 Parameters

5.1 Compulsory Input Parameters

1: **jobz** – string

If **jobz** = 'N', compute eigenvalues only.

If **jobz** = 'V', compute eigenvalues and eigenvectors.

Constraint: **jobz** = 'N' or 'V'.

2: **range** – string

If **range** = 'A', all eigenvalues will be found.

If **range** = 'V', all eigenvalues in the half-open interval $(vl, vu]$ will be found.

If **range** = 'I', the **ilth** to **iuth** eigenvalues will be found.

Constraint: **range** = 'A', 'V' or 'I'.

3: **uplo** – string

If **uplo** = 'U', the upper triangular part of A is stored.

If **uplo** = 'L', the lower triangular part of A is stored.

Constraint: **uplo** = 'U' or 'L'.

4: **n** – **int32 scalar**

n , the order of the matrix A .

Constraint: $n \geq 0$.

5: **ap**(*) – **double array**

Note: the dimension of the array **ap** must be at least $\max(1, n \times (n + 1)/2)$.

The n by n symmetric matrix A , packed by columns.

More precisely,

if **uplo** = 'U', the upper triangle of A must be stored with element A_{ij} in **ap**($i + j(j - 1)/2$) for $i \leq j$;

if **uplo** = 'L', the lower triangle of A must be stored with element A_{ij} in **ap**($i + (2n - j)(j - 1)/2$) for $i \geq j$.

6: **vl** – **double scalar**

7: **vu** – **double scalar**

If **range** = 'V', the lower and upper bounds of the interval to be searched for eigenvalues.

If **range** = 'A' or 'I', **vl** and **vu** are not referenced.

Constraint: if **range** = 'V', $vl < vu$.

8: **il** – **int32 scalar**

9: **iu** – **int32 scalar**

If **range** = 'I', the indices (in ascending order) of the smallest and largest eigenvalues to be returned.

If **range** = 'A' or 'V', **il** and **iu** are not referenced.

Constraints:

if $n = 0$, **il** = 1 and **iu** = 0;

if $n > 0$, $1 \leq il \leq iu \leq n$.

10: **abstol** – **double scalar**

The absolute error tolerance for the eigenvalues. An approximate eigenvalue is accepted as converged when it is determined to lie in an interval $[a, b]$ of width less than or equal to

$$abstol + \epsilon \max(|a|, |b|),$$

where ϵ is the *machine precision*. If **abstol** is less than or equal to zero, then $\epsilon \|T\|_1$ will be used in its place, where T is the tridiagonal matrix obtained by reducing A to tridiagonal form. Eigenvalues will be computed most accurately when **abstol** is set to twice the underflow threshold $2 \times x02am()$, not zero. If this function returns with **info** > 0, indicating that some eigenvectors did not converge, try setting **abstol** to $2 \times x02am()$. See Demmel and Kahan 1990.

5.2 Optional Input Parameters

None.

5.3 Input Parameters Omitted from the MATLAB Interface

ldz, work, iwork

5.4 Output Parameters

1: **ap**(*) – double array

Note: the dimension of the array **ap** must be at least $\max(1, n \times (n + 1)/2)$.

ap contains the values generated during the reduction to tridiagonal form. The elements of the diagonal and the off-diagonal of the tridiagonal matrix overwrite the corresponding elements of *A*.

2: **m** – int32 scalar

The total number of eigenvalues found.

If **range** = 'A', **m** = **n**.

If **range** = 'V', the exact value of **m** is not known in advance, but will satisfy $0 \leq m \leq n$.

If **range** = 'I', **m** = **iu** – **il** + 1.

3: **w**(*) – double array

Note: the dimension of the array **w** must be at least $\max(1, n)$.

If **info** = 0, the selected eigenvalues in ascending order.

4: **z**(ldz,*) – double array

The first dimension, **ldz**, of the array **z** must satisfy

if **jobz** = 'V', **ldz** $\geq \max(1, n)$;
ldz ≥ 1 otherwise.

The second dimension of the array must be at least $\max(1, m)$ if **jobz** = 'V', and at least 1 otherwise

If **jobz** = 'V', then if **info** = 0, the first *m* columns of *Z* contain the orthonormal eigenvectors of the matrix *A* corresponding to the selected eigenvalues, with the *i*th column of *Z* holding the eigenvector associated with **w**(*i*).

If an eigenvector fails to converge, then that column of *Z* contains the latest approximation to the eigenvector, and the index of the eigenvector is returned in **jfail**.

If **jobz** = 'E', **z** is not referenced.

Note: you must ensure that at least $\max(1, m)$ columns are supplied in the array **z**; if **range** = 'V', the exact value of **m** is not known in advance and an upper bound must be used.

5: **jfail**(*) – int32 array

Note: the dimension of the array **jfail** must be at least $\max(1, n)$.

If **jobz** = 'V', then if **info** = 0, the first **m** elements of **jfail** are zero.

If **info** > 0, **jfail** contains the indices of the eigenvectors that failed to converge.

If **jobz** = 'E', **jfail** is not referenced.

6: **info** – int32 scalar

info = 0 unless the function detects an error (see Section 6).

6 Error Indicators and Warnings

Errors or warnings detected by the function:

info = $-i$

If **info** = $-i$, parameter *i* had an illegal value on entry. The parameters are numbered as follows:

1: **jobz**, 2: **range**, 3: **uplo**, 4: **n**, 5: **ap**, 6: **vl**, 7: **vu**, 8: **il**, 9: **iu**, 10: **abstol**, 11: **m**, 12: **w**, 13: **z**, 14: **ldz**, 15: **work**, 16: **iwork**, 17: **jfail**, 18: **info**.

It is possible that **info** refers to a parameter that is omitted from the MATLAB interface. This usually indicates that an error in one of the other input parameters has caused an incorrect value to be inferred.

info > 0

If **info** = i , then i eigenvectors failed to converge. Their indices are stored in array **jfail**. Please see **abstol**.

7 Accuracy

The computed eigenvalues and eigenvectors are exact for a nearby matrix $(A + E)$, where

$$\|E\|_2 = O(\epsilon)\|A\|_2,$$

and ϵ is the *machine precision*. See Section 4.7 of Anderson *et al.* 1999 for further details.

8 Further Comments

The total number of floating-point operations is proportional to n^3 .

The complex analogue of this function is f08gp.

9 Example

```

jobz = 'Vectors';
range = 'Values in range';
uplo = 'U';
n = int32(4);
ap = [1;
      2;
      2;
      3;
      3;
      3;
      4;
      4;
      4;
      4];
vl = -1;
vu = 1;
il = int32(0);
iu = int32(0);
abstol = 0;
[apOut, m, w, z, jfail, info] = f08gb(jobz, range, uplo, n, ap, vl, vu,
il, iu, abstol)

apOut =
    -0.3571
     0.1237
    -0.9762
     0.6262
    -1.2472
     7.3333
     0.3660
     0.3660
    -6.9282
     4.0000

m =
           2

w =

```

```
      -0.5146  
      -0.2943  
         0  
         0  
z =  
      -0.5144      0.2767  
       0.4851     -0.6634  
       0.5420      0.6504  
      -0.4543     -0.2457  
jfail =  
         0  
         0  
         0  
         0  
info =  
         0
```
