

Multiple High Voltage Power Supply HCV 100M-20000

Type:



F.u.G. Elektronik GmbH

Florianstr. 2
D - 83024 Rosenheim

**Low and High Voltage
Power Supplies**

DIN EN ISO 9001

Tel. : ..49(0)8031 2851-0
Fax : ..49(0)8031 81099

eMail:
fug-elektronik@t-online.de

Internet:
<http://www.fug-elektronik.de>



Special Features

High voltage power supply for scanning electron microscope (SEM)
with pulsed electron beam

Application

Test of Thin Film Transistors (TFT) of LCD glass sheets by means of electron beam

External control

Customer specific control unit for all adjustable or readable values

Technical Data

Mains: 230 V \pm 10%, 47 - 53 Hz

Outputs

Primary energy: 0 - 20 kV / 0 - 300 μ A

Voltage stability: <10ppm / 8h ; <10ppm / with pulsed load

Tc: <10ppm / K

Residual ripple: <10ppm p - p

Grid voltage: -100V ... - 700V / 100 μ A

Auxiliary voltage: 18 V / 750 mA, regulated, floating at 20 kV

Filament supply: max. 10 V / 0 - 2 A floating at 20 kV , current regulated

Environment temperature: 0 to 40°C

Design

Single modules in 19" rack 9 U

June 2003